

## **WARNING!**

THE INTERCONNECT WIRING AND CABLES ON THE REAR OF THE SASL ARE FACTORY INSTALLED AND ARE NOT INTENDED TO BE FIELD SERVICEABLE. THE RF CABLES ARE SPECIALLY TUNED. ANY TAMPERING OR MODIFICATION OF THESE CABLES OR CONNECTIONS WILL INVALIDATE TYPE APPROVAL AND MAY SERIOUSLY COMPROMISE THE DEVICE PERFORMANCE. NOTE THAT THE CONNECTORS ARE FITTED WITH TAMPER EVIDENT SEALS.

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.

## **WARNING!**

THE INTERCONNECT WIRING AND CABLES ON THE REAR OF THE SASL ARE FACTORY INSTALLED AND ARE NOT INTENDED TO BE FIELD SERVICEABLE. THE RF CABLES ARE SPECIALLY TUNED. ANY TAMPERING OR MODIFICATION OF THESE CABLES OR CONNECTIONS WILL INVALIDATE TYPE APPROVAL AND MAY SERIOUSLY COMPROMISE THE DEVICE PERFORMANCE. NOTE THAT THE CONNECTORS ARE FITTED WITH TAMPER EVIDENT SEALS.

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.

THE ANTENNA USED ON THIS EQUIPMENT MUST BE INSTALLED TO PROVIDE A SEPARATION DISTANCE OF AT LEAST 20CM FROM ALL PERSONS AND MUST NOT BE CO-LOCATED OR OPERATED IN CONJUNCTION WITH ANOTHER ANTENNA OR TRANSMITTER.

**PN: ITCS-A-100**  
**MAC: 00:D0:69:41:10:48**  
**DEFAULT IP ADX: 10.10.6.103**  
**SN: 004**  
**FCC ID: WFQITCSA100**

THE ANTENNA USED ON THIS EQUIPMENT MUST BE INSTALLED TO PROVIDE A SEPARATION DISTANCE OF AT LEAST 20CM FROM ALL PERSONS AND MUST NOT BE CO-LOCATED OR OPERATED IN CONJUNCTION WITH ANOTHER ANTENNA OR TRANSMITTER.

**PN: ITCS-A-100**  
**MAC: <mac address>**  
**DEFAULT IP ADX: <ip adx>**  
**SN: <serial number>**  
**FCC ID: WFQITCSA100**