



HCT.CO., LTD.

Product Compliance Division, EMC Team

SAN 136-1, AMI-RI , BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701, KOREA

TEL : +82 31 639 8518 FAX : +82 31 639 8525

**CERTIFICATE OF COMPLIANCE**  
**FCC PART 15.247 Certification**

<b>Applicant Name:</b> Mobile Appliance, Inc.	<b>Date of Testing:</b> June. 16, 2008
<b>Address:</b> #819 Kranz Techno, Sangdaewon-1 Dong, Jungwon-Gu, Seongnam-City, Gyeonggi-Do, 462-729 Korea	<b>Test Site/Location:</b> HCT.CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si, Kyungki-do, Korea <b>Test Report No.:</b> HCT-R08-068 <b>HCT FRN:</b> 0005866421

<b>FCC ID:</b>	<b>WHB-PNX-5</b>
<b>APPLICANT:</b>	<b>Mobile Appliance, Inc.</b>

<b>Model(s):</b>	PNX-5,
<b>EUT Type:</b>	Portable Navigation with Bluetooth
<b>Max. RF Output Power:</b>	0.53 dBm(1.12 mW)
<b>Frequency Range:</b>	2402 - 2480 MHz (Bluetooth)
<b>Modulation type</b>	GFSK(Normal)
<b>FCC Classification:</b>	FCC Part 15 Frequency Hopping Spread Spectrum Transceiver
<b>FCC Rule Part(s):</b>	Part 15 subpart C 15.247
<b>Application Type:</b>	Certification

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT.CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)

*Chang Seok Choi*  
Report prepared by  
: Chang Seok Choi  
Test engineer of RF Part

*Sang Jun Lee*  
Approved by  
: Sang Jun Lee  
Manager of RF Part

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Cellular/PCS GSM/EDGE/WCDMA Phone with Bluetooth	FCC ID: WHB-PNX-5	Page 41 of 41



# Table of Contents

1. GENERAL INFORMATION .....	3
2. EUT DESCRIPTION .....	3
3. TEST METHODOLOGY .....	4
3.1 EUT CONFIGURATION .....	4
3.2 EUT EXERCISE .....	4
3.3 GENERAL TEST PROCEDURES .....	4
3.4 DESCRIPTION OF TEST MODES .....	4
4. INSTRUMENT CALIBRATION .....	5
5. FACILITIES AND ACCREDITATIONS .....	6
5.1 FACILITIES .....	6
5.2 EQUIPMENT .....	6
6. ANTENNA REQUIREMENTS .....	7
7. FCC PART 15.247 REQUIREMENTS .....	8
7.1 PEAK POWER .....	8
7.2 BAND EDGES MEASUREMENT .....	1 1
7.2.1 BAND EDGES MEASUREMENT (RADIATED) .....	1 3
7.3 FREQUENCY SEPARATION .....	1 5
7.4 NUMBER OF HOPPING FREQUENCY .....	1 8
7.5 TIME OF OCCUPANCY (DWELL TIME) .....	2 0
7.6 SPURIOUS EMISSIONS .....	2 3
7.6.1 Conducted Spurious Measurement .....	2 3
7.6.2 Radiated Spurious Emissions .....	2 6
7.7 POWERLINE CONDUCTED EMISSIONS .....	3 4
7.8 RF Exposure statement .....	3 9
8. LIST OF TEST EQUIPMENT .....	4 1



## 1. GENERAL INFORMATION

**Applicant:** Mobile Appliance, Inc.  
#819 Kranz Techno, Sangdaewon-1 Dong, Jungwon-Gu,  
Seongnam-City, Gyeonggi-Do, 462-729 Korea

**FCC ID:** WHB-PNX-5

**EUT:** Portable Navigation with Bluetooth

**Date of Test:** June. 16, 2008

**Contact person:** Name: Sang Gon Lee  
Phone #: +82-31-777-8071  
Fax #: +82-31-777-8073

## 2. EUT DESCRIPTION

<b>Product</b>	Portable Navigation with Bluetooth
<b>Model Name</b>	PNX-5
<b>Power Supply</b>	DC 12.0 V
<b>Battery type</b>	Standard
<b>Frequency Range</b>	2402 ~ 2480 MHz
<b>Transmit Power</b>	0.54 dBm (1.13 mW)
<b>Modulation Type</b>	GFSK(Normal)
<b>Modulation Technique</b>	FHSS
<b>Number of Channels</b>	79 Channels
<b>Antenna Specification</b>	Manufacturer: AMOTECH CO., LTD. Antenna type: Chip ANTENNA Antenna gain: 1.16 dBi



### 3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz(ANSI C63.4-2003) and FCC Public Notice DA 00-705 dated March 30, 2000 entitled “Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems” were used in the measurement of the **Mobile Appliance,Inc.**

**Portable Navigation with Bluetooth. FCC ID: WHB-PNX-5**

#### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### 3.3 GENERAL TEST PROCEDURES

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

#### 3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Portable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 4 of 41



#### 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

<b>HCT PT.15.247 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCT-R08-068	<b>Test Dates:</b> June 16, 2008	<b>EUT Type:</b> Portable Navigation with Bluetooth	<b>FCC ID:</b> WHB-PNX-5	Page 5 of 41



## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 6, 2006(Registration Number: 90661)

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Portable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 6 of 41



## 6. ANTENNA REQUIREMENTS

### According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

\* The antennas of this E.U.T are permanently attached.

\*The E.U.T Complies with the requirement of §15.203

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 7 of 41

## 7. FCC PART 15.247 REQUIREMENTS


### 7.1 PEAK POWER

#### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902 ~ 928 MHz, 2400 ~ 2483.5 MHz, and 5725 ~ 5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Test Configuration



#### TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode.

1. Span = 2 MHz
2. RBW = 1 MHz
3. VBW = 1 MHz
4. Sweep = auto

#### TEST RESULTS

*No non-compliance noted*

#### Test Data


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Limit (W)	Result
Low	2402	-0.31	0.93	1	PASS
Mid	2441	0.54	1.13		PASS
High	2480	0.33	1.07		PASS






Test Plots

Peak Power ( Low CH )




Peak Power ( Mid CH )



HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 9 of 41



Peak Power ( High CH )




HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 1 0 of 41

## 7.2 BAND EDGES MEASUREMENT

### LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test Configuration



### TEST PROCEDURE


The spectrum analyzer is set to :

1. Span = 8 MHz
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Sweep = auto
5. Detector Mode = Peak


### TEST RESULTS

See attached.

### Band Edges (Low- CH)



### Band Edges (High-CH)




### 7.2.1 BAND EDGES MEASUREMENT (RADIATED))

#### LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

#### Test Configuration



#### TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW = VBW = 1 MHz / Sweep = AUTO
  - (b) AVERAGE: RBW = 1 MHz / VBW = 10 Hz / Sweep = AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

#### TEST RESULTS

Refer to attached data chart.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Portable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 13 of 41



## Test Data

### (Low- CH)

Frequency [MHz]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2382.95	H	40.73	74	33.27	PK
2392.19	H	29.91	54	24.09	AV
2381.27	V	41.12	74	32.88	PK
2392.12	V	31.43	54	22.57	AV

### (High- CH)


Frequency [MHz]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2504	H	43.55	74	30.45	PK
2504	H	32.49	54	21.51	AV
2498.8	V	42.88	74	31.12	PK
2490	V	30.28	54	23.72	AV

### 7.3 FREQUENCY SEPARATION

#### LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Test Configuration



#### TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 3 MHz
2. RBW = 100 KHz
3. VBW = 300 KHz
4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

#### TEST RESULTS


*No non-compliance noted*

#### Test Data

Channel Separation (KHz)	20dB Bandwidth (KHz)		Limit (KHz)	Result
990	Low CH	939.25	>25	Pass
	Middle CH	935.38		
	High CH	939.30		

## Test Plot


### Measurement of Channel Separation



## Test Plot

### 20 dB bandwidth


### (Low CH)








( Mid CH)



(High CH)




## 7.4 NUMBER OF HOPPING FREQUENCY

### LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

### Test Configuration



### TEST PROCEDURE

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

1. Span = the frequency band of operation ( Start = 2400 MHz, Stop = 2483.5 MHz )
2. RBW = 300 kHz
3. VBW = 300 kHz
4. Sweep = auto

The trace was allowed to stabilize.

### TEST RESULTS

*No non-compliance noted*

### Test Data


Result (No. of CH)	Limit (No. of CH)	Result
79	>75	Pass




Test Plot

Number of Channels

2.4 GHz – 2.441 GHz



2.441 GHz – 2.4835 GHz




## 7.5 TIME OF OCCUPANCY (DWELL TIME)

### LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### Test Configuration



### TEST PROCEDURE

EUT was set to transmit the longest packet type (DH5)

1. Span = zero span
2. RBW = 1 MHz
3. VBW = 1 MHz
4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the dwell time.

### TEST RESULTS

See the table.

#### DH 5(The longest packet type)

CH Low :  $2925 * (1600/6)/79 * 31.6 = 312.00$  (ms)

CH Mid :  $2908 * (1600/6)/79 * 31.6 = 312.00$  (ms)


CH High :  $2916 * (1600/6)/79 * 31.6 = 312.00$  (ms)

Channel	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.925	312.00	31.6	400	PASS
Mid	2.908	310.18	31.6		PASS
High	2.916	311.04	31.6		PASS


## Test Plots

### DH 5


#### ( Low CH )



#### ( Mid CH )



(CH High)




## 7.6 SPURIOUS EMISSIONS

### 7.6.1 Conducted Spurious Measurement

#### LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### Test Configuration



#### TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Detector Mode is set to a peak detector Mode.


Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.

#### TEST RESULTS


*No non-compliance noted*

## Test Plots

( Low CH )




( Mid CH )





( High CH )





## 7.6.2 Radiated Spurious Emissions


### LIMIT

1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed


Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

## Test Configuration


### Below 30 MHz



### 30 MHz - 1 GHz



## Above 1 GHz



### TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.



**TEST RESULTS**

**9 kHz – 30MHz**

**Operation Mode:** Normal Link

**Notes:**

1. *Measuring frequencies from 9 kHz to the 30MHz.*
2. *The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.*
3. *Distance extrapolation factor = 40 log (specific distance / test distance) (dB)*
4. *Limit line = specific Limits (dBuV) + Distance extrapolation factor*

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 29 of 41



## TEST RESULTS

Below 1 GHz

Operation Mode: Normal Link

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
69	19.58	9.9	1.9	H	31.4	40.0	8.6
153	13.78	13.1	2.9	H	29.8	43.5	13.7

### Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Quasi peak detector mode.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 3 0 of 41



**Above 1 GHz**

**Operation Mode:** CH Low

Frequency [MHz]	Level [dBm]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4804	-93.92	58.68	H	45.60	74	28.40	PK
4804	-96.05	44.60	H	33.65	54	20.35	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.



**Operation Mode:** CH Mid

Frequency [MHz]	Level [dBm]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4811	-90.56	61.96	H	45.52	74	28.48	PK
4811	-94.66	45.67	H	33.33	54	20.67	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.





**Operation Mode: CH High**

Frequency [MHz]	Reading dBuV	AN.+CL-AMP GAIN. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4955	54.63	-5.54	H	49.09	74	24.91	PK
4955	47.97	-5.54	H	42.43	54	11.57	AV
7354	56.17	-0.02	H	56.15	74	17.86	PK
7354	48.48	-0.02	H	48.46	54	5.55	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MH.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.



## 7.7 POWERLINE CONDUCTED EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.




HCT

**EMC TEST LAB**

EUT: PNX-5(E)  
 Manufacturer: MOBILEAPPLIANCE  
 Operating Condition: BLUETOOTH MODE  
 Test Site: SHIELD ROOM  
 Operator: DH.RYU  
 Test Specification: EN55022 CLASS B  
 Comment: H

**SCAN TABLE: "EN 55022 Voltage"**

Short Description:		EN 55022 Voltage					
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
Frequency	Frequency	Width					
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



**MEASUREMENT RESULT: "NAVIGATION\_fin QP"**

3/21/2008 1:37PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.434000	37.20	10.0	57	20.0	---	---
0.478000	38.20	10.1	56	18.2	---	---
0.498000	38.70	10.1	56	17.3	---	---
0.536000	40.20	10.1	56	15.8	---	---
1.232000	38.60	10.2	56	17.4	---	---
1.920000	39.00	10.3	56	17.0	---	---
5.104000	34.10	10.6	60	25.9	---	---
5.488000	31.90	10.7	60	28.1	---	---
5.864000	34.50	10.7	60	25.5	---	---

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 3 5 of 41



**MEASUREMENT RESULT: "NAVIGATION\_fin AV"**

3/21/2008 1:37PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.482000	25.30	10.1	46	21.0	---	---
0.490000	25.80	10.1	46	20.3	---	---
0.498000	24.00	10.1	46	22.0	---	---
0.548000	26.50	10.1	46	19.5	---	---
0.584000	25.90	10.1	46	20.1	---	---
3.260000	24.40	10.4	46	21.6	---	---
5.864000	21.20	10.7	50	28.8	---	---
6.164000	22.00	10.8	50	28.0	---	---
6.520000	22.80	10.8	50	27.2	---	---

<b>HCT PT.15.247 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCT-R08-068	<b>Test Dates:</b> June 16, 2008	<b>EUT Type:</b> Prtable Navigation with Bluetooth	<b>FCC ID:</b> WHB-PNX-5	Page 3 6 of 41




HCT

**EMC TEST LAB**

EUT: PNX-5 (E)  
 Manufacturer: MOBILEAPPLIANCE  
 Operating Condition: BLUETOOTH MODE  
 Test Site: SHIELD ROOM  
 Operator: DH.RYU  
 Test Specification: EN55022 CLASS B  
 Comment: N

**SCAN TABLE: "EN 55022 Voltage"**

Short Description:		EN 55022 Voltage					
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer	
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



**MEASUREMENT RESULT: "NAVIGATION\_fin QP"**

3/21/2008 1:42PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.450000	32.50	10.1	57	24.3	---	---
0.470000	31.80	10.1	57	24.7	---	---
0.478000	33.60	10.1	56	22.8	---	---
0.516000	34.00	10.1	56	22.0	---	---
0.540000	34.00	10.1	56	22.0	---	---
3.404000	34.60	10.4	56	21.4	---	---
5.000000	28.20	10.6	56	27.8	---	---
19.432000	28.30	12.2	60	31.7	---	---
19.784000	28.30	12.3	60	31.7	---	---

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 37 of 41



MEASUREMENT RESULT: "NAVIGATION\_fin AV"

3/21/2008 1:42PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.158000	27.50	10.0	56	28.1	---	---
0.426000	20.40	10.0	47	26.9	---	---
0.490000	22.10	10.1	46	24.0	---	---
0.592000	21.70	10.1	46	24.3	---	---
3.208000	20.40	10.4	46	25.6	---	---
3.508000	20.80	10.5	46	25.2	---	---
5.000000	17.90	10.6	46	28.1	---	---
18.884000	19.90	12.2	50	30.1	---	---
20.332000	19.70	12.3	50	30.3	---	---

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-068	Test Dates: June 16, 2008	EUT Type: Prtable Navigation with Bluetooth	FCC ID: WHB-PNX-5	Page 3 8 of 41



## 7.8 RF Exposure statement

### 1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	1.0	30

F = frequency in MHz

\* = Plane-wave equivalent power density

### 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna



## 2-1. BT Band

Max Peak output Power at antenna input terminal (dBm)	0.54000
Max Peak output Power at antenna input terminal (mW)	1.13240
Prediction distance (cm)	20.00000
Prediction frequency (MHz)	2441.00000
Antenna Gain(typical) (dBi)	1.16000
Antenna Gain(numeric)	1.30617
Power density at prediction frequency (mW/cm <sup>2</sup> )	0.00029
MPE limit for uncontrolled exposure at prediction frequency (mW/cm <sup>2</sup> )	1.00000

## 3. RESULTS

3-2. The power density level at 20 cm is 0.00029 mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit of 1.0 mW/cm<sup>2</sup> at 2441 MHz for Bluetooth band.





## 8. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESCI/ EMI Test Receiver	08/24/2007	Annual	08/24/2008	100033
Rohde & Schwarz	ESH2-Z5/ LISN	04/20/2008	Annual	04/20/2009	861741/013
Rohde & Schwarz	ESH3-Z6/ LISN	06/13/2008	Annual	06/13/2009	100329
Schwarzbeck	VULB 9160/ TRILOG Antenna	04/20/2007	Biennial	04/20/2009	9160-3150
HD	MA240/ Antenna Position Tower	N/A	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	10/03/2007	Annual	10/03/2008	375.8810.352
MITEQ	AMF-60-0010 1800-35-20P	01/15/2008	Annual	01/15/2009	1200937
Schwarzbeck	BBHA 9120D/ Horn Antenna	03/30/2007	Biennial	03/30/2009	147
Schwarzbeck	BBHA9170/ SHF-EHF Horn Antenna	03/20/2007	Biennial	03/20/2009	BBHA9170342
Rohde & Schwarz	6502/Loop Antenna	12/26/2007	Biennial	12/26/2009	9009-2536
Rohde & Schwarz	FSP30/Spectrum Analyzer	06/28/2007	Annual	06/28/2008	839117/011
Agilent	E4440A/Spectrum Analyzer	01/08/2008	Annual	01/08/2009	US45303008
Advantest	R3273/Spectrum Analyzer	05/19/2008	Annual	05/19/2009	J004821
Agilent	E4416A /Power Meter	01/22/2008	Annual	01/22/2009	GB41291412
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	06/28/2007	Annual	06/28/2008	1
Hewlett Packard	11636B/Power Divider	01/14/2008	Annual	01/14/2009	11377
DIGITAL	EP-3010 /DC POWER SUPPLY	01/10/2008	Annual	01/10/2009	3110117