

RF EXPOSURE

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, *= plane-wave equivalent power density

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

SAR test exclusion considerations : WLAN 802.11b

- Frequency Range : 2 412 MHz ~ 2 462 MHz
- Measured RF Maximum Output Power (Avg.) : 4.86 dBm
- Target Power & Tolerance 4.00 dBm & ± 1.00 dB
 (Maximum : 5.00 dBm & Minimum : 3.00 dBm)
- Maximum Peak Antenna Gain : 1.99 dBi
- **Maximum Output Power for the Calculation : 5.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
 The SAR test exclusion considerations for this exposure is shown below.

<p>- EIRP = P + G</p> <p>= <u>5.00</u> dBm + <u>1.99</u> dBi</p> <p>= <u>6.99</u> dBm</p> <p>= <u>5.00</u> mW</p>	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

Power Density at the specific separation

<p>- S = EIRP / (4 X R²π)</p> <p>= 5.00 / (4 X 20² X π)</p> <p>= <u>0.000 995</u> mW/cm²</p>	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
---	--

SAR test exclusion considerations : WLAN 802.11g

- Frequency Range : 2 412 MHz ~ 2 462 MHz
- Measured RF Maximum Output Power (Avg.) : 5.97 dBm
- Target Power & Tolerance 6.00 dBm & ± 1.00 dB
(Maximum : 7.00 dBm & Minimum : 5.00 dBm)
- Maximum Peak Antenna Gain : 1.99 dBi
- **Maximum Output Power for the Calculation : 7.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The SAR test exclusion considerations for this exposure is shown below.

<p>- EIRP = P + G</p> <p>= <u>7.00</u> dBm + <u>1.99</u> dBi</p> <p>= <u>8.99</u> dBm</p> <p>= <u>7.93</u> mW</p>	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

Power Density at the specific separation

<p>- S = EIRP / (4 X R²π)</p> <p>= 7.93 / (4 X 20² X π)</p> <p>= <u>0.001 577</u> mW/cm²</p>	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
--	--

SAR test exclusion considerations : WLAN 802.11n_HT20

- Frequency Range : 2 412 MHz ~ 2 462 MHz
- Measured RF Maximum Output Power (Avg.) : 6.00 dBm
- Target Power & Tolerance 6.00 dBm & ± 1.00 dB
(Maximum : 7.00 dBm & Minimum : 5.00 dBm)
- Maximum Peak Antenna Gain : 1.99 dBi
- **Maximum Output Power for the Calculation : 7.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The SAR test exclusion considerations for this exposure is shown below.

<p>- EIRP = P + G</p> <p>= <u>7.00</u> dBm + <u>1.99</u> dBi</p> <p>= <u>8.99</u> dBm</p> <p>= <u>7.93</u> mW</p>	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

Power Density at the specific separation

<p>- S = EIRP / (4 X R²π)</p> <p>= 7.93 / (4 X 20² X π)</p> <p>= <u>0.001 577</u> mW/cm²</p>	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
--	--