



FCC ID: WHZ-DM351
IC: 7824A-DM351

**Statement of compliance to
Maximum Permissible Exposure (MPE)
No. 140800005SHA-002**

Applicant : Canton Elektronik GmbH & Co. KG

Neugasse 21-23, 61276 Weilrod / Niederlauken, Germany

Manufacturer : Canton Elektronik GmbH & Co. KG

Neugasse 21-23, 61276 Weilrod / Niederlauken, Germany

Product Name : Soundbar Speaker

Brand Name : CANTON

Type/Model : DM 75 SE, DM 90.3, VRA 2, BRA 2, DM 75 HD, DM 95

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency band	Power		Antenna Gain		R	S	Limits
(MHz)	dBm	mW	dBi	(Numeric)	(cm)	(mW/cm ²)	(mW/cm ²)
2400 -2483.5	7.99	6.30	2.0	1.58	20	0.002	1

Note: 1 mW/cm² from 1.310 Table 1

Date of issue: Dec. 17, 2014

Prepared by:

Wade Zhang (Project Engineer)

Reviewed by:

Daniel Zhao (Reviewer)



FCC ID: WHZ-DM351
IC: 7824A-DM351

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.