

RF Exposure Evaluation Report

APPLICANT : CASTLES TECHNOLOGY CO., LTD.
EQUIPMENT : POS Terminal
BRAND NAME :  CASTLES
TECHNOLOGY
MODEL NAME : S1P2
FCC ID : WIYS1P2001
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Jul. 04, 2024 and completed on Jul. 04, 2024. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	8
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	9
5.1. Standalone Power Density Calculation	9
5.2. Collocated Power Density Calculation.....	10



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA441703	Rev. 01	Initial issue of report.	Jul. 19, 2024



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	CASTLES TECHNOLOGY CO., LTD.
Address	6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C)

Manufacturer	
Company Name	CASTLES TECHNOLOGY CO., LTD.
Address	6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C)



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	POS Terminal
Brand Name	 CASTLES TECHNOLOGY
Model Name	S1P2
FCC ID	WIYS1P2001
Wireless Technology and Frequency Range	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 26 : 814 MHz ~ 849 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2535 MHz ~ 2655 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Mode	GPRS/EGPRS RMC 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+(16QAM uplink is supported) LTE: QPSK, 16QAM, 64QAM, 256QAM WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC:ASK
Antenna Gain	GSM850: 0.29 dBi GSM1900: -0.51 dBi WCDMA Band II: -0.51 dBi WCDMA Band IV: -0.31 dBi WCDMA Band V: 0.29 dBi LTE Band 2 : -0.51 dBi LTE Band 4 : -0.31 dBi LTE Band 5 : 0.29 dBi LTE Band 7 : 0.77 dBi LTE Band 12 : -1.18 dBi LTE Band 17 : -1.18 dBi LTE Band 26 : 0.29 dBi LTE Band 38 : 0.77 dBi LTE Band 41: 0.77 dBi LTE Band 66: -0.31 dBi Bluetooth: 0.3 dBi WLAN2.4GHz: 0.3 dBi WLAN5.2GHz: 2.11 dBi WLAN5.3GHz: 1.56 dBi WLAN5.5GHz: 1.90 dBi



Antenna Type	WWAN: Monopole Antenna WLAN/Bluetooth: Monopole Antenna NFC: Loop Antenna
HW Version	HW-V-1D.00
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

3. Maximum RF average output tune up power among production units**<GSM>**

Mode	Maximum Average power(dBm)	
	GSM850	GSM1900
GPRS 1 Tx slot	33.5	31.0
GPRS 2 Tx slots	31.5	29.0
GPRS 3 Tx slots	30.0	27.0
GPRS 4 Tx slots	28.0	25.0
EDGE 1 Tx slot	28.0	30.0
EDGE 2 Tx slots	26.0	28.0
EDGE 3 Tx slots	25.0	27.0
EDGE 4 Tx slots	23.0	25.0

<WCDMA>

Mode		Maximum Average power(dBm)
WCDMA	Band II	25.0
	Band IV	25.0
	Band V	25.0

<LTE>

Mode		Maximum Average power(dBm)
LTE	Band 2	25.0
	Band 4	25.0
	Band 5	25.0
	Band 7	25.0
	Band 12	25.0
	Band 17	25.0
	Band 26	25.0
	Band 38	23.0
	Band 41	23.0
	Band 66	25.0

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	17.50
	802.11g	15.50
	802.11n-HT20	14.50

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	BR/EDR	11.0
	LE	-1.0

<5GHz WLAN >

Mode		Maximum Average Power (dBm)
5.2GHz	802.11a	16.0
	802.11n-HT20	15.0
	802.11n-HT40	15.0
	802.11ac-VHT20	14.0
	802.11ac-VHT40	14.0
	802.11ac-VHT80	14.0
5.3GHz	802.11a	16.0
	802.11n-HT20	15.0
	802.11n-HT40	15.0
	802.11ac-VHT20	14.0
	802.11ac-VHT40	14.0
	802.11ac-VHT80	14.0
5.5GHz	802.11a	16.0
	802.11n-HT20	15.0
	802.11n-HT40	15.0
	802.11ac-VHT20	14.0
	802.11ac-VHT40	14.0
	802.11ac-VHT80	14.0



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
GPRS 850 (1 Tx slot)	824	0.29	33.50	33.790	301.301	0.060	0.549	0.109
GPRS 850 (2 Tx slots)	824	0.29	31.50	31.790	379.315	0.076	0.549	0.137
GPRS 850 (3 Tx slots)	824	0.29	30.00	30.290	400.867	0.080	0.549	0.145
GPRS 850 (4 Tx slots)	824	0.29	28.00	28.290	338.065	0.067	0.549	0.122
EGPRS 850 (1 Tx slot)	824	0.29	28.00	28.290	84.918	0.017	0.549	0.031
EGPRS 850 (2 Tx slots)	824	0.29	26.00	26.290	106.905	0.021	0.549	0.039
EGPRS 850 (3 Tx slots)	824	0.29	25.00	25.290	126.765	0.025	0.549	0.046
EGPRS 850 (4 Tx slots)	824	0.29	23.00	23.290	106.905	0.021	0.549	0.039
GPRS 1900 (1 Tx slot)	1850	-0.51	31.00	30.490	140.929	0.028	1.000	0.028
GPRS 1900 (2 Tx slots)	1850	-0.51	29.00	28.490	177.419	0.035	1.000	0.035
GPRS 1900 (3 Tx slots)	1850	-0.51	27.00	26.490	167.109	0.033	1.000	0.033
GPRS 1900 (4 Tx slots)	1850	-0.51	25.00	24.490	140.929	0.028	1.000	0.028
EGPRS 1900 (1 Tx slot)	1850	-0.51	30.00	29.490	111.944	0.022	1.000	0.022
EGPRS 1900 (2 Tx slots)	1850	-0.51	28.00	27.490	140.929	0.028	1.000	0.028
EGPRS 1900 (3 Tx slots)	1850	-0.51	27.00	26.490	167.109	0.033	1.000	0.033
EGPRS 1900 (4 Tx slots)	1850	-0.51	25.00	24.490	140.929	0.028	1.000	0.028
WCDMA Band 2	1850	-0.51	25.00	24.490	281.190	0.056	1.000	0.056
WCDMA Band 4	1710	-0.31	25.00	24.690	294.442	0.059	1.000	0.059
WCDMA Band 5	824	0.29	25.00	25.290	338.065	0.067	0.549	0.122
LTE Band 2	1850	-0.51	25.00	24.490	281.190	0.056	1.000	0.056
LTE Band 4	1710	-0.31	25.00	24.690	294.442	0.059	1.000	0.059
LTE Band 5	824	0.29	25.00	25.290	338.065	0.067	0.549	0.122
LTE Band 7	2500	0.77	25.00	25.770	377.572	0.075	1.000	0.075
LTE Band 12	699	-1.18	25.00	23.820	240.991	0.048	0.466	0.103
LTE Band 17	704	-1.18	25.00	23.820	240.991	0.048	0.469	0.102
LTE Band 26	814	0.29	25.00	25.290	338.065	0.067	0.543	0.124
LTE Band 38	1850	0.77	23.00	23.770	238.232	0.047	1.000	0.047
LTE Band 41	2535	0.77	23.00	23.770	238.232	0.047	1.000	0.047
LTE Band 66	1710	-0.31	25.00	24.690	294.442	0.059	1.000	0.059
Bluetooth	2402	0.30	11.00	11.300	13.490	0.003	1.000	0.003
2.4GHz WLAN	2412	0.30	17.50	17.800	60.256	0.012	1.000	0.012
5.2GHz WLAN	5180	2.11	16.00	18.110	64.714	0.013	1.000	0.013
5.3GHz WLAN	5260	1.56	16.00	17.560	57.016	0.011	1.000	0.011
5.5GHz WLAN	5500	1.90	16.00	17.900	61.660	0.012	1.000	0.012
NFC	13.56			-18.510	1.000	0.0002	0.979	0.0002

Note:

- For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
- Chose the maximum power to do MPE analysis.
- NFC maximum EIRP power calculate from NFC E-Field level from RF test report which can be referred to Sporton No: FR431401D.
 - This device maximum E-Field level is 76.72dBuV/m at 3m, so the EIRP power is -18.51dBm(0.0014mW).
 - Pout EIRP (dBm) = Field Strength of Fundamental (dBuV/m) - 95.23 (dB)

5.2. Collocated Power Density Calculation

WWAN Power Density / Limit	Bluetooth Power Density / Limit	NFC Power Density / Limit	Σ (Power Density / Limit) of WWAN + Bluetooth+NFC
0.145	0.003	0.0002	0.148
WWAN Power Density / Limit	WLAN 2.4GHz Power Density / Limit	NFC Power Density / Limit	Σ (Power Density / Limit) of WWAN + WLAN 2.4GHz+NFC
0.145	0.012	0.0002	0.157
WWAN Power Density / Limit	WLAN 5GHz Power Density / Limit	NFC Power Density / Limit	Σ (Power Density / Limit) of WWAN + WLAN 5GHz+NFC
0.145	0.013	0.0002	0.158

Note:

1. According to the EUT characteristic, NFC can transmit simultaneously with other Radios.
2. According to the EUT characteristic, WLAN (2.4GHz or 5GHz) and Bluetooth cannot transmit simultaneously, WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously
3. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + Bluetooth&WLAN 2.4GHz& WLAN 5GHz+NFC.
4. Considering all transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 2 collocated transmitters is compliant

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----