



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20220300372E-02
Applicant: Avantronics Limited
Address of Applicant: The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen
Equipment Under Test (EUT):
EUT Name: Avantree NB18
Test Model No.: BTHS-NB18, BTHS-NB18T, BTHS-NB18-P
Model No.: BTHS-NB18
Brand Name: Avantree
FCC ID: WJ5-BTHS-NB18
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2022-03-22
Date of Test: 2022-03-22 to 2022-04-06
Date of Issue: 2022-05-20
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Rock Huang
(Rock Huang)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

| Report No. | Version | Description | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20220300372E-02 | Rev.01 | Initial report | 2022-05-20 |

2 Contents

| | Page |
|--|------|
| 1 VERSION | 2 |
| 2 CONTENTS | 3 |
| 3 GENERAL INFORMATION | 4 |
| 3.1 CLIENT INFORMATION | 4 |
| 3.2 GENERAL DESCRIPTION OF EUT | 4 |
| 3.3 GENERAL DESCRIPTION OF BT&BLE | 4 |
| 4 MPE EVALUATION | 5 |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT | 5 |
| 4.1.1 <i>Standard Requirement</i> | 5 |
| 4.1.2 <i>Limits</i> | 5 |
| 4.1.3 <i>EUT RF Exposure</i> | 7 |

3 General Information

3.1 Client Information

| | |
|--------------------------|--|
| Applicant: | Avantronics Limited |
| Address of Applicant: | The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen |
| Manufacturer: | Avantronics Limited |
| Address of Manufacturer: | The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen |
| Factory: | Avantronics Limited |
| Address of Factory: | The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen |

3.2 General Description of EUT

| | |
|----------------------------------|--|
| Product Name: | Avantree NB18 |
| Model No.: | BTHS-NB18, BTHS-NB18T, BTHS-NB18-P |
| Test Model No | BTHS-NB18 |
| Trade Mark: | Avantree |
| EUT Supports Radios application: | Bluetooth mode 2402-2480MHz |
| Software Version: | V01 |
| Hardware Version: | V03 |
| Sample Type: | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location |
| EUT Power Supply: | Li-ion battery: DC 3.7V 310mAh, Charge by DC 5V for adapter |

3.3 General Description of BT

| | |
|-----------------------|---|
| Operation Frequency: | 2402MHz~2480MHz |
| Bluetooth Version: | V5.0 |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Modulation Type: | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Number of Channel: | 79 |
| Transfer Rate: | 1Mbps/2Mbps/3Mbps |
| Test Software of EUT: | BlueTest3 |
| Antenna Type: | Chip antenna |
| Antenna Gain: | 0dBi |

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

447498 D04 Interim General RF Exposure Guidance v01

3.2. SAR Test Reduction Guidance

SAR test reduction procedures [Glossary] allow using a particular set of test data as representative of other, similar, test conditions. This may be applied for data within different test positions (e.g. body, head, extremity), wireless modes (e.g. Wi-Fi, cellular), and frequency bands. This test reduction process provides for the use of test data for one specific channel, while referencing to those data for demonstrating compliance in other required channels for each test position of an exposure condition, within the operating mode of a frequency band. This is limited specifically to when the reported 1-g or 10-g SAR for the mid-band or highest output power channel meets any of the following conditions.

4.1.2 Limits

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance (mm) | | | | | | | | | |
|-----------------|---------------|----|----|-----|-----|-----|-----|-----|-----|-----|
| | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 |
| 300 | 39 | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
| 450 | 22 | 44 | 67 | 89 | 112 | 135 | 158 | 180 | 203 | 226 |
| 835 | 9 | 25 | 44 | 66 | 90 | 116 | 145 | 175 | 207 | 240 |
| 1900 | 3 | 12 | 26 | 44 | 66 | 92 | 122 | 157 | 195 | 236 |
| 2450 | 3 | 10 | 22 | 38 | 59 | 83 | 111 | 143 | 179 | 219 |
| 3600 | 2 | 8 | 18 | 32 | 49 | 71 | 96 | 125 | 158 | 195 |
| 5800 | 1 | 6 | 14 | 25 | 40 | 58 | 80 | 106 | 136 | 169 |

4.1.3 EUT RF Exposure

Measurement Data

| Channel | maximum output power(dBm) | Maximum tune-up Power (mW) | Exclusion threshold (mW) |
|----------------------|---------------------------|----------------------------|--------------------------|
| Lowest (2402MHz) | 2.59 | 1.816 | 3.0 |
| Middle (2441MHz) | 3.66 | 2.323 | |
| Highest (2480MHz) | 3.3 | 2.138 | |

Remark: The maximum output power data refer to report Report No.: CQASZ20220300372E-01.

*** END OF REPORT ***