Avantronics Limited

Bluetooth Headset

Model: TREX PRO

8 February 2010 Report No.: 1002073 (This report supersedes NONE)



Modifications made to the product: None This Test Report is Issued Under the Authority of: Jackson, chen **Peter Cai** Jackson Chen **Compliance Engineer Technical Manager**

This test report may be reproduced in full only. Test result presented in this test report is applicable to the representative sample only.





Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 2 of 43 www.siemic.com.c

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the <u>global markets</u>.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope		
USA	FCC, A2LA	EMC , RF/Wireless , Telecom		
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom		
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom , Safety		
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom		
Australia	NATA, NIST	EMC, RF, Telecom , Safety		
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety		
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom		
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom		
Europe	A2LA, NIST	EMC, RF, Telecom , Safety		

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 3 of 43 www.siemic.com.0

This page has been left blank intentionally.



| Serial#: 1002073 | Issue Date: 8 Februray 2010 | Page: 4 of 43 | www.siemic.com.cn

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
	TECHNICAL DETAILS	
	MODIFICATION	
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
ANN	EX A. TEST INSTRUMENT & METHOD	20
ANN	EX B. EUT AND TEST SETUP PHOTOGRAPHS	24
ANN	EX C. TEST SETUP AND SUPPORTING EQUIPMENT	25
ANN	EX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	29
ANN	EX E. SIEMIC ACCREDITATION CERTIFICATES	30



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 5 of 43 www.siemic.com.c

1 Executive Summary & EUT information

The purpose of this test programme was to demonstrate compliance of the Avantronics Limited, Bluetooth Headset, and model: TREX PRO against the current Stipulated Standards. The Bluetooth Headset has demonstrated compliance with the FCC 15.249:2009.

EUT Information

: Avantalk Trex Pro is an elegant designed noise cancelling Bluetooth Headset.

The dual microphones and advanced Digital Signal Processing technology help to eliminate the background noise so you can be heard clearly from even the very noisy environment. You can comfortably wear this headset inside the ear, or

discreetly on the neck stripe to avoid attention when not using. Overall, Trex Pro offers good sound quality, trendy design/finish, and comfortableness for long

time wearing.

Model No : TREX PRO

Serial No : N/A

Input Power : 3.7Vdc, 21mA

Classification

EUT

Description

Per Stipulated : FCC 15.249: 2009

Test Standard



Modulation:

FCC ID:

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 6 of 43

N/A

WJ5-TREXPRO

	2 TECHNICAL DETAILS
Purpose	Compliance testing of Bluetooth Headset with stipulated standard
Applicant / Client	Avantronics Limited Unit 1903, Shenhua Commercial Building, No.2018 Jiabin Rd, Luohu District, Shenzhen, China.
Manufacturer	Avantronics Limited Unit 1903, Shenhua Commercial Building, No.2018 Jiabin Rd, Luohu District, Shenzhen, China.
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email:info@siemic.com
Test report reference number	1002073
Date EUT received	12 January 2010
Standard applied	FCC 15.249:2009
Dates of test (from – to)	2 February to 5 February 2010
No of Units:	#1
Equipment Category:	DXT
Trade Name:	N/A
Model:	TREX PRO
RF Operating Frequency (ies)	2402-2480MHz



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 7 of 43

3 MODIFICATION

NONE



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 8 of 43 www.siemic.com.

4 TEST SUMMARY

The product was tested in accordance with the following specifications.

All Testing has been performed according to below product classification:

DXT

Test Results Summary

Test Standard	Description	Pass / Fail
CFR 47 Part 15.249: 2009		
15.203	Antenna Requirement	Pass
15.207(a)	Conducted Emissions Voltage	Pass
15.209;15.249	Radiated Spurious Emissions	Pass

ANSI C63.4: 2009

PS: All measurement uncertainties are not taken into consideration for all presented test result.

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 9 of 43 www.siemic.com.c

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

EUT antenna is PCB antenna. It is compliance with the requirement of permanently attached to the device.

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 10 of 43 www.siemic.com.c

5.2 Conducted Emissions Voltage

Requirement:

	Conducted limit (dBµV)			
Frequency of emission (MHz)	Quasi-peak	Average		
0.15–0.5	66 to 56*	56 to 46*		
0.5–5	56	46		
5–30	60	50		

^{*}Decreases with the logarithm of the frequency.

Procedures:


- 1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. Conducted Emissions Measurement Uncertainty
 All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz 30MHz (Average & Quasi-peak) is ±3.5dB.

4. Environmental Conditions Temperature 15°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar

5. Test date: 2 February to 5 February 2010

Tested By: Peter Cai

5.2.1 Test Result Complying For 47 CFR §15.207




Test Data

Line

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
0.74	43.32	56.00	-12.68	42.60	46.00	-3.40	10.14
0.67	42.89	56.00	-13.11	41.77	46.00	-4.23	10.13
1.04	42.69	56.00	-13.31	41.65	46.00	-4.35	10.16
1.26	39.11	56.00	-16.89	37.45	46.00	-8.55	10.17
3.63	32.49	56.00	-23.51	24.17	46.00	-21.83	10.39
0.45	43.72	56.96	-13.24	43.05	46.96	-3.91	10.17

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 12 of 43 www.siemic.com.



Test Data

Neutral

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
3.62	32.49	56.00	-23.51	23.86	46.00	-22.14	10.41
0.74	41.33	56.00	-14.67	40.48	46.00	-5.52	10.14
1.26	42.51	56.00	-13.49	41.29	46.00	-4.71	10.18
3.77	34.55	56.00	-21.45	31.94	46.00	-14.06	10.46
0.67	43.09	56.00	-12.91	42.43	46.00	-3.57	10.14
0.96	42.84	56.00	-13.16	42.04	46.00	-3.96	10.17

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 13 of 43 www.siemic.com.cn

5.3 Radiated Spurious Emission < 1 GHz

- 1. <u>All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.</u>
- 2. <u>A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.</u>
- 3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz & 1GHz above (3m & 10m) is +5.6/-4.5dB.

4. Environmental Conditions Temperature 15°C Relative Humidity 50%

Atmospheric Pressure 1019mbar

5. Test date: 2 February to 5 February 2010

Tested By: Peter Cai

Requirement(s): 47 CFR §15.249

Procedures: Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set to transmit at low mid high channel.


The limit is converted from microvolts/meter to decibel microvolts/meter.

Sample Calculation: Corrected Amplitude=Raw Amplitude (dBuV/m) + ACF (dB) +Cable Loss (dB)

Test Result:

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 14 of 43 www.siemic.com.

Radiated Emission Plot (Transmitter)




Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
37.77	26.96	100.00	V	106.00	-32.69	40.00	-13.04
39.98	22.78	160.00	V	101.00	-34.43	40.00	-17.22
904.78	20.93	90.00	V	132.00	-19.73	46.00	-25.07
150.03	29.91	247.00	V	100.00	-32.01	43.50	-13.59
209.93	24.50	73.00	V	110.00	-31.76	43.50	-19.00
214.50	25.29	86.00	V	112.00	-31.85	43.50	-18.21



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 15 of 43 www.siemic.com.cn



Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
215.70	31.77	171.00	Н	119.00	-32.01	43.50	-11.73
210.13	32.23	160.00	Н	130.00	-31.89	43.50	-11.27
226.17	32.34	170.00	Н	102.00	-32.23	46.00	-13.66
235.41	30.20	178.00	Н	102.00	-32.42	46.00	-15.80
248.12	28.60	22.00	Н	106.00	-32.70	46.00	-17.40
203.94	28.30	151.00	Н	148.00	-31.75	43.50	-15.20

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 16 of 43 www.siemic.com.

5.4 Radiated Spurious Emissions > 1GHz

- 1. <u>All possible modes of operation were investigated. Only the 6 worst case emissions measured,</u> using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- 2. <u>A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.</u>
- 3. Radiated Emissions Measurement Uncertainty
 All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz 1GHz & 1GHz above (3m & 10m) is +5.6/-4.5dB.

4. Environmental Conditions Temperature 15°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar

5. Test date: 2 February to 5 February 2010

Tested By: Peter

Standard Requirement: 47 CFR §15.249

.**Procedures:** Equipment was setup in a semi-anechoic chamber. For measurements above 1GHz an average measurement was taken with a 10Hz video bandwidth. The EUT was tested at low, mid, high with the highest output power. Investigated up to 10th harmonics of the operating frequency.

Sample Calculation:

EUT Field Strength= Raw Amplitude(dBuV/m) — Amplifier Gain(dB) + Antenna Factor(dB) + Cable Loss(dB) + Filter Attenuation(dB, if used)

Test Result:



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 17 of 43 www.siemic.com.

Fundamental

Low channel

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.249/15.209	15.249/15.209	
GHz	Degree	Meter	H/V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
2.402	15	1.06	٧	5.15	55.00	102.34	114.00	-11.66	PK
2.402	11	1.87	h	5.15	55.00	104.30	114.00	-9.7	PK
2.402	13	1.06	٧	5.15	55.00	79.51	94.00	-14.49	AV
2.402	15	1.87	h	5.15	55.00	81.20	94.00	-12.80	AV

Middle channel

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.249/15.209	15.249/15.209	
GHz	Degree	Meter	H/V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
2.441	2	1.15	٧	5.15	55.00	104.22	114.00	-9.78	PK
2.441	16	2.01	h	5.15	55.00	100.51	114.00	-13.49	PK
2.441	2	1.15	٧	5.15	55.00	82.39	94.00	-11.61	AV
2.441	23	2.01	h	5.15	55.00	83.18	94.00	-10.82	AV

High channel

ingh chumici									
Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.249/15.209	15.249/15.209	
GHz	Degree	Meter	H/V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
2.480	354	1.36	٧	5.15	55.00	99.42	114.00	-14.58	PK
2.480	16	1.94	h	5.15	55.00	100.59	114.00	-13.41	PK
2.480	354	1.36	٧	5.15	55.00	80.58	94.00	-13.42	AV
2.480	29	1.94	h	5.15	55.00	81.67	94.00	-12.33	AV

x, y, z axis has been checked, only worst orientation test result is presented in this test result.

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 18 of 43 www.siemic.com.

@ 2402MHz @ 3 Meter

				_					
Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.249/15.209	15.249/15.209	
GHz	Degree	Meter	H/V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.804	16	1.21	٧	5.15	55.00	60.47	74.00	-13.53	Peak
4.804	7	1.87	h	5.15	55.00	62.33	74.00	-11.67	Peak
4.804	16	1.21	٧	5.15	55.00	49.51	54.00	-4.49	Ave
4.804	7	1.87	h	5.15	55.00	48.64	54.00	-5.36	Ave
7.206	28	1.31	٧	7.23	55.00	58.24	74.00	-15.76	Peak
7.206	36	1.97	h	7.23	55.00	59.61	74.00	-14.39	Peak
7.206	28	1.34	٧	7.23	55.00	47.68	54.00	-6.32	Ave
7.206	37	2.09	h	7.23	55.00	48.60	54.00	-5.40	Ave

Emission was scanned up to 25GHz.

@ 2441MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.249/15.209	15.249/15.209	
GHz	Degree	Meter	H/V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.882	34	1.08	٧	5.16	55.00	61.53	74.00	-12.47	Peak
4.882	40	1.64	h	5.16	55.00	60.08	74.00	-13.92	Peak
4.882	34	1.07	٧	5.16	55.00	48.79	54.00	-5.21	Ave
4.882	40	1.72	h	5.16	55.00	48.93	54.00	-5.07	Ave
7.323	2	1.34	٧	7.31	55.00	57.32	74.00	-16.68	Peak
7.323	34	1.98	h	7.31	55.00	58.64	74.00	-15.36	Peak
7.323	52	1.25	٧	7.31	55.00	47.92	54.00	-6.08	Ave
7.323	43	2.06	h	7.31	55.00	48.27	54.00	-5.73	Ave

Emission was scanned up to 25GHz.

@ 2480MHz @ 3Meter

	e zhounitz e shieur								
Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.249/15.209	15.249/15.209	
GHz	Degree	Meter	H/V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.960	62	1.32	٧	5.17	55.00	60.18	74.00	-13.82	Peak
4.960	18	1.79	h	5.17	55.00	59.41	74.00	-14.59	Peak
4.960	65	1.24	٧	5.17	55.00	48.77	54.00	-5.23	Ave
4.960	5	1.87	h	5.17	55.00	47.92	54.00	-6.08	Ave
7.440	32	1.12	٧	7.36	55.00	61.25	74.00	-12.75	Peak
7.440	41	2.05	h	7.36	55.00	60.81	74.00	-13.19	Peak
7.440	57	1.22	٧	7.36	55.00	47.61	54.00	-6.39	Ave
7.440	42	2.19	h	7.36	55.00	47.00	54.00	-7.00	Ave

Emission was scanned up to 25GHz.



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 19 of 43 www.siemic.com.cn

Band edge

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading			
GHz	Degree	Meter	H/V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
2.400	15	1.20	٧	3.81	55.00	46.2	74.00	-27.8	Peak
2.400	32	1.69	h	3.81	55.00	46.8	74.00	-27.2	Peak
2.400	15	1.20	٧	3.81	55.00	34.6	54.00	-19.4	Ave
2.400	32	1.69	h	3.81	55.00	33.2	54.00	-20.8	Ave
2.4835	11	1.42	٧	3.90	55.00	45.8	74.00	-28.2	Peak
2.4835	38	1.99	h	3.90	55.00	44.6	74.00	-29.4	Peak
2.4835	11	1.42	٧	3.90	55.00	33.4	54.00	-20.6	Ave
2.4835	38	1.99	h	3.90	55.00	34.6	54.00	-19.4	Ave



| Serial#: 1002073 |
| Issue Date: 8 Februray 2010 |
| Page: 20 of 43 |
| www.siemic.com.cn

Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Model	Serial #	Calibration Due
Conducted Emissions			
R&S Receiver	ESPI 3	101216	02/19/2010
Com-Power LISN	LI 115	241090	05/02/2010
Com-Power LISN	LI 115	241091	05/02/2010
Com-Power LIMITER	LIT-153	531021	N/A
Radiated Emissions			
R&S Receiver	ESPI 3	101216	02/19/2010
Sunol Sciences, Inc. Antenna (30MHz~2GHz)	JB1	A112107	10/04/2010
Horn Antenna (1~18GHz)	A-INFOMW	JXTXLB-10180	11/18/2010
Horn Antenna (1~18GHz)	N/A	N/A	10/04/2010
Pre-Amplifier(0.1 ~ 18GHz)	MITEQ	AMF-7D-00101800- 30-10P	03/05/2010
HP Pre-Amplifier	8447F	1937A01160	04/24/2010

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 21 of 43 www.siemic.com.

Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in <u>Annex B</u>.
- 2. The power supply for the EUT was fed through a $50\Omega/50\mu H$ EUT LISN, connected to filtered mains.
- The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
- 4. All other supporting equipments were powered separately from another main supply.

Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition.
- 2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
- 3. High peaks, relative to the limit line, were then selected.
- 4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
- 5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz $\lim_{t \to 0} t = 250 \,\mu\text{V} = 47.96 \,d\text{B}\mu\text{V}$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00 \text{ dB}\mu\text{V}$ (Calibrated for system losses)

Therefore, Q-P margin = 47.96 - 40.00 = 7.96 i.e. **7.96 dB below limit**

Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



 Serial#:
 1002073

 Issue Date:
 8 Februray 2010

 Page:
 23 of 43

 www.siemic.com.cn

Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from $0 \circ 100$ with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
- 5. Repeat step 4 until all frequencies need to be measured were complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
Above 1000	Average	1 MHz	10 Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any) And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz. VBW = 10Hz.

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



 Serial#:
 1002073

 Issue Date:
 8 Februray 2010

 Page:
 24 of 43

 www.siemic.com.cn

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Please see attachment

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 25 of 43 www.siemic.com.

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION


The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
Host Computer	SL020660 & SAW5114366	N/A
Dell Monitor	SE198WFPf & N/A	2m VGA Cable
Dell Keyboard	SK-8115 & N/A	2m USB Cable
Dell Mouse	MOC5UO & H0S00A91	USB Cable unshield 1.5m

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions





 Serial#:
 1002073

 Issue Date:
 8 Februray 2010

 Page:
 28 of 43

 www.siemic.com.cn

Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was running test program to stimulate the worst case.



 Serial#:
 1002073

 Issue Date:
 8 Februray 2010

 Page:
 29 of 43

 www.siemic.com.cn

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment

1002073 Issue Date: 8 Februray 2010

Annex E. SIEMIC ACCREDITATION CERTIFICATES

SIEMIC ACREDITATION DETAILS: A2LA Certificate Number: 2742.01



ACCREDITED LABORATORY

A2LA has accredited

SIEMIC LABORATORIES

San Jose, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 18 June 2005).



Presented this 11th day of July 2008

President For the Accreditation Council Certificate Number 2742.01 Valid to September 30, 2010

For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation



THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION

ACCREDITED PRODUCT CERTIFICATION BODY

A2LA has accredited

SIEMIC INC.

San Jose, CA

for technical competence as a

Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 General requirements for bodies operating product certification systems. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), IDA (Singapore) and IC (Canada) requirements.

Presented this 9th day of January 2009.

President

For the Accreditation Council Certificate Number: 2742.02 Valid to: September 30, 2010

For the product certification schemes to which this accreditation applies. please refer to the certification body's Scope of Accreditation.

Issue Date: 8 Februray 2010

SIEMIC ACCREDITATION DETAILS: FCC Registration NO:986914



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 32 of 43 www.siemic.com

SIEMIC ACCREDITATION DETAILS: FCC Listing, Registration NO:986914

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division 7435 Oakland Mills Road Columbia, MD 21046

April 25, 2008

Registration Number: 986914

SIEMIC Nanjing (China) Laboratories 2-1 Longcang Avenue, Yuhua Economic and Technology Development Park, Nanjing, 210039 China

Attention: Leslie Bai

Re: Measurement facility located at 2-1 Longcang Avenue, Nanjing, China

Anechoic chamber (3 meters) and 3&10 meter OATS

Date of Listing: April 25, 2008

Dear Sir or Madam:

Your request for registration of the subject measurement facility has been reviewed and found to be in compliance with the requirements of Section 2.948 of the FCC rules. The information has, therefore, been placed on file and the name of your organization added to the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Katie Hawkins Electronics Engineer

1002073 Serial#: Issue Date: 8 Februray 2010

SIEMIC ACCREDITATION DETAILS: Industry of Canada Registration No. 4842

Industry Industrie

February 19, 2009

OUR FILE: 46405-4842 Submission No: 131645

SIEMIC NANJING (CHINA) LABORATORIES

2-1 Longcang Avenue Yuhua Economic & Technology Dev. Park Nanjing China

Attention: Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration of a 3m/10m alternative test site. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (4842B-1). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- Your primary code is: 4842
- The company number associated to the site(s) located at the above address is: 4842B

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 meter OATS or 3 meter chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;

http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely

For: Wireless Laboratory Manager Certification and Engineering Bureau 3701 Carling Ave., Building 94 P.O. Box 11490, Station "H" Ottawa, Ontario K2H 8S2

Email: joshua laviolette@ic.gc.ce Tel. No. (613) 990-2681 Fax. No. (613) 990-4752



Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 34 of 43 www.siemic.com.c

SIEMIC ACCREDITATION DETAILS: Japan VCCI Accreditation No. 3081





CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Main Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

This is to certify that the following measuring facility has been registered in accordance with the Rules for Voluntary Control Measures

Registration No.: C-3421

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010





Serial#: 1002073 Issue Date: 8 Februray Page: 35 of 43 www.siemi

SIEMIC ACCREDITATION DETAILS: Japan VCCI Accreditation No. 3081





VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Radiation

3 meter site)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

This is to certify that the following measuring facility has been registered in accordance with the Rules for Voluntary Control Measures

Registration No.: R-3083

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010





Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 36 of 43 www.siemic.com.

SIEMIC ACCREDITATION DETAILS: Japan VCCI Accreditation No. 3081





VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Telecominication Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

This is to certify that the following measuring facility has been registered in accordance with the Rules for Voluntary Control Measures

Registration No.: T-1597

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010





Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 37 of 43 www.siemic.com.c

SIEMIC ACCREDITATION DETAILS: Korea CAB from NIST: US0160



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899

October 1, 2008

Mr. Leslie Bai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Radio Research Agency (RRA) Korea Communications Commission (KCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.

Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131

Identification No.: US0160

Recognized Scope: EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI

KN22: Test Method for EMI

EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS Wireless: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,

RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21,

RRL Notice 2007-80, RRL Notice 2004-68

Wired: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6

President Notice 20664, RRL Notice 2008-7 with attachment 4

You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

Standards Services Division

Panil To alde

Enclosure

cc: Ramona Saar

NIST

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 38 of 43

SIEMIC ACCREDITATION DETAILS: Taiwan BSMI CAB Accreditation No. SL2-IN-E-1130R



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899-

May 3, 2006

Mr. Leslie Bai SIEMIC Laboratories 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: SL2-IN-E-1130R (Must be applied to the test reports)

U.S Identification No: US0160
 Scope of Designation: CNS 13438
 Authorized signatory: Mr. Leslie Bai

The names of all recognized CABs will be posted on the NIST website at http://ts.nist.gov/mra. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

12 audi

cc: Jogindar Dhillon

NIST

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 39 of 43 www.siemic.com

www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: Taiwan NCC CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899-

March 16, 2009

Mr. LeslieBai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) for the requested scope expansion under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name:

SIEMIC, Inc.

Physical Location:

2206 Ringwood Avenue, San Jose, CA 95131

Identification No.:

US0160

Current Scope:

LP0002, PSTN01, ADSL01, ID0002, IS6100 and CNS 14336

Additional Scope: PLMN07

You may submit test data to NCC to verify that the equipment to be imported into China satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

12 acre

Standards Services Division

Enclosure

cc: Ramona Saar

NST

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 40 of 43 www.siemic.com

SIEMIC ACCREDITATION DETAILS: Mexico NOM Recognition



Laboratorio Valentín V. Rivero

Maxico D.F. a 16 de octubre de 2006.

LESLIE BAI DIRECTOR OF CERTIFICATION SIEMIC LABORATORIES, INC. ACCESSING GLOBAL MARKETS P.R.E.S.E.N.T.E.

En contestación a su escrito de fecha 5 de septembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo qual adjunto a este escrito encontrara el Acuerdo en Idioma ingles y español prelienado de los quales le pido sea revisado y en su caso corregido, para que si esta de acuerdo poder firmario para mandario con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediano gester será la empresa Isacel de México. S. A. de C. V., empresa que ha calaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que quenta con amplia experiencia en la gestoria de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de ustad enviándole un cordial seludo y experendo sus comentarios al Acuerdo que nos ocupa.

Atentamente:

Ing. Faustino Sorfez González Gerorito-Psorfico del Laboratorio de GAMEN.

College 71 Family en Condeta Derto Maeo, D7 Ter 52ts 2000 con 12 tress Family 2000 may 2000 con

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 41 of 43 www.siemic.com.

SIEMIC ACCREDITATION DETAILS: Hong Kong OFTA Recognition No. D23/16V



Your Ref 來函檔號: Our Ref 本局檔號: D23/16 V Telephone 電話: (852) 2961 6320 Fax No 圖文傳真: (852) 2838 5004

E-mail 電郵地址:

20 July 2005

Mr. Leslie Bai Director of Certification, SIEMIC Laboratories 2206 Ringwood Avenue San Jose, California 95131 USA

Dear Mr. Bai,

Application of Recognised Testing Agency (RTA)

Referring your submission of 28 June 2005 in relation to the application of RTA, I am pleased to inform you that OFTA has appointed SIEMIC Laboratories (SIEMIC) as a Recognised Testing Agency (RTA):

Please note that, under the Hong Kong Telecommunications Equipment Evaluation and Certification (HKTEC) Scheme, SIEMIC is authorized to conduct evaluation tests on telecommunications equipment against the following HKTA specifications:

Scope of recognition (HKTA Specifications):

1001, 1002, 1004, 1006, 1007, 1008 1010, 1015, 1016 1022, 1026, 1027, 1029 1030, 1031, 1032, 1033, 1034, 1035, 1039

1041, 1042, 1043, 1045, 1047, 1048

2001

You are requested to refer to and comply with the code of practice and guidelines for RTA as given in the Information Note OFTA I 411 "Recognised Testing Agency (RTA) for Conducting Evaluation Test of Telecommunications Equipment", which can be downloaded from OFTA's homepage at http://www.ofta.gov.hk/tec/information-notes.html.

If you have any queries, please do not hesitate to contact me.

Yours sincerely,

(K K Sin)

for Director-General of Telecommunications

Office of the Telecommunications Authority
29/F Wu Chung House 213 Queen's Road East Wan Chai Hong Kong

http://www.ofta.gov.hk

電訊管理局

香港灣仔皇后大道東 213 號胡忠大廈 29 字樓

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 42 of 43

SIEMIC ACCREDITATION DETAILS: OFTA CAB from NIST: US0160



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899-

December 8, 2008

Mr. Leslie Bai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name:

Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA

SIEMIC, Inc.

Identification No.: US016

Recognized Scope: Radio: HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026,

1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041,

1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051

Telecom: HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026,

2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely.

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

Standards Services Division

David I. alden

Enclosure

cc: Ramona Saar

NIST

Serial#: 1002073 Issue Date: 8 Februray 2010 Page: 43 of 43 www.siemic.com

SIEMIC ACCREDITATION DETAILS: Australia NATA Recognition



Leslie Bai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

November 4, 2008

Under Australian government legislation, the Australian Communications and Media Authority (ACMA) has determined the National Association of Testing Authorities, Australia (NATA) as an accreditation body as per Section 409(1) of the Telecommunications Act 1997 (Cth). Pursuant to Section 409(2) of the Telecommunications Act 1997 (Cth), I am pleased to advise that your laboratory has been determined as a Recognised Testing Authority (RTA).

This determination has been made on the basis of your accreditation by A2LA accreditation no. 2742.01 and the Mutual Recognition Agreement between NATA and A2LA. It is effective from 11 July 2008. RTA status applies only to the following standards and is contingent upon their continued inclusion in your laboratory's scope of accreditation.

AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S041 and AS/ACIF S043.2

As an RTA, your laboratory has the following obligations:

- 1. the laboratory shall continue to meet all of the accreditation criteria of A2LA;
- the authorised representative of the laboratory shall notify NATA of changes to the staff or operations of the laboratory which would affect the performance of the tests for which the laboratory has been determined;
- compliance of equipment shall be reported on test reports bearing the A2LA logo/endorsement.

Current information on the Australian Communications and Media Authority and regulatory requirements for telecommunications products within Australia can be obtained from the ACMA's web-site at "http://www.acma.gov.au. Further information about NATA may be gained by visiting "http://www.nata.asm.au.

Please note that AS/ACIF S040 and New Zealand standards do not form part of the RTA scheme.

Your RTA listing will appear on the NATA website shortly.

Kind Regards

Chris Norton,
Senior Scientific Officer
Measurement Science and Technology
National Association of Testing Authorities (NATA)
71-73 Flemington Road
North Melbourne Vic 3051
Australia
Ph: +61 3 9329 1633 Fx: +61 3 9326 5148

Ph: +61 3 9329 1633 Fx: +61 3 9326 5148
E-Mail: Christopher.Norton@nata.asn.au
Internet: www.nata.asn.au