

Mühlau, 04.01.2018

RF Exposure Considerations for the ARU 3400

FCC ID: WJ9-ARU3400

The transmitter operation for the ARU 3400 covers the 902 – 928MHz operating band. The ARU3400 supports up to three external antennas but operates on only one antenna at a time.

The following FCC Rule Parts and procedures are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

Part 2.1091 – Radiofrequency radiation exposure evaluation: mobile devices

KDB447498 D01 v06

Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies

MPE CALCULATIONS

The MPE calculation used to calculate the safe operating distance for the user is:

$$S = \text{EIRP}/4 \pi R^2$$

Where

S = Power density

EIRP = Effective Isotropic Radiated Power (EIRP = P x G)

P = Conducted Transmitter Power

G = Antenna Gain (relative to an isotropic radiator)

R = distance to the centre of radiation of the antenna (safe operating distance)

ARU3400 Values:

Transmitter frequency range: 902 – 928MHz

Transmitter power: (Ref 15.247 (b)(4) – Antennas with gains >6dBi)

KATHREIN Sachsen GmbH

Lindenstraße 3
09241 Mühlau
Germany

Phone: +49 3722 60 73 10
Fax: +49 3722 60 73 24
info@kathrein-sachsen.de
www.kathrein-sachsen.de

Your reference: [Klicken Sie hier, um Ihr Zeichen einzubuchen.](#)

Your letter: [Klicken Sie hier, um Ihre Nachricht einzubuchen.](#)

Our reference: [Klicken Sie hier, um Unser Zeichen einzubuchen.](#)

VAT Reg. No.: DE 140 915 677

Company headquarters: Mühlau
HRB 2398 Chemnitz

Managing director(s): Daniel Schkalda

Bank details:

EUR-Accounts:

Deutsche Bank Chemnitz
IBAN: DE28 8707 0000 0263 7270 00
BIC: DEUTDE8CXXX

Volksbank Chemnitz
IBAN: DE60 8709 6214 0320 0014 47
BIC: GENODEF1CH1

Sparkasse Mittelsachsen
IBAN: DE93 8705 2000 3545 0015 54
BIC: WELADED1FGX

- 1) For external 13dBi gain antenna use, 30dBm max. power is reduced by 7dB (13dBi – 6dB)
EIRP_{max} = +23dBm + 13dBi antenna gain = +36dBm (4.0W)
- 2) For external 10dBi gain antenna use, 30dBm max. power is reduced by 4dB (10dBi – 6dB)
EIRP_{max} = +26dBm + 10dBi antenna gain = +36dBm (4.0W)
- 3) For internal +6dBi gain antenna use
EIRP_{max} = +30dBm + 6dBi antenna gain = +36dBm (4.0W)

Power Density Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of
FCC Rule Part 1.1310 for 2.4GHz

$$S_{req1} = f_{MHz}/1500 \text{ mW/cm}^2 = 902/1500 = 0.6 \text{ mW/cm}^2$$

Calculation:

$$S = \text{EIRP} / 4 \pi R^2$$

$$R = \sqrt{\text{EIRP} / 4 \pi S}$$

$$R = \sqrt{4000 / (4 \pi \times 0.6)}$$

$$R = \sqrt{4000 / (7.54)}$$

$$R = 23.0$$

$$R = 23\text{cm}$$

Conclusion

The safe operating distance for the ARU3400 for General Population/ Uncontrolled Exposure limits is a minimum of 23cm using for all antennas specified to be used with the equipment

Signature:  Date: 04/01/2018

Daniel Schkalda
Managing director