

# FCC Part 15C

## Measurement and Test Report

For

**IPEVO corp.**

**3F, No. 53, Bo-ai Road, Taipei, 100 Taiwan**

**FCC ID: WKPCSBB-03IP**

|  |  |
|--|--|
| <b>Report Concerns:</b><br>Original Report | <b>Equipment Type:</b><br>360° Rotating Folio + Wireless Keyboard  |
| <b>Model:</b>                              | <u>CSBB-03IP</u>   |
| <b>Report No.:</b>                         | <u>STR12058276I</u>  |
| <b>Test Date:</b>                          | <u>2012-05-24 to 2012-05-30</u>  |
| <b>Issue Date:</b>                         | <u>2012-06-04</u>  |
| <b>Tested By:</b>                          | <u>Vigoss Xiong / Engineer</u>    |
| <b>Reviewed By:</b>                        | <u>Lahm Peng / EMC Manager</u>    |
| <b>Approved &amp; Authorized By:</b>       | <u>Jandy so / PSQ Manager</u>   |
| <b>Prepared By:</b>                        | <b>SEM.Test Compliance Service Co., Ltd.</b><br>3/F, Jinbao Commerce Building, Xin'an Fanshen Road,<br>Bao'an District, Shenzhen, P.R.C. (518101)<br>Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn |

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

**TABLE OF CONTENTS**

|   |           |
|---|-----------|
| <b>1. GENERAL INFORMATION.....</b>                            | <b>4</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....   | 4         |
| 1.2 TEST STANDARDS.....                                       | 4         |
| 1.3 TEST METHODOLOGY.....                                     | 5         |
| 1.4 TEST FACILITY.....  | 5         |
| 1.5 EUT TEST MODE.....  | 6         |
| 1.6 ACCESSORIES EQUIPMENT LIST AND DETAILS.....               | 6         |
| 1.7 EUT CABLE LIST AND DETAILS.....                           | 6         |
| <b>2. SUMMARY OF TEST RESULTS.....</b>                        | <b>7</b>  |
| <b>3. ANTENNA REQUIREMENT.....</b>                            | <b>8</b>  |
| 3.1 STANDARD APPLICABLE.....                                  | 8         |
| 3.2 EVALUATION INFORMATION.....                               | 8         |
| <b>4. FREQUENCY HOPPING SYSTEM REQUIREMENTS.....</b>          | <b>9</b>  |
| 4.1 STANDARD APPLICABLE.....                                  | 9         |
| 4.2 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....          | 9         |
| 4.3 FREQUENCY HOPPING SYSTEM.....                             | 10        |
| <b>5. NUMBER OF HOPPING CHANNELS AND CHANNEL SPACING.....</b> | <b>11</b> |
| 5.1 STANDARD APPLICABLE.....                                  | 11        |
| 5.2 TEST EQUIPMENT LIST AND DETAILS.....                      | 11        |
| 5.3 TEST PROCEDURE.....                                       | 11        |
| 5.4 ENVIRONMENTAL CONDITIONS.....                             | 11        |
| 5.5 SUMMARY OF TEST RESULTS/PLOTS.....                        | 12        |
| <b>6. DWELL TIME OF A HOPPING CHANNEL.....</b>                | <b>14</b> |
| 6.1 STANDARD APPLICABLE.....                                  | 14        |
| 6.2 TEST EQUIPMENT LIST AND DETAILS.....                      | 14        |
| 6.3 TEST PROCEDURE.....                                       | 14        |
| 6.4 ENVIRONMENTAL CONDITIONS.....                             | 14        |
| 6.5 SUMMARY OF TEST RESULTS/PLOTS.....                        | 15        |
| <b>7. 20-DB BANDWIDTH.....</b>                                | <b>21</b> |
| 7.1 STANDARD APPLICABLE.....                                  | 21        |
| 7.2 TEST EQUIPMENT LIST AND DETAILS.....                      | 21        |
| 7.3 TEST PROCEDURE.....                                       | 21        |
| 7.4 ENVIRONMENTAL CONDITIONS.....                             | 21        |
| 7.5 SUMMARY OF TEST RESULTS/PLOTS.....                        | 21        |
| <b>8. POWER OUTPUT.....</b>                                   | <b>24</b> |
| 8.1 STANDARD APPLICABLE.....                                  | 24        |
| 8.2 TEST EQUIPMENT LIST AND DETAILS.....                      | 24        |
| 8.3 TEST PROCEDURE.....                                       | 24        |
| 8.4 ENVIRONMENTAL CONDITIONS.....                             | 24        |
| 8.5 SUMMARY OF TEST RESULTS/PLOTS.....                        | 25        |
| <b>9. FIELD STRENGTH OF SPURIOUS EMISSIONS.....</b>           | <b>26</b> |
| 9.1 MEASUREMENT UNCERTAINTY.....                              | 26        |
| 9.2 STANDARD APPLICABLE.....                                  | 26        |
| 9.3 TEST EQUIPMENT LIST AND DETAILS.....                      | 26        |
| 9.4 TEST PROCEDURE.....                                       | 27        |
| 9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....             | 27        |
| 9.6 ENVIRONMENTAL CONDITIONS.....                             | 27        |
| 9.7 SUMMARY OF TEST RESULTS/PLOTS.....                        | 28        |
| <b>10. OUT OF BAND EMISSIONS.....</b>                         | <b>37</b> |
| 10.1 STANDARD APPLICABLE.....                                 | 37        |
| 10.2 TEST EQUIPMENT LIST AND DETAILS.....                     | 37        |
| 10.3 TEST PROCEDURE.....                                      | 37        |
| 10.4 ENVIRONMENTAL CONDITIONS.....                            | 38        |
| 10.5 SUMMARY OF TEST RESULTS/PLOTS.....                       | 38        |

**11. CONDUCTED EMISSION.....42**

11.1 MEASUREMENT UNCERTAINTY .....42

11.2 TEST EQUIPMENT LIST AND DETAILS .....42

11.3 TEST PROCEDURE.....42

11.4 BASIC TEST SETUP BLOCK DIAGRAM.....42

11.5 ENVIRONMENTAL CONDITIONS .....43

11.6 TEST RECEIVER SETUP .....43

11.7 SUMMARY OF TEST RESULTS/PLOTS .....43

11.8 CONDUCTED EMISSIONS TEST DATA.....43

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: IPEVO corp.  
Address of applicant: 3F, No. 53, Bo-ai Road, Taipei, 100 Taiwan

Manufacturer: Dion International Co., Ltd  
Address of manufacturer: Chenwu, Houjie Town, Dongguan City, Guangdong Province, China

#### General Description of E.U.T

| Items               | Description                             |
|---------------------|---|
| Product Name:       | 360° Rotating Folio + Wireless Keyboard |
| Trade Name:         | IPEVO                                   |
| Model No.:          | CSBB-03IP                               |
| Adding Model:       | /                                       |
| Rated Voltage:      | DC 3.7V Lithium Battery                 |
| Max. Output Power:  | -3.232dBm (Conducted)                   |
| Antenna Gain        | 2.0 dBi                                 |
| Frequency range:    | 2402-2480MHz                            |
| Number of channels: | 79                                      |
| Channel Separation: | 1MHz                                    |
| Type of Antenna:    | PCB Antenna                             |
| Bluetooth Version:  | V3.0                                    |
| Modulation:         | GFSK(1Mbps)                             |

*Note: The test data is gathered from a production sample, provided by the manufacture.*

### 1.2 Test Standards

The following report is prepared on behalf of the Shenzhen IPEVO corp. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

### 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted with Low Channel, Middle Channel and High Channel, accordingly in reference to the Operating Instructions.

### 1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

## 1.5 EUT Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements, all testing shall be perform at the low, middle, high channel.

Modulation Configure

| Modulation | Packet | Packet Type | Packet Size |
|------------|--------|-------------|-------------|
| GFSK       | DH1    | 4           | 27          |
|            | DH3    | 11          | 183         |
|            | DH5    | 15          | 339         |
| Pi/4 QDPSK | 2DH1   | 20          | 54          |
|            | 2DH3   | 26          | 367         |
|            | 2DH5   | 30          | 379         |
| 8DPSK      | 3DH1   | 24          | 83          |
|            | 3DH3   | 27          | 552         |
|            | 3DH5   | 31          | 1021        |

Normal mode: the Bluetooth has been tested on the modulation of GFSK.

EDR mode: the Bluetooth has been tested on the modulation of ( $\Pi/4$ )QDPSK and 8DPSK, compliance test and record the worst case on 8DPSK.

## 1.6 Accessories Equipment List and Details

| Description | Manufacturer | Model | Serial Number |
|-------------|--------------|-------|---------------|
| N/A/        | N/A/         | N/A/  | N/A/          |

## 1.7 EUT Cable List and Details

| Cable Description | Length (M) | Shielded/Unshielded | With Core/Without Core |
|-------------------|------------|---------------------|------------------------|
| N/A/              | N/A/       | N/A/                | N/A/                   |

## 2. SUMMARY OF TEST RESULTS

| FCC RULES                   | DESCRIPTION OF TEST            | RESULT    |
|-----------------------------|--------------------------------|-----------|
| § 15.203; § 15.247(b)(4)(i) | Antenna Requirement            | Compliant |
| § 15.247(a)(1)(iii)         | Quantity of Hopping Channel    | Compliant |
| § 15.247(a)(1)              | Channel Separation             | Compliant |
| § 15.247(a)(1)(iii)         | Time of Occupancy (Dwell time) | Compliant |
| § 15.247(a)                 | 20dB Bandwidth                 | Compliant |
| § 15.247(b)(1)              | Power Output                   | Compliant |
| § 15.209(a)(f)              | Radiated Emission              | Compliant |
| § 15.247(d)                 | Band Edge                      | Compliant |
| § 15.207(a)                 | Conducted Emission             | Compliant |
| § 15.247(a)(1)              | Frequency Hopping Sequence     | Compliant |
| § 15.247(g), (h)            | Frequency Hopping System       | Compliant |

### **3. ANTENNA REQUIREMENT**

---

#### **3.1 Standard Applicable**

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Evaluation Information**

This product has a permanent antenna, fulfill the requirement of this section.



## 4. Frequency Hopping System Requirements

### 4.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.


### 4.2 EUT Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.


Number of shift register stages: 9

Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits

Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 4.3 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

## 5. NUMBER OF HOPPING CHANNELS AND CHANNEL SPACING

### 5.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 5.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2012-03-28 | 2013-03-27 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2012-03-28 | 2013-03-27 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 5.3 Test Procedure

According to the DA 00-705, the number of hopping frequencies test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = the frequency band of operation (2400MHz to 2483.5MHz)

RBW = 100kHz, VBW = 100kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize, observed the band of 2400MHz to 2483.5MHz, than count it out the number of channels for comparing with the FCC rules.

The channel spacing test method as follows:

Set span = wide enough to capture the peaks of two adjacent channels

Other setting as above

Allow the trace to stabilize, Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 5.4 Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 24 °C     |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

5.5 Summary of Test Results/Plots


Test mode: GFSK DH5

No. of Channel = 79


2402-2480MHz




Channel Spacing (Low CH=1MHz)



Channel Spacing (Middle CH=1MHz)



Channel Spacing (High CH=1MHz)



## 6. DWELL TIME OF A HOPPING CHANNEL

### 6.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 6.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2012-03-28 | 2013-03-27 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2012-03-28 | 2013-03-27 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 6.3 Test Procedure

According to the DA 00-705, the dwell time of a hopping channel test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = zero span, centered on a hopping channel

RBW = 1MHz, VBW = 1MHz

Sweep = auto

Detector function = peak

Trace = max hold

Use the marker-delta function to determine the dwell time

### 6.4 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 24 °C     |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

## 6.5 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length).

Test data is corrected with the worse case, which the packet length is DH1, DH3, DH5.


The test period:  $T = 0.4 \text{ Second} \times 79 \text{ Channel} = 31.6 \text{ s}$

Dwell time = time slot length  $\times$  (Hopping rate / Number of hopping channels)  $\times$  Period


| Modulation | Test Channel | Packet | Time Slot Length | Dwell Time | Limit |
|------------|--------------|--------|------------------|------------|-------|
|            |              |        | ms               | ms         | ms    |
| GFSK       | 2402MHz      | DH1    | 0.210            | 67.2       | 400   |
|            |              | DH3    | 0.210            | 33.6       | 400   |
|            |              | DH5    | 0.210            | 22.4       | 400   |
|            | 2441MHz      | DH1    | 0.210            | 67.2       | 400   |
|            |              | DH3    | 0.220            | 35.2       | 400   |
|            |              | DH5    | 0.220            | 23.5       | 400   |
|            | 2480MHz      | DH1    | 0.210            | 67.2       | 400   |
|            |              | DH3    | 0.210            | 33.6       | 400   |
|            |              | DH5    | 0.210            | 22.4       | 400   |

Please see the test plots as below:

DH1 time slot:  
CH Low:




CH Mid:






CH High:




DH3 time slot:


CH Low:




CH Mid:




CH High:




DH5 time slot:  
CH Low:



CH Mid:



CH High:



## 7. 20-dB BANDWIDTH

### 7.1 Standard Applicable

According to 15.247(a)(1)(iii). For frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

### 7.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2012-03-28 | 2013-03-27 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2012-03-28 | 2013-03-27 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 7.3 Test Procedure

According to the DA 00-705, the 20dB bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 3MHz, centered on a hopping channel

RBW  $\geq$  1% 20dB Bandwidth, VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down bandwidth of the emission.

### 7.4 Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 53%       |
| ATM Pressure:      | 1018 mbar |

### 7.5 Summary of Test Results/Plots


| Frequency<br>MHz | 20 dB Bandwidth DH5<br>kHz | Limit<br>dB |
|------------------|----------------------------|-------------|
| 2402             | 1043                       | /           |
| 2441             | 1042                       | /           |
| 2480             | 1041                       | /           |

## DH5 Mode


CH Low:



CH Mid:



CH High:



## 8. POWER OUTPUT

### 8.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### 8.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2012-03-28 | 2013-03-27 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2012-03-28 | 2013-03-27 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 8.3 Test Procedure

According to the DA 00-705, the peak output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 5MHz, centered on a hopping channel

RBW = 1MHz, VBW = 1MHz

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, the indicated level is the peak output power (the external attenuation and cable loss shall be considered).

### 8.4 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 24 °C     |
| Relative Humidity: | 55%       |
| ATM Pressure:      | 1011 mbar |



## 8.5 Summary of Test Results/Plots

Conducted Power: DH5

| Channel        | Frequency<br>MHz | Measured Value<br>dBm | Output Power<br>mW | Limit<br>mW |
|----------------|------------------|-----------------------|--------------------|-------------|
| Low Channel    | 2402             | -3.500                | 0.4467             | 1000        |
| Middle Channel | 2441             | -3.232                | 0.4751             | 1000        |
| High Channel   | 2480             | -3.553                | 0.4413             | 1000        |

Note: the antenna gain of 2.0dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

## 9. FIELD STRENGTH OF SPURIOUS EMISSIONS

### 9.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.10$  dB.

### 9.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 9.3 Test Equipment List and Details

| Description              | Manufacturer         | Model     | Serial Number | Cal. Date  | Due. Date  |
|--------------------------|----------------------|-----------|---------------|------------|------------|
| Spectrum Analyzer        | R&S                  | FSP       | 836079/035    | 2012-03-28 | 2013-03-27 |
| EMI Test Receiver        | R&S                  | ESVB      | 825471/005    | 2012-03-28 | 2013-03-27 |
| Positioning Controller   | C&C                  | CC-C-1F   | N/A           | 2012-03-28 | 2013-03-27 |
| RF Switch                | EM                   | EMSW18    | SW060023      | 2012-03-28 | 2013-03-27 |
| Pre-amplifier            | Agilent              | 8447F     | 3113A06717    | 2012-03-28 | 2013-03-27 |
| Pre-amplifier            | Compliance Direction | PAP-0118  | 24002         | 2012-03-28 | 2013-03-27 |
| Trilog Broadband Antenna | SCHWARZBECK          | VULB9163  | 9163-333      | 2012-02-25 | 2013-02-24 |
| Horn Antenna             | ETS                  | 3117      | 00086197      | 2012-02-25 | 2013-02-24 |
| Horn Antenna             | ETS                  | 3116B     | 00088203      | 2012-02-25 | 2013-02-24 |
| Loop Antenna             | SCHWARZECK           | HFRA 5165 | 9365          | 2012-03-28 | 2013-03-27 |


**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

## 9.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



## 9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

## 9.6 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1012 mbar |

## 9.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst margin of:


**-7.13 dB $\mu$ V at 32.4059 MHz in the Vertical polarization for Middle Channel Mode, 9 kHz to 25 GHz,  
3 Meters**

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

From 30 MHz to 1 GHz


Test Mode: Charging

Horizontal




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>(°) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 218.3085           | 27.65               | 5.81            | 33.46              | 46.00             | -12.54         | 264           | 100            | peak   |
| 2   | 361.7139           | 24.39               | 10.69           | 35.08              | 46.00             | -10.92         | 113           | 200            | peak   |
| 3   | 407.5144           | 22.50               | 11.22           | 33.72              | 46.00             | -12.28         | 287           | 100            | peak   |
| 4   | 739.6603           | 19.65               | 18.07           | 37.72              | 46.00             | -8.28          | 359           | 110            | peak   |

Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 32.4059   | 22.93    | 8.44    | 31.37    | 40.00    | -8.63  | 234    | 100    | peak   |
| 2   | 39.7146   | 18.87    | 9.64    | 28.51    | 40.00    | -11.49 | 118    | 100    | QP     |
| 3   | 437.1198  | 22.41    | 11.18   | 33.59    | 46.00    | -12.41 | 164    | 100    | QP     |
| 4   | 875.2469  | 19.24    | 18.80   | 38.04    | 46.00    | -7.96  | 359    | 100    | peak   |

From 30 MHz to 1 GHz  
Test Mode: Transmitting-Low channel 2402MHz  
Horizontal




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 216.7828  | 21.66    | 5.72    | 27.38    | 46.00    | -18.62 | 162    | 100    | peak   |
| 2   | 361.7139  | 26.39    | 10.69   | 37.08    | 46.00    | -8.92  | 200    | 100    | peak   |
| 3   | 407.5145  | 24.00    | 11.22   | 35.22    | 46.00    | -10.78 | 359    | 100    | peak   |
| 4   | 739.6604  | 19.15    | 18.07   | 37.22    | 46.00    | -8.78  | 359    | 100    | peak   |

Vertical



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 32.4059   | 24.09    | 8.44    | 32.53    | 40.00    | -7.47  | 240    | 100    | peak   |
| 2   | 39.4371   | 20.61    | 9.60    | 30.21    | 40.00    | -9.79  | 187    | 100    | peak   |
| 3   | 100.9339  | 17.39    | 6.75    | 24.14    | 43.50    | -19.36 | 220    | 100    | peak   |
| 4   | 893.8567  | 19.41    | 19.27   | 38.68    | 46.00    | -7.32  | 359    | 100    | peak   |


From 30 MHz to 1 GHz  
Test Mode: Transmitting-Middle channel 2441MHz  
Horizontal



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 39.7146   | 23.05    | 9.64    | 32.69    | 40.00    | -7.31  | 67     | 100    | peak   |
| 2   | 361.7139  | 24.89    | 10.69   | 35.58    | 46.00    | -10.42 | 274    | 100    | peak   |
| 3   | 407.5144  | 27.50    | 11.22   | 38.72    | 46.00    | -7.28  | 359    | 200    | peak   |
| 4   | 739.6604  | 19.15    | 18.07   | 37.22    | 46.00    | -8.78  | 359    | 200    | peak   |



Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 32.4059   | 24.43    | 8.44    | 32.87    | 40.00    | -7.13  | 57     | 100    | peak   |
| 2   | 39.7146   | 20.87    | 9.64    | 30.51    | 40.00    | -9.49  | 94     | 100    | peak   |
| 3   | 437.1199  | 18.41    | 11.18   | 29.59    | 47.00    | -17.41 | 115    | 100    | peak   |
| 4   | 875.2470  | 19.24    | 18.80   | 38.04    | 47.00    | -8.96  | 359    | 100    | peak   |

From 30 MHz to 1 GHz


Test Mode: Transmitting-High channel 2480MHz

Horizontal



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 34.5172   | 24.03    | 8.80    | 32.83    | 40.00    | -7.17  | 234    | 100    | peak   |
| 2   | 39.7147   | 23.05    | 9.64    | 32.69    | 40.00    | -7.31  | 170    | 100    | peak   |
| 3   | 361.7139  | 24.89    | 10.69   | 35.58    | 46.00    | -10.42 | 200    | 100    | peak   |
| 4   | 407.5144  | 24.50    | 11.22   | 35.72    | 46.00    | -10.28 | 359    | 100    | peak   |

Vertical



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 33.0950   | 19.86    | 8.56    | 28.42    | 40.00    | -11.58 | 215    | 100    | peak   |
| 2   | 103.0800  | 17.27    | 6.54    | 23.81    | 40.00    | -16.19 | 200    | 100    | peak   |
| 3   | 739.6604  | 18.55    | 18.07   | 36.62    | 47.00    | -10.38 | 310    | 100    | peak   |

*Spurious Emission Above 1GHz**Test Mode: Transmitting*

| Frequency<br>MHz         | Detector | Meter<br>Reading<br>dBuV | Direction<br>Degree | Polar<br>H / V | Antenna<br>Loss<br>dB | Cable loss<br>dB | Amplifier<br>dB | Correction<br>Amplitude<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB |
|--------------------------|----------|--------------------------|---------------------|----------------|-----------------------|------------------|-----------------|-----------------------------------|-----------------|--------------|
| Low Channel (2402MHz)    |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4804.0                   | AV       | 28.44                    | 57                  | H              | 34.1                  | 5.2              | 33.0            | 34.74                             | 54              | -19.26       |
| 4804.0                   | AV       | 27.39                    | 35                  | V              | 34.1                  | 5.2              | 33.0            | 33.69                             | 54              | -20.31       |
| 7206.0                   | AV       | 28.41                    | 60                  | H              | 37.4                  | 6.1              | 33.5            | 38.41                             | 54              | -15.59       |
| 7206.0                   | AV       | 26.97                    | 79                  | V              | 37.4                  | 6.1              | 33.5            | 36.97                             | 54              | -17.03       |
| 4804.0                   | PK       | 41.21                    | 65                  | H              | 34.1                  | 5.2              | 33.0            | 47.51                             | 74              | -26.49       |
| 4804.0                   | PK       | 43.46                    | 98                  | V              | 34.1                  | 5.2              | 33.0            | 49.76                             | 74              | -24.24       |
| 7206.0                   | PK       | 41.64                    | 256                 | H              | 37.4                  | 6.1              | 33.5            | 51.64                             | 74              | -22.36       |
| 7206.0                   | PK       | 40.84                    | 185                 | V              | 37.4                  | 6.1              | 33.5            | 50.84                             | 74              | -23.16       |
| Middle Channel (2441MHz) |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4882.0                   | AV       | 29.11                    | 21                  | H              | 34.1                  | 5.2              | 33.0            | 35.41                             | 54              | -18.59       |
| 4882.0                   | AV       | 27.64                    | 34                  | V              | 34.1                  | 5.2              | 33.0            | 33.94                             | 54              | -20.06       |
| 7323.0                   | AV       | 29.51                    | 342                 | H              | 37.4                  | 6.1              | 33.5            | 39.51                             | 54              | -14.49       |
| 7323.0                   | AV       | 28.69                    | 30                  | V              | 37.4                  | 6.1              | 33.5            | 38.69                             | 54              | -15.31       |
| 4882.0                   | PK       | 41.21                    | 237                 | H              | 34.1                  | 5.2              | 33.0            | 47.51                             | 74              | -26.49       |
| 4882.0                   | PK       | 42.17                    | 354                 | V              | 34.1                  | 5.2              | 33.0            | 48.47                             | 74              | -25.53       |
| 7323.0                   | PK       | 38.46                    | 264                 | H              | 37.4                  | 6.1              | 33.5            | 48.46                             | 74              | -25.54       |
| 7323.0                   | PK       | 39.31                    | 187                 | V              | 37.4                  | 6.1              | 33.5            | 49.31                             | 74              | -24.69       |
| High Channel (2480MHz)   |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4960.0                   | AV       | 30.19                    | 17                  | H              | 34.1                  | 5.2              | 33.0            | 36.49                             | 54              | -17.51       |
| 4960.0                   | AV       | 29.30                    | 13                  | V              | 34.1                  | 5.2              | 33.0            | 35.60                             | 54              | -18.40       |
| 7440.0                   | AV       | 26.04                    | 355                 | H              | 37.4                  | 6.1              | 33.5            | 36.04                             | 54              | -17.96       |
| 7440.0                   | AV       | 26.76                    | 66                  | V              | 37.4                  | 6.1              | 33.5            | 36.76                             | 54              | -17.24       |
| 4960.0                   | PK       | 42.84                    | 50                  | H              | 34.1                  | 5.2              | 33.0            | 49.14                             | 74              | -24.86       |
| 4960.0                   | PK       | 43.99                    | 59                  | V              | 34.1                  | 5.2              | 33.0            | 50.29                             | 74              | -23.71       |
| 7440.0                   | PK       | 38.14                    | 269                 | H              | 37.4                  | 6.1              | 33.5            | 48.14                             | 74              | -25.86       |
| 7440.0                   | PK       | 39.68                    | 64                  | V              | 37.4                  | 6.1              | 33.5            | 49.68                             | 74              | -24.32       |

*Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*

*The measurements greater than 20dB below the limit from 9kHz to 30MHz..*

## 10. OUT OF BAND EMISSIONS

### 10.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 10.2 Test Equipment List and Details

| Description              | Manufacturer         | Model       | Serial Number | Cal. Date  | Due. Date  |
|--------------------------|----------------------|-------------|---------------|------------|------------|
| Spectrum Analyzer        | R&S                  | FSP         | 836079/035    | 2012-03-28 | 2013-03-27 |
| EMI Test Receiver        | R&S                  | ESVB        | 825471/005    | 2012-03-28 | 2013-03-27 |
| Positioning Controller   | C&C                  | CC-C-1F     | N/A           | 2012-03-28 | 2013-03-27 |
| RF Switch                | EM                   | EMSW18      | SW060023      | 2012-03-28 | 2013-03-27 |
| Pre-amplifier            | Agilent              | 8447F       | 3113A06717    | 2012-03-28 | 2013-03-27 |
| Pre-amplifier            | Compliance Direction | PAP-0118    | 24002         | 2012-03-28 | 2013-03-27 |
| Trilog Broadband Antenna | SCHWARZBECK          | VULB9163    | 9163-333      | 2012-02-25 | 2013-02-24 |
| Horn Antenna             | ETS                  | 3117        | 00086197      | 2012-02-25 | 2013-02-24 |
| Spectrum Analyzer        | Agilent              | E4402B      | US41192821    | 2012-03-28 | 2013-03-27 |
| Attenuator               | ATTEN                | ATS100-4-20 | /             | 2012-03-28 | 2013-03-27 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 10.3 Test Procedure

According to the DA 00-705, the band-edge radiated test method as follows.

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2410MHz for low bandedge, 2470MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205.

According to the DA 00-705, the band-edge conducted test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2380MHz to 2410MHz for low bandedge, 2470MHz to 2500MHz for the high bandedge)

RBW = 100kHz, VBW = 300kHz

Sweep = auto; Detector function = peak; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the limit specified in this section (at least 20dB attenuation).

#### 10.4 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 23°C      |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |


#### 10.5 Summary of Test Results/Plots

| Test mode | Frequency<br>MHz | Limit<br>dBuV /dB | Result |
|-----------|------------------|-------------------|--------|
| Lowest    | 2353.48          | <54dBuV           | Pass   |
|           | 2390.00          | <54dBuV           | Pass   |
|           | 2400.00          | >20dBc            | Pass   |
| Highest   | 2483.50          | <54dBuV           | Pass   |
|           | 2500.00          | <54dBuV           | Pass   |

The edge emissions are below the FCC 15.209 Limits or complies with the 15.247(d) requirements.


Please refer to the test plots as below.

Bandedge (Radiated)  
Lowest Bandedge



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Remark           |
|-----|-----------|----------|---------|----------|----------|--------|------------------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   |                  |
| 1   | 2310.000  | 32.31    | -11.72  | 20.59    | 50.00    | -29.41 | Average Detector |
|     | 2310.000  | 47.39    | -11.72  | 35.67    | 74.00    | -38.33 | Peak Detector    |
| 2   | 2353.478  | 39.12    | -11.73  | 27.39    | 50.00    | -22.61 | Average Detector |
|     | 2353.478  | 53.73    | -7.41   | 46.32    | 74.00    | -27.68 | Peak Detector    |
| 3   | 2390.000  | 32.70    | -11.75  | 20.95    | 50.00    | -29.05 | Average Detector |
|     | 2390.000  | 48.48    | -11.75  | 36.73    | 74.00    | -37.27 | Peak Detector    |
| 4   | 2400.000  | 62.04    | -11.75  | 50.29    | /        | /      | Average Detector |
| 5   | 2402.047  | 86.34    | -11.75  | 74.59    | /        | /      | Average Detector |


Highest Bandedge




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Remark           |
|-----|-----------|----------|---------|----------|----------|--------|------------------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   |                  |
| 1   | 2483.500  | 39.74    | -11.78  | 27.96    | 50.00    | -22.04 | Average Detector |
|     | 2483.500  | 47.35    | -11.78  | 35.57    | 74.00    | -38.43 | Peak Detector    |
| 2   | 2500.000  | 32.58    | -11.78  | 20.80    | 50.00    | -29.20 | Average Detector |
|     | 2500.000  | 45.56    | -11.78  | 33.78    | 74.00    | -40.22 | Peak Detector    |



Bandedge (Conducted)  
Lowest Bandedge



Highest Bandedge



## 11. CONDUCTED EMISSION

### 11.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

### 11.2 Test Equipment List and Details

| Description       | Manufacturer    | Model    | Serial Number | Cal. Date  | Due. Date  |
|-------------------|-----------------|----------|---------------|------------|------------|
| EMI Test Receiver | Rohde & Schwarz | ESPI     | 101611        | 2012-03-28 | 2013-03-27 |
| L.I.S.N           | Schwarz beck    | NSLK8126 | 8126-224      | 2012-03-28 | 2013-03-27 |
| Pulse Limiter     | Rohde & Schwarz | ESH3-Z2  | 100911        | 2012-03-28 | 2013-03-27 |


### 11.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 11.4 Basic Test Setup Block Diagram



11.5 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1012 mbar |

11.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz  
Stop Frequency..... 30 MHz  
Sweep Speed ..... Auto  
IF Bandwidth..... 10 kHz  
Quasi-Peak Adapter Bandwidth ..... 9 kHz  
Quasi-Peak Adapter Mode ..... Normal

11.7 Summary of Test Results/Plots


According to the data in section 3.8, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:

**-7.31 dBµV at 0.182 MHz in the Neutral mode, Peak detector, 0.15-30MHz**

11.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


Conducted Disturbance  
EUT: 360 ° Rotating Folio + Wireless Keyboard  
M/N: CSBB-03IP  
Operating Condition: Charging  
Test Specification: Neutral  
Comment: AC 120V/60Hz; USB 5V



| EDIT PEAK LIST (Prescan Results) |            |            |                |
|----------------------------------|------------|------------|----------------|
| Trace1:                          | -QP        |            |                |
| Trace2:                          | -AV        |            |                |
| Trace3:                          | ---        |            |                |
| TRACE                            | FREQUENCY  | LEVEL dBμV | DELTA LIMIT dB |
| 1 Max Peak                       | 182 kHz    | 57.07      | -7.31          |
| 2 Average                        | 182 kHz    | 44.01      | -10.37         |
| 1 Max Peak                       | 658 kHz    | 37.02      | -18.97         |
| 2 Average                        | 2.078 MHz  | 30.86      | -15.13         |
| 1 Max Peak                       | 2.598 MHz  | 39.00      | -16.99         |
| 2 Average                        | 2.598 MHz  | 32.04      | -13.95         |
| 1 Max Peak                       | 29.626 MHz | 51.49      | -8.50          |
| 2 Average                        | 29.626 MHz | 40.97      | -9.02          |

Plot of Conducted Emissions Test Data

Conducted Disturbance  
EUT: 360 ° Rotating Folio + Wireless Keyboard  
M/N: CSBB-03IP  
Operating Condition: Charging  
Test Specification: Line  
Comment: AC 120V/60Hz; USB 5V



| EDIT PEAK LIST (Prescan Results) |            |            |                |
|----------------------------------|------------|------------|----------------|
| Trace1:                          | -QP        |            |                |
| Trace2:                          | -AV        |            |                |
| Trace3:                          | ---        |            |                |
| TRACE                            | FREQUENCY  | LEVEL dBμV | DELTA LIMIT dB |
| 1 Max Peak                       | 182 kHz    | 55.68      | -8.70          |
| 2 Average                        | 182 kHz    | 44.44      | -9.95          |
| 1 Max Peak                       | 2.078 MHz  | 36.33      | -19.66         |
| 2 Average                        | 2.078 MHz  | 29.55      | -16.44         |
| 1 Max Peak                       | 2.502 MHz  | 39.18      | -16.81         |
| 2 Average                        | 2.598 MHz  | 31.38      | -14.61         |
| 1 Max Peak                       | 29.618 MHz | 51.58      | -8.41          |
| 2 Average                        | 29.618 MHz | 41.63      | -8.36          |

\*\*\*\*\* END OF REPORT \*\*\*\*\*