# **TA80TA1**

**Motherboard Guide** 

# FEDERAL COMMUNICATIONS COMMISSION INTERFERENCE STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/ TV technician for help.

#### **CAUTION:**

Any changes or modifications not expressly approved by the grantee of this device could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

#### RF exposure warning

This equipment must be installed and operated in accordance with provided instructions and the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm

from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. End-users and installers must be provide with antenna installation instructions and transmitter operating conditions for satisfying RF exposure compliance.

#### **End Product Labeling**

This transmitter module is authorized only for use in device where the antenna may be installed such that 20cm may be maintained between the antenna and users. The final end product must be labeled in a visible area with the following: "Contains FCC ID: WL6-TABC8TA1"

### Information for the OEMs and Integrators

The following statement must be included with all versions of this document supplied to an

OEM or integrator, but should not be distributed to the end user.

- 1) This device is intended for OEM integrators only.
- Please see the full Grant of Equipment document for other restrictions.

This radio transmitter FCC ID: **WL6-TABC8TA1** has been approved by FCC to operate with the antenna types listed below with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

**Antenna List** 

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	JEM		PCB Antenna	2.85 dBi for 2.4GHz
2	WGT		PCB Antenna	1.77 dBi for 2.4GHz

Note: The antenna connector is I-PEX type.

# **Motherboard layout**

### Main components

No.	Name	No.	Name
Α	Charger IC	D	WiFi/BT IC
В	CPU+PMIC+DDR+ EMMC+CODEC	Е	Rear facing camera
С	GPS IC	F	Microphone

### System connectors

No.	Name	No.	Name
1	Battery Connector	5	Speaker Connectors
2	LCD Connector	6	Side Key FPC Connector
3	GPS Antenna Connector	7	TP Connector
4	WiFi Antenna Connector		

### I/O Ports

No.	Name	No.	Name
1	Ultrastick Connector	4	T-Flash Connector
2	Micro USB Connector	5	Mini HDMI port
3	Audio Jack		

# Features

Processor	<ul> <li>IntelBayTrail-TZ3735E</li> <li>Quad core</li> <li>Base 1.33 GHz, Burst to 1.83GHz, 2MB L2 Cache</li> </ul>
Memory	<ul><li>DDR3L-RS 1333, 1 x 32-bits</li><li>1GB (Default) / 2GB (Optional)</li></ul>
Graphics	Intel HD Graphics (Gen 7 gfx)     Max resolution upto1280x800
Storage	Single eMMC v4.5.1     Default 16 GB
Wireless	<ul> <li>Wi-Fi 802.11 b/g/n</li> <li>Bluetooth 3.0 w/o high speed supported</li> </ul>
Display	MIPI interface     Support 10-point multi-touch
Cameras Control	FrontCamera:2.0M     Rear Camera:5.0M
Antenna	• 802.11b/g,n, BT: 2.4GHz; GPS

Input/Output	<ul> <li>1 x MicroUSB 2.0, OTG port (Type A/B)</li> <li>1 x Mic/head phone jack combo (American type)</li> <li>1 x Micro HDMI 1.4</li> <li>1 x Micro SD card slot (Support 128M-32G TF Card)</li> <li>1 x Analog MIC</li> </ul>
Speaker & Mic	Build-in Speaker x 2     Internal Analog MIC x 1