



AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX A

Tel: +886 2 26099301
Fax: +886 2 26099303

APPENDIX A

TEST PLOTS

(Model: mPAD-12.....)

TABLE OF CONTENTS

A.1 EMISSION BANDWIDTH MEASUREMENT	2
A.1.1 Emission Bandwidth Result.....	2
A.1.2 Measurement Plots	4
A.2 MAXIMUM OUTPUT POWER MEASUREMENT	15
A.2.1 Emission Bandwidth Result.....	15
A.3 EMISSION LIMITATIONS MEASUREMENT.....	24
A.4 POWER SPECTRAL DENSITY.....	108
A.4.1 Power Spectral Density	108

A.1 EMISSION BANDWIDTH MEASUREMENT

Test Date	2016/06/08	Temp./Hum.	25°C/58%
Cable Loss	N/A	Test Voltage	AC 120V, 60Hz

A.1.1 Emission Bandwidth Result

Modulation Type	UNII Band	Centre Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit
802.11a	I	5180	18.91	16.235	Reference only
		5200	18.83	16.252	
		5240	19.37	16.261	
	II-2A	5260	20.50	16.314	
		5300	19.45	16.271	
		5320	19.41	16.249	
	II-2C	5500	19.23	16.255	
		5600	19.25	16.282	
		5700	19.22	16.238	
		5720	19.43	16.248	
802.11ac-VHT20	I	5180	25.11	17.963	Reference only
		5200	32.18	18.192	
		5240	39.37	19.063	
	II-2A	5260	39.77	19.403	
		5300	31.04	18.141	
		5320	24.81	17.985	
	II-2C	5500	22.47	17.857	
		5600	26.53	18.013	
		5700	22.53	17.903	
		5720	22.33	17.865	

AUDIX Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303


Modulation Type	UNII Band	Centre Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit
802.11ac-VHT40	I	5190	43.87	36.425	Reference only
		5230	76.67	37.674	
	II-2A	5270	77.77	37.588	
		5310	44.10	36.538	
	II-2C	5510	43.56	36.469	
		5590	61.07	36.889	
		5670	71.70	37.175	
		5710	43.84	36.500	
802.11ac-VHT80	I	5210	86.75	76.216	Reference only
	II-2A	5290	88.82	76.264	
	II-2C	5530	87.39	76.163	
		5610	123.10	78.093	
		5690	96.24	76.373	

Modulation Type	UNII Band	Centre Frequency (MHz)	6dB Bandwidth (MHz)	Limit
802.11a	III	5745	15.98	≥ 500kHz
		5785	15.93	
		5825	15.92	
802.11ac-VHT20	III	5745	17.77	
		5785	17.78	
		5825	17.75	
802.11ac-VHT40	III	5755	36.42	
		5795	36.49	
802.11ac-VHT80	III	5775	76.07	






A.1.2 Measurement Plots

802.11a

UNII Band I








UNII Band II-2A



802.11a


UNII Band II-2C










802.11ac-VHT20

UNII Band I



UNII Band II-2A





AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

802.11ac-VHT20

UNII Band II-2C












802.11ac-VHT40


UNII Band II-2C






802.11ac-VHT80




UNII Band I




UNII Band II-2A



UNII Band II-2C





A.2 MAXIMUM OUTPUT POWER MEASUREMENT

A.2.1 Emission Bandwidth Result

Test Date	2016/06/06 ~ 20	Temp./Hum.	25°C/58%
Cable Loss	N/A	Test Voltage	AC 120V, 60Hz

Modulation Type	UNII Band	Centre Frequency (MHz)	Output Power		10log (1/X)	MAX Output Power		Limit
			Chain 0	Chain 1		(dBm)	(W)	
802.11a	I	5180	14.07	13.66	0.22	16.90	0.048978	< 250 mW (24 dBm)
		5200	14.76	14.54		17.68	0.058614	
		5240	15.22	14.11		17.73	0.059293	
	II-2A	5260	15.45	15.10		18.30	0.067608	
		5300	14.86	15.32		18.12	0.064863	
		5320	13.38	13.23		16.34	0.043053	
	II-2C	5500	14.11	12.60		16.45	0.044157	
		5600	15.15	15.27		18.24	0.066681	
		5700	13.10	12.63		15.91	0.038994	
		5720	10.69	11.17		13.99	0.025061	
	III	5720	3.72	3.77		6.96	0.004966	< 1 W (30 dBm)
		5745	13.80	13.15		16.52	0.044875	
		5785	15.29	14.96		18.15	0.065313	
		5825	15.35	14.51		17.98	0.062806	

Note: The results have been included cable loss.

Modulation Type	UNII Band	Centre Frequency (MHz)	Output Power		10log (1/X)	MAX Output Power		Limit
			Chain 0	Chain 1		(dBm)	(W)	
802.11ac-VHT20	I	5180	14.56	14.74	1.67	17.78	0.059979	< 250 mW (24 dBm)
		5200	14.70	15.04		18.00	0.063096	
		5240	15.37	15.63		18.61	0.072611	
	II-2A	5260	15.22	15.46		18.46	0.070146	
		5300	14.37	15.14		17.90	0.061660	
		5320	13.85	14.30		17.23	0.052845	
	II-2C	5500	14.15	13.17		16.85	0.048417	
		5600	14.29	14.47		17.52	0.056494	
		5700	12.93	13.08		16.19	0.041591	
		5720	9.66	9.32		12.89	0.019454	
	III	5720	3.96	4.16		8.30	0.006761	< 1 W (30 dBm)
		5745	13.50	13.22		16.54	0.045082	
		5785	14.04	13.64		17.00	0.050119	
		5825	14.90	14.36		17.77	0.059841	
802.11ac-VHT40	I	5190	8.15	7.82	2.60	13.59	0.022856	< 250 mW (24 dBm)
		5230	13.62	13.75		19.29	0.084918	
	II-2A	5270	13.46	13.37		19.02	0.079799	
		5310	8.10	8.72		14.03	0.025293	
	II-2C	5510	8.36	9.69		14.68	0.029376	
		5590	13.31	13.71		19.12	0.081658	
		5670	12.62	12.72		18.28	0.067298	
		5710	9.60	9.74		15.28	0.033729	
	III	5710	-0.13	-0.51		5.29	0.003381	< 1 W (30 dBm)
		5755	11.63	11.71		17.28	0.053456	
		5795	13.30	13.07		18.79	0.075683	

Note: The results have been included cable loss.

AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Modulation Type	UNII Band	Centre Frequency (MHz)	Output Power		10log (1/X)	MAX Output Power		Limit
			Chain 0	Chain 1		(dBm)	(W)	
802.11ac-VHT80	I	5210	6.58	7.11	3.47	12.46	0.017620	< 250 mW (24 dBm)
	II-2A	5290	8.64	9.60		14.75	0.029854	
	II-2C	5530	6.95	7.48		12.83	0.019187	
		5610	13.11	13.93		19.15	0.082224	
		5690	8.12	8.24		13.79	0.023933	
	III	5690	-4.92	-6.34		0.04	0.001009	< 1 W (30 dBm)
		5775	10.64	10.71		16.28	0.042462	




Note: The results have been included cable loss.


802.11a


UNII Band II-2C




UNII Band III










802.11ac-VHT80

UNII Band II-2C



802.11ac-VHT80

UNII Band III

