





RF Exposure Report

FCC ID: WLQTSRX

Applicant: DEI Sales, Inc., dba Polk Audio

Address: 5541 FERMI COURT, CARLSBAD, CA,92008, USA

Manufacturer: Polk Audio, LLC

Address: 5541 FERMI COURT, CARLSBAD, CA,92008, USA

Product(s): True Surround Home Theatre System

Brand(s): pok

Test Model(s): TSRX1 TRUE SURROUND SB

Series Model(s): N/A

Test Date: Mar. 10, 2022 ~ Apr. 13, 2022

Issued Date: May 14, 2022

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang

Town, Dongguan, China

Test Firm Registration No.: 915896

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by:

Tank Tan

Reviewed by:

Scott He

Scott He

Harry Li

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of the federal government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of the federal government agencies.

Lab: <u>Hwa-Hsing (Dongguan) Testing Co., Ltd.</u>
Address: <u>No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park,</u>

HuangJiang Town, Dongguan, China

Tel: <u>0769-83078199</u> Web.: <u>www.hwa-hsing.com</u>

E-Mail: customerservice.dg@hwa-hsing.com



Table of contents

Releas	se control record	3
	General Information	
	RF exposure limit	
3	Calculation result of maximum conducted power	6

Tel: 0769-83078199 Web.: www.hwa-hsing.com E-Mail: customerservice.dg@hwa-hsing.com



HWA-HSING Test Report No.: 220115KH01-SE-US-01

Release control record

Issue No.	Reason for change	Date issued
220115KH01-SE-US-01	Original Release	May 18, 2022

Lab: Hwa-Hsing (Dongguan) Testing Co., Ltd. Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park,

HuangJiang Town, Dongguan, China

Tel: <u>0769-83078199</u>

Web.: www.hwa-hsing.com
E-Mail: customerservice.dg@hwa-hsing.com



1 General Information

1.1 General Description of EUT

Product(s)	True Surround Home Theatre System	
Test Model(s)	TSRX1 TRUE SURROUND SB	
Series Model(s)	N/A	
Status of EUT	Engineering Prototype	
Power Supply Rating	AC Input 100-240V~ 50/60Hz 65W	
Modulation Type	GFSK, π/4DQPSK,8DPSK	
Transfer Rate	1/2/3Mbps	
Operating Frequency	2402 ~ 2480MHz	
Number of Channel	79	
Output Power (AVG)	7.63dBm	
Antenna Type	PCB Antenna	
Antenna Gain	1.54dBi Maximum peak Gain	
Antenna Connector	N/A	
Accessory Device	Infrared remote controller	
Cable Supplied	AC Cable: Unshieled, Detachable, 190cm	

Note:

- 1. Please refer to the EUT photo document (Reference No.: 220115KH01-1&-2) for detailed product photo.
- 2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

Lab: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park,

Lives lines Town, Designing China

HuangJiang Town, Dongguan, China

Tel: <u>0769-83078199</u> Web.: <u>www.hwa-hsing.com</u>

E-Mail: customerservice.dg@hwa-hsing.com



HWA-HSING Test Report No.: 220115KH01-SE-US-01

2 RF exposure limit

Limits for maximum permissible exposure (MPE)

Limits for general population / uncontrolled exposure					
Frequency range (MHz)	Electric field strength (V/m) Magnetic field strength (A/m)		Power density (mW/cm²)	Average time (minutes)	
300-1500			F/1500	30	
1500-100,000			1.0	30	
Note E. Ever					

Note: F = Frequency in MHz

2.1 MPE calculation formula

 $Pd = (Pout*G) / (4*pi*r^2)$

Where:

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Classification:

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

Lab: <u>Hwa-Hsing (Dongguan) Testing Co., Ltd.</u>
Address: <u>No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park,</u>

HuangJiang Town, Dongguan, China

Tel: <u>0769-83078199</u> Web.: <u>www.hwa-hsing.com</u>

E-Mail: customerservice.dg@hwa-hsing.com



HWA-HSING Test Report No.: 220115KH01-SE-US-01

3 Calculation result of maximum conducted power

The antennas provided to the EUT, please refer to the following table:

the difference provided to the Lot, produce refer to the following table.					
Function	Frequency Band	Antenna Gain (dBi)	Antenna Type	Transmit and Receive Chain	Maximum AVG Power(dBm)
Bluetooth	2400~2483.5MHz	1.54	FPCB	1TX,1RX	7.63

Frequency band (MHz)	Max power	Antenna gain	Distance	Power density	Limit
	(mW)	(dBi)	(cm)	(mW/cm ²)	(mW/cm ²)
2400~2483.5MHz	5.79	1.54	20	0.001643	1.0

Conclusion:

Therefore, the worst-case situation is $\underline{0.001643}$ mW/cm², which is less than "1". This confirmed that the device compliance with FCC 1.1310 MPE limit.

HuangJiang Town, Dongguan, China

Tel: <u>0769-83078199</u> Web.: <u>www.hwa-hsing.com</u>

E-Mail: customerservice.dg@hwa-hsing.com



Appendix - Information on the Testing Laboratories

We, Hwa-Hsing (Dongguan) Co., Ltd., A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values "HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT", commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China

Contact Tel: 0769-83078199

Email: Customerservice.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---

Lab: Hwa-Hsing (Dongguan) Testing Co., Ltd. Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park,

HuangJiang Town, Dongguan, China

Tel: 0769-83078199 Web.: www.hwa-hsing.com

E-Mail: customerservice.dg@hwa-hsing.com