



## Accredited testing-laboratory

**DAR registration number: DAT-P-176/94-D1**

**Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97**

**Recognized by the Federal Communications Commission**

**Anechoic chamber registration no.: 90462 (FCC)**

**Anechoic chamber registration no.: 3462C-1 (IC)**

**Certification ID: DE 0001**

**Accreditation ID: DE 0002**

**Accredited Bluetooth® Test Facility (BQTF)**

*The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Cetecom ICT is under license*

**Test report no. : 1-0648-01-05/08**  
**Type identification : Confidea DU**  
**Applicant : televic nv.**  
**FCC ID : WM7CONFIDEADU**  
**IC Certification No : 7932A-CONFIDEADU**  
**Test standards : 47 CFR Part 15**  
**RSS - 210 Issue 7**

## Table of contents

<b>1</b>	<b>General information</b> .....	<b>3</b>
1.1	Notes .....	3
1.2	Testing laboratory .....	4
1.3	Details of applicant .....	4
1.4	Application details .....	4
<b>2</b>	<b>Test standard/s:</b> .....	<b>5</b>
<b>3</b>	<b>Technical tests</b> .....	<b>6</b>
3.1	Details of manufacturer.....	6
3.1.1	Test item.....	6
3.1.2	Additional EUT information For IC Canada (appendix 2).....	7
3.1.3	RF Technical Brief Cover Sheet acc. To RSS-102 .....	8
3.1.4	EUT operating modes.....	9
3.1.5	Extreme conditions testing values .....	9
<b>4</b>	<b>Summary of Measurement Results and list of all performed test cases</b> .....	<b>10</b>
<b>5</b>	<b>RF measurement testing</b> .....	<b>11</b>
5.1	Description of test set-up.....	11
5.1.1	Radiated measurements.....	11
5.1.2	Conducted measurements.....	11
5.2	Referenced Documents .....	12
5.3	Additional comments .....	12
5.4	Antenna gain .....	12
5.5	Peak Power Spectral density (digitally modulated systems) §15.247(e).....	13
5.6	Spectrum Bandwidth of a DSSS System / 6 dB Bandwidth §15.247(a)(2).....	15
5.7	Spectrum Bandwidth of a DSSS System / 20 dB Bandwidth.....	17
5.8	Maximum output power (conducted) §15.247 (b) (3).....	19
5.9	Max. peak output power (radiated) §15.247 (b)(3) .....	22
5.10	Band-edge compliance of conducted emissions §15.247 (d) .....	23
5.11	Band-edge compliance of radiated emissions §15.205 .....	25
5.12	Spurious Emissions - conducted (Transmitter) §15.247 (c).....	28
5.13	Spurious Emissions - radiated (Transmitter) §15.209 .....	33
5.14	Spurious Emissions - radiated (Receiver) §15.109 / 209 .....	42
5.15	Spurious Emissions - radiated <30 MHz §15.209 .....	46
5.16	Conducted Emissions <30 MHz §15.107/207.....	47
<b>6</b>	<b>Test equipment and ancillaries used for tests</b> .....	<b>49</b>
<b>7</b>	<b>Photographs of the Test Set-up</b> .....	<b>52</b>
<b>8</b>	<b>Photographs of the EUT</b> .....	<b>54</b>

---

## 1 General information

### 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

#### Test laboratory manager:

2009-03-10

Marco Bertolino



Date

Name

Signature

#### Technical responsibility for area of testing:

2009-03-10

Stefan Bös



Date

Name

Signature

## 1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

e-mail: info@ICT.cetecom.de

Internet: http://www.cetecom-ict.de

**State of accreditation:** The test laboratory (area of testing) is accredited according to  
DIN EN ISO/IEC 17025  
DAR registration number: DAT-P-176/94-D1

**Accredited by:** Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97

**Testing location, if different from CETECOM ICT Services GmbH:**

Name :  
Street :  
Town :  
Country :  
Phone :  
Fax :

## 1.3 Details of applicant

<b>Name:</b>	televic nv.
<b>Street:</b>	Leo Bekaertlaan 1
<b>Town:</b>	8870 Izegem
<b>Country:</b>	BELGIUM
<b>Telephone:</b>	+32 51 30 30 45
<b>Fax:</b>	+32 51 33 18 86
<b>Contact:</b>	John Gesquiere
<b>E-mail:</b>	j.gesquiere@televic.com
<b>Telephone:</b>	+32 51 30 30 45

## 1.4 Application details

<b>Date of receipt of order:</b>	2008-08-18
<b>Date of receipt of test item:</b>	2008-08-18
<b>Date of start test:</b>	2008-08-18
<b>Date of end test:</b>	2009-03-10
<b>Persons(s) who have been present during the test:</b>	Mr. Carl Lylon Development engineer

## 2 Test standard/s:

47 CFR Part 15	2007-09	Title 47 of the Code of Federal Regulations; Chapter I- Federal Communications Commission subchapter A - general, Part 15-Radio frequency devices
RSS - 210 Issue 7	2007-06	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

### 3 Technical tests

#### 3.1 Details of manufacturer

Name:	televic nv.
Street:	Leo Bekaertlaan 1
Town:	8870 Izegem
Country:	BELGIUM

##### 3.1.1 Test item

Kind of test item	:	Wireless Discussion System 2.4 / 5 GHz
Type identification	:	Confidea DU
S/N serial number	:	0x22 radiated EUT 0x25 conducted EUT
HW hardware status	:	0.01
SW software status	:	-/-
Frequency Band [MHz]	:	ISM band 2.400 - 2.483,5 MHz
Type of Modulation	:	OFDM
Number of channels	:	11
Antenna	:	Integrated antenna
Power Supply	:	115 V / 15 V AC / DC power supply
Temperature Range	:	-/- °C to -/- °C

**Max. power radiated:** 16.98 dBm  
**Max. power conducted:** 14.88 dBm

**FCC ID:** WM7CONFIDEADU  
**IC:** 7932A-CONFIDEADU

**3.1.2 Additional EUT information For IC Canada (appendix 2)**

IC Registration Number:	<b>7932A-CONFIDEADU</b>
Model Name:	<b>Confidea DU</b>
Manufacturer (complete Address):	<b>televic nv. Leo Bekaertlaan 1 8870 Izegem BELGIUM</b>
Tested to Radio Standards Specification (RSS) No.:	<b>RSS-210 Issue 7</b>
Open Area Test Site Industry Canada Number:	<b>IC 3462C-1</b>
Frequency Range (or fixed frequency) [MHz]:	<b>ISM band 2400 – 2483.5 MHz</b>
RF: Power [W] (max):	<b>OFDM: Rad. EIRP: 49.89 mW Conducted: 30.76 mW</b>
Antenna Type:	<b>Integrated antenna</b>
Occupied Bandwidth (99% BW) [MHz]:	<b>OFDM 6 dB: 16.533 MHz OFDM 20 dB: 19.739 MHz</b>
Type of Modulation:	<b>OFDM</b>
Emission Designator (TRC-43):	<b>16M5G7D 19M7G7D</b>
Transmitter Spurious (worst case) [dBµV/m in 3m]:	<b>29.77</b>
Receiver Spurious (worst case) [dBµV/m in 3m]:	<b>29.27</b>

ATTESTATION:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:



Test engineer: Marco Bertolino      Date: 2009-03-10

### 3.1.3 RF Technical Brief Cover Sheet acc. To RSS-102

All Fields must be completed with the requested information or the following codes: N/A for Not Applicable, N/P for Not Performed or N/V for Not Available. Where applicable, check appropriate box.

1. COMPANY NUMBER: **7932A**
2. MODEL NUMBER: **Confidea DU**
3. MANUFACTURER: **televic nv.**
4. TYPE OF EVALUATION: **(c) RF Evaluation**

- Evaluated against exposure limits: General Public Use  Controlled Use
  - Duty cycle used in evaluation: 40 % highest applicable duty cycle
  - Standard used for evaluation: RSS-102 Issue 2 (2005-11)
  - Measurement distance: 0.20 m
  - RF value: 0.099 V/m  A/m  W/m<sup>2</sup>
- Measured  Computed  Calculated

#### Declaration of RF Exposure Compliance

#### ATTESTATION:

I attest that the information provided in this test report is correct; that a Technical Brief was prepared and the information it contains is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed and that the device meets the SAR and/or RF exposure limits of RSS-102.

Name: Marco Bertolino  
Title: Dipl.-Ing. (FH)  
Company: Cetecom ICT Services GmbH



### 3.1.4 EUT operating modes

EUT operating mode no.*)	Description of operating modes	Additional information
Op. 0	normal mode	normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

\*) EUT operating mode no. is used to simplify the test plan

### 3.1.5 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T <sub>nom</sub>	°C	20
Nominal Humidity	H <sub>nom</sub>	%	54
Nominal Power Source	V <sub>nom</sub>	V	115 V / 15 V

Type of power source: **AC / DC power supply**

Deviations from these values are reported in chapter 2

#### 4 Summary of Measurement Results and list of all performed test cases

- No deviations from the technical specifications were ascertained
- There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	passed	2009-03-10	-/-

Test Specification Clause	Test Case	Pass	Fail	Not applicable	Not performed
None	Antenna Gain	Yes			
§15.247 (e)	Peak power spectral density	Yes			
§15.247(a)(2)	Spectrum Bandwidth of a DSSS System / 6dB BW	Yes			
§15.247(a)(2)	Spectrum Bandwidth of a DSSS System / 20dB BW	Yes			
§ 15.247 (b)(3)	Maximum output power (conducted)	Yes			
§ 15.247 (b)(3)	Max. peak output power (radiated)	Yes			
§15.247 (d)	Band-edge compliance of conducted emissions	Yes			
§15.205	Band-edge compliance of radiated emissions	Yes			
§15.247 (d)	Spurious Emission - conducted (Transmitter)	Yes			
§ 15.209	Spurious Emission -radiated (Transmitter)	Yes			
§ 15.109	Spurious Emissions-radiated (Receiver)	Yes			
§ 15.209	Spurious Emissions-radiated <30 MHz	Yes			
§ 15.107/207	Conducted Emissions <30 MHz	Yes			

## 5 RF measurement testing

### 5.1 Description of test set-up

#### 5.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 20 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber.

The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test set-ups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received.

The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.4-2003 clause 4.2.


Antennas are confirmed with ANSI C63.2-1996 item 15.

- 9 kHz - 150 MHz: Quasi Peak measurement, 200 Hz Bandwidth, passive loop antenna.
- 150 kHz - 30 MHz: Quasi Peak measurement, 9 kHz Bandwidth, passive loop antenna.
- 30 MHz - 200 MHz: Quasi Peak measurement, 120 kHz Bandwidth, bi-conical antenna
- 200MHz - 1GHz: Quasi Peak measurement, 120 kHz Bandwidth, log periodic antenna
- >1GHz: Average, RBW 1MHz, VBW 10 Hz, wave guide horn

All measurement settings are according to FCC 15.209 and 15.207

#### 5.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is connected to the spectrum analyzer. The specific losses for signal path are first checked within a calibration. The measurement readings on the spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



## 5.2 Referenced Documents

Confidea: Reference document for the initiation of the EUT's and further important settings.  
This document is provided by televic n.v.!

Test report: 1-0648-1-10/08 Confidea WCAP

## 5.3 Additional comments

-/-

## 5.4 Antenna gain


The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

	low channel (1) 2412 MHz	mid channel (6) 2437 MHz	high channel (11) 2462 MHz
Conducted power [dBm] <i>(measured)</i>	<b>14.88</b>	14.06	13.55
Radiated power [dBm] <i>(measured)</i>	<b>16.98</b>	16.79	15.90
Gain [dBi] <i>(calculated)</i>	2.10	<b>2.73</b>	2.35


5.5 Peak Power Spectral density (digitally modulated systems) §15.247(e)

OFDM


Plot 1: (result calculated by the Signal analyzer FSIQ from Rohde & Schwarz)



Plot 2: (result calculated by the Signal analyzer FSIQ from Rohde & Schwarz)



Plot 3: (result calculated by the Signal analyzer FSIQ from Rohde & Schwarz)



Results: Plot 1: Power density: - 57.66 dBm/Hz = - 22.86 dBm / 3 kHz  
 Plot 2: Power density: - 57.33 dBm/Hz = - 22.53 dBm / 3 kHz  
 Plot 3: Power density: - 57.86 dBm/Hz = - 23.06 dBm / 3 kHz

Correction factor from dBm/Hz to dBm/3 kHz is +34.8 dB


Limits:

Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission
-----------------------------------	---


5.6 Spectrum Bandwidth of a DSSS System / 6 dB Bandwidth §15.247(a)(2)

OFDM


Plot 1:



Plot 2:



Plot 3:



Results:

Test conditions		6 dB BANDWIDTH [MHz]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	<b>16.533</b>	16.433	16.483
Measurement uncertainty		± 10 kHz		

RBW: 100 kHz / VBW 100 kHz

Limits:


Under normal test conditions only	> 500 kHz
-----------------------------------	-----------




### 5.7 Spectrum Bandwidth of a DSSS System / 20 dB Bandwidth

#### OFDM


Plot 1:



Plot 2:



Plot 3:



Results:

Test conditions		20 dB BANDWIDTH [MHz]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	<b>19.739</b>	19.188	19.539
Measurement uncertainty		± 10 kHz		

RBW: 100 kHz / VBW 100 kHz


Limits:

Under normal test conditions only	> 500 kHz
-----------------------------------	-----------

5.8 Maximum output power (conducted) §15.247 (b) (3)


OFDM

Plot 1:




Date: 10.MAR.2009 10:05:04

Plot 2:



Date: 10.MAR.2009 10:07:06

Plot 3:



Date: 10.MAR.2009 10:09:38

Results:

Test conditions		Max. peak output power [dBm]		
		2412	2437	2462
Frequency [MHz]				
T <sub>nom</sub>	V <sub>nom</sub>	<b>14.88</b>	14.06	13.55
Measurement uncertainty		± 3 dB		

RBW / VBW: 50 MHz / 30 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt / 30 dBm
--	------------------------

### MPE calculation

These equations are generally accurate in the far field of an antenna but will over predict power density in the near field, where they could be used for making a “worst case” prediction.

$$S = PG/4\pi R^2$$

where S = power density ( in appropriate units, e.g. mW/cm<sup>2</sup>)  
P = power input to the antenna (in appropriate units e.g. mW)  
G = power gain of the antenna in the direction of interest relative to the isotropic radiator  
R = distance to the centre of radiation of the antenna (appropriate units e.g. cm)

Or

$$S = EIRP/4\pi R^2$$

where EIRP = equivalent isotropically radiated power

#### Calculation:

(Calculated for max. EIRP)

EIRP: 16.98 dBm (49.89 mW)

calculated at distance of 20 cm:

$$\text{power density} = 49.89 / 4\pi 20^2 = 0.0099 \text{ mW/cm}^2$$

Limit:

1mW/cm<sup>2</sup> is the reference level for general public exposure according to the OET Bulletin 65,  
Edition 97-01 Table 1.

**5.9 Max. peak output power (radiated) §15.247 (b)(3)**

**OFDM**

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	<b>16.98</b>	16.78	15.90
Measurement uncertainty		±3dB		

RBW / VBW: 10 MHz


Measured at a distance of 3m

Limits:


Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------

5.10 Band-edge compliance of conducted emissions §15.247 (d)

Plot 1: lowest channel



Plot 2: highest channel





Limits:


Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
-----------------------------------	--



### 5.11 Band-edge compliance of radiated emissions §15.205

#### OFDM


Plot 1: Max field strength in 3m distance (single frequency) peak



Result:

Frequency	Meter reading	Correction factor	Results
2462 MHz	105.70	-6.4 dB	99.30


Plot 2: Max field strength in 3m distance (single frequency) average



Result:

Frequency	Meter reading	Correction factor	Results
2462 MHz	67.70	-6.4 dB	61.30

Plot 3: Marker-Delta Method RBW/VBW = 1% of span



Result:

Marker-Delta-Value: -38.60 dB

This measurement was made to show that the behaviour of the system is conform to FCC 15.205 (restricted bands)

Results & Limits:

Radiated field strength


The field strength was measured with an EMI measuring receiver and 1 MHz RBW / VBW for peak and with 1MHz RBW / 10Hz VBW for average at a distance of 3m.

high channel	setup	measured value (3m)	correction factor (3m)	calculated value (3m)
Max. peak value	1 MHz RBW 1 MHz VBW	105.70 dB $\mu$ V/m	-6.4 dB	99.30 dB $\mu$ V/m
Max. average value	1 MHz RBW 10 Hz VBW	67.70 dB $\mu$ V/m	-6.4 dB	61.30 dB $\mu$ V/m
Delta value	Peak 300 kHz RBW/VBW	-38.60 dB		
Value at band edge	limit 54 dB $\mu$ V/m			22.70 dB $\mu$ V/m
Statement:				<b>Complies</b>


5.12 Spurious Emissions - conducted (Transmitter) §15.247 (c)

OFDM


Plot 1: Lowest Channel




Plot 2: Lowest Channel




Plot 3: Lowest Channel




Plot 4: Middle Channel




Plot 5: Middle Channel




Plot 6: Middle Channel




Plot 7: Highest Channel



Plot 8: Highest Channel



Plot 9: Highest Channel



Result & Limits:

Emission Limitations					
f [MHz]	amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results	
2412	-9.35	30 dBm		Operating frequency	
No critical peaks detected.		-20 dBc			
2437	-9.83	30 dBm		Operating frequency	
No critical peaks detected.		-20 dBc			
2462	-10.27	30 dBm		Operating frequency	
No critical peaks detected.		-20 dBc			
Measurement uncertainty		± 3dB			

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz  
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
-----------------------------------	--

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.



**5.13 Spurious Emissions - radiated (Transmitter) §15.209**

**OFDM**

Plot 1: 0.03 - 1 GHz (lowest channel)

**Information**


EUT: SCDw 9000 AP + FRA012-S24-1 + confidea CIV + FRA030E-S15-I  
 Serial Number: 0x11 + R301212401 + 19 + R33E11501  
 Test Description: FCC @ 10 m  
 Operating Conditions: Transmit bottom frequency (2412 MHz)  
 Operator Name: Folz  
 Comment: Powered with AC 115V/ 60 Hz

**Scan Setup: FCC\_Fin [EMI radiated]**

Hardware Setup: EMI radiated\Electric Field (NOS)  
 Level Unit: dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30MHz - 1GHz	QuasiPeak	120kHz	15s	Receiver

**FCC\_10m(B)\_4**




**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
37.356450	25.1	15000.000	120.000	100.0	V	231.0	13.4	4.9	30.0	
45.265400	27.0	15000.000	120.000	127.0	V	130.0	13.5	3.0	30.0	
84.962200	19.6	15000.000	120.000	220.0	V	280.0	10.2	10.4	30.0	
171.993800	24.0	15000.000	120.000	114.0	V	231.0	10.2	9.5	33.5	
182.844100	23.3	15000.000	120.000	134.0	V	195.0	10.8	10.2	33.5	
202.214450	25.2	15000.000	120.000	100.0	V	221.0	12.0	8.3	33.5	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]


Subrange 1	
Frequency Range:	30MHz - 2GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 4 GHz (lowest channel)




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 3: 4 - 12 GHz (lowest channel)



Plot 4: 12 - 25 GHz (valid for all channels)



Date: 26.AUG.2008 09:43:38

Plot 5: 0.03 - 1 GHz (middle channel)

**Information**


EUT: SCDw 9000 AP + FRA012-S24-1 + confidea CIV + FRA030E-S15-I  
 Serial Number: 0x11 + R301212401 + 19 + R33E11501  
 Test Description: FCC @ 10 m  
 Operating Conditions: Transmit mid frequency (2437 MHz)  
 Operator Name: Folz  
 Comment: Powered with AC 115V/ 60 Hz

**Scan Setup: FCC\_Fin [EMI radiated]**

Hardware Setup: EMI radiated\Electric Field (NOS)  
 Level Unit: dBµV/m

**Subrange**                      **Detectors**                      **IF Bandwidth**                      **Meas. Time**                      **Receiver**  
 30MHz - 1GHz                      QuasiPeak                      120kHz                      15s                      Receiver

**FCC\_10m(B)\_4**




**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
37.525450	24.8	15000.000	120.000	100.0	V	61.0	13.4	5.2	30.0	
45.729150	25.5	15000.000	120.000	100.0	V	162.0	13.5	4.5	30.0	
319.497600	30.8	15000.000	120.000	115.0	V	280.0	15.3	5.2	36.0	
763.550300	21.3	15000.000	120.000	220.0	V	63.0	24.3	14.7	36.0	
777.346300	21.3	15000.000	120.000	220.0	H	237.0	24.4	14.7	36.0	
911.626850	23.3	15000.000	120.000	140.0	V	221.0	26.2	12.7	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]


Subrange 1	
Frequency Range:	30MHz - 2GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 6: 1 - 4 GHz (middle channel)



The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 7: 4 - 12 GHz (middle channel)



Plot 8: 0.03 - 1 GHz (highest channel)

**Information**


EUT: SCDw 9000 AP + FRA012-S24-1 + confidea CIV + FRA030E-S15-I  
 Serial Number: 0x11 + R301212401 + 19 + R33E11501  
 Test Description: FCC @ 10 m  
 Operating Conditions: Transmit top frequency (2462 MHz)  
 Operator Name: Folz  
 Comment: Powered with AC 115V/ 60 Hz

**Scan Setup: FCC\_Fin [EMI radiated]**

Hardware Setup: EMI radiated\Electric Field (NOS)  
 Level Unit: dBµV/m

**Subrange**                      **Detectors**                      **IF Bandwidth**                      **Meas. Time**                      **Receiver**  
 30MHz - 1GHz                      QuasiPeak                      120kHz                      15s                      Receiver

**FCC\_10m(B)\_4**




**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
30.634996	24.1	15000.000	120.000	115.0	V	132.0	12.7	5.9	30.0	
37.361100	25.2	15000.000	120.000	100.0	V	314.0	13.4	4.8	30.0	
45.715950	24.5	15000.000	120.000	114.0	V	138.0	13.5	5.5	30.0	
55.303050	21.7	15000.000	120.000	172.0	V	235.0	13.1	8.3	30.0	
319.478650	31.2	15000.000	120.000	100.0	V	281.0	15.3	4.8	36.0	
908.304400	23.3	15000.000	120.000	161.0	V	238.0	26.2	12.7	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30MHz - 2GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


Plot 9: 1 - 4 GHz (highest channel)



The carrier signal is notched with a 2.4 GHz band rejection filter.



Plot 10: 4 - 12 GHz (highest channel)



Results:

SPURIOUS EMISSIONS LEVEL §15.209								
2412 MHz			2437 MHz			2462 MHz		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
No critical peaks detected.			No critical peaks detected.			No critical peaks detected.		
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz      f ≥ 1GHz : RBW/VBW: 1 MHz

Limits: § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limits: § 15.109

Frequency (MHz)	Field strength (dBµV/m)	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3

**5.14 Spurious Emissions - radiated (Receiver) §15.109 / 209**

Plot 1: 0.03 - 1 GHz vertical / horizontal (receiver)

**Information**


EUT: SCDw 9000 AP + FRA012-S24-1 + confidea CIV + FRA030E-S15-I  
 Serial Number: 0x11 + R301212401 + 19 + R33E11501  
 Test Description: FCC @ 10 m  
 Operating Conditions: Receive (2,4GHz)  
 Operator Name: Folz  
 Comment: Powered with AC 115V/ 60 Hz

**Scan Setup: FCC\_Fin [EMI radiated]**

Hardware Setup: EMI radiated\Electric Field (NOS)  
 Level Unit: dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30MHz - 1GHz	QuasiPeak	120kHz	15s	Receiver

**FCC\_10m(B)\_4**




**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
30.615250	24.5	15000.000	120.000	115.0	V	86.0	12.7	5.5	30.0	
37.535350	24.3	15000.000	120.000	100.0	V	38.0	13.4	5.7	30.0	
45.250350	26.3	15000.000	120.000	100.0	V	181.0	13.5	3.7	30.0	
50.413200	25.1	15000.000	120.000	100.0	V	211.0	13.6	4.9	30.0	
319.475700	29.9	15000.000	120.000	100.0	V	277.0	15.3	6.1	36.0	
909.887950	23.3	15000.000	120.000	178.0	H	145.0	26.2	12.7	36.0	


Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30MHz - 2GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


Plot 2: 1 - 4 GHz vertical / horizontal (receiver)



Plot 3: 4 - 12 GHz (receiver)



Plot 4: 12 - 25 GHz (receiver)



Date: 26.AUG.2008 09:42:52

Results:

Spurious Emissions level [dBµV/m]		
f[MHz]	Detector	Level [dBµV/m]
No critical peaks detected.		
Measurement uncertainty		±3 dB

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

See above plots

Measurement distance see table

Limits: § 15.109


Frequency (MHz)	Field strength (dBµV/m)	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3

**5.15 Spurious Emissions - radiated <30 MHz §15.209**

Measured at 3 m distance.

Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:




Limits:


Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dBµV/m	30
30 - 88	100 / 40 dBµV/m	3
88 - 216	150 / 43.5 dBµV/m	3
216 - 960	200 / 46 dBµV/m	3
above 960	54 dBµV/m	3

### 5.16 Conducted Emissions <30 MHz §15.107/207


Plot 1: Neutral line TX mode




Plot 2: Phase line TX mode



Plot 3: Neutral line RX mode



Plot 4: Phase line RX mode



Limits:

Under normal test conditions only	See plots
-----------------------------------	-----------



## 6 Test equipment and ancillaries used for tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

All reported calibration intervals are calibrations according to the EN/ISO/IEC 17025 standard. These calibrations were performed from an accredited external calibration laboratory.

Additional to these calibrations the laboratory performed comparison measurements with other calibrated systems and performed a weekly chamber inspection.

All used devices are connected with a 10 MHz external reference.

According to the manufacturers' instruction is it possible to establish a calibration interval for the FSP unit of 24 month, if the device has an external 10 MHz reference.

### *Anechoic chamber C:*

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Anechoic chamber	MWB	87400/02	300000996	Monthly verification		
2	System-Rack 85900	HP I.V.	*	300000222	n.a.		
3	Measurement System 1						
4	Spektrum Analyzer 8566B	HP	2747A05306	300001000	05.10.2006	24	05.10.2008
5	Spektrum Analyzer Display 85662A	HP	2816A16541	300002297	05.10.2006	24	05.10.2008
6	Quasi-Peak-Adapter 85650A	HP	2811A01131	300000999	05.10.2006	24	05.10.2008
7	RF-Preselector 85685A	HP	2837A00779	300000218	08.11.2006	24	08.11.2008
8	PC Vectra VL	HP		300001688	n.a.		
9	Software EMI	HP		300000983	n.a.		
10	Measurement System 2						
11	FSP 30	R&S	100623	ICT 300003464	05.10.2007	24	15.10.2009
12	PC	F+W			n.a.		
13	TILE	TILE			n.a.		
14	Biconical antenna	EMCO	S/N: 860 942/003		Monthly verification (System cal.)		
15	Log. Period. Antenna 3146	EMCO	2130	300001603	Monthly verification (System cal.)		
16	Double Ridged Antenna HP 3115P	EMCO	3088	300001032	Monthly verification (System cal.)		
17	Active Loop Antenna 6502	EMCO	2210	300001015	Monthly verification (System cal.)		
18	Power Supply 6032A	HP	2818A03450	300001040	12.05.2007	36	12.05.2010
19	Busisolator	Kontron		300001056	n.a.		
20	Leitungsteiler 11850C	HP		300000997	Monthly verification (System cal.)		
21	Power attenuator 8325	Byrd	1530	300001595	Monthly verification (System cal.)		
22	Band reject filter WRCG1855/1910	Wainwright	7	300003350	Monthly verification (System cal.)		
23	Band reject filter WRCG2400/2483	Wainwright	11	300003351	Monthly verification (System cal.)		

### *System Rack Room 005 :*

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	FSP 30	R&S		300003575	02.04.2007	24	02.04.2009
2	CBT	R&S	100313	300003516	24.10.2006	24	24.10.2008
3	Switch Matrix	HP		300000929	n.a.		
4	Power Supply	HP	3041A00544	300002270	13.05.2007	36	13.05.2010
5	Signal Generator	R&S	836206/0092	300002680	30.05.2007	36	30.05.2010

**Climatic Box:**

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Climatic box VT 4002	Heraeus Vötsch	58566046820010	300003019	11.05.2007	24	11.05.2009
2	Climatic box CTS T-40/50	CTS	064023	300003540	03.01.2007	24	03.01.2009

**SRD Laboratory Room 002:**

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	System Controller PSM 12	R&S	835259/007	3000002681-00xx	n.a.		
2	Memory Extension PSM-K10	R&S	To 1	3000002681	n.a.		
3	Operating Software PSM-B2	R&S	To 1	3000002681	n.a.		
4	19" Monitor		22759020-ED	3000002681	n.a.		
5	Mouse		LZE 0095/6639	3000002681	n.a.		
6	Keyboard		G00013834L461	3000002681	n.a.		
7	Spectrum Analyser FSIQ 26	R&S	835540/018	3000002681-0005	01.08.2006	24	01.08.2008
8	Tracking Generator FSIQ-B10	R&S	835107/015	3000002681	s.No.7		
10	RF-Generator SMIQ03 (B1 Signal)	R&S	835541/056	3000002681-0002	01.08.2006	36	01.08.2009
11	Modulation Coder SMIQ-B20	R&S	To 10	3000002681	s.No.10		
12	Data Generator SMIQ-B11	R&S	To 10	3000002681	s.No.10		
13	RF Rear Connection SMIQ-B19	R&S	To 10	3000002681	s.No.10		
14	Fast CPU SM-B50	R&S	To 10	3000002681	s.No.10		
15	FM Modulator SM-B5	R&S	835676/033	3000002681	s.No.10		
16	RF-Generator SMIQ03 (B2 Signal)	R&S	835541/055	3000002681-0001	01.08.2006	36	01.08.2009
17	Modulation Coder SMIQ-B20	R&S	To 16	3000002681	s.No.16		
18	Data Generator SMIQ-B11	R&S	To 16	3000002681	s.No.16		
19	RF Rear Connection SMIQ-B19	R&S	To 16	3000002681	s.No.16		
20	Fast CPU SM-B50	R&S	To 16	3000002681	s.No.16		
21	FM Modulator SM-B5	R&S	836061/022	3000002681	s.No.16		
22	RF-Generator SMP03 (B3 Signal)	R&S	835133/011	3000002681-0003	01.08.2006	36	01.08.2009
23	Attenuator SMP-B15	R&S	835136/014	3000002681	S.No.22		
24	RF Rear Connection SMP-B19	R&S	834745/007	3000002681	S.No.22		
25	Power Meter NRVD	R&S	835430/044	3000002681-0004	01.08.2006	24	01.08.2008
26	Power Sensor NRVD-Z1	R&S	833894/012	3000002681-0013	01.08.2006	24	01.08.2008
27	Power Sensor NRVD-Z1	R&S	833894/011	3000002681-0010	01.08.2006	24	01.08.2008
28	Rubidium Standard RUB	R&S		3000002681-0009	01.08.2006	24	01.08.2008
29	Switching and Signal Conditioning Unit SSCU	R&S	338864/003	3000002681-0006	01.08.2006	24	01.08.2008
30	Laser Printer HP Deskjet 2100	HP	N/A	3000002681-0011	n.a.		
31	19" Rack	R&S	11138363000004	3000002681	n.a.		
32	RF-cable set	R&S	N/A	3000002681	n.a.		
33	IEEE-cables	R&S	N/A	3000002681	n.a.		
34	Sampling System FSIQ-B70	R&S	835355/009	3000002681	s.No.7		
35	RSP programmable attenuator	R&S	834500/010	3000002681-0007	01.08.2006	24	01.08.2008
36	Signalling Unit	R&S	838312/011	3000002681	n.a.		
37	NGPE programmable Power Supply for EUT	R&S	192.033.41	3000002681			
39	Power Splitter 6005-3	Inmet Corp.	none	300002841	23.12.2006	24	23.12.2008

40	SMA Cables SPS-1151-985-SPS	Insulated Wire	different	different	n.a.		
41	CBT32 with EDR Signaling Unit	R&S					
42	Coupling unit	Narda	N/A	--	n.a.		
43	2xSwitch Matrix PSU	R&S	872584/021	300001329	n.a.		
44	RF-cable set	R&S	N/A	different	n.a.		
45	IEEE-cables	R&S	N/A	--	n.a.		

Note: 3000002681-00xx inventoried as a system

### *SRD Laboratory Room 011:*

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	NRP Power Meter	R&S	100212	300003780	27.02.2008	24	27.02.2010

### *Anechoic chamber F:*

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Control Computer	F+W	FW0502032	300003303	-/-	-/-	-/-
2	Trilog Antenna	9163-295	-/-	-/-	30.04.2008	24	30.04.2010
3	Amplifier - 0518C-138	Veritech Micro-wave Inc.	-/-	-/-	-/-	-/-	-/-
4	Switch - 3488A	HP		300000368	-/-	-/-	-/-
5	EMI Test receiver - ESCI	R&S	100083	300003312	31.01.2009	24	31.01.2011
6	Turntable Controller - 1061 3M	EMCO	1218	300000661	-/-	-/-	-/-
7	Tower Controller 1051 Controller	EMCO	1262	300000625	-/-	-/-	-/-
8	Tower - 1051	EMCO	1262	300000625	-/-	-/-	-/-
10	Ultra Notch-Filter Rejected band Ch. 62	WRCD	9	-/-	-/-	-/-	-/-

## 7 Photographs of the Test Set-up

Photo documentation:

Photo 1:




Photo 2:



Photo 3:



Photo 4:



## 8 Photographs of the EUT

Photo documentation

Photo 1:



Photo 2:



Photo 3:



Photo 4:



Photo 5:



Photo 6:





Photo 7:



Photo 8:



Photo 9:



Photo 10:



Photo 11:



Photo 12:



Photo 13:




Photo 14:



Photo 15:



Photo 16:




Photo 17:



Photo 18:




Photo 19:




Photo 20:




Photo 21:




Photo 22:

