

**Ardi Technology Corp.**  
6F., No.136, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan

Federal Communications Commission  
Authorization and Evaluation Division  
Equipment Authorization Branch  
7435 Oakland Mills Road  
Columbia, MD 21046

### **Applicant's declaration concerning RF Radiation Exposure**

We hereby indicate that the product  
Product description: iReminder  
Model No: SB10

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product : iReminder will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21210-12805-C-1 and the accompanying calculations.

Company: Ardi Technology Corp.  
Address: 6F., No.136, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan

Date: 2012-11-24

Signature





Registration number: W6M21210-12805-C-1  
FCC ID: WMPSB1000

**3.2 Equivalent isotropic radiated power**

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

$$\begin{aligned} \text{EIRP} &= -8.23 \text{ dBm} + (-2.9 \text{ dBi}) \\ &= -11.13 \text{ dBm} \end{aligned}$$

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Test equipment used: ETSTW-RE 055

**3.3 RF Exposure Compliance Requirements**

Conclusion: No Evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Conducted Power	-8.23 dBm (0.15 mW)
EIRP Power	- 11.13 dBm (0.077 mW)

- The antenna is PCB antenna, antenna gain is -2.9 dBi.

Threshold for no SAR evaluation is 24.58 mW.

Conclusion: No SAR evaluation required since Transmitter output power is below FCC threshold.