

FCC ID : WNA-HPH9

1. RF EXPOSURE

1.1. The Requirement

System operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See Section 15.247(b)(4) and Section 1.1307(b)(1)

1.2. Limit For Maximum Permissible Exposure (MPE)

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time $ E ^2, H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

F = frequency in MHz, * Plane-wave equivalent power density

1.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the antenna is 3.79 dBi, the RF power density can be obtained.

1.4.TEST RESULTS

Maximum measured transmitter power

802.11b

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm^2)	Power Density At 20 cm (mW/cm^2)	Test Results
2412	20.00	16.54	45.08	2.39	1.000	0.021	Pass
2437	20.00	16.20	41.69	2.39	1.000	0.020	Pass
2462	20.00	16.54	45.08	2.39	1.000	0.021	Pass

802.11g

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm^2)	Power Density At 20 cm (mW/cm^2)	Test Results
2412	20.00	15.36	34.36	2.39	1.000	0.016	Pass
2437	20.00	15.21	33.19	2.39	1.000	0.016	Pass
2462	20.00	15.43	34.91	2.39	1.000	0.017	Pass

802.11n(20MHz)

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm^2)	Power Density At 20 cm (mW/cm^2)	Test Results
2412	20.00	14.50	28.18	2.39	1.000	0.013	Pass
2437	20.00	14.80	30.20	2.39	1.000	0.014	Pass
2462	20.00	14.37	27.35	2.39	1.000	0.013	Pass

802.11n (40MHz)

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm^2)	Power Density At 20 cm (mW/cm^2)	Test Results
2422	20.00	13.12	20.51	2.39	1.000	0.010	Pass
2437	20.00	13.15	20.65	2.39	1.000	0.010	Pass
2452	20.00	13.16	20.70	2.39	1.000	0.010	Pass

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.

1.5.FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, Human proximity to the antenna shall not be less than 20cm(8 inches) during normal operation. Proposed RF exposure safety information to include in User's Manual.