



FCC ID:WNG-WLSMCL-01

AUDIX Technology (Shenzhen) Co., Ltd.

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

Rondish Company Limited

System Name : Wireless Nurse Call System (Long Range)

System Model Number : Protektor II

EUT Name :Multi-colored Light

Model No.: WLSMCL-01

FCC ID: WNG-WLSMCL-01

Prepared for : Rondish Company Limited  
Unit G & H, 4/F, Block 1, Kwai Tak Ind. Ctr. 15-33 Kwai  
Tak St., Kwai Chung, N. T., Hong Kong

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F13353

Date of Test : Dec.04, 2013~Jan.15,2014

Date of Report : Jan.20, 2013

**TABLE OF CONTENTS**

<u>Description</u>	<u>Page</u>
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>1-1</b>
1.1. Description of Standards and Results.....	1-1
<b>2. GENERAL INFORMATION.....</b>	<b>2-1</b>
2.1. Description of Device (EUT) .....	2-1
2.2. Block Diagram of connection between EUT and simulators .....	2-2
2.3. Test Information.....	2-2
2.4. Test Facility.....	2-3
2.5. Measurement Uncertainty (95% confidence levels, k=2) .....	2-3
<b>3. POWER LINE CONDUCTED EMISSION MEASUREMENT.....</b>	<b>3-1</b>
3.1. Test Equipment .....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits.....	3-1
3.4. Configuration of EUT on Test .....	3-1
3.5. Operating Condition of EUT.....	3-2
3.6. Test Procedure.....	3-2
3.7. Conducted Emission at Mains Terminals Test Results .....	3-2
<b>4. RADIATED EMISSION TEST .....</b>	<b>4-1</b>
4.1. Test Equipment .....	4-1
4.2. Block Diagram of Test Setup.....	4-2
4.3. Radiated Emission Limit.....	4-3
4.4. EUT Configuration on Test.....	4-3
4.5. Operating Condition of EUT.....	4-4
4.6. Test Procedure.....	4-4
4.7. Radiated Emission Test Results .....	4-4
<b>5. CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>5-1</b>
5.1. Test Equipment.....	5-1
5.2. Limit.....	5-1
5.3. Test Procedure.....	5-1
<b>6. BAND EDGE COMPLIANCE TEST.....</b>	<b>6-1</b>
6.1. Test Equipment .....	6-1
6.2. Limit.....	6-1
6.3. Test Produce .....	6-1
6.4. Test Results .....	6-1
<b>7. 6dB BANDWIDTH Test.....</b>	<b>7-1</b>
7.1. Test Equipment .....	7-1
7.2. Limit.....	7-1
7.3. Test Procedure.....	7-1
7.4. Test Results .....	7-1
<b>8. OUTPUT POWER TEST .....</b>	<b>8-1</b>
8.1. Test Equipment .....	8-1
8.2. Limit (FCC Part 15C 15.247 b(3)).....	8-1
8.3. Test Procedure.....	8-1
8.4. Test Results .....	8-1
<b>9. POWER SPECTRAL DENSITY TEST .....</b>	<b>9-1</b>
9.1. Test Equipment .....	9-1

9.2.	Limit.....	9-1
9.3.	Test Procedure.....	9-1
9.4.	Test Results .....	9-2
<b>10.</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>10-1</b>
10.1.	STANDARD APPLICABLE.....	10-1
10.2.	ANTENNA CONNECTED CONSTRUCTION.....	10-1
<b>11.</b>	<b>DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>11-1</b>
<b>12.</b>	<b>PHOTOGRAPH OF TEST.....</b>	<b>12-1</b>
12.1.	Photos of Power Line Conducted Emission Test .....	12-1
12.2.	Photos of Radiated Emission Test.....	12-2
<b>13.</b>	<b>PHOTOGRAPH OF EUT.....</b>	<b>13-1</b>

## TEST REPORT CERTIFICATION

Applicant : Rondish Company Limited  
Manufacturer : Rondish Company Limited  
System Name : Wireless Nurse Call System (Long Range)  
System Model Number : Protektor II  
EUT Name : Multi-colored Light  
FCC ID : WNG-WLSMCL-01  
(A) MODEL NO. : WLSMCL-01  
(B) SERIAL NO. : N/A  
(C) POWER SUPPLY : DC 12V  
(D) TEST VOLTAGE : DC 12V

Tested for comply with:  
FCC Rules and Regulations Part 15 Subpart C: 2012  
Test procedure used:  
ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements.

The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. This report contains data that are not covered by the NVLAP accreditation. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Oct.06~ Dec.23, 2013 Report of date: Jan.03, 2013

Prepared by : Lisa Liang / Assistant Manager  
Reviewed by : Sunny Lu / Assistant Manager

Lisa Liang / Assistant Manager

Audix Technology (Shenzhen) Co., Ltd.  
EMC 部門報告專用章

Stamp only for EMC Dept. Report

Signature: David Jin 1.3

Approved & Authorized Signer :

David Jin / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2009	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.10: 2009	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Conducted spurious emissions	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS


REMARK :ANSI C63.4: 2009 is used for all test.

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

System Name	: Wireless Nurse Call System (Long Range)
System Model Number	: Protektor II
EUT Name	: Multi-colored Light
Model Number	: WLSMCL-01
Work frequency	: 922.5MHz
Antenna Assembly Gain	: Wire antenna, 0dBi PK Gain
Applicant	: Rondish Company Limited Unit G & H, 4/F, Block 1, Kwai Tak Ind. Ctr. 15-33 Kwai Tak St., Kwai Chung, N. T., Hong Kong
Manufacturer	: Rondish Company Limited Unit G & H, 4/F, Block 1, Kwai Tak Ind. Ctr. 15-33 Kwai Tak St., Kwai Chung, N. T., Hong Kong
Date of Test	: Dec.04, 2013~Jan.15,2014
Date of Receipt	: Oct.05, 2013
Sample Type	: Prototype production

## 2.2. Block Diagram of connection between EUT and simulators



**(EUT: Multi-colored Light)**

## 2.3. Test Information

A special method was used to control EUT work in Continuous TX mode, and select test channel, wireless mode and Frequency.

Tested mode, channel, and Frequency information		
Mode	Channel	Frequency (MHz)
Tx Mode GFSK modulation	1	922.5



**2.4. Test Facility**

Site Description Name of Firm	: Audix Technology (Shenzhen) Co., Ltd. No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China
3m Anechoic Chamber	: Certificated by FCC, USA Registration Number: 90454 Valid Date: Feb.22, 2015
3m & 10m Anechoic Chamber	: Certificated by FCC, USA Registration Number: 794232 Valid Date: Oct.31, 2015
EMC Lab.	: Certificated by Industry Canada Registration Number: IC 5183A-1 Valid Date: Jun.13, 2014  : Certificated by DAkkS, Germany Registration No: D-PL-12151-01-01 Valid Date: Feb.01, 2014  Accredited by NVLAP, USA NVLAP Code: 200372-0 Valid Date: Mar.31, 2014

**2.5. Measurement Uncertainty (95% confidence levels, k=2)**

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.08dB(9KHz to 150KHz)
	3.1dB (150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.22 dB(30~200MHz, Polarize: H)
	3.23 dB(30~200MHz, Polarize: V)
	3.49 dB(200M~1GHz, Polarize: H)
	3.39 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	4.97 dB (1~6GHz, Distance: 3m)
	4.99 dB (6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57 dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Power density test	2.00 dB
Uncertainty for Frequency range test	$7 \times 10^{-8}$
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6°C
	3%




### 3. POWER LINE CONDUCTED EMISSION MEASUREMENT

#### 3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 13	1 Year
2.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	834066/011	Oct.31, 13	1 Year
3.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 13	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 13	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 13	1 Year
6.	RF Cable	Fujikura	3D-2W	No.1	May.08, 13	1Year
7.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 13	1 Year
8.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	May.08, 13	1 Year

#### 3.2. Block Diagram of Test Setup



#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

- Notes: 1. \* Decreasing linearly with logarithm of frequency.  
 2. The lower limit shall apply at the transition frequencies.

#### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

##### 3.4.1. Multi-colored Light (EUT)

Model Number : WLSMCL-01  
 Serial Number : N/A

##### 3.4.2. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1	Power Adapter	N/A	LEADER	MU12-S120100-A1	N/A	<input checked="" type="checkbox"/> FCC DoC <input type="checkbox"/> BSMI ID:
Cable: Unshielded, Detachable, 1.5m						

### 3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT and simulator as shown as Section 3.2.
- 3.5.2. Turn on the power of all equipment.
- 3.5.3. Let the EUT work in test mode (TX Mode) and measure it.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2009 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked. The test result are reported on Section 3.7.

### 3.7. Conducted Emission at Mains Terminals Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)




Trace: (Discrete)

Site no :1#conduction Data No :1  
 Dis./Ant. :2013 ESH2-Z5 LINE  
 Limit :FCC PART 15 C  
 Env./Ins. :25.5°C/55% Engineer :Leo-Li  
 EUT :Multi-colored Light  
 Power Rating :DC 12V From Adapter Input AC 120V/60Hz  
 Test Mode :Tx Mode  
 WLSMCL-01

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17985	0.15	0.01	37.47	37.63	64.49	26.86	QP
2	0.38880	0.16	0.02	31.30	31.48	58.09	26.61	QP
3	0.59775	0.16	0.02	31.50	31.68	56.00	24.32	QP
4	0.74700	0.17	0.03	35.11	35.31	56.00	20.69	QP
5	1.374	0.19	0.03	29.04	29.26	56.00	26.74	QP
6	2.120	0.22	0.04	31.10	31.36	56.00	24.64	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)

Site no :1#conduction Data No :2  
 Dis./Ant. :2013 ESH2-25 NEUTRAL  
 Limit :FCC PART 15 C  
 Env./Ins. :25.5°C/55% Engineer :Leo-Li  
 EUT :Multi-colored Light  
 Power Rating :DC 12V From Adapter Input AC 120V/60Hz  
 Test Mode :Tx Mode  
 WLSMCL-01

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.20970	0.18	0.01	35.58	35.77	63.22	27.45	QP
2	0.38880	0.21	0.02	32.21	32.44	58.09	25.65	QP
3	0.44850	0.22	0.02	32.76	33.00	56.90	23.90	QP
4	0.62760	0.26	0.02	32.79	33.07	56.00	22.93	QP
5	0.89625	0.26	0.03	27.06	27.35	56.00	28.65	QP
6	1.434	0.26	0.03	29.20	29.49	56.00	26.51	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss+Reading.  
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION TEST

### 4.1. Test Equipment

Frequency rang: 30~1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24, 13	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 13	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 13	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 13	1 Year
5	Bilog Antenna	TESEQ	CBL6112D	35375	May.30, 13	1 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 13	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 13	1 Year

Frequency rang: above 1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 13	1 Year
2	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 13	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	May.08, 13	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 13	1 Year

### 4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range above 1GHz



### 4.3.Radiated Emission Limit

#### 4.3.1.15.247 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark : (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

#### 4.3.2.15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 4.4.EUT Configuration on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

#### 4.4.1.Multi-colored Light (EUT)

Model Number : WLSMCL-01  
Serial Number : N/A



#### 4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulator as shown as Section 4.2.
- 4.5.2. Turned on the power of all equipment.
- 4.5.3. Let the EUT work in test mode (TX Mode) and measure it.

#### 4.6. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The EUT was tested at X.Y.Z position and found the worst case position reported in the report.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz .

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10<sup>th</sup> harmonic (10GHz) are checked.

#### 4.7. Radiated Emission Test Results



**PASS.**


All the emissions from 30MHz to 10 GHz were comply with 15.209 limits.

Note: The duty cycle factor for calculate average level is 2.08dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit.


Duty cycle:  $18.75\text{ms}/23.83\text{ms} * 100\% = 78.6\%$

Duty cycle factor =  $20\log (1/\text{duty cycle}) = 2.08$










Site no. : 3m Chamber Data no. : 12  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Leo-Li  
 EUT : Multi-colored Light M/N:WLSMCL-01  
 Power rating : DC 12V  
 Test Mode : 922.5MHz Tx


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	119.240	12.76	1.48	3.84	18.08	43.50	25.42	QP
2	260.860	14.00	2.02	5.21	21.23	46.00	24.77	QP
3	483.960	17.80	2.70	4.05	24.55	46.00	21.45	QP
4	839.950	21.20	3.74	5.39	30.33	46.00	15.67	QP
5	875.840	21.60	3.85	5.80	31.25	46.00	14.75	QP
6	922.400	21.80	4.00	57.51	83.31	46.00	-37.31	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.  
 3. 922.400MHz is the Signal from fundament Frequency.  
 No need to comply with the limit

Frequency: 1GHz~18GHz



Site no. : 3m Chamber Data no. : 1  
Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : Multi-colored Light M/N:WLSMCL-01  
Power supply : DC 12V  
Test mode : Tx Mode 922.5MHz




Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : Multi-colored Light M/N:WLSMCL-01  
 Power supply : DC 12V  
 Test mode : Tx Mode 922.5MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	3690.000	30.97	7.39	35.70	46.77	49.43	74.00	24.57	Peak


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber      Data no. : 3  
Dis. / Ant. : 3m    2012 3115 (4580)      Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54%      Engineer : Leo-Li  
EUT : Multi-colored Light    M/N:WLSMCL-01  
Power supply : DC 12V  
Test mode : Tx Mode    922.5MHz



Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : Multi-colored Light M/N:WLSMCL-01  
 Power supply : DC 12V  
 Test mode : Tx Mode 922.5MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			Remark
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1 3690.000	30.97	7.39	35.70	46.83	49.49	74.00	24.51	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,13	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,13	1 Year

### 5.2. Limit


In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 5.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

**Conducted emission test data:**

Frequency: 30.0MHz-1GHz



Frequency: above 1GHz-10GHz



## 6. BAND EDGE COMPLIANCE TEST

### 6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9607-4877	May.08, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

### 6.2. Limit

All the lower and upper band-edges emissions appearing within 608MHz to 614MHz and 960MHz to 1240MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 902MHz to 928MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.


### 6.3. Test Produce

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=100KHz; VBW=300KHz ;Sweep time=AUTO  
Reading out the QP value of the emission.

### 6.4. Test Results


Pass (The testing data was attached in the next pages.)



Site no. : 3m Chamber Data no. : 7  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Leo-Li  
 EUT : Multi-colored Light M/N:WLSMCL-01  
 Power rating : DC 12V  
 Test Mode : 922.5MHz Tx

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	922.800	21.80	4.00	69.84	95.64	46.00	-49.64	QP
2	931.360	21.80	4.02	5.78	31.60	46.00	14.40	QP
3	941.760	21.94	4.06	4.72	30.72	46.00	15.28	QP
4	947.040	22.04	4.07	4.87	30.98	46.00	15.02	QP
5	968.000	22.26	4.14	4.66	31.06	54.00	22.94	QP
6	983.840	22.38	4.19	5.02	31.59	54.00	22.41	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 8  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24\*C/65% Engineer : Leo-Li  
 EUT : Multi-colored Light M/N:WLSMCL-01  
 Power rating : DC 12V  
 Test Mode : 922.5MHz Tx

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	922.800	21.80	4.00	57.66	83.46	46.00	-37.46	QP
2	931.200	21.80	4.02	5.41	31.23	46.00	14.77	QP
3	940.400	21.91	4.05	4.70	30.66	46.00	15.34	QP
4	953.600	22.10	4.09	4.78	30.97	46.00	15.03	QP
5	967.040	22.24	4.14	5.09	31.47	54.00	22.53	QP
6	984.000	22.38	4.19	4.92	31.49	54.00	22.51	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 9  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Leo-Li  
 EUT : Multi-colored Light M/N:WLSMCL-01  
 Power rating : DC 12V  
 Test Mode : 922.5MHz Tx

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	842.880	21.20	3.75	5.22	30.17	46.00	15.83	QP
2	857.856	21.40	3.79	5.17	30.36	46.00	15.64	QP
3	861.696	21.43	3.80	5.82	31.05	46.00	14.95	QP
4	871.680	21.53	3.84	4.99	30.36	46.00	15.64	QP
5	906.880	21.70	3.95	4.90	30.55	46.00	15.45	QP
6	922.880	21.80	4.00	58.08	83.88	46.00	-37.88	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 10  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Leo-Li  
 EUT : Multi-colored Light M/N:WLSMCL-01  
 Power rating : DC 12V  
 Test Mode : 922.5MHz Tx

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	853.760	21.38	3.78	5.39	30.55	46.00	15.45	QP
2	865.920	21.50	3.82	5.61	30.93	46.00	15.07	QP
3	875.776	21.60	3.85	5.85	31.30	46.00	14.70	QP
4	885.120	21.60	3.88	4.80	30.28	46.00	15.72	QP
5	903.424	21.67	3.94	4.73	30.34	46.00	15.66	QP
6	922.240	21.80	4.00	69.83	95.63	46.00	-49.63	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 7. 6dB BANDWIDTH Test

### 7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Antenna	EMCO	3115	9607-4877	Aug.28, 13	1 Year
3.	HF Cable	Hubersuhner	Sucoflex104	-	May.08, 13	1 Year

### 7.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz


### 7.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100KHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### 7.4. Test Results

EUT: Multi-colored Light		
M/N:WLSMCL-01		
Test date:2013-12-09	Pressure: 101.2±1.0kpa	Humidity: 52.2±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature: 22.5±0.6℃

Cable loss: 1.0 dB		Attenuator loss: 20 dB	
Test Mode	CH ( MHz )	6 dB bandwidth ( kHz )	Limit (KHz)
GFSK	922.5	581.9	500
Conclusion : PASS			



## 8. OUTPUT POWER TEST

### 8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Power Meter	Anritsu	ML2487A	6K00002472	May.08, 13	1 Year
2.	Power Sensor	Anritsu	MA2491A	033005	May.08, 13	1 Year

### 8.2. Limit (FCC Part 15C 15.247 b(3))

For systems using digital modulation in the 902—928MHz, The Peak out put Power shall not exceed 1W(30dBm)

### 8.3. Test Procedure

- 1, Connected the EUT's antenna port to measure device by suitable attenuator.
- 2, Read the peak output power from the measure device directly.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

### 8.4. Test Results

EUT: Multi-colored Light			
M/N:WLSMCL-01			
Test date:2013-12-09		Pressure: 102.1±1.0kpa	Humidity: 51.7 ±3.0%
Tested by:Leo-Li		Test site: RF site	Temperature: 22.3±0.6°C
Cable loss: 1.0 dB		Attenuator loss: 20 dB	
Test Mode	Frequency (MHz)	Peak output Power ( dBm )	Limit (dBm)
GFSK	922.5	-1.245	30
Conclusion: PASS			

## 9. POWER SPECTRAL DENSITY TEST

### 9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9607-4877	Aug.28, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

### 9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

### 9.3. Test Procedure


1. Connected the EUT's antenna port to spectrum analyzer device by 20dB attenuator.
2. Set analyzer center frequency to center frequency.
3. Set the span to 1.5 times the DTS Bandwidth.
4. Set the RBW=3KHz; VBW=10KHz; Detector=Peak  
Sweep time= AUTO Couple; Trace Mode= max hold
5. Allow trace to fully stabilize.
6. Use the peak marker function to determine the maximum amplitude level within the RBW.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude

### 9.4. Test Results

EUT: Multi-colored Light		
M/N:WLSMCL-01		
Test date: 2014-01-15	Pressure: 101.1±1.0kpa	Humidity: 50.1±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature: 23.6±0.6°C

Cable loss: 1 dB			
Test Mode	CH (MHz)	Power density ( dBm )	Limit (dBm/3KHz)
GFSK	922.5	-25.748	8
Conclusion : PASS			



## 10. ANTENNA REQUIREMENT

### 10.1. STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 10.2. ANTENNA CONNECTED CONSTRUCTION

The antennas used for this product are wire antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.



## 11.DEVIATION TO TEST SPECIFICATIONS

[ NONE]

## 12.PHOTOGRAPH OF TEST

### 12.1.Photos of Power Line Conducted Emission Test




### 12.2.Photos of Radiated Emission Test

30-1000MHz




Above 1000MHz




### 13. PHOTOGRAPH OF EUT

**Figure 1**  
General Appearance of the EUT




**Figure 2**  
General Appearance of the EUT







**Figure 3**  
Inside of the EUT




**Figure 4**  
Inside of the EUT



**Figure 5**  
Inside of the EUT




**Figure 6**  
Inside of the EUT






**Figure 7**  
Inside of the EUT




**Figure 8**  
Inside of the EUT





**Figure 9**  
Inside of the EUT



**Figure 10**  
Inside of the EUT

