



**FCC 47 CFR PART 15 SUBPART C/Oct. 2012 AND ANSI 63.4:2003
TEST REPORT**

For

IP CAM

Model : F1105

Trade Name : ZAVIO

Issued for

ZAVIO Inc.

**2F, No.13, R&D Rd.II, Science Based Industrial Park,
Hsinchu, Taiwan**

Issued by

**Compliance Certification Services Inc.
Hsinchu Lab.**

**NO. 989-1 Wen Shan Rd., Shang Shan Village,
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C**

TEL: +886-3-5921698

FAX: +886-3-5921108

<http://www.ccsrf.com>

E-Mail : service@ccsrf.com

Issued Date: September 06, 2013



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	04/27/2012	Initial Issue	All Page 89	Cindy Pon
01	08/15/2013	Revised FCC STANDARD , MEASUREMENT UNCERTAINTY AND TEST SETUP	P.1 & P.4 & P.7 & P.8 & 11 & 22 & 25 & 28& 39 & 86	Gloria Chang
02	09/06/2013	Revised POWER SPECTRAL DENSITY Data	P.28 ~ P.37	Rubeca Yu



TABLE OF CONTENTS

TITLE	PAGE NO.
1. TEST REPORT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. DESCRIPTION OF TEST MODES	6
4. TEST METHODOLOGY	7
5. FACILITIES AND ACCREDITATION	7
5.1 FACILITIES	7
5.2 ACCREDITATIONS.....	7
5.3 MEASUREMENT UNCERTAINTY	8
6. SETUP OF EQUIPMENT UNDER TEST.....	8-10
7. FCC PART 15.247 REQUIREMENTS	8
7.1 6dB BANDWIDTH	8-21
7.2 MAXIMUM PEAK OUTPUT POWER	8-24
7.3 AVERAGE POWER	8-27
7.4 POWER SPECTRAL DENSITY	8-38
7.5 CONDUCTED SPURIOUS EMISSION	8-51
7.6 RADIATED EMISSION.....	8-84
7.7 CONDUCTED EMISSION.....	8-89



1. TEST REPORT CERTIFICATION

Applicant : ZAVIO Inc.
Address : 2F, No.13, R&D Rd.II, Science Based Industrial Park,
Hsinchu, Taiwan
Equipment Under Test : IP CAM
Model : F1105
Trade Name : ZAVIO
Tested Date : March 26 ~ April 12, 2012 ; September 05, 2013

APPLICABLE STANDARD	
Standard	Test Result
FCC Part 15 Subpart C/Oct. 2012 AND ANSI C63.4:2003	PASS

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Sb. Lu
Sr. Engineer

Reviewed by:

Gundam Lin
Sr. Engineer



2. EUT DESCRIPTION

Product Name	IP CAM
Model Number	F1105
Identify Number	T120326S04
Received Date	March 26, 2012
Frequency Range	IEEE 802.11b/g : 2412MHz ~ 2462MHz IEEE 802.11n HT40 : 2422MHz~2452MHz
Transmit Power	IEEE 802.11b : 12.20 dBm (0.0166W) IEEE 802.11g : 14.04 dBm (0.0254W) IEEE 802.11n HT20: 13.26 dBm (0.0212W) IEEE 802.11n HT40: 14.04 dBm (0.0254W)
Channel Spacing	IEEE 802.11b/g, 802.11n HT20/HT40 : 5MHz
Channel Number	IEEE 802.11b/g, 802.11n HT20 : 11 Channels IEEE 802.11n HT40 : 7 Channels
Transmit Data Rate	IEEE 802.11b : 11, 5.5, 2, 1 Mbps IEEE 802.11g : 54, 48, 36, 24, 18, 12, 9, 6 Mbps IEEE 802.11n HT20 : 65, 58.5, 52, 39, 26, 19.5, 13, 6.5Mbps IEEE 802.11n HT40 : 135, 121.5, 108, 81, 54, 40.5, 27, 13.5Mbps
Type of Modulation	IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g : OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20/40 : OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Type	Embedded Antenna ,Antenna Gain 2.70dBi
Power Rating	5Vdc
Test Voltage	120Vac, 60Hz
DC Power Cable Type	Non-shielded cable, 1.5m (Non-detachable)
I/O Port	RJ-45 Port × 1, Power Port × 1

Power Adapter :

No.	Manufacturer	Model No.	Power Input	Power Output
1	DVE	DSC-6PFA-05 FUS 050100	100-240Vac, 50/60Hz, 0.2A	5Vdc, 1A

Remark :

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. For more details, please refer to the User's manual of the EUT.
3. This submittal(s) (test report) is intended for FCC ID : WOR-5011F filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. DESCRIPTION OF TEST MODES

The EUT is an 802.11n transceiver in IP CAM form factor. It has one transmitter chain and one receive chain (1×1 configurations).

Conducted Emission / Radiated Emission Test (Below 1 GHz)

1. The following test modes were scanned during the preliminary test:

No.	Pre-Test Mode
1	Normal Operating
2	TX Mode

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test Mode		
Emission	Radiated Emission	Normal Operating
	Conducted Emission	Normal Operating

Remark : Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.

Conducted / Radiated Emission Test (Above 1 GHz)

IEEE 802.11b, 802.11g, 802.11n HT20 mode

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode : 1Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11g mode : 6Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11n HT20 mode : 6.5Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11n HT40 mode

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2422
Middle	2437
High	2452

IEEE 802.11n HT40 mode : 13.5Mbps data rate (worst case) were chosen for full testing.



4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2003 and FCC CFR 47, 15.207, 15.209, 15.247 and KDB558074.

5. FACILITIES AND ACCREDITATION

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

NO. 989-1 Wen Shan Rd., Shang Shan Village,
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C

The sites are constructed in conformance with the requirements of ANSI C63.4:2003 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4, CISPR 16-1-5.

5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Taiwan	TAF
---------------	-----

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	INDUSTRY CANADA
Japan	VCCI
Taiwan	BSMI
USA	FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>



5.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 0.009 to 30 MHz	+/- 3.3162
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.5189
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 2.5164
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 2.4967
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 2.7655
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 1.5923

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Consistent with industry standard (e.g. CISPR 22: 2006, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than U_{CISPR} which is 3.6dB and 5.2dB respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.



6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

No.	Product	Manufacturer	Model No.	Serial No.	FCC ID
1	Notebook PC	DELL	Latitude D610	CN-0C4708-48643 -625-5565	DoC
2	Notebook PC	HP	ProBook 4421s	CNF03242PJ	DoC
3	Wireless Gigabit Router	D-Link	DI-724GU	-----	-----

No.	Power & Signal Cable Description
1	Non-shielded RJ-45 cable, 12m × 1

SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

EUT OPERATING CONDITION

RF Mode

1. Set up whole system for test as shown on diagram.
2. Pc a fixed ip, into the Network Neighborhood to confirm EUT obtained ip
3. In internet website key in:
http://192.168.1.25/cgi-bin/admin/param?action=update&telnetd=23
4. Run Putty software→IP address 192.168.1.25.
5. Account: root.
6. key in : UDPserver &
7. run MP_TEST > Select the IP 192.168.1.6 on MP_TEST press OPEN.
8. Set up all computers like the setup diagram.

(1) TX Mode:

- ⇒ Tx Data Rate: 1Mbps Bandwidth 20 (IEEE 802.11b mode)
- 6Mbps Bandwidth 20 (IEEE 802.11g mode)
- MCS=0 Bandwidth 20 (IEEE 802.11n HT20 mode)
- MCS=0 Bandwidth 40 (IEEE 802.11n HT40 mode)



⇒ Power control

IEEE 802.11b Channel Low (2412MHz) TX Power=20

IEEE 802.11b Channel Mid (2437MHz) TX Power=20

IEEE 802.11b Channel High (2462MHz) TX Power=21

IEEE 802.11g Channel Low (2412MHz) TX Power=18

IEEE 802.11g Channel Mid (2437MHz) TX Power=18

IEEE 802.11g Channel High (2462MHz) TX Power=19

IEEE 802.11n HT20 Channel Low (2412MHz) TX Power=18

IEEE 802.11n HT20 Channel Mid (2437MHz) TX Power=18

IEEE 802.11n HT20 Channel High (2462MHz) TX Power=19

IEEE 802.11n HT40 Channel Low (2422MHz) TX Power=20

IEEE 802.11n HT40 Channel Mid (2437MHz) TX Power=20

IEEE 802.11n HT40 Channel High (2452MHz) TX Power=21

9. All of the functions are under run.

10. Start test.

Normal Mode

1. Setup whole system for test as shown on diagram.

2. Wireless Router to provide IP to the EUT.

3. Notebook PC (1) ping to EUT.

4. Notebook PC (2) ping to EUT.

5. All of the functions are under run.(web display video).

6. Start test.



7. FCC PART 15.247 REQUIREMENTS

7.1 6dB BANDWIDTH

LIMITS


§ 15.247(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4407B	US41443108	08/09/2012

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output was connected to a spectrum analyzer. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.



TEST RESULTS

IEEE 802.11b Mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	10.00	500	PASS
Middle	2437	10.00	500	PASS
High	2462	10.08	500	PASS

IEEE 802.11g Mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	16.33	500	PASS
Middle	2437	16.42	500	PASS
High	2462	16.50	500	PASS



IEEE 802.11n HT20 Mode



Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	17.67	500	PASS
Middle	2437	17.66	500	PASS
High	2462	17.67	500	PASS


IEEE 802.11n HT40 Mode



Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	36.33	500	PASS
Middle	2437	36.33	500	PASS
High	2462	36.33	500	PASS






6dB BANDWIDTH























7.2 MAXIMUM PEAK OUTPUT POWER

LIMITS

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.


§ 15.247(b) (4) Except as shown in paragraphs (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/07/2012
Power Sensor	Anritsu	MA2411B	1126148	12/14/2012

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the peak power detection.



TEST RESULTS

IEEE 802.11b Mode

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	12.20	0.0166	30	1	PASS
Middle	2437	11.88	0.0154	30	1	PASS
High	2462	11.66	0.0147	30	1	PASS

Remark:

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

IEEE 802.11g Mode

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	14.04	0.0254	30	1	PASS
Middle	2437	13.63	0.0231	30	1	PASS
High	2462	13.22	0.0210	30	1	PASS

Remark:

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



IEEE 802.11n HT20 Mode

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	13.26	0.0212	30	1	PASS
Middle	2437	12.80	0.0191	30	1	PASS
High	2462	12.37	0.0173	30	1	PASS

Remark:

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

IEEE 802.11n HT40 Mode

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2422	14.04	0.0254	30	1	PASS
Middle	2437	13.77	0.0238	30	1	PASS
High	2452	13.80	0.0240	30	1	PASS

Remark:

1. At final test to get the worst-case emission at 13.5Mbps
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



7.3 AVERAGE POWER

LIMITS


None; for reporting purposes only.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/07/2012
Power Sensor	Anritsu	MA2411B	1126148	12/14/2012

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to a power meter. The power meter is set to the average power detection.



TEST RESULTS

IEEE 802.11b Mode

Channel	Channel Frequency (MHz)	Average Power Output (dBm)
Low	2412	10.01
Middle	2437	9.62
High	2462	9.46

Remark:

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

IEEE 802.11g Mode

Channel	Channel Frequency (MHz)	Average Power Output (dBm)
Low	2412	4.58
Middle	2437	4.15
High	2462	3.96

Remark:

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



IEEE 802.11n HT20 Mode

Channel	Channel Frequency (MHz)	Average Power Output (dBm)
Low	2412	4.47
Middle	2437	4.03
High	2462	3.85

Remark:

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

IEEE 802.11n HT40 Mode

Channel	Channel Frequency (MHz)	Average Power Output (dBm)
Low	2422	4.97
Middle	2437	4.66
High	2452	4.80

Remark:

1. At final test to get the worst-case emission at 13.5Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



7.4 POWER SPECTRAL DENSITY

LIMITS

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set analyzer center frequency to DTS channel center frequency.
3. Set the span to 1.5 times the DTS channel bandwidth.
4. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
5. Set the VBW $\geq 3 \times \text{RBW}$.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



TEST RESULTS

IEEE 802.11b Mode

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2412	-20.08	8	PASS
Middle	2437	-19.86	8	PASS
High	2462	-20.44	8	PASS

Remark:

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11g Mode

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2412	-23.31	8	PASS
Middle	2437	-23.63	8	PASS
High	2462	-24.30	8	PASS

Remark:

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.



IEEE 802.11n HT20 Mode

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2412	-22.46	8	PASS
Middle	2437	-22.74	8	PASS
High	2462	-23.47	8	PASS

Remark:

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11n HT40 Mode



Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2422	-24.41	8	PASS
Middle	2437	-22.61	8	PASS
High	2452	-22.56	8	PASS


Remark:



1. At final test to get the worst-case emission at 13.5Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.






POWER SPECTRAL DENSITY























7.5 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4407B	US41443108	08/09/2012

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE



The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.



The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.







TEST RESULTS



OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT






































7.6 RADIATED EMISSION

LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Remark:

- 1. ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
- 2. ² Above 38.6

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

Remark: **Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST EQUIPMENT

Radiated Emission / 966Chamber_B

Name of Equipment	Manufacture	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/19/2012
EMI Receiver	ROHDE & SCHWARZ	ESCS 30	826547/004	10/27/2012
Broadband Hybrid Bi-Log Antenna	Sunol Sciences	JB1	A100209-4	10/05/2012
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078732	07/03/2012
Horn Antenna	COM-POWER	AH-840	03077	12/06/2012
Pre-Amplifier	Agilent	8447D	2944A10052	07/19/2012
Pre-Amplifier	Agilent	8449B	3008A01916	09/18/2012
Notch Filters Band Reject	Micro-Tronics	BRM05702-01	026	N.C.R
LOOP Antenna	EMCO	6502	8905-2356	06/10/2012


Remark: 1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R = No Calibration Request.




TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from below 1GHz.

9kHz ~ 30MHz




30MHz ~ 1GHz





The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Remark :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.



TEST RESULTS

Below 1 GHz (9kHz ~ 30MHz)

No emission found between lowest internal used/generated frequency to 30MHz.

Below 1 GHz (30MHz ~ 1GHz)

Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/02
Test Mode	Normal Operating	Temp. & Humidity	21°C, 51%

966 Chamber_B at 3Meter / Horizontal						
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark
156.10	55.09	-14.38	40.71	43.50	-2.79	Peak
208.48	48.31	-13.97	34.35	43.50	-9.15	Peak
312.27	53.55	-11.60	41.95	46.00	-4.05	Peak
364.65	48.47	-10.59	37.88	46.00	-8.12	Peak
468.44	45.29	-8.84	36.46	46.00	-9.54	Peak
520.82	48.17	-8.11	40.07	46.00	-5.93	Peak
573.20	45.55	-7.47	38.08	46.00	-7.92	Peak
624.61	42.82	-6.43	36.40	46.00	-9.60	Peak

966 Chamber_B at 3Meter / Vertical						
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark
39.70	44.01	-12.88	31.14	40.00	-8.86	Peak
98.87	49.54	-17.60	31.94	43.50	-11.56	Peak
156.10	53.94	-14.38	39.56	43.50	-3.94	Peak
312.27	51.64	-11.60	40.04	46.00	-5.96	Peak
365.62	52.24	-10.57	41.67	46.00	-4.33	Peak
418.00	48.46	-9.70	38.76	46.00	-7.24	Peak
520.82	49.48	-8.11	41.37	46.00	-4.63	Peak
572.23	49.21	-7.48	41.73	46.00	-4.27	Peak
624.61	48.45	-6.43	42.03	46.00	-3.97	Peak
676.99	41.28	-5.70	35.58	46.00	-10.42	Peak

Remark:

1. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
2. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – PreAmp.Gain (dB)
4. Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)
5. Margin (dB) = Remark result (dBuV/m) - Quasi-peak limit (dBuV/m).



Above 1 GHz

Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11b TX / CH Low	Temp. & Humidity	21°C, 50%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1366.00	44.82	---	-2.70	42.11	---	74.00	54.00	-11.89	Peak
1764.00	44.45	---	0.10	44.55	---	74.00	54.00	-9.45	Peak
2332.00	47.34	---	3.31	50.65	---	74.00	54.00	-3.35	Peak
3465.00	41.79	---	5.91	47.70	---	74.00	54.00	-6.30	Peak
4830.00	40.79	---	9.50	50.29	---	74.00	54.00	-3.71	Peak
7230.00	45.14	39.45	12.72	57.86	52.17	74.00	54.00	-1.83	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1224.00	45.94	---	-3.16	42.78	---	74.00	54.00	-11.22	Peak
1380.00	44.86	---	-2.66	42.20	---	74.00	54.00	-11.80	Peak
1968.00	44.68	---	1.93	46.61	---	74.00	54.00	-7.39	Peak
3225.00	42.67	---	5.65	48.32	---	74.00	54.00	-5.68	Peak
4830.00	39.98	---	9.50	49.48	---	74.00	54.00	-4.52	Peak
7230.00	43.84	37.45	12.72	56.56	50.17	74.00	54.00	-3.83	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
 Margin = Result - Limit
 Remark Peak = Result(PK) - Limit(AV)
 Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11b TX / CH Middle	Temp. & Humidity	21°C, 50%

966 Chamber_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1398.00	45.80	---	-2.60	43.21	---	74.00	54.00	-10.79	Peak
1970.00	44.01	---	1.95	45.97	---	74.00	54.00	-8.03	Peak
2356.00	46.23	---	3.39	49.61	---	74.00	54.00	-4.39	Peak
3195.00	42.11	---	5.62	47.73	---	74.00	54.00	-6.27	Peak
4875.00	42.46	---	9.61	52.07	---	74.00	54.00	-1.93	Peak
7305.00	39.61	---	12.86	52.46	---	74.00	54.00	-1.54	Peak

966 Chamber_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1842.00	44.56	---	0.80	45.36	---	74.00	54.00	-8.64	Peak
2360.00	48.13	---	3.40	51.53	---	74.00	54.00	-2.47	Peak
2528.00	46.07	---	3.95	50.02	---	74.00	54.00	-3.98	Peak
3615.00	41.52	---	6.19	47.72	---	74.00	54.00	-6.28	Peak
4875.00	40.55	---	9.61	50.17	---	74.00	54.00	-3.83	Peak
7305.00	45.02	35.86	12.86	57.88	48.72	74.00	54.00	-5.28	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11b TX / CH High	Temp. & Humidity	21°C, 50%

966 Chamber_Bat 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1306.00	46.65	---	-2.89	43.75	---	74.00	54.00	-10.25	Peak
1720.00	44.90	---	-0.29	44.61	---	74.00	54.00	-9.39	Peak
2380.00	47.28	---	3.47	50.75	---	74.00	54.00	-3.25	Peak
3150.00	42.48	---	5.57	48.05	---	74.00	54.00	-5.95	Peak
4920.00	47.44	42.09	9.72	57.16	51.81	74.00	54.00	-2.19	AVG
7380.00	42.47	35.74	12.99	55.46	48.73	74.00	54.00	-5.27	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1704.00	44.60	---	-0.44	44.16	---	74.00	54.00	-9.84	Peak
2344.00	47.00	---	3.35	50.35	---	74.00	54.00	-3.65	Peak
2382.00	48.23	---	3.47	51.70	---	74.00	54.00	-2.30	Peak
3165.00	43.15	---	5.59	48.74	---	74.00	54.00	-5.26	Peak
4920.00	49.94	42.08	9.72	59.66	51.80	74.00	54.00	-2.20	AVG
7380.00	47.50	38.67	12.99	60.49	51.66	74.00	54.00	-2.34	AVG

Remark:

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11g TX / CH Low	Temp. & Humidity	21°C, 50%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1366.00	45.60	---	-2.70	42.89	---	74.00	54.00	-11.11	Peak
1744.00	44.80	---	-0.08	44.72	---	74.00	54.00	-9.28	Peak
1970.00	44.39	---	1.95	46.34	---	74.00	54.00	-7.66	Peak
3450.00	41.57	---	5.90	47.47	---	74.00	54.00	-6.53	Peak
4185.00	40.29	---	7.63	47.91	---	74.00	54.00	-6.09	Peak
7230.00	48.53	36.54	12.72	61.25	49.26	74.00	54.00	-4.74	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1414.00	45.21	---	-2.55	42.66	---	74.00	54.00	-11.34	Peak
1716.00	44.23	---	-0.33	43.90	---	74.00	54.00	-10.10	Peak
1824.00	44.12	---	0.64	44.76	---	74.00	54.00	-9.24	Peak
3210.00	42.37	---	5.64	48.01	---	74.00	54.00	-5.99	Peak
4980.00	40.26	---	9.87	50.13	---	74.00	54.00	-3.87	Peak
7245.00	49.89	36.97	12.75	62.64	49.72	74.00	54.00	-4.28	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11g TX / CH Middle	Temp. & Humidity	21°C, 50%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1458.00	45.90	---	-2.41	43.49	---	74.00	54.00	-10.51	Peak
1936.00	44.21	---	1.65	45.86	---	74.00	54.00	-8.14	Peak
2358.00	52.30	42.69	3.39	55.69	46.08	74.00	54.00	-7.92	AVG
3960.00	40.82	---	6.92	47.73	---	74.00	54.00	-6.27	Peak
4875.00	47.51	35.31	9.61	57.12	44.92	74.00	54.00	-9.08	AVG
7305.00	49.79	36.62	12.86	62.65	49.48	74.00	54.00	-4.52	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1132.00	46.61	---	-3.45	43.15	---	74.00	54.00	-10.85	Peak
1984.00	44.22	---	2.08	46.30	---	74.00	54.00	-7.70	Peak
2350.00	52.61	42.03	3.37	55.98	45.40	74.00	54.00	-8.60	AVG
3675.00	41.45	---	6.32	47.77	---	74.00	54.00	-6.23	Peak
4875.00	42.08	---	9.61	51.69	---	74.00	54.00	-2.31	Peak
7305.00	51.24	38.50	12.86	64.10	51.36	74.00	54.00	-2.64	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11g TX / CH High	Temp. & Humidity	21°C, 50%

966 Chamber_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1720.00	44.46	---	-0.29	44.16	---	74.00	54.00	-9.84	Peak
1888.00	44.42	---	1.21	45.63	---	74.00	54.00	-8.37	Peak
2380.00	52.49	40.63	3.47	55.96	44.10	74.00	54.00	-9.90	AVG
3645.00	40.94	---	6.25	47.19	---	74.00	54.00	-6.81	Peak
4920.00	43.01	---	9.72	52.73	---	74.00	54.00	-1.27	Peak
7380.00	47.39	35.34	12.99	60.38	48.33	74.00	54.00	-5.67	AVG

966 Chamber_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1562.00	44.51	---	-1.71	42.80	---	74.00	54.00	-11.20	Peak
1840.00	43.94	---	0.78	44.72	---	74.00	54.00	-9.28	Peak
2388.00	53.08	43.07	3.49	56.57	46.56	74.00	54.00	-7.44	AVG
3750.00	40.84	---	6.47	47.32	---	74.00	54.00	-6.68	Peak
4920.00	42.92	---	9.72	52.64	---	74.00	54.00	-1.36	Peak
7380.00	48.69	36.88	12.99	61.68	49.87	74.00	54.00	-4.13	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11n HT20 TX / CH Low	Temp. & Humidity	21 °C, 50%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1412.00	45.64	---	-2.55	43.09	---	74.00	54.00	-10.91	Peak
1780.00	44.36	---	0.24	44.60	---	74.00	54.00	-9.40	Peak
1920.00	43.85	---	1.50	45.35	---	74.00	54.00	-8.65	Peak
3270.00	41.40	---	5.70	47.10	---	74.00	54.00	-6.90	Peak
4815.00	41.23	---	9.46	50.70	---	74.00	54.00	-3.30	Peak
7230.00	49.70	36.56	12.72	62.42	49.28	74.00	54.00	-4.72	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1098.00	46.18	---	-3.56	42.62	---	74.00	54.00	-11.38	Peak
1302.00	45.96	---	-2.91	43.05	---	74.00	54.00	-10.95	Peak
1902.00	43.79	---	1.34	45.13	---	74.00	54.00	-8.87	Peak
3180.00	42.39	---	5.60	47.99	---	74.00	54.00	-6.01	Peak
4830.00	40.41	---	9.50	49.91	---	74.00	54.00	-4.09	Peak
7230.00	51.75	38.13	12.72	64.47	50.85	74.00	54.00	-3.15	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11n HT20 TX / CH Middle	Temp. & Humidity	21 °C, 50%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1858.00	44.96	---	0.94	45.91	---	74.00	54.00	-8.09	Peak
2016.00	44.50	---	2.27	46.77	---	74.00	54.00	-7.23	Peak
2350.00	49.48	---	3.37	52.85	---	74.00	54.00	-1.15	Peak
3390.00	41.83	---	5.83	47.66	---	74.00	54.00	-6.34	Peak
4875.00	48.03	36.83	9.61	57.64	46.44	74.00	54.00	-7.56	AVG
7305.00	51.50	39.14	12.86	64.36	52.00	74.00	54.00	-2.00	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1716.00	44.87	---	-0.33	44.54	---	74.00	54.00	-9.46	Peak
2352.00	55.00	43.10	3.37	58.37	46.47	74.00	54.00	-7.53	AVG
2594.00	45.27	---	4.15	49.42	---	74.00	54.00	-4.58	Peak
3195.00	42.42	---	5.62	48.04	---	74.00	54.00	-5.96	Peak
4860.00	42.46	---	9.58	52.04	---	74.00	54.00	-1.96	Peak
7305.00	51.28	38.48	12.86	64.14	51.34	74.00	54.00	-2.66	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11n HT20 TX / CH High	Temp. & Humidity	21 °C, 50%

966 Chamber_Bat 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1858.00	45.13	---	0.94	46.07	---	74.00	54.00	-7.93	Peak
2116.00	44.45	---	2.60	47.05	---	74.00	54.00	-6.95	Peak
2388.00	52.18	43.30	3.49	55.67	46.79	74.00	54.00	-7.21	AVG
3885.00	40.98	---	6.76	47.74	---	74.00	54.00	-6.26	Peak
4920.00	46.48	35.56	9.72	56.20	45.28	74.00	54.00	-8.72	AVG
7380.00	47.60	35.24	12.99	60.59	48.23	74.00	54.00	-5.77	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1350.00	45.12	---	-2.75	42.37	---	74.00	54.00	-11.63	Peak
1858.00	44.49	---	0.94	45.43	---	74.00	54.00	-8.57	Peak
2372.00	52.72	43.15	3.44	56.16	46.59	74.00	54.00	-7.41	AVG
3630.00	40.98	---	6.22	47.20	---	74.00	54.00	-6.80	Peak
4920.00	47.73	38.85	9.72	57.45	48.57	74.00	54.00	-5.43	AVG
7380.00	49.69	37.12	12.99	62.68	50.11	74.00	54.00	-3.89	AVG

Remark:

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11n HT40 TX / CH Low	Temp. & Humidity	21°C, 50%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1288.00	45.55	---	-2.95	42.60	---	74.00	54.00	-11.40	Peak
1718.00	45.06	---	-0.31	44.74	---	74.00	54.00	-9.26	Peak
1938.00	44.16	---	1.66	45.82	---	74.00	54.00	-8.18	Peak
3195.00	42.25	---	5.62	47.87	---	74.00	54.00	-6.13	Peak
4125.00	40.34	---	7.42	47.77	---	74.00	54.00	-6.23	Peak
4980.00	39.99	---	9.87	49.86	---	74.00	54.00	-4.14	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1340.00	46.06	---	-2.79	43.28	---	74.00	54.00	-10.72	Peak
1712.00	44.17	---	-0.37	43.81	---	74.00	54.00	-10.19	Peak
1984.00	45.62	---	2.08	47.70	---	74.00	54.00	-6.30	Peak
3225.00	42.20	---	5.65	47.86	---	74.00	54.00	-6.14	Peak
3660.00	41.42	---	6.29	47.71	---	74.00	54.00	-6.29	Peak
4905.00	39.74	---	9.69	49.43	---	74.00	54.00	-4.57	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11n HT40 TX / CH Middle	Temp. & Humidity	21 °C, 50%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1566.00	45.49	---	-1.68	43.81	---	74.00	54.00	-10.19	Peak
1970.00	43.88	---	1.95	45.83	---	74.00	54.00	-8.17	Peak
2342.00	48.17	---	3.34	51.51	---	74.00	54.00	-2.49	Peak
3855.00	40.81	---	6.70	47.51	---	74.00	54.00	-6.49	Peak
4875.00	39.78	---	9.61	49.40	---	74.00	54.00	-4.60	Peak
7305.00	43.04	32.66	12.86	55.90	45.52	74.00	54.00	-8.48	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2290.00	47.09	---	3.17	50.27	---	74.00	54.00	-3.73	Peak
2340.00	48.24	---	3.34	51.58	---	74.00	54.00	-2.42	Peak
2540.00	47.83	---	3.98	51.82	---	74.00	54.00	-2.18	Peak
4140.00	40.46	---	7.47	47.94	---	74.00	54.00	-6.06	Peak
4860.00	39.29	---	9.58	48.86	---	74.00	54.00	-5.14	Peak
7320.00	42.90	33.21	12.88	55.78	46.09	74.00	54.00	-7.91	AVG

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/01
Test Mode	IEEE 802.11n HT40 TX / CH High	Temp. & Humidity	21 °C, 50%

966 Chamber_Bat 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1146.00	46.00	---	-3.41	42.59	---	74.00	54.00	-11.41	Peak
1590.00	44.90	---	-1.46	43.44	---	74.00	54.00	-10.56	Peak
2212.00	44.01	---	2.92	46.93	---	74.00	54.00	-7.07	Peak
3202.50	42.45	---	5.63	48.08	---	74.00	54.00	-5.92	Peak
4432.50	40.05	---	8.46	48.51	---	74.00	54.00	-5.49	Peak
4905.00	40.25	---	9.69	49.94	---	74.00	54.00	-4.06	Peak



966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1290.00	46.75	---	-2.95	43.80	---	74.00	54.00	-10.20	Peak
1932.00	44.48	---	1.61	46.09	---	74.00	54.00	-7.91	Peak
2302.00	48.36	---	3.21	51.57	---	74.00	54.00	-2.43	Peak
3247.50	42.20	---	5.68	47.88	---	74.00	54.00	-6.12	Peak
4635.00	40.76	---	9.02	49.78	---	74.00	54.00	-4.22	Peak
4920.00	40.67	---	9.72	50.39	---	74.00	54.00	-3.61	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(AV)
Remark AVG = Result(AV) - Limit(AV)




Restricted Band Edges






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average

Polarity : Vertical





7.7 CONDUCTED EMISSION

LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dB μ v)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5.00	56	46
5.00 - 30.0	60	50



TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-465	08/09/2012
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-473	03/12/2013
EMI Receiver	ROHDE & SCHWARZ	ESCS 30	835418/008	10/20/2012
Pulse Limit	ROHDE & SCHWARZ	ESH3-Z2	100117	09/14/2012

Remark: Each piece of equipment is scheduled for calibration once a year.



TEST SETUP





TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4:2003.

The test procedure is performed in a 4m × 3m × 2.4m (L×W×H) shielded room.

The EUT along with its peripherals were placed on a 1.0m (W) × 1.5m (L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.


The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.



TEST RESULTS

Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/05
Test Mode	Normal Operating	Temp. & Humidity	20 °C, 60%

LINE




Remark:

1. Correction Factor = Insertion loss + Cable loss
2. Emission level = Reading Value + Correction factor
3. Margin value = Emission level - Limit value



Product Name	IP CAM	Test By	Waternil Guan
Test Model	F1105	Test Date	2012/04/05
Test Mode	Normal Operating	Temp. & Humidity	20°C, 60%

NEUTRAL



Remark:

1. Correction Factor = Insertion loss + Cable loss
2. Emission level = Reading Value + Correction factor
3. Margin value = Emission level – Limit value