
NOTE(S):

- 1.
- ADHESIVE LABELS, FORMED OFRECOGNIZED COMPONENT, MARKING AND LABELING SYSTEM (PGDQ2) CN, RATED MINIMUM 60 C AND SUITABLE FOR SURFACE INVOLVED MATERIAL: NON-GLOSS/MATTE WHITE POLYESTER FILM & BLACK INK. 2MIL MINIMUM THICKNESS 2.

ECO	REV	VER	DESCRIPTION	BY	DATE	APVD
1430	-	00	RELEASE	LG	17-SEP-20	JH
1718	А	00	WAS: JECKSON PCB, NOW: ANTAI	LG	22-JUN-23	JH
	В	00	PRELIMINARY #1	LG	19-OCT-23	JH





			INCH TOLERANCES ARE X.X ± 0.1 X.XX ± 0.03	METRIC TOLERANCES ARE X.X ± 2.5 X.XX ± 0.8	V	ORN		415 EAST ANDOVER, 1-316-73	KS. 67002
			X.XXX ± 0.01 X.X ± 0.5°	X.XXX ± 0.25 X.X ± 0.5°	THIRD		PART NAME LABEL, FCC/IC	,	
		DRAWN BY	03-Aug-20	PROJECTION		WORKMANSHIP SHALL MEET OR EXCEED VORNADO SPECIFICATION ES-001			
			APPROVED BY	03-Aug-20	SIZE	SCALE 2:1	SHEET 1 OF 1	COLOR	
			THIS PRINT AND TH CONTAINED ON IT DISCLOSURE. THE	IS A CONFIDENTIAL			4005	REV	
	DASH NO.	DESCRIPTION	OF WHICH IS THE F VORNADO AIR, LLC	PROPERTY OF		LB3-	1665	D	00