

Report No.: TW2407221E

Applicant: Shenzhen SQT Electronics Co., Ltd

Product: Wireless Mouse

Model No.: SMK-646M8AG (see the page 4 for additional models)

Trademark: N/A

Test Standards: FCC Part 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10 & FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Terry Tang

Manager

Dated: August 05, 2024

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

## SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail: info@timeway-lab.com

Report No.: TW2407221E Page 2 of 37

Date: 2024-08-05



## **Special Statement:**

## FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

## Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

## **A2LA** (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

CAB identifier: CN0033

Report No.: TW2407221E

Date: 2024-08-05



## Test Report Conclusion

#### Content General Details ..... 1.0 Test Lab Details.... 1.1 4 1.2 Applicant Details.... 4 1.3 Description of EUT .... 4 1.4 Submitted Sample.... 4 Test Duration. 1.5 5 5 1.6 Test Uncertainty. 1.7 Test By..... 5 2.0 List of Measurement Equipment. 6 7 3.0 Technical Details..... 3.1 Summary of Test Results.... 7 3.2 7 Test Standards.... 4.0 7 EUT Modification. Power Line Conducted Emission Test. 5.0 5.1 Schematics of the Test.... 8 Test Method and Test Procedure.... 5.2 8 Configuration of the EUT..... 5.3 8 5.4 EUT Operating Condition.... 9 9 5.5 Conducted Emission Limit..... 5.6 Test Result. 6.0 Radiated Emission test.... 10 Test Method and Test Procedure.... 10 6.1 6.2 Configuration of the EUT..... 11 EUT Operation Condition.... 6.3 11 6.4 Radiated Emission Limit.... 12 6.5 Test Result. 13 7.0 Band Edge..... 21 7.1 Test Method and Test Procedure. 21 7.2 Radiated Test Setup. 21 7.3 Configuration of the EUT.... 21 7.4 EUT Operating Condition.... 21 7.5 Band Edge Limit. 21 7.6 Band Edge Test Result. 22 8.0 Antenna Requirement. 26 20dB bandwidth measurement.... 9.0 27 10.0 30 FCC ID Label.

The report refers only to the sample tested and does not apply to the bulk.

11.0

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Photo of Test Setup and EUT View.

Date: 2024-08-05



#### 1.0 General Details

#### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189 For 3m Anechoic Chamber

## 1.2 Applicant Details

Applicant: Shenzhen SQT Electronics Co., Ltd

Address: ZhengChengFeng TechnologyZone Xinsha Road, ShaYi Village, Sha jing Town, Baoan Area,

Shenzhen, China

#### 1.3 Description of EUT

Product: Wireless Mouse

Manufacturer: Shenzhen SQT Electronics Co., Ltd

Address: ZhengChengFeng TechnologyZone Xinsha Road, ShaYi Village, Sha jing

Town, Baoan Area, Shenzhen, China

Trademark: N/A

Model Number: SMK-646M8AG

Additional Model Name SK-646AG, SMK-646350AG, SMK-646367AG, SMK-646372AG,

SMK-646382AG, SMK-646398AG, SMK-646M7AG, SMK-646396AG, SMK-646376AG, SMK-646395AG, SMK-646391AG, SMK-646383AG, SMK-646M3AG, SMK-646M3DM, SMK-648M3AG, SMK-632392AG,

SMK-640M2AG, SMK-623387AG, M8AG

Rating: DC1.5V, 1pc AA battery

Modulation Type: GFSK

Operation Frequency: 2402-2480MHz

Channel Separation: 2MHz
Channel Number: 40
Hardware Version: V1.3

Software Version: FF130598-4009 Serial No.: 1315EK07240701

Antenna Designation PCB antenna with gain -0.61dBi Max (Get from the antenna test report)

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2407221E Page 5 of 37

Date: 2024-08-05



1.4 Submitted Sample: 4 Samples

1.5 Test Duration 2024-07-26 to 2024-08-05

## 1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty =6.0dB

Occupied Channel Bandwidth Uncertainty = 5%

Conducted Emissions Uncertainty = 3.6dB

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by

Print Name: Andy Xing

Page 6 of 37

Report No.: TW2407221E

Date: 2024-08-05



| 2.0 Test Equipment     |              |                  |              |              |            |
|------------------------|--------------|------------------|--------------|--------------|------------|
| Instrument Type        | Manufacturer | Model            | Serial No.   | Date of Cal. | Due Date   |
| ESPI Test Receiver R&S |              | ESPI 3           | 100379       | 2024-07-12   | 2025-07-11 |
| LISN                   | R&S          | EZH3-Z5          | 100294       | 2024-07-12   | 2025-07-11 |
| LISN                   | R&S          | EZH3-Z5          | 100253       | 2024-07-12   | 2025-07-11 |
| Impuls-Begrenzer       | R&S          | ESH3-Z2          | 100281       | 2024-07-12   | 2025-07-11 |
| Loop Antenna           | EMCO         | 6507             | 00078608     | 2022-07-18   | 2025-07-17 |
| Spectrum               | R&S          | FSIQ26           | 100292       | 2024-07-12   | 2025-07-11 |
| Horn Antenna           | A-INFO       | LB-180400-KF     | J211060660   | 2022-07-18   | 2025-07-17 |
| Horn Antenna           | R&S          | BBHA 9120D       | 9120D-631    | 2022-07-18   | 2025-07-17 |
| Power meter            | Anritsu      | ML2487A          | 6K00003613   | 2024-07-12   | 2025-07-11 |
| Power sensor           | Anritsu      | MA2491A          | 32263        | 2024-07-12   | 2025-07-11 |
| Bilog Antenna          | Schwarebeck  | VULB9163         | 9163/340     | 2022-07-18   | 2025-07-17 |
| 9*6*6 Anechoic         |              |                  | N/A          | 2022-07-26   | 2025-07-25 |
| EMI Test Receiver      | RS           | ESVB             | 826156/011   | 2024-07-12   | 2025-07-11 |
| EMI Test Receiver      | RS           | ESCS 30          | 834115/006   | 2024-07-12   | 2025-07-11 |
| Spectrum               | HP/Agilent   | E4407B           | MY50441392   | 2024-07-12   | 2025-07-11 |
| Spectrum               | RS           | FSP              | 1164.4391.38 | 2024-07-12   | 2025-07-11 |
| RF Cable               | Zhengdi      | ZT26-NJ-NJ-8M/FA |              | 2024-07-12   | 2025-07-11 |
| RF Cable               | Zhengdi      | 7m               |              | 2024-07-12   | 2025-07-11 |
| Pre-Amplifier          | Schwarebeck  | BBV9743          | #218         | 2024-07-12   | 2025-07-11 |
| Pre-Amplifier          | HP/Agilent   | 8449B            | 3008A00160   | 2024-07-12   | 2025-07-11 |
| LISN                   | SCHAFFNER    | NNB42            | 00012        | 2024-07-12   | 2025-07-11 |
| ESPI Test Receiver     | R&S          | ESPI 3           | 100379       | 2024-07-12   | 2025-07-11 |
| LISN                   | R&S          | EZH3-Z5          | 100294       | 2024-07-12   | 2025-07-11 |

## 2.2 Automation Test Software

#### For Conducted Emission Test

| Name   | Version           |  |  |
|--------|-------------------|--|--|
| EZ-EMC | Ver.EMC-CON 3A1.1 |  |  |

## For Radiated Emissions

| Name  | Version |
|---|---------|
| EMI Test Software BL410-EV18.91                 | V18.905 |
| EMI Test Software BL410-EV18.806 High Frequency | V18.06  |

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2407221E Page 7 of 37

Date: 2024-08-05



#### 3.0 Technical Details

## 3.1 Summary of test results

The EUT has been tested according to the following specifications:

| Standard  | Test Type                           | Result | Notes    |
|---|-------------------------------------|--------|----------|
| FCC Part 15, Paragraph 15.203                               | Antenna<br>Requirement              | Pass   | Complies |
| FCC Part 15, Paragraph 15.207                               | Conducted<br>Emission Test          | N/A    | N/A      |
| FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit | Field Strength<br>of<br>Fundamental | Pass   | Complies |
| FCC Part 15, Paragraph 15.209                               | Radiated<br>Emission Test           | Pass   | Complies |
| FCC Part 15 Subpart C Paragraph 15.249(d) Limit             | Band Edge<br>Test                   | Pass   | Complies |

## 3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249, ANSI C63.4:2014 and ANSI C63.10:2013

#### 4.0 EUT Modification

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES


Report No.: TW2407221E

Date: 2024-08-05



## 5. Power Line Conducted Emission Test

## 5.1 Schematics of the test




**EUT: Equipment Under Test** 

## 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum from 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: N/A

Block diagram of Test setup



## 5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

40 channels are provided to the EUT

## A. EUT

| Device         | Manufacturer                      | Model                              | FCC ID          |
|----------------|-----------------------------------|------------------------------------|-----------------|
| Wireless Mouse | Shenzhen SQT Electronics Co., Ltd | SMK-646M8AG<br>(see the page 4 for | WOX-SM-M8A<br>G |
|                |                                   | additional models)                 |                 |

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2407221E Page 9 of 37

Date: 2024-08-05



#### B. Internal Device

| Device | Manufacturer | Model | FCC ID/DOC |
|--------|--------------|-------|------------|
| N/A    |              |       |            |

## C. Peripherals

| Device | Manufacturer | Model | Rating |
|--------|--------------|-------|--------|
| N/A    |              |       |        |

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

| Frequency    | Limits (dB μ V)  |               |  |  |  |
|--------------|------------------|---------------|--|--|--|
| (MHz)        | Quasi-peak Level | Average Level |  |  |  |
| 0.15 ~ 0.50  | 66.0~56.0*       | 56.0~46.0*    |  |  |  |
| 0.50 ~ 5.00  | 56.0             | 46.0          |  |  |  |
| 5.00 ~ 30.00 | 60.0             | 50.0          |  |  |  |

Notes: 1. \*Decreasing linearly with logarithm of frequency.

2. The tighter limit shall apply at the transition frequencies

5.6 Test Results: N/A

Note: EUT powered by AA battery, so this test item not applicable.

Report No.: TW2407221E Page 10 of 37

Date: 2024-08-05




#### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 9kHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz (Note: for Fundamental frequency radiated emission measurement, RBW=3MHz, VBW=10MHz). Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

## **Block diagram of Test setup**

For radiated emissions from 9kHz to 30MHz




Report No.: TW2407221E


Date: 2024-08-05



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



# 6.2 Configuration of the EUT Same as section 5.3 of this report

## 6.3 EUT Operating Condition

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Date: 2024-08-05



Same as section 5.4 of this report.

#### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

## A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

| Fundamental Frequency | Field Stre  | ngth of Fundame | ntal (3m)  | Field Strength of Harmonics (3m) |              |           |
|-----------------------|-------------|-----------------|------------|----------------------------------|--------------|-----------|
| (MHz)                 | mV/m dBuV/m |                 |            | uV/m                             | dBu          | V/m       |
| 2400-2483.5           | 50          | 94 (Average)    | 114 (Peak) | 500                              | 54 (Average) | 74 (Peak) |

Note:

- 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

## B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

| Frequency Range (MHz) | Distance (m) | Field strength (dB $\mu$ V/m)     |  |  |
|-----------------------|--------------|-----------------------------------|--|--|
| 0.009-0.490           | 3            | 20log(2400/F(kHz)) +40log (300/3) |  |  |
| 0.490-1.705           | 3            | 20log(24000/F(kHz)) +40log (30/3) |  |  |
| 1.705-30              | 3            | 69.5                              |  |  |
| 30-80                 | 3            | 40.0                              |  |  |
| 88-216                | 3            | 43.5                              |  |  |
| 216-960               | 3            | 46.0                              |  |  |
| Above 960             | 3            | 54.0                              |  |  |

Note:

- 1. RF Voltage  $(dBuV) = 20 \log RF Voltage (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK. For fundamental measurement, PK detector used.
- 5. For radiated emissions from 9kHz to 30MHz, the emission level is much less than the limit for more than 20dB. No necessary to take down the record.
- 6. New battery was used during the radiation test.

Report No.: TW2407221E Page 13 of 37

Date: 2024-08-05




## 6.5 Test result

## A Fundamental & Harmonics Radiated Emission Data

Please refer to the following test plots for details: Low Channel-2402MHz

## Horizontal




| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table  | Height | ANT        | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|--------|--------|------------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)    | (cm)   |            |         |
| 1   | 2402      | 87.27    | -3.57  | 114.0    | -26.73     | Peak     | 198.00 | 100    | Horizontal | Pass    |
| 2   | 4803.799  | 49.60    | 3.12   | 74.0     | -24.40     | Peak     | 208.00 | 100    | Horizontal | Pass    |

Report No.: TW2407221E Page 14 of 37

Date: 2024-08-05



## Vertical



| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table | Height | ANT      | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|-------|--------|----------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)   | (cm)   |          |         |
| 1   | 2402      | 75.70    | -3.57  | 114.0    | -38.30     | Peak     | 0.00  | 100    | Vertical | Pass    |


Report No.: TW2407221E Page 15 of 37

Date: 2024-08-05



Please refer to the following test plots for details: Middle Channel- 2440MHz

#### **Horizontal**




| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table  | Height | ANT        | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|--------|--------|------------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)    | (cm)   |            |         |
| 1   | 2440      | 87.49    | -3.57  | 114.0    | -26.51     | Peak     | 161.00 | 100    | Horizontal | Pass    |
| 2   | 4879.280  | 50.06    | 3.20   | 74.0     | -23.94     | Peak     | 250.00 | 100    | Horizontal | Pass    |

Report No.: TW2407221E Page 16 of 37

Date: 2024-08-05



## Vertical



| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table | Height | ANT      | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|-------|--------|----------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)   | (cm)   |          |         |
| 1   | 2440      | 75.45    | -3.57  | 114.0    | -38.55     | Peak     | 10.00 | 100    | Vertical | Pass    |


Report No.: TW2407221E Page 17 of 37

Date: 2024-08-05



Please refer to the following test plots for details: High Channel-2480MHz

#### **Horizontal**



| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table  | Height | ANT        | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|--------|--------|------------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)    | (cm)   |            |         |
| 1   | 2480      | 86.41    | -3.57  | 114.0    | -27.59     | Peak     | 171.00 | 100    | Horizontal | Pass    |


Page 18 of 37

Report No.: TW2407221E

Date: 2024-08-05



#### Vertical



| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table | Height | ANT      | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|-------|--------|----------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)   | (cm)   |          |         |
| 1   | 2480      | 76.07    | -3.57  | 114.0    | -37.93     | Peak     | 2.00  | 100    | Vertical | Pass    |

Note: (2) Emission Level = Reading Level + Antenna Factor + Cable Loss-Amplifier

- (3) Margin=Emission-Limits
- (4) According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) For test purpose, keep EUT continuous transmitting
- (5) For emission above 18GHz and Below 30MHz, it is only the floor noise. No necessary to take down.
- (6) the measured PK value less than the AV limit.

Report No.: TW2407221E Page 19 of 37

Date: 2024-08-05




## B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

**Results:** Pass

Please refer to following diagram for individual



| No. | Frequency | Results  | Factor | Limit    | Margin | Detector | Table    | Height | Antenna    | Verdict |
|-----|-----------|----------|--------|----------|--------|----------|----------|--------|------------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)   |          | (Degree) | (cm)   |            |         |
| 1   | 190.980   | 36.95    | -14.24 | 43.5     | 6.55   | Peak     | 260.00   | 100    | Horizontal | Pass    |
| 2   | 203.344   | 37.40    | -13.46 | 43.5     | 6.10   | Peak     | 260.00   | 100    | Horizontal | Pass    |
| 3   | 277.046   | 41.00    | -11.54 | 46.0     | 5.00   | Peak     | 260.00   | 100    | Horizontal | Pass    |
| 4   | 307.836   | 41.80    | -10.93 | 46.0     | 4.20   | Peak     | 263.00   | 100    | Horizontal | Pass    |
| 5   | 478.270   | 32.84    | -7.45  | 46.0     | 13.16  | Peak     | 68.00    | 100    | Horizontal | Pass    |
| 6   | 604.096   | 31.44    | -4.96  | 46.0     | 14.56  | Peak     | 249.00   | 100    | Horizontal | Pass    |

Report No.: TW2407221E Page 20 of 37

Date: 2024-08-05




## Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

**Results:** Pass

Please refer to following diagram for individual



| No. | Frequency | Results  | Factor | Limit    | Margin | Detector | Table    | Height | Antenna  | Verdict |
|-----|-----------|----------|--------|----------|--------|----------|----------|--------|----------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)   |          | (Degree) | (cm)   |          |         |
| 1   | 32.909    | 34.44    | -14.43 | 40.0     | 5.56   | Peak     | 286.00   | 100    | Vertical | Pass    |
| 2   | 63.214    | 31.01    | -13.32 | 40.0     | 8.99   | Peak     | 228.00   | 100    | Vertical | Pass    |
| 3   | 133.522   | 34.76    | -16.98 | 43.5     | 8.74   | Peak     | 297.00   | 100    | Vertical | Pass    |
| 4   | 188.070   | 38.83    | -14.46 | 43.5     | 4.67   | Peak     | 0.00     | 100    | Vertical | Pass    |
| 5   | 197.041   | 39.10    | -13.54 | 43.5     | 4.40   | Peak     | 139.00   | 100    | Vertical | Pass    |
| 6   | 326.988   | 34.77    | -10.31 | 46.0     | 11.23  | Peak     | 225.00   | 100    | Vertical | Pass    |

Report No.: TW2407221E Page 21 of 37

Date: 2024-08-05




## 7. Band Edge

#### 7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) Set Spectrum as RBW=1MHz, VBW=3MHz and Peak detector used for PK value. RBW=1MHz, VBW=10Hz and Peak detector used for AV value.
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

## 7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

## 7.3 Configuration of the EUT

Same as section 5.3 of this report

## 7.4 EUT Operating Condition

Same as section 5.4 of this report.

## 7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No.: TW2407221E Page 22 of 37

Date: 2024-08-05



## 7.6 Test Result

| Product:     | Wireless Mouse       | Polarity     | Horizontal |
|--------------|----------------------|--------------|------------|
| Mode         | Keeping Transmitting | Test Voltage | DC1.5V     |
| Temperature  | 24 deg. C,           | Humidity     | 56% RH     |
| Test Result: | Pass                 |              |            |




| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table  | Height | ANT        | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|--------|--------|------------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)    | (cm)   |            |         |
| 1   | 2401.887  | 86.54    | -3.57  | 74.0     | 12.54      | Peak     | 145.00 | 100    | Horizontal | N/A     |
| 2   | 2400.042  | 67.32    | -3.57  | 74.0     | -6.68      | Peak     | 99.00  | 100    | Horizontal | Pass    |
| 2** | 2400.042  | 51.83    | -3.57  | 54.0     | -2.17      | AV       | 99.00  | 100    | Horizontal | Pass    |
| 3   | 2390.070  | 39.30    | -3.53  | 74.0     | -34.70     | Peak     | 140.00 | 100    | Horizontal | Pass    |
| 4   | 2386.291  | 51.41    | -3.52  | 74.0     | -22.59     | Peak     | 126.00 | 100    | Horizontal | Pass    |
| 5   | 2389.500  | 51.66    | -3.53  | 74.0     | -22.34     | Peak     | 124.00 | 100    | Horizontal | Pass    |

Report No.: TW2407221E Page 23 of 37



| N/L 1        |                      | Detector     | Vertical |
|--------------|----------------------|--------------|----------|
| Mode         | Keeping Transmitting | Test Voltage | DC1.5V   |
| Temperature  | 24 deg. C,           | Humidity     | 56% RH   |
| Test Result: | Pass                 |              |          |



| No. | Frequency | Results  | Factor | Limit    | Over Limit | Detector | Table | Height | ANT      | Verdict |
|-----|-----------|----------|--------|----------|------------|----------|-------|--------|----------|---------|
|     | (MHz)     | (dBuV/m) | (dB)   | (dBuV/m) | (dB)       |          | (o)   | (cm)   |          |         |
| 1   | 2401.617  | 75.01    | -3.57  | 74.0     | 1.01       | Peak     | 40.00 | 100    | Vertical | N/A     |
| 2   | 2400.087  | 46.44    | -3.57  | 74.0     | -27.56     | Peak     | 0.00  | 100    | Vertical | Pass    |
| 3   | 2390.055  | 36.65    | -3.53  | 74.0     | -37.35     | Peak     | 1.00  | 100    | Vertical | Pass    |
| 4   | 2397.388  | 51.60    | -3.56  | 74.0     | -22.40     | Peak     | 91.00 | 100    | Vertical | Pass    |
| 5   | 2398.633  | 53.69    | -3.56  | 74.0     | -20.31     | Peak     | 85.00 | 100    | Vertical | Pass    |

Report No.: TW2407221E Page 24 of 37



| Product:                                |            |                     | Wireless    | Mouse      |                        | Pola     | rity      |             | Horizonta | ıl          |
|---|------------|---------------------|-------------|------------|------------------------|----------|-----------|-------------|-----------|-------------|
| Mode                                    |            | K                   | eeping Tra  | ansmitting |                        | Test V   | oltage    |             | DC1.5V    |             |
| Temperatu                               | e          |                     | 24 deg      | g. C,      |                        | Hum      | idity     |             | 56% RH    |             |
| Test Resul                              | :          |                     | Pas         | SS         |                        |          | -         |             |           |             |
| Part 15C Class B 1G<br>1.0E+2-          | z-18GHz -2 |                     |             |            |                        |          |           |             |           |             |
| 90-<br>80-<br>70-                       |            |                     | M1          |            |                        |          |           |             |           |             |
| 60 -<br>50 -<br>40 -<br>30 -            |            |                     | Y I         | 1493       |                        |          |           |             |           |             |
| 50-                                     |            |                     | 1           |            |                        |          |           |             |           |             |
| 50-<br>40-<br>30-                       |            |                     |             | 2483       | 3.5<br>Frequency (MHz) |          |           |             |           | 2:          |
| 50-<br>40-<br>30-<br>20-<br>10-         | су В       | Results             | Factor      | 2483       |                        | Detector | Table     | Height      | ANT       | 1           |
| 50-<br>40-<br>30-<br>20-<br>10-<br>2470 |            | Results<br>(dBuV/m) | Factor (dB) | 1          | Frequency (MHz)        | Detector | Table (o) | Height (cm) | ANT       | 2:<br>Verdi |
| 30-<br>20-<br>10-<br>2470               | (0         |                     |             | Limit      | Over                   | Detector |           | _           | ANT       | 1           |

Report No.: TW2407221E Page 25 of 37



| ŀ                             | Product:                      |                  | Wireless N                              | Mouse                               | I                        | Detector   |               | Ve   | rtical                        |  |
|-------------------------------|-------------------------------|------------------|---|-------------------------------------|--------------------------|------------|---------------|--|-------------------------------|--|
|                               | Mode                          | Ke               | eping Trar                              | nsmitting                           | Te                       | st Voltage |               | DC   | C1.5V                         |  |
| Tei                           | mperature                     |                  | 24 deg.                                 | C,                                  | H                        | Humidity   |               | 569  | % RH                          |  |
| Te                            | est Result:                   |                  | Pass                                    |                                     |                          |            |               |  |                               |  |
| Part 1:                       | 5C Class B 1GHz-18GHz -<br>2- | 2                |   |                                     | •                        |            | •             |  |                               |  |
| 90                            | 0-                            |                  |   |                                     |                          |            |               |  |                               |  |
| 80                            | 0-                            |                  | M1                                      |                                     |                          |            |               |  |                               |  |
| 00                            |                               |                  | 1111000                                 |                                     |                          |            |               |  |                               |  |
| 70                            | 0-                            |                  | . [[]                                   | A.ı                                 |                          |            |               |  |                               |  |
| 60                            | 0-                            |                  | 4/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1 | M3                                  |                          |            |               |  |                               |  |
|                               |                               | 1                | A DESCRIPTION OF THE                    | HIIIIA KALI IA MIS                  |                          |            |               |  |                               |  |
| 50                            | 0-                            |                  |   |                                     | - Landa                  |            |               |  |                               |  |
| 50                            | والأرب المالاوال              |                  |   | IVA IVA                             |                          |            |               | h k  |                               |  |
| 40                            | 0-                            |                  |   |                                     |                          |            |               |  |                               | Hyrdinal (1)   |
| 50<br>40<br>30                | 0-                            |                  |   |                                     |                          |            |               |  | A STATE OF THE REAL PROPERTY. | Hydina de de   |
| 40                            | 0-                            |                  |   |                                     |                          |            | tti, litatiku | LL THE STREET  | the state of the state of     | No. de la del  |
| 40<br>30                      | 0-400000                      |                  |   |                                     |                          |            |               | L. L. Avalor, M. M. Alberton, A.                     | hadara galda yak              | diplomatical distribution of the second of t |
| 40<br>30<br>20<br>10          |                               |                  |   |                                     |                          |            |               | A. A. San and A. | Library Market                | hydadyd  |
| 40<br>30<br>20<br>10          |                               |                  |   | 2483.5                              | quency (MHz)             |            |               | Hallander Hadde Albert L                             | historia da da sinta          | 2500   |
| 40<br>30<br>20<br>10          |                               | Results          | Factor                                  | 2483.5                              | quency (MHz)  Over Limit | Detector   | Table         | Height   | ANT                           | 1  |
| 40<br>30<br>20<br>10          | 0-2470                        | Results (dBuV/m) | Factor (dB)                             | 2483.5<br>Free                      |                          |            |               |  |                               | 1  |
| 40<br>30<br>20<br>10<br>0.0.: | Frequency                     |                  |   | 2483.5<br>Free                      | Over Limit               |            | Table         | Height   |                               | 1  |
| 40<br>30<br>20<br>10          | Frequency<br>(MHz)            | (dBuV/m)         | (dB)                                    | 2483.5<br>Free<br>Limit<br>(dBuV/m) | Over Limit (dB)          | Detector   | Table (o)     | Height (cm)  | ANT                           | Verdi  |

Report No.: TW2407221E Page 26 of 37

Date: 2024-08-05



## 8.0 Antenna Requirement

## **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has an PCB antenna. The antenna gain is -0.61dBi Max. It fulfills the requirement of this section. Test Result: Pass

Page 27 of 37

Report No.: TW2407221E



| Product: Wireless Mouse                 |  |            |         |        |    | est Mode:             | Keep transmitting |              |                      |    |  |  |
|---|--|------------|---------|--------|----|-----------------------|-------------------|--------------|----------------------|----|--|--|
| Mode Keeping Transmitting               |  |            |         |        | Te | st Voltage            |                   |              |                      |    |  |  |
| Temperature 24 deg. C,                  |  |            |         |        | I  | Humidity              |                   | 56% RH<br>PK |                      |    |  |  |
| Test Result:                            |  | Pass       |         |        |    | Detector              |                   |              |                      |    |  |  |
| dB Bandwidth                            | 2  | 2.164MHz   |         |        |    |                       |                   |              |                      |    |  |  |
| <b>&gt;</b>                             | Delta 1  | [T1]       |         | RI     | ВW | 100 k                 | Hz F              | RF Att       | 20 dB                |    |  |  |
| Ref Lvl                                 |  | 0.         | .61 dB  | VI     | ВW | 300 k                 | Ηz                |              |                      |    |  |  |
| 10 dBm                                  | 2  | .164328    | 366 MHz | SV     | TV | 5 m                   | s t               | Jnit         | dBm                  | n  |  |  |
| 10                                      |  |            |         |        |    | ▼1                    | [T1]              | -2           | 7.51 dBm             | 1_ |  |  |
|   |  |            |         |        |    |                       |                   | 2.40095      | 291 GHz              |    |  |  |
| 0                                       |  |            |         | 2      |    | <b>▲</b> <sup>1</sup> | [T1]              |              | .61 ав               | 1  |  |  |
|   |  |            | -0      | Z<br>Z |    | <b>V</b> 2            |                   | 2.16432      | 2866 MHz<br>7.40 dBm |    |  |  |
| -10                                     |  |            | All by  | 7      |    | ¥ Z                   | [++]              | 2.40204      |                      | 1  |  |  |
|   |  |            | f       | `      | V) |                       |                   |              |                      |    |  |  |
| -20                                     |  |            |         |        |    | <del>\</del>          |                   |              |                      | 1  |  |  |
| 1MAX<br>_D1 -27.4 d                     | Bm   | <u>//·</u> |         |        |    | [e/                   | 1                 |              |                      | 11 |  |  |
| -30                                     |  |            |         |        | _  |                       | 1                 |              |                      | ł  |  |  |
|   | المسر  |            |         |        |    |                       | V                 | i a          |                      |    |  |  |
| -40                                     | and the same of th |            |         |        |    |                       |                   | W            | 4.                   | ł  |  |  |
| war |  |            |         |        |    |                       |                   | 4            | word                 | ļ  |  |  |
| -50                                     |  |            |         |        | _  |                       |                   |              |                      | ł  |  |  |
|   |  |            |         |        |    |                       |                   |              |                      |    |  |  |
| -60                                     |  |            |         |        |    |                       |                   |              |                      | ł  |  |  |
|   |  |            |         |        |    |                       |                   |              |                      |    |  |  |
| -70                                     |  |            |         |        | _  |                       |                   |              |                      | 1  |  |  |
|   |  |            |         |        |    |                       |                   |              |                      |    |  |  |
| -80                                     |  |            |         |        |    |                       |                   |              |                      | 1  |  |  |
|   |  |            |         |        |    |                       |                   |              |                      |    |  |  |
| -90                                     |  |            |         |        |    |                       |                   |              |                      | ]  |  |  |
| Center 2.40                             | 2 GHz  | <u></u>    | 500     | kHz/   |    | <u></u>               |                   | Spa          | an 5 MHz             |    |  |  |

Page 28 of 37

Report No.: TW2407221E



| Product:        | Wireless Mouse       |             |          |        |               | Т  | est Mode:   |            | Keep transmitting |               |     |  |  |
|-----------------|----------------------|-------------|----------|--------|---------------|----|-------------|------------|-------------------|---------------|-----|--|--|
| Mode            | Keeping Transmitting |             |          |        |               |    | est Voltage |            | DC1.5V            |               |     |  |  |
| Temperature     | 24 deg. C,           |             |          |        |               | ]  | Humidity    |            | 56% RH            |               |     |  |  |
| Test Result:    | Pass                 |             |          |        |               |    | Detector    |            | PK                |               |     |  |  |
| 20dB Bandwidth  | 2.184MHz             |             |          |        |               |    |             |            |                   |               |     |  |  |
| (Fee)           |                      | Delta 1     | [T1]     |        | R             | BW | 100 k       | Hz l       | RF Att            | 20 dB         |     |  |  |
| Ref Lvl         |                      |             | 0.       | 42 dB  | V             | BW | 300 k       |            |                   |               |     |  |  |
| 10 dBm          |                      | 2           | 2.184368 | 74 MHz | S             | WT | 5 m         | ıs T       | Unit              | dBm           | ı   |  |  |
| 10              |                      |             |          |        |               |    | ▼1          | [T1]       | -27               | .98 dBm       |     |  |  |
|                 |                      |             |          |        |               |    |             |            | 2.43894           | 289 GHz       | A   |  |  |
| 0               |                      |             |          |        |               |    | <b>^</b> 1  | [T1]       |                   | .42 dB        |     |  |  |
|                 |                      |             |          |        | 2<br><b>∀</b> |    | <b></b>     |            | 2.18436           | 874 MHz       |     |  |  |
| -10             |                      |             |          | -      | 1             |    | <b>∇</b> 2  | [T1]       | 2.44003           | .66 dBm       |     |  |  |
| -20             |                      |             |          |        | }             | 7  |             |            | 2.44003           | 307 GHZ       |     |  |  |
| 1MAX            |                      | 1/          | ممريم    |        |               |    |             | $\gamma_1$ |                   |               | 1MA |  |  |
| D1 -27.         | 66 dBm               | <del></del> | ¥        |        |               |    |             | 4          |                   |               |     |  |  |
|                 |                      | and a       |          |        |               |    |             | 1          |                   |               |     |  |  |
| -40             | un                   |             |          |        |               |    |             |            |                   | Ven           |     |  |  |
| -50             |                      |             |          |        |               |    |             |            |                   |               |     |  |  |
| -60             |                      |             |          |        |               |    |             |            |                   |               |     |  |  |
|                 |                      |             |          |        |               |    |             |            |                   |               |     |  |  |
| -70             |                      |             |          |        |               |    |             |            |                   |               |     |  |  |
| -80             |                      |             |          |        |               |    |             |            |                   |               |     |  |  |
|                 |                      |             |          |        |               |    |             |            |                   |               |     |  |  |
| -90<br>Center 2 | .44 GH2              | Z           |          | 500    | kHz/          |    |             |            | Spa               | l<br>ın 5 MHz | ı   |  |  |
| Date: 33        | 1.JUL.2              | 024 16      | :30:51   |        |               |    |             |            |                   |               |     |  |  |

Page 29 of 37

Report No.: TW2407221E



| Product:         | Wireless Mouse       |         |                |         |               | Test Mode: |  |      | Keep transmitting |        |                 |         |  |
|------------------|----------------------|---------|----------------|---------|---------------|------------|--|------|-------------------|--------|-----------------|---------|--|
| Mode             | Keeping Transmitting |         |                |         |               | Te         | est Voltage  | e    | DC1.5V            |        |                 |         |  |
| Temperature      | 24 deg. C,           |         |                |         |               | Humidity   |  |      | 56% RH            |        |                 |         |  |
| Test Result:     | Pass                 |         |                |         |               | Detector   |  |      | PK                |        |                 |         |  |
| 20dB Bandwidth   | 2.184MHz             |         |                |         |               |            |  |      |                   |        |                 |         |  |
| /s/m             |                      | Delta 1 | [T1]           |         | R             | BW         | 100 k  | KHZ  | RF                | Att    | 20 d            | lB      |  |
| Ref Lvl          |                      |         | 0.             | 33 dB   | V             | BW         | 300 k  | KHZ  |                   |        |                 |         |  |
| 10 dBm           |                      | 2       | 2.184368       | 374 MHz | S             | WT         | 5 n  | ns   | Uni               | .t     | d               | Bm      |  |
| 10               |                      |         |                |         |               |            | ▼1   | [T1] |                   | -27    | .78 d           |         |  |
|                  |                      |         |                |         |               |            |  |      | 2                 | .47894 | 289 G           | Ηz      |  |
| 0                |                      |         |                |         |               |            | <b>▲</b> ¹   | [T1] |                   | 0      | .33 d           | В       |  |
|                  |                      |         |                |         | 2<br><b>X</b> |            | <b>∇</b> 2   | [T1] | 2                 | .18436 | 874 M           |         |  |
| -10              |                      |         |                | /k/     |               |            | <b>V</b> Z   | [TI] | 2                 | .48003 |                 | Hz      |  |
|                  |                      |         |                |         | ,             | Z          |  |      |                   |        |                 |         |  |
| -20              |                      |         | ~ ~~           |         |               |            | the state of the s |      |                   |        |                 | -       |  |
| 1MAX<br>_D1 -28. | 08 dBm               | 1       | \ <del>\</del> |         |               |            | V—   |      |                   |        |                 | 1MA     |  |
| -30              |                      |         |                |         |               |            |  | 1    |                   |        |                 |         |  |
|                  |                      | A Park  |                |         |               |            |  | 7    | M                 |        |                 |         |  |
| -40              | \n \                 |         |                |         |               |            |  |      | T                 |        | <u></u>         |         |  |
|                  | $\sim$               |         |                |         |               |            |  |      |                   | -      | -               | ~_      |  |
| -50              |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
|                  |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
| -60              |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
|                  |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
| -70              |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
|                  |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
| -80              |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
|                  |                      |         |                |         |               |            |  |      |                   |        |                 |         |  |
| -90<br>Center 2  | 18 CU                | 7       | [              | 500     | kHz/          |            |  |      |                   | c n c  | n 5 M           | <u></u> |  |
|                  |                      |         |                | 300     | KHZ/          |            |  |      |                   | spa    | .ı ∪ I <u>M</u> | 112     |  |
| Date: 31         | .JUL.2               | 024 16  | :40:29         |         |               |            |  |      |                   |        |                 |         |  |

Report No.: TW2407221E Page 30 of 37

Date: 2024-08-05




## 10.0 FCC ID Label

#### FCC ID: WOX-SM-M8AG

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

## **Mark Location:**



Report No.: TW2407221E


Date: 2024-08-05



11.0 Photo of testing

11.1 Conducted test View-N/A

Radiated emission test view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 32 of 37

Report No.: TW2407221E

Date: 2024-08-05



11.2 Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 33 of 37

Report No.: TW2407221E

Date: 2024-08-05



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Page 34 of 37

Report No.: TW2407221E

Date: 2024-08-05



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 35 of 37

Report No.: TW2407221E

Date: 2024-08-05



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Page 36 of 37

Report No.: TW2407221E

Date: 2024-08-05



Inside View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Page 37 of 37

Report No.: TW2407221E

Date: 2024-08-05



Inside View



-- End of the Report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.