

TEST REPORT

ACCORDING TO: FCC 47CFR part 15 subpart C § 15.247 (FHSS) and
RSS-210 issue 8 Annex 8

FOR:

Visonic Ltd.

**Two-way wireless magnetic contact
device with hard-wired input**

Model: MC-302EL PG2

FCC ID:WP3MC302ELPG2

IC:1467C-MC302ELPG2

This report is in conformity with ISO/ IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested.
This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.

Table of contents

1	Applicant information	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details	3
5	Tests summary	4
6	EUT description	5
6.1	General information	5
6.2	Test configuration	5
6.3	Changes made in the EUT	5
6.4	Transmitter characteristics	6
7	Transmitter tests according to 47CFR part 15 subpart C and RSS-210 Annex 8 requirements	7
7.1	20 dB bandwidth	7
7.2	Carrier frequency separation	13
7.3	Number of hopping frequencies	15
7.4	Average time of occupancy	19
7.5	Peak output power	23
7.6	Band edge radiated emissions	28
7.7	Field strength of spurious emissions	33
7.8	Antenna requirements	69
8	APPENDIX A Test equipment and ancillaries used for tests	70
9	APPENDIX B Measurement uncertainties	71
10	APPENDIX C Test laboratory description	72
11	APPENDIX D Specification references	72
12	APPENDIX E Test equipment correction factors	73
13	APPENDIX F Abbreviations and acronyms	79
14	APPENDIX G Manufacturer's declaration of identity	80

1 Applicant information

Client name: Visonic Ltd.
Address: Habarzel street 24, Tel Aviv 69710, Israel
Telephone: +972 3 645 6714
Fax: +972 3645 6788
E-mail: obarel@tycoint.com
Contact name: Mr. Oren Barel

2 Equipment under test attributes

Product name: Two-way wireless magnetic contact device with hard-wired input
Product type: Transceiver
Model(s): MC-302EL PG2
Part number: 88-030325/0-102423
Hardware version: 90-205040 Rev 00
Software release: V1.1
Receipt date 5/5/2013

3 Manufacturer information

Manufacturer name: Visonic Ltd.
Address: Habarzel street 24, Tel Aviv 69710, Israel
Telephone: +972 3 645 6714
Fax: +972 3645 6788
E-Mail: obarel@tycoint.com
Contact name: Mr. Oren Barel

4 Test details

Project ID: 24462
Location: Hermon Laboratories Ltd. Harakevet Industrial Zone, Binyamina 30500, Israel
Test started: 5/5/2013
Test completed: 5/28/2013
Test specification(s): FCC 47CFR part 15, subpart C, §15.247 (FHSS);
RSS-210 issue 8 Annex 8




5 Tests summary

Test	Status
Transmitter characteristics	
FCC Section 15.247(a)1, RSS-210 section A8.1(a), The 20 dB bandwidth	Pass
FCC Section 15.247(a)1, RSS-210 section A8.1(b), Frequency separation	Pass
FCC Section 15.247(a)1, RSS-210 section A8.1(c), Number of hopping frequencies	Pass
FCC Section 15.247(a)1, RSS-210 section A8.1(c), Average time of occupancy	Pass
FCC Section 15.247(b), RSS-210 section A8.4(1), Peak output power	Pass
FCC Section 15.247(d), RSS-210 section A8.5, Emissions at band edges	Pass
FCC Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	Pass
FCC Section 15.203, RSS-Gen section 7.1.2, Antenna requirements	Pass
FCC Section 15.207(a), RSS-Gen section 7.2.4, Conducted emission	Not required
FCC Section 15.247(i), RSS-Gen, section 5.5, RF exposure	Pass, the exhibit to the application of certification is provided

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.

The test results relate only to the items tested. Pass/ fail decision was based on nominal values.

This test report supersedes the previously issued test report identified by Doc ID:VISRAD_FCC.24462.

	Name and Title	Date	Signature
Tested by:	Mr. Alex Chaplik, test engineer Mr. S.Samokha, test engineer	May 28, 2013	
Reviewed by:	Mrs. M. Cherniavsky, certification engineer	August 28, 2013	
Approved by:	Mr. M. Nikishin, EMC and radio group manager	August 28, 2013	

6 EUT description


6.1 General information

The EUT, model name MC-302EL PG2, is a battery fed device, comprises the transmitter operating in 912.750 – 919.106 MHz.

The EUT is produced in two plastic enclosures: of white or brown color. According to manufacturer's declaration provided in Appendix G of the test report, the plastic material of white housing P/N 88-030325/0-102423 is identical to brown housing P/N 88-030363/0-102954.

That is why only the EUT P/N 88-030325/0-102423 in white color enclosure was tested.

6.2 Test configuration



6.3 Changes made in the EUT

No changes were implemented in the EUT.



6.4 Transmitter characteristics

Type of equipment					
X	Stand-alone (Equipment with or without its own control provisions)				
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)				
	Plug-in card (Equipment intended for a variety of host systems)				
Intended use		Condition of use			
	fixed	Always at a distance more than 2 m from all people			
X	mobile	Always at a distance more than 20 cm from all people			
	portable	May operate at a distance closer than 20 cm to human body			
Assigned frequency ranges		902 – 928 MHz			
Operating frequencies		912.750 – 919.106 MHz			
Maximum rated output power		At transmitter 50 Ω RF output connector		dBm	
		Peak output power		8.1 dBm	
Is transmitter output power variable?		X	No		
			continuous variable		
			stepped variable with stepsize		dB
		Yes	minimum RF power		dBm
		maximum RF power		dBm	
Antenna connection					
unique coupling	standard connector	X	integral	with temporary RF connector	
				X without temporary RF connector	
Antenna/s technical characteristics					
Type	Manufacturer	Model number		Gain	
Internal	Visonic	Built-in helical antenna		-1 dBi	
Transmitter aggregate data rate/s		50 kbps			
Type of modulation		GFSK			
Modulating test signal (baseband)		PRBS			
Transmitter power source					
X	Battery	Nominal rated voltage	3.0 VDC	Battery type	
	DC	Nominal rated voltage	VDC	Lithium CR123A GP	
	AC mains	Nominal rated voltage	VAC	Frequency	
Common power source for transmitter and receiver		X	yes	no	
Spread spectrum technique used		X	Frequency hopping (FHSS)		
			Digital transmission system (DTS)		
			Hybrid		
Spread spectrum parameters for transmitters tested per FCC 15.247 only					
FHSS	Total number of hops	50			
	Bandwidth per hop	106.2 kHz			
	Max. separation of hops	125 kHz			



Test specification: Section 15.247(a)1, RSS-210 section A8.1(a), 20 dB bandwidth			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/23/2013			
Temperature: 25.9 °C	Air Pressure: 1012 hPa	Relative Humidity: 47 %	Power Supply: 3V battery
Remarks:			

7 Transmitter tests according to 47CFR part 15 subpart C and RSS-210 Annex 8 requirements

7.1 20 dB bandwidth

7.1.1 General

This test was performed to measure the 20 dB bandwidth of the transmitter hopping channel. Specification test limits are given in Table 7.1.1.

Table 7.1.1 The 20 dB bandwidth limits

Assigned frequency, MHz	Maximum bandwidth, kHz	Modulation envelope reference points*, dBc
902.0 – 928.0	250	20
2400.0 – 2483.5	NA	
5725.0 – 5850.0	1000	

* - Modulation envelope reference points provided in terms of attenuation below the peak of modulated carrier.

7.1.2 Test procedure

7.1.2.1 The EUT was set up as shown in Figure 7.1.1, energized and its proper operation was checked.

7.1.2.2 The EUT was set to transmit modulated carrier at maximum data rate.

7.1.2.3 The transmitter bandwidth was measured with spectrum analyzer as frequency delta between reference points on modulation envelope and provided in Table 7.1.2 and the associated plots.

Figure 7.1.1 The 20 dB bandwidth test setup





Test specification: Section 15.247(a)1, RSS-210 section A8.1(a), 20 dB bandwidth	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 5/23/2013	
Temperature: 25.9 °C	Air Pressure: 1012 hPa
Relative Humidity: 47 %	
Power Supply: 3V battery	
Remarks:	

Table 7.1.2 The 20 dB bandwidth test results

ASSIGNED FREQUENCY BAND: 902-928 MHz
DETECTOR USED: Peak
SWEEP TIME: Auto
VIDEO BANDWIDTH: ≥ RBW
MODULATION ENVELOPE REFERENCE POINTS: 20.0 dBc
FREQUENCY HOPPING: Disabled

Carrier frequency, MHz	Type of modulation	Data rate, kbps	Symbol rate, Msymbols/s	20 dB bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
Low frequency							
912.750	GFSK	50	NA	105.3	250	-144.7	Pass
Mid frequency							
915.863	GFSK	50	NA	105.3	250	-144.7	Pass
High frequency							
919.106	GFSK	50	NA	106.2	250	-143.8	Pass

Reference numbers of test equipment used

HL 3818	HL 4135	HL 4274					
---------	---------	---------	--	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification: Section 15.247(a)1, RSS-210 section A8.1(a), 20 dB bandwidth			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/23/2013			
Temperature: 25.9 °C	Air Pressure: 1012 hPa	Relative Humidity: 47 %	Power Supply: 3V battery
Remarks:			

Plot 7.1.1 The 20 dB bandwidth test result at low frequency



Plot 7.1.2 The 20 dB bandwidth test result at mid frequency






HERMON LABORATORIES

Test specification: Section 15.247(a)1, RSS-210 section A8.1(a), 20 dB bandwidth			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/23/2013			
Temperature: 25.9 °C	Air Pressure: 1012 hPa	Relative Humidity: 47 %	Power Supply: 3V battery
Remarks:			


Plot 7.1.3 The 20 dB bandwidth test result at high frequency






Test specification:		Section 15.247(a)1, RSS-210 section A8.1(a), 20 dB bandwidth	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		5/23/2013	
Temperature: 25.9 °C		Air Pressure: 1012 hPa	
		Relative Humidity: 47 %	
		Power Supply: 3V battery	
Remarks:			
		Verdict: PASS	

Plot 7.1.4 The 99% power occupied bandwidth at low frequency



Plot 7.1.5 The 99% power occupied bandwidth at mid frequency






HERMON LABORATORIES

Test specification: Section 15.247(a)1, RSS-210 section A8.1(a), 20 dB bandwidth			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/23/2013			
Temperature: 25.9 °C	Air Pressure: 1012 hPa	Relative Humidity: 47 %	Power Supply: 3V battery
Remarks:			

Plot 7.1.6 The 99% power occupied bandwidth at high frequency



Transmit Freq Error -90.716 Hz
x dB Bandwidth 103.444 kHz*



Test specification: Section 15.247(a)1, RSS-210 section A8.1(b), Frequency separation	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 5/23/2013	
Temperature: 24.7 °C	Air Pressure: 1012 hPa
Relative Humidity: 41 %	
Power Supply: 3V battery	
Remarks:	

7.2 Carrier frequency separation

7.2.1 General

This test was performed to measure frequency separation between the peaks of adjacent channels. Specification test limits are given in Table 7.2.1.

Table 7.2.1 Carrier frequency separation limits

Assigned frequency range, MHz	Carrier frequency separation
902.0 – 928.0	25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater
2400.0 – 2483.5	
5725.0 – 5850.0	

7.2.2 Test procedure

- 7.2.2.1 The EUT was set up as shown in Figure 7.2.1, energized with frequency hopping function enabled and its proper operation was checked.
- 7.2.2.2 The spectrum analyzer span was set to capture the carrier frequency and both of adjacent channels, the lower and the higher. The resolution bandwidth was set wider than 1 % of the frequency span.
- 7.2.2.3 The spectrum analyzer was set in max hold mode and allowed trace to stabilize.
- 7.2.2.4 The frequency separation between the peaks of adjacent channels was measured as provided in Table 7.2.2 and the associated plot.

Figure 7.2.1 Carrier frequency separation test setup





Test specification: Section 15.247(a)1, RSS-210 section A8.1(b), Frequency separation	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 5/23/2013	
Temperature: 24.7 °C	Air Pressure: 1012 hPa
Relative Humidity: 41 %	
Power Supply: 3V battery	
Remarks:	

Table 7.2.2 Carrier frequency separation test results

ASSIGNED FREQUENCY: 902 - 928 MHz
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 50kbps
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: ≥ 1% of the span
 VIDEO BANDWIDTH: ≥ RBW
 FREQUENCY HOPPING: Enabled
 20 dB BANDWIDTH: 106.2 kHz

Carrier frequency separation, kHz	Limit, kHz	Margin*	Verdict
125.00	106.20	18.8	Pass


* - Margin = Carrier frequency separation – specification limit.

Reference numbers of test equipment used

HL 3818	HL 4135	HL 4274				
---------	---------	---------	--	--	--	--

Full description is given in Appendix A.

Plot 7.2.1 Carrier frequency separation





Test specification:	Section 15.247(a)1, RSS-210 section A8.1(c), Number of hopping frequencies		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/27/2013		
Temperature: 24.8 °C	Air Pressure: 1012 hPa	Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:			

7.3 Number of hopping frequencies

7.3.1 General

This test was performed to calculate the number of hopping frequencies used by the EUT. Specification test limits are given in Table 7.3.1.

Table 7.3.1 Minimum number of hopping frequencies

Assigned frequency range, MHz	Number of hopping frequencies
902.0 – 928.0	50 (if the 20 dB bandwidth is less than 250 kHz) 25 (if the 20 dB bandwidth is 250 kHz or greater)
2400.0 – 2483.5	15
5725.0 – 5850.0	75

7.3.2 Test procedure

7.3.2.1 The EUT was set up as shown in Figure 7.3.1, energized with frequency hopping function enabled and its proper operation was checked.

7.3.2.2 Initially the spectrum analyzer span was set equal to frequency band of operation and the resolution bandwidth was set wider than 1 % of the frequency span. If the separate hopping channels were not clearly resolved the frequency band of operation was broken to sections and the resolution bandwidth was set wider than 1 % of the frequency span of each section.

7.3.2.3 The spectrum analyzer was set in max hold mode and allowed trace to stabilize.

7.3.2.4 The number of frequency hopping channels was calculated as provided in Table 7.3.2 and the associated plots.

Figure 7.3.1 Hopping frequencies test setup





Test specification:	Section 15.247(a)1, RSS-210 section A8.1(c), Number of hopping frequencies		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict: PASS	
Date(s):	5/27/2013		
Temperature: 24.8 °C	Air Pressure: 1012 hPa	Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:			

Table 7.3.2 Hopping frequencies test results

ASSIGNED FREQUENCY: 902 - 928 MHz
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 50 kbps
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: ≥ 1% of the span
 VIDEO BANDWIDTH: ≥ RBW
 FREQUENCY HOPPING: Enabled

Number of hopping frequencies	Minimum number of hopping frequencies	Margin*	Verdict
50	50	0	Pass

* - Margin = Number of hopping frequencies – Minimum number of hopping frequencies.

Reference numbers of test equipment used

HL 3001	HL 4136					
---------	---------	--	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:	Section 15.247(a)1, RSS-210 section A8.1(c), Number of hopping frequencies		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/27/2013		
Temperature: 24.8 °C	Air Pressure: 1012 hPa	Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:			

Plot 7.3.1 Number of hopping frequencies in the frequency range 912 – 914.5 MHz (fourteen)



Plot 7.3.2 Number of hopping frequencies in the frequency range 914.5 – 917 MHz (nineteen)






HERMON LABORATORIES

Test specification:	Section 15.247(a)1, RSS-210 section A8.1(c), Number of hopping frequencies		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/27/2013		
Temperature: 24.8 °C	Air Pressure: 1012 hPa	Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:			

Plot 7.3.3 Number of hopping frequencies in the frequency range 917 – 919.5 MHz (seventeen)





Test specification:		Section 15.247(a)1, RSS-210 section A8.1(c), Average time of occupancy	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		5/27/2013	
Temperature: 24.7 °C		Air Pressure: 1012 hPa	
Remarks:		Verdict: PASS	
		Relative Humidity: 40 %	
		Power Supply: 3V battery	

7.4 Average time of occupancy

7.4.1 General

This test was performed to calculate the average time of occupancy (dwell time) on any frequency channel of the EUT. Specification test limits are given in Table 7.4.1.


Table 7.4.1 Average time of occupancy limits

Assigned frequency range, MHz	Maximum average time of occupancy, s	Investigated period, s	Number of hopping frequencies
902.0 – 928.0	0.4	20.0	≥ 50
902.0 – 928.0	0.4	10.0	< 50
2400.0 – 2483.5	0.4	0.4 × N	N (≥ 15)
5725.0 – 5850.0	0.4	30.0	≥ 75

7.4.2 Test procedure

- 7.4.2.1 The EUT was set up as shown in Figure 7.4.1, energized with frequency hopping function enabled and its proper operation was checked.
- 7.4.2.2 The spectrum analyzer span was set to zero centered on a hopping channel.
- 7.4.2.3 The single transmission duration and period were measured with oscilloscope.
- 7.4.2.4 The average time of occupancy was calculated as the single transmission time multiplied by the investigated period and divided by the single transmission period.
- 7.4.2.5 The test was repeated at each data rate and modulation type as provided in Table 7.4.2 and the associated plots.

Figure 7.4.1 Average time of occupancy test setup





Test specification:		Section 15.247(a)1, RSS-210 section A8.1(c), Average time of occupancy	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		5/27/2013	
Temperature: 24.7 °C		Air Pressure: 1012 hPa	
		Relative Humidity: 40 %	
		Power Supply: 3V battery	
Remarks:			

Table 7.4.2 Average time of occupancy test results

ASSIGNED FREQUENCY: 902 - 928 MHz
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1 MHz
 VIDEO BANDWIDTH: 3 MHz
 NUMBER OF HOPPING FREQUENCIES: 50
 INVESTIGATED PERIOD: 20 s
 FREQUENCY HOPPING: Enabled

Carrier frequency, MHz	Single pulse duration, s	Number of pulses during 20 s	Average time of occupancy*, s	Bit rate, Mbps	Limit, s	Margin, s**	Verdict
917.8	0.004012	12	0.04944	50	0.4	-0.35056	Pass

* - Average time of occupancy = (Single transmission duration × Investigated period) / (Single transmission period × number of hopping channels).

** - Margin = Average time of occupancy – specification limit.

Reference numbers of test equipment used

HL 3001	HL 4136						
---------	---------	--	--	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:		Section 15.247(a)1, RSS-210 section A8.1(c), Average time of occupancy	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		5/27/2013	
Temperature: 24.7 °C	Air Pressure: 1012 hPa	Relative Humidity: 40 %	Power Supply: 3V battery
Remarks:			

Plot 7.4.1 Single transmission period



Plot 7.4.2 Transmission train, pulse period






HERMON LABORATORIES

Test specification:		Section 15.247(a)1, RSS-210 section A8.1(c), Average time of occupancy	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		5/27/2013	
Temperature: 24.7 °C		Air Pressure: 1012 hPa	
		Relative Humidity: 40 %	Power Supply: 3V battery
Remarks:			

Plot 7.4.3 Transmission single pulse duration





Test specification: Section 15.247(b), RSS-210 section A8.4(1), Peak output power	
Test procedure:	Public notice DA 00-705
Test mode:	Compliance
Date(s):	5/5/2013
Temperature: 22.3 °C	Air Pressure: 1010 hPa
Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:	
Verdict: PASS	

7.5 Peak output power

7.5.1 General

This test was performed to measure the maximum peak output power radiated by transmitter. Specification test limits are given in Table 7.5.1.

Table 7.5.1 Peak output power limits

Assigned frequency range, MHz	Peak output power*		Equivalent field strength limit @ 3m, dB(μV/m)*	Maximum antenna gain, dBi
	W	dBm		
902.0 – 928.0	0.25 (<50 hopping channels)	24.0(<50 hopping channels)	125.2 (<50 hopping channels)	6.0*
	1.0 (≥50 hopping channels)	30.0 (≥50 hopping channels)	131.2 (≥50 hopping channels)	
2400.0 – 2483.5	0.125 (<75 hopping channels)	21.0(<75 hopping channels)	122.2 (<75 hopping channels)	
	1.0 (≥75 hopping channels)	30.0 (≥75 hopping channels)	131.2 (≥75 hopping channels)	
5725.0 – 5850.0	1.0	30.0	131.2	

*- Equivalent field strength limit was calculated from the peak output power as follows: $E = \sqrt{(30 \times P \times G)/r}$, where P is peak output power in Watts, r is antenna to EUT distance in meters and G is transmitter antenna gain in dBi.

** - The limit is provided in terms of conducted RF power at the antenna connector. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power limit shall be reduced below the stated value as follows:

- by 1 dB for every 3 dB that the directional gain of antenna exceeds 6 dBi for fixed point-to-point transmitters operate in 2400-2483.5 MHz band;
- without any corresponding reduction for fixed point-to-point transmitters operate in 5725-5850 MHz band;
- by the amount in dB that the directional gain of antenna exceeds 6 dBi for the rest of transmitters.

7.5.2 Test procedure

7.5.2.1 The EUT was set up as shown in Figure 7.5.1, energized and its proper operation was checked.

7.5.2.2 The EUT was adjusted to produce maximum available to end user RF output power.

7.5.2.3 The frequency span of spectrum analyzer was set approximately 5 times wider than 20 dB bandwidth of the EUT and the resolution bandwidth was set wider than 20 dB bandwidth of the EUT. To find maximum radiation the turntable was rotated 360° and the measuring antenna height was swept in both vertical and horizontal polarizations.

7.5.2.4 The maximum field strength of the EUT carrier frequency was measured as provided in Table 7.5.2 and associated plots.

7.5.2.5 The maximum peak output power was calculated from the field strength of carrier as follows:

$$P = (E \times d)^2 / (30 \times G),$$

where P is the peak output power in W, E is the field strength in V/m, d is the test distance and G is the transmitter numeric antenna gain over an isotropic radiator.

The above equation was converted in logarithmic units for 3 m test distance:


$$\text{Peak output power in dBm} = \text{Field strength in dB}(\mu\text{V/m}) - \text{Transmitter antenna gain in dBi} - 95.2 \text{ dB}$$

7.5.2.6 The worst test results (the lowest margins) were recorded in Table 7.5.2.



Test specification:	Section 15.247(b), RSS-210 section A8.4(1), Peak output power		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/5/2013		
Temperature: 22.3 °C	Air Pressure: 1010 hPa	Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:			

Figure 7.5.1 Setup for carrier field strength measurements





Test specification:		Section 15.247(b), RSS-210 section A8.4(1), Peak output power	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		5/5/2013	
Temperature: 22.3 °C		Air Pressure: 1010 hPa	
		Relative Humidity: 41 %	
		Power Supply: 3V battery	
Remarks:			
Verdict: PASS			

Table 7.5.2 Peak output power test results

ASSIGNED FREQUENCY: 902-928 MHz
TEST DISTANCE: 3 m
TEST SITE: Semi anechoic chamber
EUT HEIGHT: 0.8 m
DETECTOR USED: Peak
TEST ANTENNA TYPE: Biconilog (30 MHz – 1000 MHz)
MODULATION: GFSK
MODULATING SIGNAL: PRBS
BIT RATE: 50 kbps
TRANSMITTER OUTPUT POWER SETTINGS: Maximum
DETECTOR USED: Peak
RESOLUTION BANDWIDTH: 120 kHz
VIDEO BANDWIDTH: 300 kHz
FREQUENCY HOPPING: Disabled

Frequency, MHz	Field strength, dB(μV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	EUT antenna gain, dBi	Peak output power, dBm**	Limit, dBm	Margin, dB***	Verdict
912.7875	102.3	Vertical	1.0	360	-1	8.1	30.0	-21.9	Pass
915.850	100.1	Vertical	1.4	293	-1	5.9	30.0	-24.1	Pass
919.175	100.4	Vertical	1.0	342	-1	6.2	30.0	-23.8	Pass

*- EUT front panel refer to 0 degrees position of turntable.

** - Peak output power was calculated from the field strength of carrier as follows: $P = (E \times d)^2 / (30 \times G)$, where P is the peak output power in W, E is the field strength in V/m, d is the test distance in meters and G is the transmitter numeric antenna gain over an isotropic radiator. The above equation was converted in logarithmic units for 3 m test distance: *Peak output power in dBm = Field strength in dB(μV/m) - Transmitter antenna gain in dBi - 95.2 dB*

*** - Margin = Peak output power – specification limit.

Note: Maximum peak output power was obtained at Unom (115%Unom, 85%Unom) input power voltage.

Reference numbers of test equipment used

HL 0604	HL 2780	HL 2871	HL 4353				
---------	---------	---------	---------	--	--	--	--

Full description is given in Appendix A.





HERMON LABORATORIES

Test specification: Section 15.247(b), RSS-210 section A8.4(1), Peak output power			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/5/2013			
Temperature: 22.3 °C	Air Pressure: 1010 hPa	Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:			

Plot 7.5.1 Field strength of carrier at low frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical



Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal



Plot 7.5.2 Field strength of carrier at mid frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(b), RSS-210 section A8.4(1), Peak output power			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/5/2013			
Temperature: 22.3 °C	Air Pressure: 1010 hPa	Relative Humidity: 41 %	Power Supply: 3V battery
Remarks:			

Plot 7.5.3 Field strength of carrier at high frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal





Test specification: Section 15.247(d), RSS-210 section A8.5, Emissions at band edges	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 5/23/2013	
Temperature: 25 °C	Air Pressure: 1012 hPa
Remarks:	

7.6 Band edge radiated emissions

7.6.1 General

This test was performed to measure emissions, radiated from the EUT at the assigned frequency band edges. Specification test limits are given in Table 7.6.1.

Table 7.6.1 Band edge emission limits

Assigned frequency, MHz	Attenuation below carrier*, dBc	Field strength at 3 m within restricted bands, dB(µV/m)	
		Peak	Average
902.0 – 928.0	20.0	74.0	54.0
2400.0 – 2483.5			
5725.0 – 5850.0			

* - Band edge emission limit is provided in terms of attenuation below the peak of modulated carrier measured with the same resolution bandwidth.

7.6.2 Test procedure

- 7.6.2.1 The EUT was set up as shown in Figure 7.6.1, energized normally modulated at the maximum data rate with its hopping function disabled and its proper operation was checked.
- 7.6.2.2 The EUT was adjusted to produce maximum available to end user RF output power at the lowest carrier frequency.
- 7.6.2.3 The spectrum analyzer span was set to capture the carrier frequency and associated modulation products. The resolution bandwidth was set wider than 1 % of the frequency span.
- 7.6.2.4 The spectrum analyzer was set in max hold mode and allowed trace to stabilize. The highest emission level within the authorized band was measured.
- 7.6.2.5 The maximum band edge emission and modulation product outside of the band were measured as provided in Table 7.6.2 and associated plots and referenced to the highest emission level measured within the authorized band.
- 7.6.2.6 The above procedure was repeated with the EUT adjusted to produce maximum RF output power at the highest carrier frequency.
- 7.6.2.7 The above procedure was repeated with the frequency hopping function enabled.

Figure 7.6.1 Band edge emission test setup





Test specification: Section 15.247(d), RSS-210 section A8.5, Emissions at band edges	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 5/23/2013	
Temperature: 25 °C	Air Pressure: 1012 hPa
Remarks:	

Table 7.6.2 Band edge emission test results

ASSIGNED FREQUENCY RANGE: 902 – 928 MHz
DETECTOR USED: Peak
MODULATION: GFSK
MODULATING SIGNAL: PRBS
BIT RATE: 50 kbps
TRANSMITTER OUTPUT POWER SETTINGS: Maximum
RESOLUTION BANDWIDTH: ≥ 1% of the span
VIDEO BANDWIDTH: ≥ RBW

Frequency, MHz	Band edge emission, dBuV	Emission at carrier, dBuV	Attenuation below carrier, dBc	Limit, dBc	Margin, dB*	Verdict
Frequency hopping disabled						
902.018	26.59	95.10	68.51	20.0	48.51	Pass
927.992	26.38	95.54	69.16		49.16	
Frequency hopping enabled						
902.018	28.40	95.10	66.70	20.0	46.7	Pass
927.992	28.15	95.54	67.39		47.39	

*- Margin = Attenuation below carrier – specification limit.

Reference numbers of test equipment used

HL 3818	HL 4135	HL 4274				
---------	---------	---------	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:		Section 15.247(d), RSS-210 section A8.5, Emissions at band edges	
Test procedure:		Public notice DA 00-705	
Test mode:		Verdict:	
Compliance		PASS	
Date(s):		5/23/2013	
Temperature: 25 °C	Air Pressure: 1012 hPa	Relative Humidity: 43 %	Power Supply: 3V battery
Remarks:			

Plot 7.6.1 The highest emission level within the assigned band at low carrier frequency




Plot 7.6.2 The highest emission level within the assigned band at high carrier frequency






Test specification:		Section 15.247(d), RSS-210 section A8.5, Emissions at band edges	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		5/23/2013	
Temperature: 25 °C		Air Pressure: 1012 hPa	
		Relative Humidity: 43 %	
		Power Supply: 3V battery	
Remarks:			
		Verdict: PASS	

Plot 7.6.3 The highest band edge emission at low carrier frequency with hopping function disabled



Plot 7.6.4 The highest band edge emission at high carrier frequency with hopping function disabled







HERMON LABORATORIES

Test specification:	Section 15.247(d), RSS-210 section A8.5, Emissions at band edges		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/23/2013		
Temperature: 25 °C	Air Pressure: 1012 hPa	Relative Humidity: 43 %	Power Supply: 3V battery
Remarks:			

Plot 7.6.5 The highest band edge emission at low carrier frequency with hopping function enabled



Plot 7.6.6 The highest band edge emission at high carrier frequency with hopping function enabled





Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

7.7 Field strength of spurious emissions

7.7.1 General

This test was performed to measure field strength of spurious emissions from the EUT. Specification test limits are given in Table 7.7.1.

Table 7.7.1 Radiated spurious emissions limits

Frequency, MHz	Field strength at 3 m within restricted bands, dB(μV/m) ^{***}			Attenuation of field strength of spurious versus carrier outside restricted bands, dBc ^{***}
	Peak	Quasi Peak	Average	
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5 ^{**}	20.0
0.090 – 0.110	NA	108.5 – 106.8 ^{**}	NA	
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8 ^{**}	
0.490 – 1.705	NA	73.8 – 63.0 ^{**}	NA	
1.705 – 30.0*		69.5		
30 – 88		40.0		
88 – 216		43.5		
216 – 960		46.0		
960 - 1000		54.0		
1000 – 10 th harmonic	74.0	NA	54.0	

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$\text{Lim}_{S_2} = \text{Lim}_{S_1} + 40 \log (S_1/S_2),$$

where S₁ and S₂ – standard defined and test distance respectively in meters.

** - The limit decreases linearly with the logarithm of frequency.

*** - The field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.

7.7.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

7.7.2.1 The EUT was set up as shown in Figure 7.7.1, energized and the performance check was conducted.

7.7.2.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.

7.7.2.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.

7.7.3 Test procedure for spurious emission field strength measurements above 30 MHz

7.7.3.1 The EUT was set up as shown in Figure 7.7.2, energized and the performance check was conducted.

7.7.3.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.

7.7.3.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.



Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Figure 7.7.1 Setup for spurious emission field strength measurements below 30 MHz





Figure 7.7.2 Setup for spurious emission field strength measurements above 30 MHz





HERMON LABORATORIES

Test specification:		Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4	
Test mode:	Compliance	Verdict: PASS	
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Table 7.7.2 Field strength of emissions outside restricted bands

ASSIGNED FREQUENCY: 902-928 MHz
 INVESTIGATED FREQUENCY RANGE: 0.009 -9200 MHz
 TEST DISTANCE: 3 m
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 50 kbps
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 100 kHz
 VIDEO BANDWIDTH: 300 kHz
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconilog (30 MHz – 1000 MHz)
 Double ridged guide (above 1000 MHz)
 FREQUENCY HOPPING: Disabled

Frequency, MHz	Field strength of spurious, dB(μV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	Field strength of carrier, dB(μV/m)	Attenuation below carrier, dBc	Limit, dBc	Margin, dB**	Verdict
Low carrier frequency									
1831.6825	47.27	V	1.2	297	102.3	55.03	20.0	35.03	Pass
5476.3475	61.65	H	1.4	187		40.65		20.65	
6389.0750	63.20	V	1.4	174		39.10		19.10	
Mid carrier frequency									
1831.6800	47.79	V	1.0	307	100.1	52.31	20.0	32.31	Pass
5495.0255	57.39	V	1.4	160		42.71		22.71	
6410.8700	68.00	V	1.3	171		32.10		12.10	
High carrier frequency									
1838.2645	51.22	V	1.2	360	100.4	49.18	20.0	29.18	Pass
5514.4818	64.75	V	1.1	180		35.65		15.65	
6433.5600	61.66	V	1.4	171		38.74		18.74	

*- EUT front panel refers to 0 degrees position of turntable.

**- Margin = Attenuation below carrier – specification limit.



Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance		Verdict: PASS	
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Table 7.7.3 Field strength of spurious emissions above 1 GHz within restricted bands

ASSIGNED FREQUENCY: 902-928 MHz
 INVESTIGATED FREQUENCY RANGE: 0.009 -9200 MHz
 TEST DISTANCE: 3 m
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 50 kbps
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 TRANSMITTER OUTPUT POWER: Peak
 DETECTOR USED: 1000 kHz
 RESOLUTION BANDWIDTH: 1 MHz
 TEST ANTENNA TYPE: Double ridged guide
 FREQUENCY HOPPING: Disabled

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength(VBW=3 MHz)			Average field strength(VBW=10 Hz)				Verdict
	Polarization	Height, m		Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB**	Measured, dB(μV/m)	Calculated, dB(μV/m)	Limit, dB(μV/m)	Margin, dB***	
Low carrier frequency											
2738.1125	H	1.0	181	48.53	74.00	-25.47	44.20	25.80	54.00	-28.20	Pass
3650.9720	H	1.5	170	48.96	74.00	-25.04	44.84	26.44	54.00	-27.56	
4563.5660	V	1.3	340	49.28	74.00	-24.72	44.64	26.24	54.00	-27.76	
7301.9250	H	1.0	166	55.40	74.00	-18.60	51.25	32.85	54.00	-21.15	
8214.6520	V	1.2	180	51.11	74.00	-22.89	40.41	22.01	54.00	-31.99	
9127.7690	H	1.4	220	55.09	74.00	-18.91	47.01	28.61	54.00	-25.39	
Mid carrier frequency											
2747.4475	H	1.0	166	48.84	74.00	-25.16	45.46	27.06	54.00	-26.94	Pass
3663.1470	H	1.8	30	47.63	74.00	-26.37	41.75	23.35	54.00	-30.65	
4579.4430	H	1.5	200	50.94	74.00	-23.06	46.89	28.49	54.00	-25.51	
7327.0165	H	1.1	166	52.59	74.00	-21.41	45.80	27.4	54.00	-26.6	
8242.8600	H	1.3	166	50.64	74.00	-23.36	37.77	19.37	54.00	-34.63	
9158.7430	V	1.1	170	57.99	74.00	-16.01	53.70	35.30	54.00	-18.70	
High carrier frequency											
2757.2930	V	1.0	345	47.10	74.00	-26.90	41.43	23.03	54.00	-30.97	Pass
3676.3610	H	1.4	50	48.19	74.00	-25.81	43.60	25.20	54.00	-28.80	
4595.2710	V	1.3	170	50.11	74.00	-23.89	45.94	27.54	54.00	-26.46	
7352.9605	H	1.3	166	55.37	74.00	-18.63	52.45	34.05	54.00	-19.95	
8271.5590	H	1.3	190	51.73	74.00	-22.27	40.92	22.52	54.00	-31.48	
9191.2540	H	1.3	265	55.71	74.00	-18.29	48.27	29.87	54.00	-24.13	

*- EUT front panel refers to 0 degrees position of turntable.
 **- Margin = Measured field strength - specification limit.
 ***- Margin = Calculated field strength - specification limit,
 where Calculated field strength = Measured field strength + average factor.

Table 7.7.4 Average factor calculation

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Period, ms	Duration, ms	Period, ms		
4.012	39	NA	NA	NA	-18.4

*- Average factor was calculated as follows

for pulse train shorter than 100 ms:

$$Average\ factor = 20 \times \log_{10} \left(\frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{Train\ duration} \times Number\ of\ bursts\ within\ pulse\ train \right)$$

for pulse train longer than 100 ms:

$$Average\ factor = 20 \times \log_{10} \left(\frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{100\ ms} \times Number\ of\ bursts\ within\ 100\ ms \right)$$



HERMON LABORATORIES

Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict: PASS	
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Table 7.7.5 Field strength of spurious emissions below 1 GHz within restricted bands

ASSIGNED FREQUENCY: 902-928 MHz
 INVESTIGATED FREQUENCY RANGE: 0.009 -1000 MHz
 TEST DISTANCE: 3 m
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 50 kbps
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 RESOLUTION BANDWIDTH: 0.2 kHz (9 kHz – 150 kHz)
 9.0 kHz (150 kHz – 30 MHz)
 120 kHz (30 MHz – 1000 MHz)
 VIDEO BANDWIDTH: > Resolution bandwidth
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconilog (30 MHz – 1000 MHz)
 FREQUENCY HOPPING: Disabled

Frequency, MHz	Peak emission, dB(µV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*				
Low carrier frequency								
No emissions were found								Pass
Mid carrier frequency								
No emissions were found								Pass
High carrier frequency								
No emissions were found								Pass

*- Margin = Measured emission - specification limit.
 **- EUT front panel refer to 0 degrees position of turntable.

Table 7.7.6 Restricted bands

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	Above 38.6
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	

Reference numbers of test equipment used

HL 0446	HL 0604	HL 1984	HL 2871	HL 3818	HL 4160	HL 4353
---------	---------	---------	---------	---------	---------	---------

Full description is given in Appendix A.




HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			


Plot 7.7.1 Radiated emission measurements at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.7.2 Radiated emission measurements at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal






Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			


Plot 7.7.3 Radiated emission measurements at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.7.4 Radiated emission measurements at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			


Plot 7.7.5 Radiated emission measurements at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.7.6 Radiated emission measurements at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal






HERMON LABORATORIES

Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			


Plot 7.7.7 Radiated emission measurements from 9 to 150 kHz at the low, mid, high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.7.8 Radiated emission measurements from 0.15 to 30 MHz at the low, mid, high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			


Plot 7.7.9 Radiated emission measurements from 30 to 1000 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.7.10 Radiated emission measurements from 30 to 1000 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.11 Radiated emission measurements from 30 to 1000 MHz at the high carrier frequency



TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.7.12 Radiated emission measurements from 1000 to 9500 MHz at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
DETECTOR: Peak

Semi anechoic chamber
3 m
Vertical and Horizontal
DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.13 Radiated emission measurements from 1000 to 9500 MHz at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
DETECTOR: Peak



Semi anechoic chamber
3 m
Vertical and Horizontal
DETECTOR: Average



Plot 7.7.14 Radiated emission measurements from 1000 to 9500 MHz at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
DETECTOR: Peak

Semi anechoic chamber
3 m
Vertical and Horizontal
DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.15 Radiated emission measurements at the second harmonic of low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical



Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal



Plot 7.7.16 Radiated emission measurements at the second harmonic of mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 5/6/2013	
Temperature: 22 °C	Air Pressure: 1010 hPa
Relative Humidity: 59 %	
Power Supply: 3V battery	
Remarks:	

Plot 7.7.17 Radiated emission measurements at the second harmonic of high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.18 Radiated emission measurements at the third harmonic of low carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average









HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 5/6/2013	
Temperature: 22 °C	Air Pressure: 1010 hPa
Remarks:	

Plot 7.7.19 Radiated emission measurements at the third harmonic of mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak









HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 5/6/2013	
Temperature: 22 °C	Air Pressure: 1010 hPa
Remarks:	

Plot 7.7.20 Radiated emission measurements at the third harmonic of high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak







HERMON LABORATORIES

Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.21 Radiated emission measurements at the fourth harmonic of low carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.22 Radiated emission measurements at the fourth harmonic of mid carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.23 Radiated emission measurements at the fourth harmonic of high carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.24 Radiated emission measurements at the fifth harmonic of low carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.25 Radiated emission measurements at the fifth harmonic of mid carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.26 Radiated emission measurements at the fifth harmonic of high carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 5/6/2013	
Temperature: 22 °C	Air Pressure: 1010 hPa
Remarks:	


Plot 7.7.27 Radiated emission measurements at the sixth harmonic of low carrier frequency

TEST SITE:	Semi anechoic chamber
TEST DISTANCE:	3 m
ANTENNA POLARIZATION: Vertical	ANTENNA POLARIZATION: Horizontal



Plot 7.7.28 Radiated emission measurements at the sixth harmonic of mid carrier frequency

TEST SITE:	Semi anechoic chamber
TEST DISTANCE:	3 m
ANTENNA POLARIZATION: Vertical	ANTENNA POLARIZATION: Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			


Plot 7.7.29 Radiated emission measurements at the sixth harmonic of high carrier frequency

TEST SITE:	Semi anechoic chamber
TEST DISTANCE:	3 m
ANTENNA POLARIZATION: Vertical	ANTENNA POLARIZATION: Horizontal



Plot 7.7.30 Radiated emission measurements at the seventh harmonic of low carrier frequency

TEST SITE:	Semi anechoic chamber
TEST DISTANCE:	3 m
ANTENNA POLARIZATION: Vertical	ANTENNA POLARIZATION: Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.31 Radiated emission measurements at the seventh harmonic of mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical



Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal



Plot 7.7.32 Radiated emission measurements at the seventh harmonic of high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.33 Radiated emission measurements at the 8th harmonic low carrier frequency

TEST SITE:	Semi anechoic chamber
TEST DISTANCE:	3 m
ANTENNA POLARIZATION: Vertical	ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak	DETECTOR: Peak







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.34 Radiated emission measurements at the 8th harmonic of mid carrier frequency

TEST SITE:	Semi anechoic chamber
TEST DISTANCE:	3 m
ANTENNA POLARIZATION: Vertical	ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak	DETECTOR: Peak






HERMON LABORATORIES

Test specification:	Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/6/2013		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			


Plot 7.7.35 Radiated emission measurements at the 8th harmonic of high carrier frequency

TEST SITE:	Semi anechoic chamber
TEST DISTANCE:	3 m
ANTENNA POLARIZATION: Vertical	ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak	DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.36 Radiated emission measurements at the 9th harmonic of low carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.37 Radiated emission measurements at the 9th harmonic of mid carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average









HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.38 Radiated emission measurements at the 9th harmonic of high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 5/6/2013	
Temperature: 22 °C	Air Pressure: 1010 hPa
Remarks:	

Plot 7.7.39 Radiated emission measurements at the 10th harmonic of low carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average









HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 5/6/2013	
Temperature: 22 °C	Air Pressure: 1010 hPa
Remarks:	

Plot 7.7.40 Radiated emission measurements at the 10th harmonic of mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.41 Radiated emission measurements at the 10th harmonic of high carrier frequency



TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical
DETECTOR: Peak

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal
DETECTOR: Peak



DETECTOR: Average

DETECTOR: Average







HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-210 section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(d) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 5/6/2013			
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 59 %	Power Supply: 3V battery
Remarks:			

Plot 7.7.42 Transmission pulse duration



Plot 7.7.43 Transmission pulse period





Test specification:	Section 15.203, RSS-Gen section 7.1.2, Antenna requirements		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	5/27/2013		
Temperature: 24.8 °C	Air Pressure: 1012 hPa	Relative Humidity: 42 %	Power Supply: 3V battery
Remarks:			

7.8 Antenna requirements

The EUT was verified for compliance with antenna requirements. A transmitter shall be designed to ensure that no antenna other than that furnished by the responsible party will be used with the device. It may be either permanently attached or employs a unique antenna connector for every antenna proposed for use with the EUT. This requirement does not apply to professionally installed transmitters. The rationale for compliance with the above requirements was either visual inspection results or supplier declaration. The summary of results is provided in Table 7.8.1.

Table 7.8.1 Antenna requirements

Requirement	Rationale	Verdict
The transmitter antenna is permanently attached	Visual inspection	Comply
The transmitter employs a unique antenna connector	NA	
The transmitter requires professional installation	NA	

Photograph 7.8.1 Antenna assembly



**8 APPENDIX A Test equipment and ancillaries used for tests**

HL No	Description	Manufacturer	Model	Ser. No.	Last Cal./ Check	Due Cal./ Check
0446	Antenna, Loop, Active, 10 kHz - 30 MHz	EMCO	6502	2857	03-Jul-12	03-Jul-13
0604	Antenna BiconiLog Log-Periodic/T Bow-TIE, 26 - 2000 MHz	EMCO	3141	9611-1011	20-May-12	20-May-14
1984	Antenna, Double-Ridged Waveguide Horn, 1-18 GHz, 300 W	EMC Test Systems	3115	9911-5964	07-Dec-12	07-Dec-13
2780	EMC analyzer, 100 Hz to 26.5 GHz	Agilent Technologies	E7405A	MY45102462	09-Jul-12	09-Jul-13
2871	Microwave Cable Assembly, 18 GHz, 6.4 m, SMA - SMA	Huber-Suhner	198-8155-00	2871	04-Dec-12	04-Dec-13
3001	EMC Analyzer, 9 kHz to 3 GHz	Agilent Technologies	E7402A	US39440180	15-Jan-13	15-Feb-14
3818	PSA Series Spectrum Analyzer, 3 Hz- 44 GHz	Agilent Technologies	E4446A	MY48250288	24-Apr-13	24-Apr-14
4135	Shield Box	TESCOM CO., LTD	TC-5916A	5916A000136	09-Apr-13	09-Apr-14
4136	Shield Box	TESCOM CO., LTD	TC-5916A	5916A000137	09-Apr-13	09-Apr-14
4160	Preamplifier, 0.1 to 18 GHz, Gain 25 dB, N-type(f) in, N-type(m) out	Agilent Technologies	87405C	MY47010594	08-Aug-12	08-Aug-13
4274	Test Cable , DC-18 GHz, 1.8 m, SMA/M - N/M	Mini-Circuits	CBL-6FT-SMNM+	70047	26-Nov-12	26-Nov-13
4353	Low Loss Armored Test Cable, DC - 18 GHz, 6.2 m, N type-M/N type-M	MegaPhase	NC29-N1N1-244	12025101003	06-Mar-13	06-Mar-14

9 APPENDIX B Measurement uncertainties

Expanded uncertainty at 95% confidence in Hermon Labs EMC measurements

Test description	Expanded uncertainty
Conducted carrier power at RF antenna connector	Below 12.4 GHz: ± 1.7 dB 12.4 GHz to 40 GHz: ± 2.3 dB
Conducted emissions at RF antenna connector	9 kHz to 2.9 GHz: ± 2.6 dB 2.9 GHz to 6.46 GHz: ± 3.5 dB 6.46 GHz to 13.2 GHz: ± 4.3 dB 13.2 GHz to 22.0 GHz: ± 5.0 dB 22.0 GHz to 26.8 GHz: ± 5.5 dB 26.8 GHz to 40.0 GHz: ± 4.8 dB
Occupied bandwidth	± 8.0 %
Duty cycle, timing (Tx ON / OFF) and average factor measurements	± 1.0 %
Radiated emissions at 3 m measuring distance	
Horizontal polarization	Biconilog antenna: ± 5.3 dB Biconical antenna: ± 5.0 dB Log periodic antenna: ± 5.3 dB Double ridged horn antenna: ± 5.3 dB
Vertical polarization	Biconilog antenna: ± 6.0 dB Biconical antenna: ± 5.7 dB Log periodic antenna: ± 6.0 dB Double ridged horn antenna: ± 6.0 dB

Hermon Laboratories is accredited by A2LA for calibration according to present requirements of ISO/IEC 17025 and NCSL Z540-1. The accreditation is granted to perform calibration of parameters that are listed in the Scope of Hermon Laboratories Accreditation.

Hermon Laboratories calibrates its reference and transfer standards by calibration laboratories accredited to ISO/IEC 17025 by a mutually recognized Accreditation Body or by a recognized national metrology institute. All reference and transfer standards used in the calibration system are traceable to national or international standards.

In-house calibration of all test and measurement equipment is performed on a regular basis according to Hermon Laboratories calibration procedures, manufacturer calibration/verification procedures or procedures defined in the relevant standards. The Hermon Laboratories test and measurement equipment is calibrated within the tolerances specified by the manufacturers and/or by the relevant standards.

10 APPENDIX C Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, safety, environmental and telecommunication testing facility.

Hermon Laboratories is listed by the Federal Communications Commission (USA) for all parts of Code of Federal Regulations 47 (CFR 47), Registration Numbers 90624 for OATS and 90623 for the anechoic chamber; by Industry Canada for electromagnetic emissions (file numbers IC 2186A-1 for OATS, IC 2186A-2 for anechoic chamber, IC 2186A-3 for full-anechoic chamber for RE measurements above 1 GHz), certified by VCCI, Japan (the registration numbers are R-808 for OATS, R-1082 for anechoic chamber, G-27 for full-anechoic chamber for RE measurements above 1 GHz, C-845 for conducted emissions site, T-1606 for conducted emissions at telecommunication ports), has a status of a Telefication - Listed Testing Laboratory, Certificate No. L138/00. The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing and environmental simulation (for exact scope please refer to Certificate No. 839.01). The FCC Designation Number is US1003.

Address: P.O. Box 23, Binyamina 30500, Israel.
Telephone: +972 4628 8001
Fax: +972 4628 8277
e-mail: mail@hermonlabs.com
website: www.hermonlabs.com

Person for contact: Mr. Alex Usoskin, CEO.

11 APPENDIX D Specification references

FCC 47CFR part 15: 2012	Radio Frequency Devices
Public notice DA 00- 705: 2000	Filing and measurement guidelines for frequency hopping spread spectrum systems.
ANSI C63.2: 1996	American National Standard for Instrumentation-Electromagnetic Noise and Field Strength, 10 kHz to 40 GHz-Specifications
ANSI C63.4: 2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
RSS-210 Issue 8: 2010	Low Power Licence- Exempt Radiocommunication Devices
RSS-Gen Issue 3: 2010	General Requirements and Information for the Certification of Radiocommunication Equipment



12 APPENDIX E Test equipment correction factors

Antenna factor
Active loop antenna
Model 6502, S/N 2857, HL 0446

Frequency, MHz	Magnetic antenna factor, dB	Electric antenna factor, dB
0.009	-32.8	18.7
0.010	-33.8	17.7
0.020	-38.3	13.2
0.050	-41.1	10.4
0.075	-41.3	10.2
0.100	-41.6	9.9
0.150	-41.7	9.8
0.250	-41.6	9.9
0.500	-41.8	9.8
0.750	-41.9	9.7
1.000	-41.4	10.1
2.000	-41.5	10.0
3.000	-41.4	10.2
4.000	-41.4	10.1
5.000	-41.5	10.1
10.000	-41.9	9.6
15.000	-41.9	9.6
20.000	-42.2	9.3
25.000	-42.8	8.7
30.000	-44.0	7.5

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).



Antenna factor
Biconilog antenna EMCO Model 3141
Ser.No.1011, HL 0604

Frequency, MHz	Antenna Factor, dB(1/m)
26	7.8
28	7.8
30	7.8
40	7.2
60	7.1
70	8.5
80	9.4
90	9.8
100	9.7
110	9.3
120	8.8
130	8.7
140	9.2
150	9.8
160	10.2
170	10.4
180	10.4
190	10.3
200	10.6
220	11.6
240	12.4
260	12.8
280	13.7
300	14.7
320	15.2
340	15.4
360	16.1
380	16.4
400	16.6
420	16.7
440	17.0
460	17.7
480	18.1
500	18.5
520	19.1
540	19.5
560	19.8
580	20.6
600	21.3
620	21.5
640	21.2
660	21.4
680	21.9
700	22.2
720	22.2
740	22.1
760	22.3
780	22.6
800	22.7
820	22.9
840	23.1
860	23.4
880	23.8
900	24.1
920	24.1

Frequency, MHz	Antenna Factor, dB(1/m)
940	24.0
960	24.1
980	24.5
1000	24.9
1020	25.0
1040	25.2
1060	25.4
1080	25.6
1100	25.7
1120	26.0
1140	26.4
1160	27.0
1180	27.0
1200	26.7
1220	26.5
1240	26.5
1260	26.5
1280	26.6
1300	27.0
1320	27.8
1340	28.3
1360	28.2
1380	27.9
1400	27.9
1420	27.9
1440	27.8
1460	27.8
1480	28.0
1500	28.5
1520	28.9
1540	29.6
1560	29.8
1580	29.6
1600	29.5
1620	29.3
1640	29.2
1660	29.4
1680	29.6
1700	29.8
1720	30.3
1740	30.8
1760	31.1
1780	31.0
1800	30.9
1820	30.7
1840	30.6
1860	30.6
1880	30.6
1900	30.6
1920	30.7
1940	30.9
1960	31.2
1980	31.6
2000	32.0

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).



Antenna factor
Double-ridged wave guide horn antenna
Model 3115, S/N 9911-5964, HL1984

Frequency, MHz	Antenna factor, dB(1/m)
1000.0	24.7
1500.0	25.7
2000.0	27.6
2500.0	28.9
3000.0	31.2
3500.0	32.0
4000.0	32.5
4500.0	32.7
5000.0	33.6
5500.0	35.1
6000.0	35.4
6500.0	34.9
7000.0	36.1
7500.0	37.8
8000.0	38.0
8500.0	38.1
9000.0	39.1
9500.0	38.3
10000.0	38.6
10500.0	38.2
11000.0	38.7
11500.0	39.5
12000.0	40.0
12500.0	40.4
13000.0	40.5
13500.0	41.1
14000.0	41.6
14500.0	41.7
15000.0	38.7
15500.0	38.2
16000.0	38.8
16500.0	40.5
17000.0	42.5
17500.0	45.9
18000.0	49.4

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).



Cable loss
Cable coaxial, Huber-Suhner, 18 GHz, 6.4 m, SMA - SMA, model 198-8155-00,
HL 2871

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.12	5750	2.34	12000	3.55
30	0.14	6000	2.39	12250	3.61
100	0.27	6250	2.46	12500	3.67
250	0.45	6500	2.52	12750	3.74
500	0.63	6750	2.58	13000	3.79
750	0.76	7000	2.64	13250	3.82
1000	0.89	7250	2.68	13500	3.83
1250	1.01	7500	2.73	13750	3.83
1500	1.12	7750	2.78	14000	3.88
1750	1.23	8000	2.83	14250	3.93
2000	1.32	8250	2.88	14500	3.96
2250	1.41	8500	2.94	14750	4.01
2500	1.49	8750	2.97	15000	4.00
2750	1.58	9000	3.02	15250	4.01
3000	1.66	9250	3.07	15500	4.00
3250	1.73	9500	3.13	15750	4.13
3500	1.80	9750	3.18	16000	4.22
3750	1.87	10000	3.21	16250	4.29
4000	1.93	10250	3.26	16500	4.29
4250	2.01	10500	3.30	16750	4.32
4500	2.06	10750	3.36	17000	4.37
4750	2.12	11000	3.39	17250	4.45
5000	2.17	11250	3.44	17500	4.49
5250	2.24	11500	3.48	17750	4.53
5500	2.29	11750	3.52	18000	4.55



Cable loss
Test cable, Mini-Circuits, S/N 70047, 18 GHz, 1.8 m, SMA/M - N/M
CBL-6FT-SMNM+, HL 4274

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.07	4800	1.69	9800	2.62	14800	3.42
30	0.11	4900	1.70	9900	2.63	14900	3.39
50	0.14	5000	1.72	10000	2.64	15000	3.38
100	0.21	5100	1.75	10100	2.64	15100	3.40
200	0.26	5200	1.76	10200	2.66	15200	3.41
300	0.30	5300	1.77	10300	2.67	15300	3.40
400	0.37	5400	1.79	10400	2.68	15400	3.39
500	0.44	5500	1.82	10500	2.68	15500	3.41
600	0.49	5600	1.85	10600	2.70	15600	3.44
700	0.54	5700	1.86	10700	2.71	15700	3.46
800	0.58	5800	1.87	10800	2.73	15800	3.45
900	0.63	5900	1.91	10900	2.74	15900	3.47
1000	0.67	6000	1.94	11000	2.76	16000	3.51
1100	0.71	6100	1.97	11100	2.77	16100	3.56
1200	0.75	6200	1.98	11200	2.78	16200	3.55
1300	0.78	6300	1.99	11300	2.79	16300	3.54
1400	0.81	6400	2.02	11400	2.80	16400	3.57
1500	0.85	6500	2.05	11500	2.82	16500	3.62
1600	0.88	6600	2.06	11600	2.83	16600	3.61
1700	0.91	6700	2.06	11700	2.84	16700	3.60
1800	0.94	6800	2.08	11800	2.85	16800	3.62
1900	0.97	6900	2.10	11900	2.87	16900	3.68
2000	1.00	7000	2.12	12000	2.88	17000	3.70
2100	1.03	7100	2.12	12100	2.89	17100	3.68
2200	1.06	7200	2.13	12200	2.90	17200	3.70
2300	1.08	7300	2.16	12300	2.92	17300	3.80
2400	1.11	7400	2.19	12400	2.94	17400	3.84
2500	1.14	7500	2.22	12500	2.95	17500	3.83
2600	1.16	7600	2.23	12600	2.96	17600	3.83
2700	1.19	7700	2.26	12700	2.98	17700	3.86
2800	1.21	7800	2.30	12800	3.00	17800	3.86
2900	1.27	7900	2.33	12900	3.02	17900	3.80
3000	1.29	8000	2.35	13000	3.03	18000	3.79
3100	1.32	8100	2.37	13100	3.06		
3200	1.35	8200	2.41	13200	3.08		
3300	1.37	8300	2.44	13300	3.09		
3400	1.38	8400	2.47	13400	3.10		
3500	1.41	8500	2.48	13500	3.13		
3600	1.43	8600	2.51	13600	3.17		
3700	1.46	8700	2.53	13700	3.17		
3800	1.47	8800	2.55	13800	3.18		
3900	1.49	8900	2.56	13900	3.22		
4000	1.52	9000	2.57	14000	3.26		
4100	1.55	9100	2.58	14100	3.28		
4200	1.56	9200	2.59	14200	3.30		
4300	1.58	9300	2.59	14300	3.35		
4400	1.60	9400	2.60	14400	3.39		
4500	1.63	9500	2.60	14500	3.39		
4600	1.65	9600	2.61	14600	3.39		
4700	1.67	9700	2.61	14700	3.41		



Cable loss
Low Loss Armored Test Cable, MegaPhase, 18 GHz, 6.2 m, N type-M/N type-M,
NC29-N1N1-244S/N 12025101 003,
HL 4353

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
50	0.20	9000	2.71
100	0.27	9500	2.81
300	0.47	10000	2.90
500	0.61	10500	2.97
1000	0.87	11000	3.06
1500	1.07	11500	3.13
2000	1.24	12000	3.20
2500	1.39	12500	3.26
3000	1.53	13000	3.34
3500	1.65	13500	3.39
4000	1.77	14000	3.47
4500	1.89	14500	3.54
5000	1.99	15000	3.62
5500	2.07	15500	3.69
6000	2.20	16000	3.76
6500	2.30	16500	3.83
7000	2.39	17000	3.86
7500	2.51	17500	3.94
8000	2.58	18000	4.02
8500	2.65		



13 APPENDIX F Abbreviations and acronyms

A	ampere
AC	alternating current
A/m	ampere per meter
AM	amplitude modulation
AVRG	average (detector)
cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
dB(μ V)	decibel referred to one microvolt
dB(μ V/m)	decibel referred to one microvolt per meter
dB(μ A)	decibel referred to one microampere
DC	direct current
EIRP	equivalent isotropically radiated power
ERP	effective radiated power
EUT	equipment under test
F	frequency
GHz	gigahertz
GND	ground
H	height
HL	Hermon laboratories
Hz	hertz
k	kilo
kHz	kilohertz
LO	local oscillator
m	meter
MHz	megahertz
min	minute
mm	millimeter
ms	millisecond
μ s	microsecond
NA	not applicable
NB	narrow band
OATS	open area test site
Ω	Ohm
PM	pulse modulation
PS	power supply
ppm	part per million (10^{-6})
QP	quasi-peak
RE	radiated emission
RF	radio frequency
rms	root mean square
Rx	receive
s	second
T	temperature
Tx	transmit
V	volt
WB	wideband

END OF TEST REPORT

14 APPENDIX G Manufacturer's declaration of identity



*Visonic Ltd.
24 Habarzel Street
P.O.Box 22020
Tel-Aviv 69710, Israel*

*Tele: +972 3 645 6789
Fax: +972 3 645 6788
www.visonic.com*

From: Visonic Ltd.,
24 Habarzel Street,
TEL AVIV 69710
Israel

TO: Hermon Laboratories Ltd.
Hatachana St., POB 23
Binyamina 30500 Israel

Mrs. Elena Shevchenko

Declaration of identity of plastic – MC-302EL in Brown and White housing colored models

On behalf of Visonic Ltd., the Manufacturer, I hereby declare that the:

- White plastic housing (PN: P/N:88-030325/ 0-102423) and
- Brown plastic housing (P/N:88-030363/ 0-102954)

Are same size and same shape and use same plastic material.

Oren Barel



International Standards Certification Manager, Visonic

27-Aug-2013

END OF DOCUMENT