



Hermon Laboratories Ltd.  
P.O. Box 23, Binyamina 3055001, Israel  
Tel. +972 4628 8001  
Fax. +972 4628 8277  
E-mail: mail@hermonlabs.com

## TEST REPORT

ACCORDING TO: FCC 47CFR part 15 subpart C §15.247 (FHSS) and subpart B,  
RSS-247 Issue 2:2017, RSS-Gen Issue 5:2018, ICES-003 Issue 6:2016

FOR:

**Visonic Ltd.**

**Wireless Magnetic Contact**

**Model: MC-303 PG2**

**FCC ID: WP3MC303PG2**

**IC: 1467C-MC303PG2**

This report is in conformity with ISO/IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested. This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.



## Table of contents

1	Applicant information.....	3
2	Equipment under test attributes .....	3
3	Manufacturer information .....	3
4	Test details.....	3
5	Tests summary.....	4
6	EUT description.....	5
6.1	General information.....	5
6.2	Test configuration.....	5
6.3	Changes made in EUT .....	5
6.4	Transmitter characteristics .....	6
7	Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements .....	7
7.1	20 dB bandwidth .....	7
7.2	Carrier frequency separation.....	10
7.3	Number of hopping frequencies .....	12
7.4	Average time of occupancy .....	14
7.5	Peak output power .....	17
7.6	Field strength of spurious emissions .....	21
7.7	Band edge radiated emissions .....	31
7.8	Antenna requirements.....	35
8	Unintentional emissions according to 47CFR part 15 subpart B and ICES-003 requirements.....	36
8.1	Radiated emission measurements .....	36
9	APPENDIX A Test equipment and ancillaries used for tests.....	40
10	APPENDIX B Test equipment correction factors.....	41
11	APPENDIX C Measurement uncertainties .....	46
12	APPENDIX D Test laboratory description .....	47
13	APPENDIX E Specification references.....	48
14	APPENDIX F Abbreviations and acronyms.....	49



## 1 Applicant information

**Client name:** Visonic Ltd.  
**Address:** 24 Habarzel street, Tel Aviv 69710, Israel  
**Telephone:** +972 3645 6832  
**Fax:** +972 3645 6788  
**E-mail:** [zuri.rubin@jci.com](mailto:zuri.rubin@jci.com)  
**Contact name:** Mr. Zuri Rubin

## 2 Equipment under test attributes

**Product name:** Magnetic Contact  
**Product type:** Transceiver  
**Model:** MC-303 PG2  
**Serial number:** N/A  
**Hardware version:** 90-208795  
**Software release:** JS-703582  
**Receipt date:** 24-May-18

## 3 Manufacturer information

**Manufacturer name:** Visonic Ltd.  
**Address:** 24 Habarzel street, Tel Aviv 69710, Israel  
**Telephone:** +972 3645 6832  
**Fax:** +972 3645 6788  
**E-Mail:** [zuri.rubin@jci.com](mailto:zuri.rubin@jci.com)  
**Contact name:** Mr. Zuri Rubin

## 4 Test details

**Project ID:** 31113  
**Location:** Hermon Laboratories Ltd. P.O. Box 23, Binyamina 3055001, Israel  
**Test started:** 11-Jun-18  
**Test completed:** 27-Jun-18  
**Test specifications:** FCC 47CFR part 15 subpart C §15.247 (FHSS) and subpart B, RSS-247 Issue 2:2017, RSS-Gen Issue 5:2018, ICES-003 Issue 6:2016



## 5 Tests summary

Test	Status
<b>Transmitter characteristics</b>	
Section 15.247(a)1 / RSS-247 section 5.1(c), 20 dB bandwidth	Pass
Section 15.247(a)1 / RSS-247 section 5.1(b), Frequency separation	Pass
Section 15.247(a)1 / RSS-247 section 5.1(c), Number of hopping frequencies	Pass
Section 15.247(a)1 / RSS-247 section 5.1(c), Average time of occupancy	Pass
Section 15.247(b) / RSS-247 section 5.4(a), Peak output power	Pass
Section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions	Pass
Section 15.247(d) / RSS-247 section 5.5, Emissions at band edges	Pass
Section 15.247(i)5 / RSS-102 section 2.5, RF exposure	Pass, the exhibit to the application of certification is provided
Section 15.203 / RSS-Gen section 8.3, Antenna requirements	Pass
Section 15.207(a) / RSS-Gen section 8.8, Conducted emission	Not required
<b>Unintentional emissions</b>	
Section 15.107/ICES-003, Section 6.1, Class B, Conducted emission at AC power port	Not required
Section 15.109/ RSS-Gen section 7.1.2 /ICES-003, Section 6.2, Class B, Radiated emission	Pass

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.

The test results relate only to the items tested. Pass/fail decision was based on nominal values.

This test report supersedes the previously issued test report identified by Doc ID: VISRAD\_FCC.31113.

	Name and Title	Date	Signature
<b>Tested by:</b>	Mrs. E. Pitt, test engineer	11-Jun-18 – 27-Jun-18	
<b>Reviewed by:</b>	Mrs. Y. Rapin, technical writer	15-Nov-18	
<b>Approved by:</b>	Mr. K. Zushchyk, project and customer manager, EMC and radio group	15-Nov-18	




## 6 EUT description

### 6.1 General information

The EUT is an indoor magnet detector operating at 912.750 – 919.106 MHz. The EUT is equipped with an integral antenna and is powered from 3 VDC internal battery.

### 6.2 Test configuration



### 6.3 Changes made in EUT

No changes were implemented in the EUT during the testing.



### 6.4 Transmitter characteristics

<b>Type of equipment</b>						
X	Stand-alone (Equipment with or without its own control provisions)					
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)					
	Plug-in card (Equipment intended for a variety of host systems)					
<b>Intended use</b>		<b>Condition of use</b>				
	fixed	Always at a distance more than 2 m from all people				
X	mobile	Always at a distance more than 20 cm from all people				
	portable	May operate at a distance closer than 20 cm to human body				
<b>Assigned frequency ranges</b>		902 – 928 MHz				
<b>Operating frequencies</b>		912.750 – 919.106 MHz				
<b>Maximum rated output power</b>		At transmitter 50 Ω RF output connector			dBm	
		Peak output power			14.38 dBm	
<b>Is transmitter output power variable?</b>		X	No			
			Yes	continuous variable		
				stepped variable with stepsize		
				minimum RF power	dBm	
		maximum RF power	dBm			
<b>Antenna connection</b>						
unique coupling		standard connector		X	integral	
				X	with temporary RF connector	
					without temporary RF connector	
<b>Antenna/s technical characteristics</b>						
Type		Manufacturer		Model number		
Intergrated		Visonic		Inverted F		
Gain		-3 dBi				
<b>Transmitter aggregate data rate/s</b>		50 kbps				
<b>Type of modulation</b>		GFSK				
<b>Modulating test signal (baseband)</b>		PRBS				
<b>Transmitter power source</b>						
X	Battery	<b>Nominal rated voltage</b>	3.0 VDC	Battery type	Lithium, CR2450, Panasonic	
	DC	<b>Nominal rated voltage</b>				
	AC mains	<b>Nominal rated voltage</b>		Frequency		
<b>Common power source for transmitter and receiver</b>				X	yes	
					no	
<b>Spread spectrum technique used</b>		X	Frequency hopping (FHSS)			
			Digital transmission system (DTS)			
			Hybrid			
<b>Spread spectrum parameters for transmitters tested per FCC 15.247 only</b>						
FHSS	Total number of hops		50			
	Bandwidth per hop		110.40 kHz			
	Max. separation of hops		129.75 kHz			



<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), 20 dB bandwidth</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.7		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

## 7 Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements

### 7.1 20 dB bandwidth

#### 7.1.1 General

This test was performed to measure the 20 dB bandwidth of the transmitter hopping channel. Specification test limits are given in Table 7.1.1.

Table 7.1.1 The 20 dB bandwidth limits

Assigned frequency, MHz	Maximum bandwidth, kHz	Modulation envelope reference points*, dBc
902.0 – 928.0	250	20
2400.0 – 2483.5	NA	
5725.0 – 5850.0	1000	

\* - Modulation envelope reference points provided in terms of attenuation below the peak of modulated carrier.

#### 7.1.2 Test procedure

7.1.2.1 The EUT was set up as shown in Figure 7.1.1, energized and its proper operation was checked.

7.1.2.2 The EUT was set to transmit modulated carrier at maximum data rate.

7.1.2.3 The transmitter bandwidth was measured with spectrum analyzer as frequency delta between reference points on modulation envelope and provided in Table 7.1.2 and associated plot.

7.1.2.4 The test was repeated for each data rate and each modulation format.

Figure 7.1.1 The 20 dB bandwidth test setup





<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), 20 dB bandwidth</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.7		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

**Table 7.1.2 The 20 dB bandwidth test results**

ASSIGNED FREQUENCY BAND: 902.0 – 928.0 MHz  
 DETECTOR USED: Peak  
 SWEEP TIME: Auto  
 VIDEO BANDWIDTH: ≥ RBW  
 MODULATION ENVELOPE REFERENCE POINTS: 20.0 dBc  
 FREQUENCY HOPPING: Disabled


Carrier frequency, MHz	Type of modulation	Data rate, kbps	Symbol rate, Msymbols/s	20 dB bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
912.750	QPSK	50	NA	110.069	250	-139.931	Pass
915.863				110.400	250	-139.600	Pass
919.106				109.733	250	-140.267	Pass

**Reference numbers of test equipment used**

HL 2909	HL 4136						
---------	---------	--	--	--	--	--	--

Full description is given in Appendix A.

**Plot 7.1.1 The 20 dB bandwidth test result at low frequency**









<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), 20 dB bandwidth</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.7		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

Plot 7.1.2 The 20 dB bandwidth test result at mid frequency



Plot 7.1.3 The 20 dB bandwidth test result at high frequency





<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(2), Frequency separation</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.2		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature:</b> 23 °C	<b>Relative Humidity:</b> 55 %	<b>Air Pressure:</b> 1009 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

## 7.2 Carrier frequency separation

### 7.2.1 General

This test was performed to measure frequency separation between the peaks of adjacent channels. Specification test limits are given in Table 7.2.1.

Table 7.2.1 Carrier frequency separation limits

Assigned frequency range, MHz	Carrier frequency separation	
	Output power 30 dBm	Output power 21 dBm
902.0 – 928.0	25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater	25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater
2400.0 – 2483.5		
5725.0 – 5850.0		

### 7.2.2 Test procedure

- 7.2.2.1 The EUT was set up as shown in Figure 7.2.1, energized with frequency hopping function enabled and its proper operation was checked.
- 7.2.2.2 The spectrum analyzer span was set to capture the carrier frequency and both of adjacent channels, the lower and the higher. The resolution bandwidth was set wider than 1 % of the frequency span.
- 7.2.2.3 The spectrum analyzer was set in max hold mode and allowed trace to stabilize.
- 7.2.2.4 The frequency separation between the peaks of adjacent channels was measured as provided in Table 7.2.2 and associated plots.

Figure 7.2.1 Carrier frequency separation test setup





<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(2), Frequency separation</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.2		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

**Table 7.2.2 Carrier frequency separation test results**

ASSIGNED FREQUENCY: 902-928 MHz  
 MODULATION: GFSK  
 DETECTOR USED: Peak  
 RESOLUTION BANDWIDTH: ≥ 1% of the span  
 VIDEO BANDWIDTH: ≥ RBW  
 FREQUENCY HOPPING: Enabled  
 20 dB BANDWIDTH: 110.4 kHz

Carrier frequency separation, kHz	Limit, kHz	Margin*	Verdict
129.75	110.4	19.35	Pass


\* - Margin = Carrier frequency separation – specification limit.

**Reference numbers of test equipment used**

HL 2909	HL 4136					
---------	---------	--	--	--	--	--

Full description is given in Appendix A.

**Plot 7.2.1 Carrier frequency separation**





<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), Number of hopping frequencies</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.3		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1010 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

### 7.3 Number of hopping frequencies

#### 7.3.1 General

This test was performed to calculate the number of hopping frequencies used by the EUT. Specification test limits are given in Table 7.3.1.

Table 7.3.1 Minimum number of hopping frequencies

Assigned frequency range, MHz	Number of hopping frequencies
902.0 – 928.0	50 (if the 20 dB bandwidth is less than 250 kHz) 25 (if the 20 dB bandwidth is 250 kHz or greater)
2400.0 – 2483.5	15
5725.0 – 5850.0	75

#### 7.3.2 Test procedure

7.3.2.1 The EUT was set up as shown in Figure 7.3.1, energized with frequency hopping function enabled and its proper operation was checked.

7.3.2.2 Initially the spectrum analyzer span was set equal to frequency band of operation and the resolution bandwidth was set wider than 1 % of the frequency span. If the separate hopping channels were not clearly resolved the frequency band of operation was broken to sections and the resolution bandwidth was set wider than 1 % of the frequency span of each section.

7.3.2.3 The spectrum analyzer was set in max hold mode and allowed trace to stabilize.

7.3.2.4 The number of frequency hopping channels was calculated as provided in Table 7.3.2 and associated plots.

Figure 7.3.1 Hopping frequencies test setup





<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), Number of hopping frequencies</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.3		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature:</b> 23 °C	<b>Relative Humidity:</b> 55 %	<b>Air Pressure:</b> 1010 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

**Table 7.3.2 Hopping frequencies test results**

ASSIGNED FREQUENCY: 902.0 – 928.0 MHz  
 MODULATION: GFSK  
 DETECTOR USED: Peak  
 RESOLUTION BANDWIDTH: ≥ 1% of the span  
 VIDEO BANDWIDTH: ≥ RBW  
 FREQUENCY HOPPING: Enabled

Number of hopping frequencies	Minimum number of hopping frequencies	Margin*	Verdict
50	50	0	Pass



\* - Margin = Number of hopping frequencies – Minimum number of hopping frequencies.

**Reference numbers of test equipment used**

HL 2909	HL 4136						
---------	---------	--	--	--	--	--	--

Full description is given in Appendix A.

**Plot 7.3.1 Number of hopping frequencies**





<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), Average time of occupancy</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.4		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

## 7.4 Average time of occupancy

### 7.4.1 General

This test was performed to calculate the average time of occupancy (dwell time) on any frequency channel of the EUT. Specification test limits are given in Table 7.4.1.


**Table 7.4.1 Average time of occupancy limits**

Assigned frequency range, MHz	Maximum average time of occupancy, s	Investigated period, s	Number of hopping frequencies
902.0 – 928.0	0.4	20.0	≥ 50
902.0 – 928.0	0.4	10.0	< 50
2400.0 – 2483.5	0.4	0.4 × N	N (≥ 15)
5725.0 – 5850.0	0.4	30.0	≥ 75

### 7.4.2 Test procedure

- 7.4.2.1 The EUT was set up as shown in Figure 7.4.1, energized with frequency hopping function enabled and its proper operation was checked.
- 7.4.2.2 The spectrum analyzer span was set to zero centered on a hopping channel.
- 7.4.2.3 The single transmission duration and period were measured with oscilloscope.
- 7.4.2.4 The average time of occupancy was calculated as the single transmission time multiplied by the investigated period and divided by the single transmission period.
- 7.4.2.5 The test was repeated at each data rate and modulation type as provided in Table 7.4.2 and associated plots.

**Figure 7.4.1 Average time of occupancy test setup**





HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), Average time of occupancy</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.4		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature:</b> 23 °C	<b>Relative Humidity:</b> 55 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

**Table 7.4.2 Average time of occupancy test results**

ASSIGNED FREQUENCY: 902-928 MHz  
 MODULATION: GFSK  
 DETECTOR USED: Peak  
 NUMBER OF HOPPING FREQUENCIES: 50  
 INVESTIGATED PERIOD: 20s  
 FREQUENCY HOPPING: Enabled

Carrier frequency, MHz	Single transmission duration, ms	Number transmission during 20 s	Average time of occupancy*, s	Bit rate, kbps	Symbol rate, Msymbol/s	Limit, s	Margin, s**	Verdict
915.863	4.0	1	0.004	50	NA	0.4	-0.396	Pass

\* - Average time of occupancy = (Single transmission duration × Investigated period) / (Single transmission period × number of hopping channels).

\*\* - Margin = Average time of occupancy – specification limit.

**Reference numbers of test equipment used**

HL 3818	HL 4136						
---------	---------	--	--	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.247(a)1, RSS-247 section 5.1(3), Average time of occupancy</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.4		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

**Plot 7.4.1 Single transmission duration**



**Plot 7.4.2 Number transmission**







<b>Test specification:</b>	<b>Section 15.247(b), RSS-247 section 5.4(1), Peak output power</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.5		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	06-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

## 7.5 Peak output power

### 7.5.1 General

This test was performed to measure the maximum peak output power radiated by transmitter. Specification test limits are given in Table 7.5.1.

**Table 7.5.1 Peak output power limits**

Assigned frequency range, MHz	Peak output power*		Equivalent field strength limit @ 3m, dB(μV/m)*	Maximum antenna gain, dBi
	W	dBm		
902.0 – 928.0	0.25 (<50 hopping channels)	24.0(<50 hopping channels)	125.2 (<50 hopping channels)	6.0*
	1.0 (≥50 hopping channels)	30.0 (≥50 hopping channels)	131.2 (≥50 hopping channels)	
2400.0 – 2483.5	0.125 (<75 hopping channels)	21.0(<75 hopping channels)	122.2 (<75 hopping channels)	
	1.0 (≥75 hopping channels)	30.0 (≥75 hopping channels)	131.2 (≥75 hopping channels)	
5725.0 – 5850.0	1.0	30.0	131.2	

\*- Equivalent field strength limit was calculated from the peak output power as follows:  $E = \sqrt{30 \times P \times G} / r$ , where P is peak output power in Watts, r is antenna to EUT distance in meters and G is transmitter antenna gain in dBi.

\*\* - The limit is provided in terms of conducted RF power at the antenna connector. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power limit shall be reduced below the stated value as follows:

- by 1 dB for every 3 dB that the directional gain of antenna exceeds 6 dBi for fixed point-to-point transmitters operate in 2400-2483.5 MHz band;
- without any corresponding reduction for fixed point-to-point transmitters operate in 5725-5850 MHz band;
- by the amount in dB that the directional gain of antenna exceeds 6 dBi for the rest of transmitters.

### 7.5.2 Test procedure

**7.5.2.1** The EUT was set up as shown in Figure 7.5.1, energized and its proper operation was checked.

**7.5.2.2** The EUT was adjusted to produce maximum available to end user RF output power.

**7.5.2.3** The frequency span of spectrum analyzer was set approximately 5 times wider than 20 dB bandwidth of the EUT and the resolution bandwidth was set wider than 20 dB bandwidth of the EUT. To find maximum radiation the turntable was rotated 360° and the measuring antenna height was swept in both vertical and horizontal polarizations.

**7.5.2.4** The maximum field strength of the EUT carrier frequency was measured as provided in Table 7.5.2 and associated plots.

**7.5.2.5** The maximum peak output power was calculated from the field strength of carrier as follows:

$$P = (E \times d)^2 / (30 \times G),$$

where P is the peak output power in W, E is the field strength in V/m, d is the test distance and G is the transmitter numeric antenna gain over an isotropic radiator.

The above equation was converted in logarithmic units for 3 m test distance:


$$\text{Peak output power in dBm} = \text{Field strength in dB}(\mu\text{V/m}) - \text{Transmitter antenna gain in dBi} - 95.2 \text{ dB}$$

**7.5.2.6** The worst test results (the lowest margins) were recorded in Table 7.5.2.



<b>Test specification:</b>	<b>Section 15.247(b), RSS-247 section 5.4(1), Peak output power</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.5		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	06-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

Figure 7.5.1 Setup for carrier field strength measurements





HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.247(b), RSS-247 section 5.4(1), Peak output power</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.5		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	06-Jun-18		
<b>Temperature:</b> 23 °C	<b>Relative Humidity:</b> 55 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

Table 7.5.2 Peak output power test results

ASSIGNED FREQUENCY: 902-928 MHz  
TEST DISTANCE: 3 m  
EUT HEIGHT: 0.8 m  
TEST SITE: Semi anechoic chamber  
DETECTOR USED: Peak  
TEST ANTENNA TYPE: Biconilog (30 MHz – 1000 MHz)  
Double ridged guide (above 1000 MHz)  
MODULATION: GFSK  
BIT RATE: 50 kbps  
TRANSMITTER OUTPUT POWER SETTINGS: Maximum  
DETECTOR USED: Peak  
EUT 20 dB BANDWIDTH: 110.40 MHz  
RESOLUTION BANDWIDTH: 1 MHz  
VIDEO BANDWIDTH: 10 MHz  
FREQUENCY HOPPING: Disabled  
NUMBER OF FREQUENCY HOPPING CHANNELS: 50

Frequency, MHz	Field strength, dB(µV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	EUT antenna gain, dBi	Peak output power, dBm**	Limit, dBm	Margin, dB***	Verdict
912.7500	106.58	Vertical	1.23	-160.0	-3	14.38	30	-15.62	Pass
915.8666	105.37	Vertical	1.23	-1.0	-3	13.17	30	-16.83	Pass
919.1019	106.37	Vertical	1.23	19.0	-3	14.17	30	-15.83	Pass

\*- EUT front panel refer to 0 degrees position of turntable.

\*\* - Peak output power was calculated from the field strength of carrier as follows:  $P = (E \times d)^2 / (30 \times G)$ , where P is the peak output power in W, E is the field strength in V/m, d is the test distance in meters and G is the transmitter numeric antenna gain over an isotropic radiator. The above equation was converted in logarithmic units for 3 m test distance: *Peak output power in dBm = Field strength in dB(µV/m) - Transmitter antenna gain in dBi - 95.2 dB*

\*\*\* - Margin = Peak output power – specification limit.

Note: Maximum peak output power was obtained at Unom input power voltage.

**Reference numbers of test equipment used**

HL 3615	HL 4277	HL 4320	HL 5288				
---------	---------	---------	---------	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.247(b), RSS-247 section 5.4(1), Peak output power</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.5		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	06-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			


Plot 7.5.1 Field strength of carrier at low frequency



Plot 7.5.2 Field strength of carrier at mid frequency



Plot 7.5.3 Field strength of carrier at high frequency





<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature: 25 °C</b>	<b>Relative Humidity: 46 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

## 7.6 Field strength of spurious emissions

### 7.6.1 General

This test was performed to measure field strength of spurious emissions from the EUT. Specification test limits are given in Table 7.6.1.

**Table 7.6.1 Radiated spurious emissions limits**

Frequency, MHz	Field strength at 3 m within restricted bands, dB(μV/m)***			Attenuation of field strength of spurious versus carrier outside restricted bands, dBc***
	Peak	Quasi Peak	Average	
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5**	20.0
0.090 – 0.110	NA	108.5 – 106.8**	NA	
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8**	
0.490 – 1.705	NA	73.8 – 63.0**	NA	
1.705 – 30.0*		69.5		
30 – 88		40.0		
88 – 216		43.5		
216 – 960		46.0		
960 - 1000		54.0		
1000 – 10 <sup>th</sup> harmonic	74.0	NA	54.0	

\*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$Lims_2 = Lims_1 + 40 \log (S_1/S_2),$$

where S<sub>1</sub> and S<sub>2</sub> – standard defined and test distance respectively in meters.

\*\* - The limit decreases linearly with the logarithm of frequency.

\*\*\* - The field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.

#### 7.6.1 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

7.6.1.1 The EUT was set up as shown in Figure 7.6.1, energized and the performance check was conducted.

7.6.1.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.

7.6.1.3 The worst test results (the lowest margins) were recorded in and shown in the associated tables and plots.

#### 7.6.2 Test procedure for spurious emission field strength measurements above 30 MHz

7.6.2.1 The EUT was set up as shown in Figure 7.6.2 / Figure 7.6.3, energized and the performance check was conducted.

7.6.2.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.

7.6.2.3 The worst test results (the lowest margins) were recorded in the associated tables and plots.



<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

Figure 7.6.1 Setup for spurious emission field strength measurements below 30 MHz




Figure 7.6.2 Setup for spurious emission field strength measurements from 30 to 1000 MHz





Figure 7.6.3 Setup for spurious emission field strength measurements above 1000 MHz





<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

**Table 7.6.2 Field strength of emissions outside restricted bands**

ASSIGNED FREQUENCY: 902-928 MHz  
 INVESTIGATED FREQUENCY RANGE: 0.009 – 10000 MHz  
 TEST DISTANCE: 3 m  
 MODULATION: GFSK  
 BIT RATE: 50 kbps  
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum  
 DETECTOR USED: Peak  
 RESOLUTION BANDWIDTH: 100 kHz  
 VIDEO BANDWIDTH: 300 kHz  
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)  
 Biconilog (30 MHz – 1000 MHz)  
 Double ridged guide (above 1000 MHz)  
 FREQUENCY HOPPING: Disabled

Frequency, MHz	Field strength of spurious, dB(μV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	Field strength of carrier, dB(μV/m)	Attenuation below carrier, dBc	Limit, dBc	Margin, dB**	Verdict
<b>Low carrier frequency</b>									
1825.6675	54.21	Horizontal	1.89	9.0	106.58	-52.37	20.0	-32.37	Pass
6270.7625	44.44	Vertical	1.30	-137.0		-62.14		-42.14	
<b>Mid carrier frequency</b>									
1831.8100	61.98	Vertical	1.00	-169.0	105.37	-43.39	20.0	-23.39	Pass
5573.9100	44.37	Vertical	3.96	-56.0		-61.00		-41.00	
6481.8225	44.66	Horizontal	2.70	-169.0		-60.71		-40.71	
<b>High carrier frequency</b>									
1838.2450	50.02	Vertical	4.00	-169.0	106.37	-56.35	20.0	-36.35	Pass
6433.8450	51.63	Horizontal	1.92	50.0		-54.74		-34.74	

\*- EUT front panel refers to 0 degrees position of turntable.  
 \*\*- Margin = Attenuation below carrier – specification limit.



<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>			
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6			
<b>Test mode:</b>	Compliance	<b>Verdict:</b>		<b>PASS</b>
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18			
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC	
<b>Remarks:</b>				

**Table 7.6.3 Field strength of spurious emissions above 1 GHz within restricted bands**

ASSIGNED FREQUENCY: 902 - 928 MHz  
 INVESTIGATED FREQUENCY RANGE: 1000 – 10000 MHz  
 TEST DISTANCE: 3 m  
 MODULATION: GFSK  
 BIT RATE: 50 Kbps  
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum  
 DETECTOR USED: Peak  
 RESOLUTION BANDWIDTH: 1000 kHz  
 TEST ANTENNA TYPE: Double ridged guide  
 FREQUENCY HOPPING: Disabled

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength			Average field strength				Verdict
	Polarization	Height, m		Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB**	Measured, dB(μV/m)	Calculated, dB(μV/m)	Limit, dB(μV/m)	Margin, dB***	
<b>Low carrier frequency</b>											
2738.2450	Horizontal	2.38	1.0	54.98	74	-19.02	54.98	26.98	54	-27.02	Pass
3650.9550	Horizontal	1.85	41.0	42.03	74	-31.97	42.03	14.03	54	-39.97	
4563.6075	Horizontal	1.29	45.0	41.84	74	-32.16	41.84	13.84	54	-40.16	
8158.1250	Vertical	1.02	-79.0	49.87	74	-24.13	49.87	21.87	54	-32.13	
9311.6975	Vertical	1.30	33.0	49.20	74	-24.80	49.20	21.20	54	-32.80	
<b>Mid carrier frequency</b>											
2747.8125	Vertical	2.63	-32.0	38.51	74	-35.49	38.51	10.51	54	-43.49	Pass
3751.8150	Vertical	3.70	180.0	41.71	74	-32.29	41.71	13.71	54	-40.29	
4641.6100	Vertical	3.16	154.0	43.51	74	-30.49	43.51	15.51	54	-38.49	
7384.6175	Horizontal	1.02	101.0	46.91	74	-27.09	46.91	18.91	54	-35.09	
8058.1200	Horizontal	2.63	-103.0	49.96	74	-24.04	49.96	21.96	54	-32.04	
9086.4075	Vertical	4.00	171.0	47.98	74	-26.02	47.98	19.98	54	-34.02	
<b>High carrier frequency</b>											
2757.1725	Vertical	2.11	180.0	53.64	74	-20.36	53.64	25.64	54	-28.36	Pass
3701.3275	Vertical	4.00	-71.0	39.76	74	-34.24	39.76	11.76	54	-42.24	
4595.6125	Vertical	1.00	-102.0	51.17	74	-22.83	51.17	23.17	54	-30.83	
7352.9800	Horizontal	2.12	-160.0	50.41	74	-23.59	50.41	22.41	54	-31.59	
8271.9075	Horizontal	1.92	-114.0	53.95	74	-20.05	53.95	25.95	54	-28.05	
9191.2125	Horizontal	1.84	178.0	51.64	74	-22.36	51.64	23.64	54	-30.36	

\*- EUT front panel refers to 0 degrees position of turntable.  
 \*\*- Margin = Measured field strength - specification limit.  
 \*\*\*- Margin = Calculated field strength - specification limit,  
 where Calculated field strength = Measured field strength + average factor.

**Table 7.6.4 Average factor calculation**

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Number of pulses within 100 ms	Duration, ms	Period, ms		
4	1	N/A	N/A	N/A	-28

Average factor or pulse train shorter than 100 ms was calculated as follows:

$$Average\ factor = 20 \times \log_{10} \left( \frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{Train\ duration} \times Number\ of\ bursts\ within\ pulse\ train \right)$$

Average factor or pulse train longer than 100 ms was calculated as follows:

$$Average\ factor = 20 \times \log_{10} \left( \frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{100ms} \times Number\ of\ bursts\ within\ 100ms \right)$$





<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

**Table 7.6.5 Field strength of spurious emissions below 1 GHz within restricted bands**

ASSIGNED FREQUENCY: 902-928 MHz  
 INVESTIGATED FREQUENCY RANGE: 0.009 – 1000 MHz  
 TEST DISTANCE: 3 m  
 MODULATION: GFSK  
 MODULATING SIGNAL: PRBS  
 BIT RATE: 50 Kbps  
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum  
 RESOLUTION BANDWIDTH: 0.2 kHz (9 kHz – 150 kHz)  
 9.0 kHz (150 kHz – 30 MHz)  
 120 kHz (30 MHz – 1000 MHz)  
 VIDEO BANDWIDTH: > Resolution bandwidth  
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)  
 Biconilog (30 MHz – 1000 MHz)  
 FREQUENCY HOPPING: Disabled

Frequency, MHz	Peak emission, dB(µV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*				
No spurious emissions have been found								Pass

\*- Margin = Measured emission - specification limit.  
 \*\*- EUT front panel refer to 0 degrees position of turntable.



<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>				
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6				
<b>Test mode:</b>	Compliance	<b>Verdict:</b>			<b>PASS</b>
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18				
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC		
<b>Remarks:</b>					

**Table 7.6.6 Restricted bands according to FCC section 15.205**

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	Above 38.6
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	

**Table 7.6.7 Restricted bands according to RSS-Gen**

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.291 - 8.294	16.80425 - 16.80475	399.9 - 410	3260 - 3267	10.6 - 12.7
2.1735 - 2.1905	8.362 - 8.366	25.5 - 25.67	608 - 614	3332 - 3339	13.25 - 13.4
3.020 - 3.026	8.37625 - 8.38675	37.5 - 38.25	960 - 1427	3345.8 - 3358	14.47 - 14.5
4.125 - 4.128	8.41425 - 8.41475	73 - 74.6	1435 - 1626.5	3500 - 4400	15.35 - 16.2
4.17725 - 4.17775	12.29 - 12.293	74.8 - 75.2	1645.5 - 1646.5	4500 - 5150	17.7 - 21.4
4.20725 - 4.20775	12.51975 - 12.52025	108 - 138	1660 - 1710	5350 - 5460	22.01 - 23.12
5.677 - 5.683	12.57675 - 12.57725	156.52475 - 156.52525	1718.8 - 1722.2	7250 - 7750	23.6 - 24
6.215 - 6.218	13.36 - 13.41	156.7 - 156.9	2200 - 2300	8025 - 8500	31.2 - 31.8
6.26775 - 6.26825	16.42 - 16.423	240 - 285	2310 - 2390	9000 - 9200	36.43 - 36.5
6.31175 - 6.31225	16.69475 - 16.69525	322 - 335.4	2655 - 2900	9300 - 9500	Above 38.6

**Reference numbers of test equipment used**

HL 1915	HL 3615	HL 4277	HL 4339	HL 4360	HL 4933	HL 5111	HL 5288
---------	---------	---------	---------	---------	---------	---------	---------

Full description is given in Appendix A.




HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

**Plot 7.6.1 Radiated emission measurements from 9 kHz to 30 MHz at the low; mid; high carrier frequency**

TEST SITE: Semi anechoic chamber  
TEST DISTANCE: 3 m  
ANTENNA POLARIZATION: Vertical and Horizontal






<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			


**Plot 7.6.2 Radiated emission measurements from 30 to 1000 MHz at the low carrier frequency**

TEST SITE: Semi anechoic chamber  
TEST DISTANCE: 3 m  
ANTENNA POLARIZATION: Vertical and Horizontal




**Plot 7.6.3 Radiated emission measurements from 30 to 1000 MHz at the mid carrier frequency**

TEST SITE: Semi anechoic chamber  
TEST DISTANCE: 3 m  
ANTENNA POLARIZATION: Vertical and Horizontal



**Plot 7.6.4 Radiated emission measurements from 30 to 1000 MHz at the high carrier frequency**

TEST SITE: Semi anechoic chamber  
TEST DISTANCE: 3 m  
ANTENNA POLARIZATION: Vertical and Horizontal






<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature: 25 °C</b>	<b>Relative Humidity: 46 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			


**Plot 7.6.5 Radiated emission measurements from 1000 to 10000 MHz at the low carrier frequency**

TEST SITE: Semi anechoic chamber  
TEST DISTANCE: 3 m  
ANTENNA POLARIZATION: Vertical and Horizontal




**Plot 7.6.6 Radiated emission measurements from 1000 to 10000 MHz at the mid carrier frequency**

TEST SITE: Semi anechoic chamber  
TEST DISTANCE: 3 m  
ANTENNA POLARIZATION: Vertical and Horizontal



**Plot 7.6.7 Radiated emission measurements from 1000 to 10000 MHz at the high carrier frequency**

TEST SITE: Semi anechoic chamber  
TEST DISTANCE: 3 m  
ANTENNA POLARIZATION: Vertical and Horizontal







HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions</b>		
<b>Test procedure:</b>	ANSI C63.10, sections 6.5, 6.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	19-Jun-18 - 20-Jun-18		
<b>Temperature: 25 °C</b>	<b>Relative Humidity: 46 %</b>	<b>Air Pressure: 1008 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

Plot 7.6.8 Transmission pulse duration



Plot 7.6.9 Transmission pulse period





<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Emissions at band edges</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature:</b> 23 °C	<b>Relative Humidity:</b> 55 %	<b>Air Pressure:</b> 1009 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

## 7.7 Band edge radiated emissions

### 7.7.1 General

This test was performed to measure emissions, radiated from the EUT at the assigned frequency band edges. Specification test limits are given in Table 7.7.1.

Table 7.7.1 Band edge emission limits

Assigned frequency, MHz	Attenuation below carrier*, dBc	Field strength at 3 m within restricted bands, dB(μV/m)	
		Peak	Average
902.0 – 928.0	20.0	74.0	54.0
2400.0 – 2483.5			
5725.0 – 5850.0			

\* - Band edge emission limit is provided in terms of attenuation below the peak of modulated carrier measured with the same resolution bandwidth.

### 7.7.2 Test procedure

- 7.7.2.1 The EUT was set up as shown in Figure 7.7.1, energized normally modulated at the maximum data rate with its hopping function disabled and its proper operation was checked.
- 7.7.2.2 The EUT was adjusted to produce maximum available to end user RF output power at the lowest carrier frequency.
- 7.7.2.3 The spectrum analyzer span was set to capture the carrier frequency and associated modulation products. The resolution bandwidth was set wider than 1 % of the frequency span.
- 7.7.2.4 The spectrum analyzer was set in max hold mode and allowed trace to stabilize. The highest emission level within the authorized band was measured.
- 7.7.2.5 The maximum band edge emission and modulation product outside of the band were measured as provided in Table 7.7.2 and associated plots and referenced to the highest emission level measured within the authorized band.
- 7.7.2.6 The above procedure was repeated with the EUT adjusted to produce maximum RF output power at the highest carrier frequency.
- 7.7.2.7 The above procedure was repeated with the frequency hopping function enabled.

Figure 7.7.1 Band edge emission test setup





HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Emissions at band edges</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature:</b> 23 °C	<b>Relative Humidity:</b> 55 %	<b>Air Pressure:</b> 1009 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

**Table 7.7.2 Band edge emission test results**

ASSIGNED FREQUENCY RANGE: 902-928 MHz  
 DETECTOR USED: Peak  
 MODULATION: GFSK  
 BIT RATE: 50 kbps  
 RESOLUTION BANDWIDTH: ≥ 1% of the span  
 VIDEO BANDWIDTH: ≥ RBW

Frequency, MHz	Band edge emission, dBm	Emission at carrier, dBm	Attenuation below carrier, dBc	Limit, dBc	Margin, dB*	Verdict
<b>Frequency hopping disabled</b>						
902	-83.33	-27.71	55.62	20.0	35.62	Pass
928	-83.52	-27.83	55.69		35.69	
<b>Frequency hopping enabled</b>						
902	-82.37	-26.70	55.67	20.0	55.67	Pass
928	-82.15	-27.73	54.42		54.42	

\*- Margin = Attenuation below carrier – specification limit.

**Reference numbers of test equipment used**

HL 2909						
---------	--	--	--	--	--	--


Full description is given in Appendix A.






<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Emissions at band edges</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.6		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

Plot 7.7.1 The highest band edge emission at low carrier frequency with hopping function disabled




Plot 7.7.2 The highest band edge emission at high carrier frequency with hopping function disabled






<b>Test specification:</b>	<b>Section 15.247(d), RSS-247 section 5.5, Emissions at band edges</b>		
<b>Test procedure:</b>	ANSI C63.10, section 7.8.6		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	20-Jun-18		
<b>Temperature: 23 °C</b>	<b>Relative Humidity: 55 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

Plot 7.7.3 The highest band edge emission at low carrier frequency with hopping function enabled



Plot 7.7.4 The highest band edge emission at high carrier frequency with hopping function enabled





<b>Test specification:</b>	<b>Section 15.203, RSS-Gen, Section 7.1.4, Antenna requirements</b>		
<b>Test procedure:</b>	Visual inspection		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	20-Jun-18		
<b>Temperature:</b> 23 °C	<b>Relative Humidity:</b> 55 %	<b>Air Pressure:</b> 1008 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

### 7.8 Antenna requirements

The EUT was verified for compliance with antenna requirements. A transmitter shall be designed to ensure that no antenna other than that furnished by the responsible party will be used with the device. It may be either permanently attached or employs a unique antenna connector for every antenna proposed for use with the EUT. This requirement does not apply to professionally installed transmitters.

The rationale for compliance with the above requirements was either visual inspection results or supplier declaration. The summary of results is provided in Table 7.8.1.

**Table 7.8.1 Antenna requirements**

Requirement	Rationale	Verdict
The transmitter antenna is permanently attached	Visual inspection	Comply
The transmitter employs a unique antenna connector	NA	
The transmitter requires professional installation	NA	



<b>Test specification:</b>	<b>Section 15.109, RSS-Gen, Section 7.1.2, ICES-003, Radiated emission</b>		
<b>Test procedure:</b>	ANSI C63.4, Section 12.2.5		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	26-Jun-18 - 27-Jun-18		
<b>Temperature: 25 °C</b>	<b>Relative Humidity: 46 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			

## 8 Unintentional emissions according to 47CFR part 15 subpart B and ICES-003 requirements

### 8.1 Radiated emission measurements

#### 8.1.1 General

This test was performed to measure radiated emissions from the EUT enclosure. Specification test limits are given in Table 8.1.1.

**Table 8.1.1 Radiated emission test limits**


Frequency, MHz	Class B limit, dB(μV/m)		Class A limit, dB(μV/m)	
	10 m distance	3 m distance	10 m distance	3 m distance
30 - 88	29.5*	40.0	39.0	49.5*
88 - 216	33.0*	43.5	43.5	54.0*
216 - 960	35.5*	46.0	46.4	56.9*
Above 960	43.5*	54.0	49.5	60.0*

\* The limit for test distance other than specified was calculated using the inverse linear distance extrapolation factor as follows:  $Lim_{S2} = Lim_{S1} + 20 \log(S1/S2)$ , where  $S1$  and  $S2$  – standard defined and test distance respectively in meters.

#### 8.1.2 Test procedure for measurements

- 8.1.2.1 The EUT was set up as shown in Figure 8.1.1 and associated photographs, energized and the performance check was conducted.
- 8.1.2.2 The specified frequency range was investigated with biconilog antenna connected to EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal and the EUT cables position was varied.
- 8.1.2.3 The worst test results (the lowest margins) were recorded in Table 8.1.2 and shown in the associated plots.

**Figure 8.1.1 Setup for radiated emission measurements in anechoic chamber**






HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.109, RSS-Gen, Section 7.1.2, ICES-003, Radiated emission</b>		
<b>Test procedure:</b>	ANSI C63.4, Section 12.2.5		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	26-Jun-18 - 27-Jun-18		
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1009 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

Photograph 8.1.1 Setup for final radiated emission measurements, general view



Photograph 8.1.2 Setup for final radiated emission measurements, EUT cabling





<b>Test specification:</b>	<b>Section 15.109, RSS-Gen, Section 7.1.2, ICES-003, Radiated emission</b>		
<b>Test procedure:</b>	ANSI C63.4, Section 12.2.5		
<b>Test mode:</b>	Compliance	<b>Verdict: PASS</b>	
<b>Date(s):</b>	26-Jun-18 - 27-Jun-18		
<b>Temperature:</b> 25 °C	<b>Relative Humidity:</b> 46 %	<b>Air Pressure:</b> 1009 hPa	<b>Power:</b> 3 VDC
<b>Remarks:</b>			

**Table 8.1.2 Radiated emission test results**

EUT SET UP: TABLE-TOP  
LIMIT: Class B  
EUT OPERATING MODE: Receive  
TEST SITE: SEMI ANECHOIC CHAMBER  
TEST DISTANCE: 3 m  
DETECTORS USED: PEAK / QUASI-PEAK  
FREQUENCY RANGE: 30 MHz – 1000 MHz  
RESOLUTION BANDWIDTH: 120 kHz

Frequency, MHz	Peak emission, dB(µV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*				
No emission peaks were found								Pass

TEST SITE: SEMI ANECHOIC CHAMBER  
TEST DISTANCE: 3 m  
DETECTORS USED: PEAK / AVERAGE  
FREQUENCY RANGE: 1000 MHz – 5000 MHz  
RESOLUTION BANDWIDTH: 1000 kHz

Frequency, MHz	Peak			Average			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
	Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*	Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*				
No emission peaks were found										Pass

\*- Margin = Measured emission - specification limit.  
\*\*- EUT front panel refer to 0 degrees position of turntable.

**Reference numbers of test equipment used**

HL 3615	HL 4277	HL 4360	HL 4933	HL 5111	HL 5288		
---------	---------	---------	---------	---------	---------	--	--

Full description is given in Appendix A.




HERMON LABORATORIES

<b>Test specification:</b>	<b>Section 15.109, RSS-Gen, Section 7.1.2, ICES-003, Radiated emission</b>		
<b>Test procedure:</b>	ANSI C63.4, Section 12.2.5		
<b>Test mode:</b>	Compliance	<b>Verdict:</b>	<b>PASS</b>
<b>Date(s):</b>	26-Jun-18 - 27-Jun-18		
<b>Temperature: 25 °C</b>	<b>Relative Humidity: 46 %</b>	<b>Air Pressure: 1009 hPa</b>	<b>Power: 3 VDC</b>
<b>Remarks:</b>			


Plot 8.1.1 Radiated emission measurements in 30 - 1000 MHz range, vertical & horizontal antenna polarization

TEST SITE: Semi anechoic chamber  
LIMIT: Class B  
TEST DISTANCE: 3 m  
EUT OPERATING MODE: Receive



Plot 8.1.2 Radiated emission measurements above 1000 MHz, vertical & horizontal antenna polarization

TEST SITE: Semi anechoic chamber  
LIMIT: Class B  
TEST DISTANCE: 3 m  
EUT OPERATING MODE: Receive



**9 APPENDIX A Test equipment and ancillaries used for tests**

HL No	Description	Manufacturer	Model	Ser. No.	Last Cal./ Check	Due Cal./ Check
1915	Antenna, Loop, Active Receiving, 1 kHz - 30 MHz	EMC Test Systems	6507	1457	11-Feb-18	11-Feb-19
2909	Spectrum analyzer, ESA-E, 100 Hz to 26.5 GHz	Agilent Technologies	E4407B	MY41444762	27-Mar-18	27-Mar-19
3615	Cable RF, 6.5 m, N type-N type, DC-6 GHz	Suhner Switzerland	RG 214/U	NA	10-Jun-18	10-Jun-19
3818	PSA Series Spectrum Analyzer, 3 Hz-44 GHz	Agilent Technologies	E4446A	MY48250288	28-May-18	28-May-19
4136	Shield Box	TESCOM CO., LTD	TC-5916A	5916A000137	04-Apr-18	04-Apr-19
4277	Test Cable , DC-18 GHz, 3.05 m, N/M - N/M	Mini-Circuits	APC-10FT-NMNM+	0748A	01-Aug-18	01-Aug-19
4339	High pass Filter, 50 Ohm, 1000 to 18000 MHz, SMA-FM / SMA-M	Micro-Tronics	HPM50115-02	1	14-May-17	14-Mar-19
4360	EMI Test Receiver, 20 Hz to 40 GHz.	Rohde & Schwarz	ESU40	100322	26-Dec-17	26-Dec-18
4933	Active Horn Antenna, 1 GHz to 18 GHz	COM-POWER CORPORATION	AHA-118	701046	04-Jan-18	04-Jan-19
5111	RF cable, 40 GHz, 5.5 m, K-type	Huber-Suhner	SF102EA/11S K/11SK/5500 MM	502493/2EA	09-Apr-18	09-Apr-19
5288	Trilog Antenna, 25 MHz - 8 GHz, 100W	Frankonia	ALX-8000E	809	21-Jan-18	21-Jan-19





### 10 APPENDIX B Test equipment correction factors

HL 4933: Active Horn Antenna  
COM-POWER CORPORATION, model: AHA-118, s/n 701046

Frequency, MHz	Measured antenna factor (with preamplifier), dB/m
1000	-16.1
1500	-15.1
2000	-10.9
2500	-11.9
3000	-11.1
3500	-10.6
4000	-8.6
4500	-8.3
5000	-5.9
5500	-5.7
6000	-3.3
6500	-4.0
7000	-2.2
7500	-1.7
8000	1.1
8500	-0.8
9000	-1.5
9500	-0.2

Frequency, MHz	Measured antenna factor (with preamplifier), dB/m
10000	1.8
10500	1.0
11000	0.3
11500	-0.5
12000	3.1
12500	1.4
13000	-0.3
13500	-0.4
14000	2.5
14500	2.2
15000	1.9
15500	0.5
16000	2.1
16500	1.2
17000	0.6
17500	3.1
18000	4.2

The antenna factor shall be added to receiver reading in dB $\mu$ V to obtain field strength in dB $\mu$ V/m.

HL 5288: Antenna factor Trilog Antenna  
Frankonia, model: ALX-8000E, s/n: 00809

Frequency, MHz	Antenna factor, dB/m
30	14.96
35	15.33
40	16.37
45	17.56
50	17.95
60	16.87
70	13.22
80	10.56
90	13.61
100	15.46
120	14.03
140	12.23

Frequency, MHz	Antenna factor, dB/m
160	12.67
180	13.34
200	15.40
250	16.42
300	17.28
400	19.98
500	21.11
600	22.90
700	24.13
800	25.25
900	26.35
1000	27.18

The antenna factor shall be added to receiver reading in dB $\mu$ V to obtain field strength in dB $\mu$ V/m.



HL 3615: RF Cable  
Suhner Switzerland, model: RG 214/U, s/n: NA

Set / Applied, MHz	Measured, dB	Uncertainty, dB
50	0.31	+0.08 / -0.08 dB
100	0.45	+0.08 / -0.08 dB
200	0.66	+0.08 / -0.08 dB
300	0.83	+0.09 / -0.09 dB
400	0.98	+0.09 / -0.09 dB
500	1.12	+0.09 / -0.09 dB
600	1.26	+0.09 / -0.09 dB
700	1.38	+0.09 / -0.09 dB
800	1.50	+0.09 / -0.09 dB
900	1.63	+0.09 / -0.09 dB
1000	1.74	+0.09 / -0.09 dB
1100	1.85	+0.09 / -0.09 dB
1200	1.97	+0.09 / -0.09 dB
1300	2.08	+0.09 / -0.09 dB
1400	2.19	+0.09 / -0.09 dB
1500	2.30	+0.09 / -0.09 dB
1600	2.41	+0.09 / -0.09 dB
1700	2.53	+0.09 / -0.09 dB
1800	2.63	+0.09 / -0.09 dB
1900	2.74	+0.09 / -0.09 dB
2000	2.83	+0.09 / -0.09 dB
2100	2.93	+0.11 / -0.11 dB
2200	3.00	+0.11 / -0.11 dB
2300	3.07	+0.11 / -0.11 dB
2400	3.13	+0.11 / -0.11 dB
2500	3.19	+0.15 / -0.15 dB
2600	3.25	+0.15 / -0.15 dB
2700	3.33	+0.15 / -0.15 dB
2800	3.40	+0.15 / -0.15 dB
2900	3.48	+0.15 / -0.15 dB
3000	3.57	+0.15 / -0.15 dB
3100	3.63	+0.17 / -0.17 dB
3200	3.71	+0.17 / -0.17 dB

Set / Applied, MHz	Measured, dB	Uncertainty, dB
3300	3.78	+0.17 / -0.17 dB
3400	3.88	+0.17 / -0.17 dB
3500	3.96	+0.17 / -0.17 dB
3600	4.06	+0.17 / -0.17 dB
3700	4.15	+0.17 / -0.17 dB
3800	4.26	+0.17 / -0.17 dB
3900	4.36	+0.17 / -0.17 dB
4000	4.48	+0.17 / -0.17 dB
4100	4.58	+0.22 / -0.23 dB
4200	4.72	+0.22 / -0.23 dB
4300	4.80	+0.22 / -0.23 dB
4400	4.93	+0.22 / -0.23 dB
4500	5.00	+0.22 / -0.23 dB
4600	5.10	+0.22 / -0.23 dB
4700	5.20	+0.22 / -0.23 dB
4800	5.30	+0.22 / -0.23 dB
4900	5.43	+0.22 / -0.23 dB
5000	5.54	+0.22 / -0.23 dB
5100	5.65	+0.22 / -0.23 dB
5200	5.73	+0.22 / -0.23 dB
5300	5.86	+0.22 / -0.23 dB
5400	5.95	+0.22 / -0.23 dB
5500	6.05	+0.22 / -0.23 dB
5600	6.16	+0.22 / -0.23 dB
5700	6.28	+0.22 / -0.23 dB
5800	6.38	+0.22 / -0.23 dB
5900	6.53	+0.22 / -0.23 dB
6000	6.63	+0.22 / -0.23 dB
6100	6.75	+0.22 / -0.23 dB
6200	6.82	+0.22 / -0.23 dB
6300	6.93	+0.22 / -0.23 dB
6400	7.00	+0.22 / -0.23 dB
6500	7.05	+0.22 / -0.23 dB



HL 4277: Test Cable  
Mini-Circuits, model: APC-10FT-NMNM+, s/n 0748A

Set / Applied, MHz	Measured, dB	Uncertainty, dB
0.1	0.26	+0.07 / -0.07 dB
50	0.27	+0.07 / -0.07 dB
100	0.38	+0.07 / -0.07 dB
200	0.55	+0.07 / -0.07 dB
300	0.69	+0.08 / -0.09 dB
400	0.80	+0.08 / -0.09 dB
500	0.91	+0.08 / -0.09 dB
600	1.00	+0.08 / -0.09 dB
700	1.08	+0.08 / -0.09 dB
800	1.17	+0.08 / -0.09 dB
900	1.24	+0.08 / -0.09 dB
1000	1.32	+0.08 / -0.09 dB
1100	1.39	+0.12 / -0.13 dB
1200	1.45	+0.12 / -0.13 dB
1300	1.52	+0.12 / -0.13 dB
1400	1.58	+0.12 / -0.13 dB
1500	1.65	+0.12 / -0.13 dB
1600	1.71	+0.12 / -0.13 dB
1700	1.77	+0.12 / -0.13 dB
1800	1.82	+0.12 / -0.13 dB
1900	1.88	+0.12 / -0.13 dB
2000	1.93	+0.12 / -0.13 dB
2100	1.99	+0.12 / -0.13 dB
2200	2.05	+0.12 / -0.13 dB
2300	2.10	+0.12 / -0.13 dB
2400	2.15	+0.12 / -0.13 dB
2500	2.20	+0.17 / -0.18 dB
2600	2.25	+0.17 / -0.18 dB
2700	2.30	+0.17 / -0.18 dB
2800	2.35	+0.17 / -0.18 dB
2900	2.40	+0.17 / -0.18 dB
3000	2.44	+0.17 / -0.18 dB
3100	2.49	+0.19 / -0.2 dB
3200	2.54	+0.19 / -0.2 dB
3300	2.58	+0.19 / -0.2 dB
3400	2.62	+0.19 / -0.2 dB
3500	2.66	+0.19 / -0.2 dB
3600	2.71	+0.19 / -0.2 dB
3700	2.75	+0.19 / -0.2 dB
3800	2.79	+0.19 / -0.2 dB
3900	2.84	+0.19 / -0.2 dB
4000	2.88	+0.19 / -0.2 dB

Set / Applied, MHz	Measured, dB	Uncertainty, dB
4100	2.84	+0.19 / -0.2 dB
4200	2.88	+0.19 / -0.2 dB
4300	2.92	+0.3 / -0.33 dB
4400	2.96	+0.3 / -0.33 dB
4500	3.01	+0.3 / -0.33 dB
4600	3.05	+0.3 / -0.33 dB
4700	3.09	+0.3 / -0.33 dB
4800	3.13	+0.3 / -0.33 dB
4900	3.18	+0.3 / -0.33 dB
5000	3.21	+0.3 / -0.33 dB
5100	3.25	+0.3 / -0.33 dB
5200	3.30	+0.3 / -0.33 dB
5300	3.34	+0.3 / -0.33 dB
5400	3.39	+0.3 / -0.33 dB
5500	3.44	+0.3 / -0.33 dB
5600	3.48	+0.3 / -0.33 dB
5700	3.53	+0.3 / -0.33 dB
5800	3.57	+0.3 / -0.33 dB
5900	3.60	+0.3 / -0.33 dB
6000	3.65	+0.3 / -0.33 dB
6100	3.68	+0.3 / -0.33 dB
6200	3.72	+0.3 / -0.33 dB
6300	3.77	+0.3 / -0.33 dB
6400	3.83	+0.3 / -0.33 dB
6500	3.86	+0.3 / -0.33 dB
6600	3.92	+0.3 / -0.33 dB
6700	3.96	+0.3 / -0.33 dB
6800	4.00	+0.3 / -0.33 dB
6900	4.04	+0.3 / -0.33 dB
7000	4.08	+0.3 / -0.33 dB
7100	4.11	+0.3 / -0.33 dB
7200	4.16	+0.3 / -0.33 dB
7300	4.20	+0.3 / -0.33 dB
7400	4.24	+0.3 / -0.33 dB
7500	4.29	+0.3 / -0.33 dB
7600	4.33	+0.3 / -0.33 dB
7700	4.38	+0.3 / -0.33 dB
7800	4.42	+0.3 / -0.33 dB
7900	4.51	+0.3 / -0.33 dB
8000	4.52	+0.3 / -0.33 dB
8100	4.55	+0.34 / -0.36 dB
8200	4.55	+0.34 / -0.36 dB



HL 4277: Test cable

Set / Applied, MHz	Measured, dB	Uncertainty, dB
8300	4.57	+0.34 / -0.36 dB
8400	4.60	+0.34 / -0.36 dB
8500	4.60	+0.34 / -0.36 dB
8600	4.63	+0.34 / -0.36 dB
8700	4.63	+0.34 / -0.36 dB
8800	4.64	+0.34 / -0.36 dB
8900	4.65	+0.34 / -0.36 dB
9000	4.67	+0.34 / -0.36 dB
9100	4.69	+0.34 / -0.36 dB
9200	4.71	+0.34 / -0.36 dB
9300	4.73	+0.34 / -0.36 dB
9400	4.76	+0.34 / -0.36 dB
9500	4.78	+0.34 / -0.36 dB
9600	4.81	+0.34 / -0.36 dB
9700	4.85	+0.34 / -0.36 dB
9800	4.87	+0.34 / -0.36 dB
9900	4.89	+0.34 / -0.36 dB
10000	4.93	+0.34 / -0.36 dB
10100	4.96	+0.4 / -0.44 dB
10200	4.99	+0.4 / -0.44 dB
10300	5.02	+0.4 / -0.44 dB
10400	5.05	+0.4 / -0.44 dB
10500	5.08	+0.4 / -0.44 dB
10600	5.11	+0.4 / -0.44 dB
10700	5.14	+0.4 / -0.44 dB
10800	5.17	+0.4 / -0.44 dB
10900	5.19	+0.4 / -0.44 dB
11000	5.22	+0.4 / -0.44 dB
11100	5.25	+0.4 / -0.44 dB
11200	5.28	+0.4 / -0.44 dB
11300	5.31	+0.4 / -0.44 dB
11400	5.34	+0.4 / -0.44 dB
11500	5.38	+0.4 / -0.44 dB
11600	5.41	+0.4 / -0.44 dB
11700	5.45	+0.4 / -0.44 dB
11800	5.49	+0.4 / -0.44 dB
11900	5.53	+0.4 / -0.44 dB
12000	5.56	+0.4 / -0.44 dB
12100	5.60	+0.4 / -0.44 dB
12200	5.63	+0.4 / -0.44 dB
12300	5.68	+0.4 / -0.44 dB
12400	5.72	+0.4 / -0.44 dB
12500	5.75	+0.47 / -0.52 dB
12600	5.80	+0.47 / -0.52 dB
12700	5.84	+0.47 / -0.52 dB
12800	5.93	+0.47 / -0.52 dB
12900	5.94	+0.47 / -0.52 dB
13000	5.98	+0.47 / -0.52 dB
13100	6.03	+0.47 / -0.52 dB

Set / Applied, MHz	Measured, dB	Uncertainty, dB
13200	6.09	+0.47 / -0.52 dB
13300	6.17	+0.47 / -0.52 dB
13400	6.27	+0.47 / -0.52 dB
13500	6.37	+0.47 / -0.52 dB
13600	6.49	+0.47 / -0.52 dB
13700	6.57	+0.47 / -0.52 dB
13800	6.60	+0.47 / -0.52 dB
13900	6.61	+0.47 / -0.52 dB
14000	6.59	+0.47 / -0.52 dB
14100	6.57	+0.47 / -0.52 dB
14200	6.54	+0.47 / -0.52 dB
14300	6.53	+0.47 / -0.52 dB
14400	6.49	+0.47 / -0.52 dB
14500	6.48	+0.47 / -0.52 dB
14600	6.46	+0.47 / -0.52 dB
14700	6.46	+0.47 / -0.52 dB
14800	6.49	+0.47 / -0.52 dB
14900	6.51	+0.47 / -0.52 dB
15000	6.54	+0.47 / -0.52 dB
15100	6.57	+0.47 / -0.52 dB
15200	6.62	+0.47 / -0.52 dB
15300	6.64	+0.47 / -0.52 dB
15400	6.68	+0.47 / -0.52 dB
15500	6.71	+0.47 / -0.52 dB
15600	6.78	+0.47 / -0.52 dB
15700	6.79	+0.47 / -0.52 dB
15800	6.82	+0.47 / -0.52 dB
15900	6.88	+0.47 / -0.52 dB
16000	6.89	+0.47 / -0.52 dB
16100	6.96	+0.47 / -0.52 dB
16200	6.97	+0.47 / -0.52 dB
16300	7.02	+0.47 / -0.52 dB
16400	7.07	+0.47 / -0.52 dB
16500	7.12	+0.47 / -0.52 dB
16600	7.17	+0.47 / -0.52 dB
16700	7.20	+0.47 / -0.52 dB
16800	7.22	+0.47 / -0.52 dB
16900	7.23	+0.47 / -0.52 dB
17000	7.24	+0.47 / -0.52 dB
17100	7.27	+0.47 / -0.52 dB
17200	7.28	+0.47 / -0.52 dB
17300	7.28	+0.47 / -0.52 dB
17400	7.30	+0.47 / -0.52 dB
17500	7.34	+0.47 / -0.52 dB
17600	7.35	+0.47 / -0.52 dB
17700	7.39	+0.47 / -0.52 dB
17800	7.41	+0.47 / -0.52 dB
17900	7.41	+0.47 / -0.52 dB
18000	7.44	+0.47 / -0.52 dB



HL 5111: RF cable  
Huber-Suhner, SF102EA/11SK/11SK/5500MM, s/n 502493/2EA

Set / Applied, MHz	Measured, dB	Uncertainty, dB
100	0.70	±0.07
200	0.99	±0.08
300	1.21	±0.08
500	1.56	±0.08
1000	2.20	±0.08
1500	2.69	±0.08
2000	3.11	±0.08
2500	3.50	±0.10
3000	3.85	±0.10
3500	4.16	±0.10
4000	4.47	±0.10
4500	4.74	±0.10
5000	5.03	±0.10
5500	5.30	±0.10
6000	5.57	±0.10
6500	5.76	±0.10
7000	6.00	±0.10
7500	6.20	±0.10
8000	6.44	±0.10
8500	6.67	±0.10
9000	6.82	±0.10
9500	7.04	±0.10
10000	7.18	±0.10
10500	7.36	±0.10
11000	7.55	±0.10
11500	7.75	±0.10
12000	7.90	±0.10
12500	8.08	±0.13
13000	8.19	±0.13
13500	8.39	±0.13
14000	8.58	±0.13
14500	8.76	±0.18
15000	8.92	±0.18
15500	9.03	±0.18
16000	9.18	±0.18
16500	9.34	±0.18
17000	9.51	±0.18
17500	9.66	±0.18
18000	9.80	±0.18
18500	9.94	±0.23
19000	10.05	±0.23
19500	10.22	±0.23

Set / Applied, MHz	Measured, dB	Uncertainty, dB
20000	10.32	±0.23
20500	10.48	±0.23
21000	10.60	±0.23
21500	10.73	±0.23
22000	10.87	±0.23
22500	10.97	±0.29
23000	11.09	±0.29
23500	11.26	±0.29
24000	11.37	±0.29
24500	11.50	±0.29
25000	11.61	±0.23
25500	11.72	±0.23
26000	11.87	±0.23
26500	11.99	±0.23
27000	12.09	±0.33
27500	12.24	±0.33
28000	12.34	±0.40
28500	12.47	±0.40
29000	12.61	±0.40
29500	12.70	±0.40
30000	12.86	±0.40
30500	12.92	±0.33
31000	13.09	±0.33
31500	13.16	±0.33
32000	13.33	±0.33
32500	13.40	±0.33
33000	13.62	±0.33
33500	13.70	±0.33
34000	13.88	±0.33
34500	13.97	±0.40
35000	14.05	±0.40
35500	14.23	±0.40
36000	14.25	±0.40
36500	14.46	±0.40
37000	14.49	±0.33
37500	14.72	±0.33
38000	14.77	±0.33
38500	14.97	±0.33
39000	15.04	±0.33
39500	15.22	±0.33
40000	15.63	±0.47



11 APPENDIX C Measurement uncertainties

Expanded uncertainty at 95% confidence in Hermon Labs EMC measurements

Test description	Expanded uncertainty
Conducted carrier power at RF antenna connector	Below 12.4 GHz: ± 1.7 dB 12.4 GHz to 40 GHz: ± 2.3 dB
Conducted emissions at RF antenna connector	9 kHz to 2.9 GHz: ± 2.6 dB 2.9 GHz to 6.46 GHz: ± 3.5 dB 6.46 GHz to 13.2 GHz: ± 4.3 dB 13.2 GHz to 22.0 GHz: ± 5.0 dB 22.0 GHz to 26.8 GHz: ± 5.5 dB 26.8 GHz to 40.0 GHz: ± 4.8 dB
Occupied bandwidth	± 8.0 %
Duty cycle, timing (Tx ON / OFF) and average factor measurements	± 1.0 %
Conducted emissions with LISN	9 kHz to 150 kHz: ± 3.9 dB 150 kHz to 30 MHz: ± 3.8 dB
Radiated emissions at 3 m measuring distance Horizontal polarization  Vertical polarization	Biconilog antenna: ± 5.3 dB Biconical antenna: ± 5.0 dB Log periodic antenna: ± 5.3 dB Double ridged horn antenna: ± 5.3 dB Biconilog antenna: ± 6.0 dB Biconical antenna: ± 5.7 dB Log periodic antenna: ± 6.0 dB Double ridged horn antenna: ± 6.0 dB

Hermon Laboratories is accredited by A2LA for calibration according to present requirements of ISO/IEC 17025 and NCSL Z540-1. The accreditation is granted to perform calibration of parameters that are listed in the Scope of Hermon Laboratories Accreditation.

Hermon Laboratories calibrates its reference and transfer standards by calibration laboratories accredited to ISO/IEC 17025 by a mutually recognized Accreditation Body or by a recognized national metrology institute. All reference and transfer standards used in the calibration system are traceable to national or international standards.

In-house calibration of all test and measurement equipment is performed on a regular basis according to Hermon Laboratories calibration procedures, manufacturer calibration/verification procedures or procedures defined in the relevant standards. The Hermon Laboratories test and measurement equipment is calibrated within the tolerances specified by the manufacturers and/or by the relevant standards.



HERMON LABORATORIES

Report ID: VISRAD\_FCC.31113\_rev1  
Date of Issue: 15-Nov-18

## 12 APPENDIX D Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, safety, environmental and telecommunication testing facility.

Hermon Laboratories is recognized and accredited by the Federal Communications Commission (USA) for 1, 2, 15, 18 parts of Code of Federal Regulations 47 (CFR 47), Test Firm Registration Number is 927748, Designation Number is IL1001; registered by Industry Canada for electromagnetic emissions, file number IC 2186A-1 for OATS, certified by VCCI, Japan (the registration numbers are R-808 for OATS, R-1082 for anechoic chamber, G-869 for RE measurements above 1 GHz, C-845 for conducted emissions site, T-1606 for conducted emissions at telecommunication ports). The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing and environmental simulation (for exact scope please refer to Certificate No. 839.01).

Address: P.O. Box 23, Binyamina 3055001, Israel  
Telephone: +972 4628 8001  
Fax: +972 4628 8277  
e-mail: [mail@hermonlabs.com](mailto:mail@hermonlabs.com)  
website: [www.hermonlabs.com](http://www.hermonlabs.com)

Person for contact: Mr. Michael Nikishin, EMC and radio group manager



### 13 APPENDIX E

### Specification references

FCC 47CFR part 15: 2017	Radio Frequency Devices.
ICES-003: 2016, Issue 6	Information Technology Equipment (Including Digital Apparatus) – Limits and methods of measurement
ANSI C63.2: 2016	American National Standard for Instrumentation-Electromagnetic Noise and Field Strength, 10 kHz to 40 GHz-Specifications.
ANSI C63.4: 2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
ANSI C63.10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
RSS-247: 2017, Issue 2	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices
RSS-Gen: 2018, Issue 5	General Requirements for Compliance of Radio Apparatus



## 14 APPENDIX F Abbreviations and acronyms

A	ampere
AC	alternating current
AM	amplitude modulation
AVRG	average (detector)
cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
dB( $\mu$ V)	decibel referred to one microvolt
dB( $\mu$ V/m)	decibel referred to one microvolt per meter
dB( $\mu$ A)	decibel referred to one microampere
DC	direct current
EIRP	equivalent isotropically radiated power
ERP	effective radiated power
EUT	equipment under test
F	frequency
GHz	gigahertz
GND	ground
H	height
HL	Hermon laboratories
Hz	hertz
k	kilo
kHz	kilohertz
LO	local oscillator
m	meter
MHz	megahertz
min	minute
mm	millimeter
ms	millisecond
$\mu$ s	microsecond
NA	not applicable
NB	narrow band
OATS	open area test site
$\Omega$	Ohm
PM	pulse modulation
PS	power supply
ppm	part per million ( $10^{-6}$ )
QP	quasi-peak
RE	radiated emission
RF	radio frequency
rms	root mean square
Rx	receive
s	second
T	temperature
Tx	transmit
V	volt
WB	wideband

END OF DOCUMENT