

Applicant:

Elatec GmbH
Zeppelinstraße 1
82178 Puchheim
Tel.: +49 89 5529961-0
Fax: +49 89 5529961-129

Test report no.:

200698-AU01+W03

for:

Elatec GmbH
BLE module
EINTLEG

according to:

Part 2

RSS 102



Deutsche
Akkreditierungsstelle
D-PL-12155-01-04



Deutsche
Akkreditierungsstelle
D-PL-12155-01-03

Accreditation:

Deutsche
Akkreditierungsstelle
D-PL-12155-01-04

FCC test firm accreditation expiration date: 2021-05-30
MRA US-EU, FCC designation number: DE0010
FCC registration number: 97268
BnetzA-CAB-02/21-02/5 Valid until 2023-11-26



Deutsche
Akkreditierungsstelle
D-PL-12155-01-03

Recognized on March 14th, 2019 by the
Department of Innovation, Science and Economic Development (ISED) Canada
as a wireless testing laboratory
CAB identifier: DE0011
ISED#: 3472A

Location of Testing:

Element Materials Technology Straubing GmbH

Tel.: +49 9421 56868-0

Fax: +49 9421 56868-100

Email: info.straubing@element.com

Gustav-Hertz-Straße 35

94315 Straubing, Germany

The technical accuracy is guaranteed through the quality management of
Element Materials Technology Straubing GmbH.

Table of contents

1	Test regulations	5
2	Summary of test results	6
3	Equipment under test (EUT)	7
4	Photographs of EUT	7
5	Test results	8
5.1	FCC	9
5.2	Canada	11
6	Revision history	14

List of tables

Table 1: Exposure to the head and body at lowest channel	10
Table 2: Exposure to the head and body at middle channel	10
Table 3: Exposure to the head and body at highest channel	10
Table 4: Exposure to the head and body at lowest channel	13
Table 5: Exposure to the head and body at lowest channel	13
Table 6: Exposure to the head and body at lowest channel	13


1 Test regulations

<i>Standard</i>	<i>Title</i>
RSS-102 Issue 5 March 2015	Spectrum Management and Telecommunications Radio Standards Specification Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands)
SPR-002 Issue 1 September 2016	Spectrum Management and Telecommunications Supplementary Procedure Supplementary Procedure for Assessing Compliance with RSS-102 Nerve Stimulation Exposure Limits
Safety Code 6 (2015)	Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz
IEEE C95.3-2002 (R2008) Approved December 11, 2002 Reaffirmed June 12, 2008	IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields With Respect to Human Exposure to Such Fields, 100 kHz–300 GHz
OET Bulletin 65, 65A, 65B Edition 97-01, August 1997	Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields
Part 1, Subpart I, Section 1.1310	Radiofrequency radiation exposure limits
Part 1, Subpart 2, Section 2.1093	Radiofrequency radiation exposure evaluation: portable device
KDB 447498 D01 v06	Mobile and portable devices RF Exposure procedures and equipment authorisation policies, October 23, 2015.
KDB 865664 D01	SAR Measurement Requirements for 100 MHz to 6 GHz, August 7, 2015.
ANSI C95.1: 2005	IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
ANSI C63.10 June 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

2 Summary of test results

<i>Standard</i>	<i>Result</i>	<i>Page</i>	<i>Remark</i>
<i>Part 2</i>	Passed	9	---
<i>RSS-102 Issue 5</i>	Passed	11	---

Straubing, October 28, 2020



Jennifer Riedel B.Eng.
Radio Test Engineer



Konrad Graßl
Department Manager Radio

3 Equipment under test (EUT)

Product type:	BLE module		
Model Name:	EINTLEG		
HVIN:	EL20206		
Manufacturer:	Elatec GmbH		
Serial number:	Serial prototype		
Version:	Hardware:	A	
	Software:	TWN4/B1.20/NKD4.03/C6T1.06 (Beta 1)	
Short description:	EUT is a Bluetooth low energy 5.0 module operating in the 2.4 GHz frequency band.		
FCC ID:	WP5EINTLEG1		
IC certification number:	7948A-EINTLEG1		
Application frequency band:	2400 MHz – 2483.5 MHz		
Number of RF channels:	40		
Modulation:	GFSK		
Data rate:	1 Mbps		
Antenna types:	Chip antenna		
	<input type="checkbox"/> detachable	<input checked="" type="checkbox"/> not detachable	
Power supply:	DC supply nominal voltage: 1.7 V to 3.6 V		
Exposure to:	<input checked="" type="checkbox"/>	Head	
	<input checked="" type="checkbox"/>	Body	
	<input type="checkbox"/>	Limbs	
	<input type="checkbox"/>	other	
Separation distance:	<input checked="" type="checkbox"/>	≤ 20 cm	
	<input type="checkbox"/>	> 20 cm	
Evaluated against exposure limits:	<input checked="" type="checkbox"/>	General public use	
	<input type="checkbox"/>	Controlled use	

4 Photographs of EUT

See Annex B of test report 200698-AU01+W02 of test laboratory Element Materials Technology Straubing GmbH.

5 Test results

This clause gives details about the test results as collected on page 6.

5.1 FCC

5.1.1 Evaluation for separation distance ≤ 20 cm, except WPT

Reference: Part 2, Section 2.1093

Basic standard: n/a

Performed by:	Jennifer Riedel B. Eng.	Date of test:	October 26, 2020
---------------	-------------------------	---------------	------------------

Result:	<input checked="" type="checkbox"/> Limits kept	<input type="checkbox"/> Limits not kept
---------	-------------------------------------------------	------------------------------------------

5.1.1.1 Requirements and limits for separation distance ≤ 20 cm

This estimation follows the general guidelines for RF Exposure according to KDB 447498.

As noted in §2.103(b) For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

According §2.1093 (d)(i)(2): The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

5.1.1.2 Results

The following data are based on applicants document:

Test report 200698-AU01+W02 of the test laboratory Element Materials Technology Straubing GmbH

RF technology :

Application: Bluetooth low energy 5.0

Operation frequency range: 2402 MHz – 2480 MHz

Antenna model Chip antenna

Antenna connector: none

Antenna type: internal

not detachable

Antenna gain: 0.5 dBi

Maximum conducted output power: -1.25 dBm at 2402 MHz
-1.15 dBm at 2436 MHz
-1.16 dBm at 2480 MHz

Tune-up tolerance (according to the manufacturer): ± 4 dB

Information related to Exposure:

Separation distance: < 5 mm

Exposure tier: general public

Power averaging over time: Not applied

<i>Separation distance (mm)</i>	<i>Channel Frequency (MHz)</i>	<i>rated power + tolerance (dBm)</i>	<i>Rounded rated power + tolerance (mW)</i>	<i>Rounded 1-g SAR</i>	<i>Limit 1-g SAR</i>	<i>Result</i>
< 5	2402	2.75	2	0.7	3.0	passed

Table 1: Exposure to the head and body at lowest channel

<i>Separation distance (mm)</i>	<i>Channel Frequency (MHz)</i>	<i>rated power + tolerance (dBm)</i>	<i>Rounded rated power + tolerance (mW)</i>	<i>Rounded 1-g SAR</i>	<i>Limit 1-g SAR</i>	<i>Result</i>
< 5	2436	2.85	2	0.7	3.0	passed

Table 2: Exposure to the head and body at middle channel

<i>Separation distance (mm)</i>	<i>Channel Frequency (MHz)</i>	<i>rated power + tolerance (dBm)</i>	<i>Rounded rated power + tolerance (mW)</i>	<i>Rounded 1-g SAR</i>	<i>Limit 1-g SAR</i>	<i>Result</i>
< 5	2480	2.84	2	0.7	3.0	passed

Table 3: Exposure to the head and body at highest channel

5.2 Canada

5.2.1 Evaluation for separation distance ≤ 20 cm, except 3 kHz -10 MHz

Reference: RSS 102 clause 2.5.1

Basic standard: n/a

Performed by:	Jennifer Riedel B. Eng.	Date of test:	October 26, 2020
Result:	<input checked="" type="checkbox"/> Limits kept	<input type="checkbox"/> Limits not kept	

5.2.1.1 Exemption Limits for Routine Evaluation – SAR Evaluation

According RSS 102 clause 2.5.1:

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1.

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤ 300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥ 50 mm
≤ 300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

⁴ The exemption limits in Table 1 are based on measurements and simulations of half-wave dipole antennas at separation distances of 5 mm to 25 mm from a flat phantom, providing a SAR value of approximately 0.4 W/kg for 1 g of tissue. For low frequencies (300 MHz to 835 MHz), the exemption limits are derived from a linear fit. For high frequencies (1900 MHz and above), the exemption limits are derived from a third order polynomial fit.

⁵ Transmitters operating between 0.003-10 MHz, meeting the exemption from routine SAR evaluation, shall demonstrate compliance to the instantaneous limits in Section 4.

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power. For controlled use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5. If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.

For medical implants devices, the exemption limit for routine evaluation is set at 1 mW. The output power of a medical implants device is defined as the higher of the conducted or e.i.r.p to determine whether the device is exempt from the SAR evaluation.

5.2.1.2 Results

The following data are based on applicants document:

Test report 200698-AU01+W02 of the test laboratory Element Materials Technology Straubing GmbH

RF technology :

Application: Bluetooth low energy 5.0

Operation frequency range: 2402 MHz – 2480 MHz

Antenna model Chip antenna

Antenna connector: none

Antenna type: internal

not detachable

Antenna gain: 0.5 dBi

Maximum conducted output power: -1.25 dBm at 2402 MHz
-1.15 dBm at 2436 MHz
-1.16 dBm at 2480 MHz

Tune-up tolerance (according to the manufacturer): ± 4 dB

Information related to Exposure:

Separation distance: < 5 mm

Exposure tier: general public

Power averaging over time: Not applied

<i>Separation distance (mm)</i>	<i>Channel Frequency (MHz)</i>	<i>EIRP + tolerance (dBm)</i>	<i>Rounded EIRP + tolerance (mW)</i>	<i>Limit 1-g SAR (mW)</i>	<i>Result</i>
< 5	2402	3.25	3.0	4.00	passed

Table 4: Exposure to the head and body at lowest channel

<i>Separation distance (mm)</i>	<i>Channel Frequency (MHz)</i>	<i>EIRP + tolerance (dBm)</i>	<i>Rounded EIRP + tolerance (mW)</i>	<i>Limit 1-g SAR (mW)</i>	<i>Result</i>
< 5	2436	3.35	3.0	4.00	passed

Table 5: Exposure to the head and body at lowest channel

<i>Separation distance (mm)</i>	<i>Channel Frequency (MHz)</i>	<i>EIRP + tolerance (dBm)</i>	<i>Rounded EIRP + tolerance (mW)</i>	<i>Limit 1-g SAR (mW)</i>	<i>Result</i>
< 5	2480	3.34	3.0	4.00	passed

Table 6: Exposure to the head and body at lowest channel

6 Revision history

<i>Revision</i>	<i>Date</i>	<i>Issued by</i>	<i>Description of modifications</i>
0	2020-10-28	Jennifer Riedel B. Eng.	First edition