

Elatec TWN3 HID Prox

Functional Description

1. General

The TWN3 HID Prox is an integrated device for contactless read operations on a transponder, i.e. a transponder card.

2. Description

Please refer to the block diagram and the manual for better understanding of the description.

2.1. Power Supply

The device is supplied with power via the the communication cable. In case of USB, the device is directly supplied from the USB bus. The voltage is 5V nominal, but the valid range for a USB device, which is 4.3V to 5.5V is tolerated.

2.2. Host Communication

Data communication with the host is accomplished with either USB or RS232. In case of USB, the device acts as a full speed (12Mbit/s) device. In case of RS232 the standard data rate is 9600 Baud.

2.3. Interface Processor

The micro controller AT89C513xA acts as protocol converter (“interface processor”). It converts the data stream from the host controller to appropriate commands for the HID Prox reader module. On the other side, data coming form the reader module is converted into the appropriate format for the host.

Furthermore, the interface processor takes over control of speaker and the red and the green signal LED.

2.4. Reader Module

The HID Prox reader module HID Global eProx MCM Modul 4025 handles the transceiver functionality for contactless communication with a transponder at a frequency of 125kHz. Modulation is ASK 100%.

2.5. Oscillators

The device is equipt with an oscillator. The interface processor is clocked with 24MHz., the HID Global eProx MCM Modul 4025 has a additional built-in clock, which generates the carrier frequency of 125kHz.