



Test Report

Prepared for: NextLink Video Communications

Model: Starlink Wireless 1525

Description: 2.4 GHz Wireless Transmitter

Serial Number: N/A

FCC ID: WPSSL-1525-T8RX1

To

FCC Part 1.1310

Date of Issue: March 10, 2016

On the behalf of the applicant:

NextLink Video Communications
9810 E 2nd St
Tucson, AZ 85748

Attention of:

Van Sarkiss, CEO
Ph: 520-444-7311
Email: van@nextlinkvideo.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1510007



Alex Macon
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	March 8, 2016	Alex Macon	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: Starlink Wireless 1525

Description: 2.4GHz Wireless Transmitter

Firmware: N/A

Software: N/A

Additional Information:

The Starlink Wireless 1525 is a wireless transmitter which transmits in the 2.4GHz range. Its intended use is as a portable means to transmit video.



Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
2470	700	100	700 mW



MPE Evaluation

This is a portable device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure

47 CFR 1.1310

Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	2470
Power, Conducted, mW (P)	700
Antenna Gain Isotropic	6 dBi
Antenna Gain Numeric (G)	3.98
Antenna Type	sma
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) = 0.5542
Limit =(from above table) = 1.0

END OF TEST REPORT