

PDI-P19LCDC solution:

TV **MSD119+XC5000+LGDT1129**

Panel 19" CMO M190A1-LOA

Inverter MP1048

Power supply NCP1351

1、 Features

- ◎ 19" 16:10 panel ,1280×1024
- ◎ Y/Pb/Pr interface ,support 480P ,720P,1080I.
- ◎ Support AV VGA S-Video HDMI, CCI&MTI ,PILLOW SPEAKER ,NTSC/ATSC TUNER,FM
- ◎ V-chip and CCD

2、 General Specifications

Dimension	458mmx184mmx373mm (with stand)
weight	12.2 Pounds (5.54 Kg) (TV Only without stand)
Voltage	120V
Temperature	-10~+40℃
Frequency Range	57~ 803MHz
Receive Sensitivity	0DB~80DB
Power Consumption	60W

3、 The channel center frequency and CHNL_ID numbers shall be shown in the following table.

Tuner Channel Center Frequency							
CHNL_ID	Frequency (MHz)	CHNL_ID	Frequency (MHz)	CHNL_ID	Frequency (MHz)	CHNL_ID	Frequency (MHz)
2	57	21	515	40	629	59	743
3	63	22	521	41	635	60	749
4	69	23	527	42	641	61	755
5	79	24	533	43	647	62	761
6	85	25	539	44	653	63	767
7	177	26	545	45	659	64	773
8	183	27	551	46	665	65	779
9	189	28	557	47	671	66	785
10	195	29	563	48	677	67	791
11	201	30	569	49	683	68	797
12	207	31	575	50	689	69	803
13	213	32	581	51	695		
14	473	33	587	52	701		
15	479	34	593	53	707		
16	485	35	599	54	713		
17	491	36	605	55	719		
18	497	37	611	56	725		
19	503	38	617	57	731		
20	509	39	623	58	737		

Bluetooth function is sheilded by software and can not opened by user.