

Trademarks

Autel®, MaxiCOM®, MaxiDAS®, MaxiScan®, MaxiTPMS®, MaxiRecorder®, and MaxiCheck® are trademarks of Autel Intelligent Technology Corp., Ltd., registered in China, the United States and other countries. All other marks are trademarks or registered trademarks of their respective holders.

Copyright Information

No part of this manual may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without the prior written permission of Autel.

Disclaimer of Warranties and Limitation of Liabilities

All information, specifications and illustrations in this manual are based on the latest information available at the time of printing. Autel reserves the right to make changes at any time without notice. While information of this manual has been carefully checked for accuracy, no guarantee is given for the completeness and correctness of the contents, including but not limited to the product specifications, functions, and illustrations.

Autel will not be liable for any direct damages or for any special, incidental, or indirect damages or for any economic consequential damages (including the loss of profits).



IMPORTANT: Before operating or maintaining this unit, please read this manual carefully, paying extra attention to the safety warnings and precautions.

For Services and Support:



pro.autel.com

www.autel.com



1-855-288-3587/1-855-AUTELUS (North America)

0086-755-86147779 (China)




support@autel.com

For technical assistance in all other markets, please contact your local distributor.

1 General Introduction

The Autel universal smart key IKEY is a dual-band (315/433 MHz) product that supports car-finding within 40 meters and comes with various models to meet customers' needs.

1.1 Product Overview

No.	Model	Appearance
1	IKEYTY8A4AL IKEYTY8A3AL IKEYTY8A3BL	

1.2 Specifications

Item	Description
Product Name	Universal Smart Key
Model	IKEYTY8A4AL, IKEYTY8A3AL, IKEYTY8A3BL
Battery	Type: CR2032 220 mAh, 3 V Li-MnO2 button cell

1.3 Key Function



Unlock key: Unlock the vehicle,

Trunk key: open the trunk,

Car lock key: lock the vehicle after parking to prevent theft,

Car search key: press this key, the car will beep and the lights will be on.

1.4 Pairing Method

1. Matching a new key, especially a key with a chip, requires a vehicle detection computer to assist in pairing. The vehicle detection computer can purchase a third-party decoder online or a car repair shop for adaptation;
2. After the vehicle detection computer is inserted into the OBD on-board diagnostic system socket, take the original car key to adjust the vehicle to the power-on state of the vehicle, and the indicator light should flash after the detection computer and the OBD on-board diagnostic system are successfully matched;
3. Insert the matching key into the key hole. If the matching is successful, the indicator light of the key decoder will flash. You should immediately operate the unlock button on the original remote control, then click the unlock button on the new remote control, and wait for about ten seconds to complete the key pairing.

2 Compliance Information

FCC STATEMENT:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

RF warning statement:

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

IC STATEMENT:

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions:

- (1) This device may not cause interference, and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

French:"

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- (1) l'appareil ne doit pas produire de brouillage, et
- (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement."