

FCC TEST REPORT

For

Autel Intelligent Tech. Corp., Ltd.

Professional Scan Tool

Model No.: TS201

Prepared For : Autel Intelligent Tech. Corp., Ltd.
Address : 6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan, Shenzhen, China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited
Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102
Tel: (86) 755-26066440 **Fax:** (86) 755-26014772

Report Number : SZAWW181109005-01
Date of Receipt : Nov. 09, 2018
Date of Test : Nov. 09~26, 2018
Date of Report : Nov. 26, 2018

Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	5
1.4. Description of Test Modes.....	5
1.5. Description Of Test Setup.....	6
1.6. Test Equipment List.....	7
1.7. Description of Test Facility.....	8
2. Summary of Test Results.....	9
3. Conducted Emission Test.....	10
3.1. Test Standard and Limit.....	10
3.2. Test Setup.....	10
3.3. Test Procedure.....	10
3.4. Test Data.....	10
4. Radiation Spurious Emission and Band Edge.....	15
4.1. Test Standard and Limit.....	15
4.2. Test Setup.....	15
4.3. Test Procedure.....	16
4.4. Test Data.....	17
5. Antenna Requirement.....	23
5.1. Test Standard and Requirement.....	23
5.2. Antenna Connected Construction.....	23
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	24
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	26
APPENDIX III -- INTERNAL PHOTOGRAPH.....	30

TEST REPORT

Applicant : Autel Intelligent Tech. Corp., Ltd.
Manufacturer : Autel Intelligent Tech. Corp., Ltd.
Product Name : Professional Scan Tool
Model No. : TS201
Trade Mark : AUTEL
Rating(s) : Input: DC 5V, 1A(with DC 3.7V, 1050 mAh Battery inside)

Test Standard(s) : FCC Part15 Subpart C 2018, Paragraph 15.209
Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test

Nov. 09~26, 2018

Prepared By



Oliay Yang

(Engineer / Oliay Yang)

Reviewer

Snowy Meng

(Supervisor / Snowy Meng)

Approved & Authorized Signer

Sally Zhang

(Manager / Sally Zhang)

1. General Information

1.1. Client Information

Applicant	:	Autel Intelligent Tech. Corp., Ltd.
Address	:	6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan, Shenzhen, China
Manufacturer	:	Autel Intelligent Tech. Corp., Ltd.
Address	:	6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan, Shenzhen, China
Factory	:	Autel Intelligent Technology Corp.,Ltd.
Address	:	6 th Floor, Building 1, Yanxiang Zhigu, NO.11 Gaoxin West Rd., Guangming New District, Shenzhen City, Guangdong Province, China.
Factory	:	AUTEL VIETNAM COMPANY LIMITED
Address	:	4th Floor, Factory#6, Land#CN1, An Duong Industrial Zone, Hong Phong Township, An Duong County, Hai Phong, Viet Nam

1.2. Description of Device (EUT)

Product Name	:	Professional Scan Tool
Model No.	:	TS201
Trade Mark	:	AUTEL
Test Power Supply	:	AC 240V, 60Hz for adapter/ AC 120V, 60Hz for adapter DC 3.7V By battery
Test Sample No.	:	S1(Normal Sample), S2(Engineering Sample)
Product Description	Operation Frequency:	125KHz
	Modulation Type:	RFID
	Antenna Type:	Inductive loop coil Antenna
	Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.3. Auxiliary Equipment Used During Test

Adapter	:	Manufacturer: ZTE M/N: STC-A2050I1000USBA-C S/N: 201202102100876 Input: 100-240V~50/60Hz 0.3A Output: DC 5V, 1000mA

1.4. Description of Test Modes



To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode

1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 05, 2018	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 05, 2018	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 05, 2018	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 05, 2018	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 05, 2018	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 19, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 19, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 19, 2018	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Nov. 20, 2018	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Nov. 05, 2018	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 05, 2018	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 05, 2018	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 05, 2018	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 05, 2018	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 05, 2018	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Apr. 02, 2018	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Nov. 01, 2018	1 Year

1.7. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS
Part 15.203	Antenna Requirement	PASS


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
5MHz~30MHz	60	50	

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 240V, 60Hz for adapter
 Comment: Live Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2020	32.16	19.90	52.06	63.52	-11.46	QP	
2	0.2020	13.23	19.90	33.13	53.52	-20.39	AVG	
3	0.3100	27.02	19.89	46.91	59.97	-13.06	QP	
4	0.4060	6.71	19.94	26.65	47.73	-21.08	AVG	
5	0.4660	17.43	19.96	37.39	56.58	-19.19	QP	
6	0.6220	6.62	20.02	26.64	46.00	-19.36	AVG	
7	0.6300	17.90	20.02	37.92	56.00	-18.08	QP	
8	0.9380	15.64	20.10	35.74	56.00	-20.26	QP	
9	1.1940	4.52	20.12	24.64	46.00	-21.36	AVG	
10	1.6100	3.60	20.13	23.73	46.00	-22.27	AVG	
11	1.6980	15.55	20.13	35.68	56.00	-20.32	QP	
12	2.1180	3.51	20.14	23.65	46.00	-22.35	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 240V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1940	34.08	19.90	53.98	63.86	-9.88	QP	
2	0.2620	27.41	19.89	47.30	61.36	-14.06	QP	
3	0.2700	9.87	19.89	29.76	51.12	-21.36	AVG	
4	0.3899	22.73	19.93	42.66	58.06	-15.40	QP	
5	0.3980	6.36	19.93	26.29	47.89	-21.60	AVG	
6	0.6060	7.09	20.01	27.10	46.00	-18.90	AVG	
7	0.6220	22.86	20.02	42.88	56.00	-13.12	QP	
8	1.1340	21.96	20.12	42.08	56.00	-13.92	QP	
9	1.1340	5.72	20.12	25.84	46.00	-20.16	AVG	
10	1.5980	4.24	20.13	24.37	46.00	-21.63	AVG	
11	1.7100	22.97	20.13	43.10	56.00	-12.90	QP	
12	2.0140	4.15	20.14	24.29	46.00	-21.71	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Live Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1500	34.79	19.90	54.69	65.99	-11.30	QP	
2	0.1500	13.66	19.90	33.56	55.99	-22.43	AVG	
3	0.2060	30.25	19.90	50.15	63.36	-13.21	QP	
4	0.2140	9.58	19.90	29.48	53.04	-23.56	AVG	
5	0.3500	19.68	19.91	39.59	58.96	-19.37	QP	
6	0.3660	5.51	19.92	25.43	48.59	-23.16	AVG	
7	0.5700	15.52	20.00	35.52	56.00	-20.48	QP	
8	0.6340	1.99	20.02	22.01	46.00	-23.99	AVG	
9	1.0100	14.92	20.12	35.04	56.00	-20.96	QP	
10	1.0820	1.20	20.12	21.32	46.00	-24.68	AVG	
11	2.0660	14.79	20.14	34.93	56.00	-21.07	QP	
12	2.0820	0.97	20.14	21.11	46.00	-24.89	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1500	34.25	19.90	54.15	65.99	-11.84	QP	
2	0.1500	16.33	19.90	36.23	55.99	-19.76	AVG	
3	0.1980	28.69	19.90	48.59	63.69	-15.10	QP	
4	0.2140	9.66	19.90	29.56	53.04	-23.48	AVG	
5	0.5180	4.86	19.99	24.85	46.00	-21.15	AVG	
6	0.5980	19.29	20.01	39.30	56.00	-16.70	QP	
7	0.8580	4.07	20.08	24.15	46.00	-21.85	AVG	
8	1.1019	18.31	20.12	38.43	56.00	-17.57	QP	
9	1.3940	2.92	20.13	23.05	46.00	-22.95	AVG	
10	1.7900	18.13	20.14	38.27	56.00	-17.73	QP	
11	1.8020	2.83	20.14	22.97	46.00	-23.03	AVG	
12	2.1340	16.31	20.14	36.45	56.00	-19.55	QP	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.


4.4. Test Data

PASS

Test Results

(Between 9KHz – 30MHz)

Job No.:	SZAWW181109005-01	Power Source:	AC 120V, 60Hz for adapter
Standard:	FCC PART15 C _3m	Temp.(C)/Hum.(%RH):	24.7°C/51%RH
Test item:	Radiation Test	Distance:	3m
Test Mode:	Mode 1		




Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	degree (dgc)
0.0371	-14.65	19.28	2.53	0	7.16	136.09	-128.93	Peak	127
0.0371	37.39	19.28	2.53	0	59.20	116.09	-56.89	AV	127
0.0792	41.46	19.53	2.59	0	63.58	129.54	-65.96	Peak	254
0.0792	32.23	19.53	2.59	0	54.35	109.54	-55.19	AV	254
0.1250	70.49	19.30	2.54	0	92.33	125.60	-33.27	Peak	89
0.1250	62.64	19.30	2.54	0	84.48	105.60	-21.12	AV	89
0.2500	52.24	19.53	2.59	0	74.36	119.61	-45.25	Peak	328
0.2500	44.45	19.53	2.59	0	66.57	99.61	-33.04	AV	328
0.3750	45.80	19.53	2.59	0	67.92	116.11	-48.19	Peak	220
0.3750	36.51	19.53	2.59	0	58.63	96.11	-37.48	AV	220
0.5540	26.98	20.34	2.59	0	49.91	72.73	-22.82	QP	103

Remark: According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.


(Between 30MHz -1000 MHz)

Job No.:	SZAWW181109005-01	Polarization:	Horizontal
Standard:	FCC PART15 C _3m	Power Source:	AC 120V, 60Hz for adapter
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.7°C/54%RH
Test Mode:	Mode 1	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	56.9912	35.78	-17.83	17.95	40.00	-22.05	QP	300	360	
2	95.0930	40.23	-22.20	18.03	43.50	-25.47	QP	300	223	
3	125.0066	41.90	-22.53	19.37	43.50	-24.13	QP	300	121	
4	248.5519	49.17	-18.96	30.21	46.00	-15.79	QP	300	0	
5	330.1949	41.73	-15.47	26.26	46.00	-19.74	QP	300	93	
6	401.8385	39.93	-12.82	27.11	46.00	-18.89	QP	300	25	

Job No.: SZAWW181109005-01 **Polarization:** Vertical
Standard: FCC PART15 C _3m **Power Source:** AC 120V, 60Hz for adapter
Test item: Radiation Test **Temp.(C)/Hum.(%RH):** 24.7°C/54%RH
Test Mode: Mode 1 **Distance:** 3m




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.1272	42.53	-15.47	27.06	40.00	-12.94	QP	300	0	
2	55.4147	38.24	-16.75	21.49	40.00	-18.51	QP	300	77	
3	126.3286	36.36	-17.27	19.09	43.50	-24.41	QP	300	141	
4	210.0482	32.53	-15.59	16.94	43.50	-26.56	QP	300	242	
5	249.4250	33.88	-14.54	19.34	46.00	-26.66	QP	300	342	
6	332.5187	34.89	-14.34	20.55	46.00	-25.45	QP	300	360	

Job No.:	SZAWW181109005-01	Polarization:	Horizontal
Standard:	FCC PART15 C _3m	Power Source:	AC 240V, 60Hz for adapter
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.7°C/54%RH
Test Mode:	Mode 1	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	66.0342	35.98	-20.28	15.70	40.00	-24.30	QP	300	0	
2	112.5244	39.36	-21.80	17.56	43.50	-25.94	QP	300	98	
3	246.8149	49.22	-18.87	30.35	46.00	-15.65	QP	300	122	
4	324.4561	41.27	-15.80	25.47	46.00	-20.53	QP	300	176	
5	394.8545	39.99	-13.02	26.97	46.00	-19.03	QP	300	254	
6	560.6928	34.18	-11.13	23.05	46.00	-22.95	QP	300	360	

Job No.: SZAWW181109005-01 **Polarization:** Vertical
Standard: FCC PART15 C _3m **Power Source:** AC 240V, 60Hz for adapter
Test item: Radiation Test **Temp.(C)/Hum.(%RH):** 24.7°C/54%RH
Test Mode: Mode 1 **Distance:** 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	34.1561	44.02	-16.34	27.68	40.00	-12.32	QP	300	0	
2	43.2017	36.06	-14.31	21.75	40.00	-18.25	QP	300	54	
3	53.8818	38.39	-16.70	21.69	40.00	-18.31	QP	300	96	
4	66.2662	43.54	-19.36	24.18	40.00	-15.82	QP	300	188	
5	125.4457	41.12	-17.14	23.98	43.50	-19.52	QP	300	241	
6	209.3129	39.17	-15.61	23.56	43.50	-19.94	QP	300	360	


5. Antenna Requirement

5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard

5.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement






Photo of Radiation Emission Test





APPENDIX II -- EXTERNAL PHOTOGRAPH
















APPENDIX III -- INTERNAL PHOTOGRAPH









----- End of Report -----