

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: WQ8MAXIFLASHULTRA

### EUT Specification

EUT	Vehicle Communication Interface
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz (BT 2.1 EDR)
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5\text{mW/cm}^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1\text{mW/cm}^2$ )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	15.81 dBm (0.0381W) for Wifi 17.805 dBm (0.0603W) for BT
<b>Antenna gain (Max)</b>	BT 2.1+EDR: 0 dBi 2.4G WIFI: 1 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in  $\text{mW/cm}^2$

$P_{out}$ =output power to antenna in  $\text{Mw}$

$G$ = gain of antenna in linear scale

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Operating Mode	Channel Frequency (MHz)	Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm ( $\text{mW/cm}^2$ )	Power density Limits ( $\text{mW/cm}^2$ )
802.11b	2412	15.26	15.26±1	16.26	1	0.0106	1
	2437	15.81	15.81±1	16.81	1	0.0120	1
	2462	15.47	15.47±1	16.47	1	0.0111	1
802.11g	2412	13.63	13.63±1	14.63	1	0.0073	1
	2437	13.08	13.08±1	14.08	1	0.0064	1
	2462	12.95	12.95±1	13.95	1	0.0062	1
802.11n (HT20)	2412	12.42	12.42±1	13.42	1	0.0055	1
	2437	12.82	12.82±1	13.82	1	0.0060	1
	2462	11.81	11.81±1	12.81	1	0.0048	1
BT 2.1 EDR	2402	17.318	17.318±1	18.318	0	0.0135	1
	2441	17.464	17.464±1	18.464	0	0.0140	1
	2480	17.805	17.805±1	18.805	0	0.0151	1
	2402	17.251	17.251±1	18.251	0	0.0133	1
	2441	17.548	17.548±1	18.548	0	0.0142	1
	2480	17.027	17.027±1	18.027	0	0.0126	1