

Shenzhen Huatongwei International Inspection Co., Ltd. 1/F,Bldg 3,Hongfa Hi-tech Industrial Park,Genyu Road,Tianliao,Gongming,Shenzhen,China Phone:86-755-26748019 Fax:86-755-26748089 http://www.szhtw.com.en



TEST REPORT

Report No:	CHTEW19090166	Report verificaiton:		
Project No:	SHT1907074402EW			
FCC ID:	WQ8MAXISYSULTRA			
Applicant's name:	Autel Intelligent Technology (Sorp., Ltd.		
Address:	7th-8th, 10th Floor, Bldg. B1, Zh Nanshan, Shenzhen, China	iiyuan, Xueyuan Rd., Xili,		
Manufacturer	Autel Intelligent Technology Cor	p., Ltd.		
Address	7th-8th, 10th Floor, Bldg. B1, Zh Nanshan, Shenzhen, China	iiyuan, Xueyuan Rd., Xili,		
Factory 1	Autel Intelligent Technology Cor	·p., Ltd.		
Address	6th Floor,Building 1,Yanxiang Z Rd,Guangming New District, Sh Province,China	higu,NO.11 Gaoxin West lenzhen City, Guangdong		
Factory 2	AUTEL VIETNAM COMPANY L	IMITED		
Address	4th Floor, Factory#6, Land#CN1, An Duong Industrial Zone, Hong Phong Township, An Duong County, Hai Phong, VietNam			
Test item description:	ADVANCED DIAGNOSTIC & N	AEASUREMENT SYSTEM		
Trade Mark:	AUTEL			
Model/Type reference:	MaxiSys Ultra			
Listed Model(s)	-			
Standard:	FCC 47 CFR Part2.1093			
	IEEE Std C95.1, 1999 Edition			
Date of receipt of test sample	Sep.17,2019			
Date of testing	Sep.18,2019- Sep.27,2019			
Date of issue	Sep.29,2019			
Result	PASS			
Compiled by (position+printedname+signature):	File administrators:Xiaodong Zh	ao Xiaodong Zheo		
Supervised by		Xigodome Zhan		
(position+printedname+signature):	Test Engineer: Xiaodong Zh	iao		
Approved by				
(position+printedname+signature):	Manager: Hans Hu	1 Jours Free		
Testing Laboratory Name: :	Shenzhen Huatongwei Interna	ational Inspection Co., Ltd		
Address	1/F, Bldg 3, Hongfa Hi-tech Indu Gongming, Shenzhen, China	ustrial Park, Genyu Road, Tianliao,		
Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.				

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	Test Standards and Report version	3
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	Summary	4
2.1.	Client Information	4
2.2.	Product Description	4
<u>3.</u>	Test Environment	5
3.1.	Test laboratory	5
3.2.	Test Facility	5
3.3.		5
<u>4.</u>	Equipments Used during the Test	<u> </u>
<u>5.</u>	Measurement Uncertainty	7
<u>6.</u>	SAR Measurements System Configuration	8
6.1.	SAR Measurement Set-up	8
6.2. 6.3	DASY5 E-TIEID Probe System	9 10
6.4.	Device Holder	10
7.	SAR Test Procedure	11
7.1.	Scanning Procedure	11
7.2.	Data Storage and Evaluation	13
<u>8.</u>	Position of the wireless device in relation to the phantom	15
8.1.	Body-supported device	15
<u>9.</u>	Dielectric Property Measurements & System Check	16
9.1.	Tissue Dielectric Parameters	16
9.2.	System Check	17
<u>10.</u>	SAR Exposure Limits	21
<u>11.</u>	Conducted Power Measurement Results	22
<u>12.</u>	Maximum Tune-up Limit	26
<u>13.</u>	RF Exposure Conditions (Test Configurations)	27
13.1.	Antenna Location	27
13.2.	Standalone SAR test exclusion considerations	28
13.3.	Required Test Configurations	29
<u>14.</u>	SAR Measurement Results	30
<u>15.</u>	Simultaneous Transmission analysis	32
<u>16.</u>	TestSetup Photos	33
<u>17.</u>	External Photos of the EUT	34

1. Test Standards and Report version

1.1. Test Standards

The tests were performed according to following standards:

<u>FCC 47 Part 2.1093</u>: Radiofrequency Radiation Exposure Evaluation:Portable Devices <u>IEEE Std C95.1, 1999 Edition</u>: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz

FCC published RF exposure KDB procedures:

KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz

KDB 865664 D02 RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations

KDB 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies

<u>KDB 248227 D01 802 11 Wi-Fi SAR v02r02:</u> SAR Measurement Proceduresfor802.11 a/b/g Transmitters <u>KDB 616217 D04 SAR for laptop and tablets v01r02:</u> SAR Evaluation Requirements for Laptop, Notebook, Netbook and Tablet Computers

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-09-29	Original

2. <u>Summary</u>

2.1. Client Information

Applicant:	Autel Intelligent Technology Corp., Ltd.	
Address:	7th-8th, 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan, Shenzhen, China	
Manufacturer:	Autel Intelligent Technology Corp., Ltd.	
Address:	7th-8th, 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan, Shenzhen, China	
Factory 1:	Autel Intelligent Technology Corp., Ltd.	
Address:	6th Floor,Building 1,Yanxiang Zhigu,NO.11 Gaoxin West Rd,Guangming New District, Shenzhen City, Guangdong Province,China	
Factory 2:	AUTEL VIETNAM COMPANY LIMITED	
Address:	4th Floor, Factory#6, Land#CN1, An Duong Industrial Zone, Hong Phong Township, An Duong County, Hai Phong, VietNam	

2.2. Product Description

Name of EUT:	ADVANCED DIAGNOSTIC & MEASUREMENT SYSTEM
Trade Mark:	AUTEL
Model No.:	MaxiSys Ultra
Listed Model(s):	-
Power supply:	Rechargeable Li-ion Battery DC3.8V, 18000mAh
Device Category:	Portable
Product stage:	Production unit
RF Exposure Environment:	General Population / Uncontrolled
Maximum SAR Value	
Separation Distance:	Body: 0mm
Max Report SAR Value (1g):	Body: 0.546 W/kg
WIFI 5G	
Operation Band:	U-NII-1
	U-NII-3
Operating Mode:	802.11a
	802.11n(HT20)
	802.11n(HT40)
	802.11ac(VHT20)
	802.11ac(VHT40)
	802.11ac(VHT80)
Antenna Type:	FPC
Remark: 1. The EUT battery must be power	fully charged and checked periodically during the test to ascertain uniform

3. Test Environment

3.1. Test laboratory

Laboratory:Shenzhen Huatongwei International Inspection Co., Ltd. Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

3.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 762235.

IC-Registration No.: 5377A

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Ambient temperature	18 °C to 25 °C
Ambient humidity	30%RH to 70%RH
Air Pressure	950-1050mbar

4. Equipments Used during the Test

Used	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date (YY-MM-DD)	Due date (YY-MM-DD)
•	Data Acquisition Electronics DAEx	SPEAG	DAE4	1549	2019/03/19	2020/03/18
•	E-field Probe	SPEAG	EX3DV4	7494	2019/03/25	2020/03/24
0	Universal Radio Communication Tester	R&S	CMW500	137681	2019/06/27	2020/06/26
• T	issue-equivalent liquids Va	llidation				
•	Dielectric Assessment Kit	SPEAG	DAK-3.5	1267	N/A	N/A
0	Dielectric Assessment Kit	SPEAG	DAK-12	1130	N/A	N/A
•	Network analyzer	Keysight	E5071C	MY46733048	2019/09/21	2020/09/20
• S	ystem Validation					
0	System Validation Antenna	SPEAG	CLA-150	4024	2018/02/21	2021/02/20
0	System Validation Dipole	SPEAG	D450V3	1102	2018/02/23	2021/02/22
0	System Validation Dipole	SPEAG	D750V3	1180	2018/02/07	2021/02/06
0	System Validation Dipole	SPEAG	D835V2	4d238	2018/02/19	2021/02/18
0	System Validation Dipole	SPEAG	D1750V2	1164	2018/02/06	2021/02/05
0	System Validation Dipole	SPEAG	D1900V2	5d226	2018/02/22	2021/02/21
0	System Validation Dipole	SPEAG	D2450V2	1009	2018/02/05	2021/02/04
0	System Validation Dipole	SPEAG	D2600V2	1150	2018/02/05	2021/02/04
•	System Validation Dipole	SPEAG	D5GHzV2	1273	2018/02/21	2021/02/20
•	Signal Generator	R&S	SMB100A	114360	2019/08/15	2020/08/14
•	Power Viewer for Windows	R&S	N/A	N/A	N/A	N/A
•	Power sensor	R&S	NRP18A	101010	2019/08/15	2020/08/14
•	Power sensor	R&S	NRP18A	101011	2019/08/15	2020/08/14
•	Power Amplifier	BONN	BLWA 0160-2M	1811887	2018/11/15	2019/11/14
•	Dual Directional Coupler	Mini-Circuits	ZHDC-10-62-S+	F975001814	2018/11/15	2019/11/14
•	Attenuator	Mini-Circuits	VAT-3W2+	1819	2018/11/15	2019/11/14
•	Attenuator	Mini-Circuits	VAT-10W2+	1741	2018/11/15	2019/11/14

Note:

1. The DAE , Probe and Dipole calibration reference to the Appendix A and Appendix B.

2. Referring to KDB865664 D01, the dipole calibration interval can be extended to 3 years with justificatio. The dipole are also not physically damaged or repaired during the interval.

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be \leq 30%, for a confidence interval of k = 2. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

Therefore, the measurement uncertainty is not required.

6. SAR Measurements System Configuration

6.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, ADconversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

A unit to operate the optical surface detector which is connected to the EOC.

The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.

The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.

DASY5 software and SEMCAD data evaluation software.

Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.

The generic twin phantom enabling the testing of left-hand and right-hand usage.

The device holder for handheld Mobile Phones.

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles allowing to validate the proper functioning of the system.



6.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

• Probe Specification

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB (30 MHz to 10 GHz)
Directivity	± 0.1 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 W/kg; Linearity: ±0.2 dB (noise: typically <1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 6 GHz Dosimetry in strong gradient fields Compliance tests of Mobile Phones
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

• Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



6.3. Phantoms

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI isfully compatible with standard and all known tissuesimulating liquids. ELI has been optimized regarding its performance and can beintegrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of thecomplete setup, including all predefined phantom positions and measurementgrids, by teaching three points. The phantom is compatible with all SPEAGdosimetric probes and dipoles.

			-		2
STORAGE NO. NO.	Constants	100 Miles		Ţ	1266666666
No.	1111		Colored a		1010101

ELI4 Phantom

6.4. Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the DASY system.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.



Device holder supplied by SPEAG

7. SAR Test Procedure

7.1. Scanning Procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. ± 5 %.

The "surface check" measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1 mm). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^{\circ}$.)

Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot.Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

Zoom Scan

After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm.

Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space.

They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

able 1. Area and 20011 Scan Resolutions per 1 CC RDB Fubication 003004 D01704					
			\leq 3 GHz	> 3 GHz	
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		$5 \text{ mm} \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \hat{o} \cdot \ln(2) \text{ mm} \pm 0.5 \text{ mm}$		
Maximum probe angle surface normal at the r	e from prol neasureme	be axis to phantom ent location	$30^{\circ} \pm 1^{\circ}$	$20^{\circ} \pm 1^{\circ}$	
			$\leq 2 \text{ GHz:} \leq 15 \text{ mm}$ 2 – 3 GHz: $\leq 12 \text{ mm}$	$\begin{array}{l} 3-4 \ \mathrm{GHz:} \leq 12 \ \mathrm{mm} \\ 4-6 \ \mathrm{GHz:} \leq 10 \ \mathrm{mm} \end{array}$	
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.			
Maximum zoom scan	spatial res	olution: Δx_{Zoom} , Δy_{Zoom}	$\leq 2 \text{ GHz:} \leq 8 \text{ mm}$ 2 - 3 GHz: $\leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz:} \le 5 \text{ mm}^*$ $4 - 6 \text{ GHz:} \le 4 \text{ mm}^*$	
	uniform grid: $\Delta z_{Zoom}(n)$		\leq 5 mm	$3-4 \text{ GHz:} \le 4 \text{ mm}$ $4-5 \text{ GHz:} \le 3 \text{ mm}$ $5-6 \text{ GHz:} \le 2 \text{ mm}$	
Maximum zoom scan spatial resolution, normal to phantom surface	graded	$\Delta z_{Z_{com}}(1)$: between 1 st two points closest to phantom surface	\leq 4 mm	$3 - 4 \text{ GHz:} \le 3 \text{ mm}$ $4 - 5 \text{ GHz:} \le 2.5 \text{ mm}$ $5 - 6 \text{ GHz:} \le 2 \text{ mm}$	
Δz _{Zoom} (between points		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1) \text{ mm}$		
Minimum zoom scan volume	x, y, z		≥ 30 mm	$\begin{array}{l} 3-4 \text{ GHz:} \geq 28 \text{ mm} \\ 4-5 \text{ GHz:} \geq 25 \text{ mm} \\ 5-6 \text{ GHz:} \geq 22 \text{ mm} \end{array}$	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium: see IEEE Std					

Table 1: Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v04

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.

* When zoom scan is required and the <u>reported</u> SAR from the *area scan based 1-g SAR estimation* procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.2. Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors),s together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [W/kg], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	Sensitivity:	Normi, ai0, ai1, ai2
·	Conversion factor:	ConvFi
	Diode compression point:	Dcpi
Device parameters:	Frequency:	f
-	Crest factor:	cf
Media parameters:	Conductivity:	σ
	Density:	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

 $V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$

ы

Vi: compensated signal of channel (i = x, y, z)

Ui: input signal of channel (i = x, y, z)

cf: crest factor of exciting field (DASY parameter)

dcpi: diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E – fieldprobes :
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

fieldprobes : $H_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$

II = heaprobes :
$$H_i = \sqrt{V_i}$$
Vi:compensated signal of channel (i = x, y, z)Normi:sensor sensitivity of channel (i = x, y, z),
[mV/(V/m)2] for E-field ProbesConvF:sensitivity enhancement in solutionaij:sensor sensitivity factors for H-field probesf:carrier frequency [GHz]Ei:electric field strength of channel i in V/mHi:magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

- SAR: local specific absorption rate in W/kg
- Etot: total field strength in V/m
- σ: conductivity in [mho/m] or [Siemens/m]
- ρ: equivalent tissue density in g/cm3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

8. <u>Position of the wireless device in relation to the phantom</u>

8.1. Body-supported device

Other devices that fall into this category include tablet type portable computers and credit card transaction authorisation terminals, point-of-sale and/or inventory terminals. Where these devices may be torso or limb-supported, the same principles for body-supported devices are applied.



b) Tablet form factor portable computer

9. Dielectric Property Measurements & System Check

9.1. Tissue Dielectric Parameters

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C

and within $\pm 2^{\circ}$ C of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3-4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

The dielectric constant (ε_r) and conductivity (σ) of typical tissue-equivalent media recipes are expected to be within \pm 5% of the required target values; but for SAR measurement systems that have implemented the SAR error compensation algorithms documented in IEEE Std 1528-2013, to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, the tolerance for ε_r and σ may be relaxed to \pm 10%. This is limited to frequencies \leq 3 GHz.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Tissue dielectric parameters for head and Body phantoms				
Target Frequency Body				
(MHz)	εr σ(s/m)			
5200	49.01	5.299		
5800	5800 48.20 6.000			

Dielectric Property Measurements Results:

Dielectric performance of Body tissue simulating liquid									
Frequency (MHz)	٤r		σ(s/m)		Delta	Delta		Temp	5.4
	Target	Measured	Target	Measured	(ɛr)	(σ)	Limit	(°C)	Date
5200	49.01	49.06	5.299	5.366	0.10%	1.26%	±5%	22.5	2019-09-24
5800	48.20	47.54	6.000	6.076	-1.37%	1.27%	±5%	22.5	2019-09-25

9.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0±0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz

and \geq 10.0 cm for measurements > 3 GHz.

- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
 For 5 GHz band The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- The results are normalized to 1 W input power.



System Performance Check Setup



Photo of Dipole Setup

System Check Result:

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within ±10% of the manufacturer calibrated dipole SAR target.

Body											
Frequency		1g SAR		10g SAR			Delta	Delta		Temp	
(MHz)	Target 1W	Normalize to 1W	Measured 100mW	Target 1W	Normalize to 1W	Measured 100mW	(1g) (10	(10g)	Limit	(°C)	Date
5200	73.60	76.20	7.62	20.40	21.70	2.17	3.53%	6.37%	±10%	22.5	2019-09-24
5800	76.50	74.10	7.41	21.10	20.70	2.07	-3.14%	-1.90%	±10%	22.5	2019-09-25

Plots of System Performance Check

SystemPerformanceCheck-Body 5200MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1273 Date:2019-09-24 Communication System: UID 0, A-CW (0); Frequency: 5200 MHz;Duty Cycle: 1:1 Medium parameters used: f = 5200 MHz; σ = 5.366 S/m; ϵ r = 49.063; ρ = 1000 kg/m3 Phantom section: Flat Section Ambient Temperature:22.0°C;Liquid Temperature:21.8°C;

DASY5 Configuration:

- Probe: EX3DV4 SN7494; ConvF(5.11, 5.11, 5.11) @ 5200 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: ELI V8.0 ; Type: QD OVA 004 AA ; Serial: 2078
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm, Pin=100Mw/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm,

dy=1.000 mm Maximum value of SAR (interpolated) = 18.7 W/kg

Head/d=10mm, Pin=100mW/Zoom Scan(8x8x7)/Cube 0: Measurement grid: dx=4mm,

dy=4mm, dz=1.4mm Reference Value = 54.33 V/m; Power Drift = -0.13 dB Peak SAR (extrapolated) = 31.6 W/kg **SAR(1 g) = 7.62 W/kg; SAR(10 g) = 2.17 W/kg** Maximum value of SAR (measured) = 18.3 W/kg



SystemPerformanceCheck-Body 5800MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1273 Date: 2019-09-25 Communication System: UID 0, A-CW (0); Frequency: 5800 MHz;Duty Cycle: 1:1 Medium parameters used: f = 5800 MHz; σ = 6.076 S/m; ϵ r = 47.54; ρ = 1000 kg/m3 Phantom section: Flat Section Ambient Temperature:21.9°C;Liquid Temperature:21.7°C;

DASY5 Configuration:

- Probe: EX3DV4 SN7494; ConvF(4.5, 4.5, 4.5) @ 5800 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: ELI V8.0 ; Type: QD OVA 004 AA ; Serial: 2078
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm, Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm,

dy=1.000 mm Maximum value of SAR (interpolated) = 19.6 W/kg

Head/d=10mm, Pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm,

dy=4mm, dz=1.4mm Reference Value = 56.26 V/m; Power Drift = -0.16 dB Peak SAR (extrapolated) = 36.0 W/kg SAR(1 g) = 7.41 W/kg; SAR(10 g) = 2.07 W/kg Maximum value of SAR (measured) = 19.0 W/kg



0 dB = 19.0 W/kg = 12.79 dBW/kg

10. SAR Exposure Limits

SAR assessments have been made in line with the requirements of part2.1093.

	Limit (W/kg)				
Type Exposure	General Population /	Occupational /			
	Uncontrolled Exposure Environment	Controlled Exposure Environment			
Spatial Average SAR (whole body)	0.08	0.4			
Spatial Peak SAR (1g cube tissue for head and trunk)	1.6	8.0			
Spatial Peak SAR (10g for limb)	4.0	20.0			

Population/Uncontrolled Environments: are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

11. Conducted Power Measurement Results

WLAN Conducted Power

The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures.

SAR testing is not required for OFDM mode(s) when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is \leq 1.2 W/kg.

WIFI 5G U-NII-1(Left ANT1)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		36	5180	9.90				
	802.11ac (VHT20)	40	5200	9.91				
	(11120)	48	5240	10.04				
		36	5180	9.92				
20	802.11n (HT20)	40	5200	9.78				
		48	5240	10.17				
		36	5180	11.03				
	802.11a	40	5200	11.06				
		48	5240	11.26				
	802.11ac	38	5190	4.87				
10	(VHT40)	46	5230	4.87				
40	802.11n	38	5190	4.97				
	(HT40)	46	5230	4.87				
80	802.11ac (VHT80)	42	5210	4.67				

WIFI 5G U-NII-1(Left ANT2)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		36	5180	11.60				
	802.11ac (VHT20)	40	5200	11.43				
	(11120)	48	5240	11.43				
		36	5180	11.44				
20	802.11n (HT20)	40	5200	11.51				
		48	5240	11.60				
		36	5180	11.51				
	802.11a	40	5200	11.55				
		48	5240	11.67				
	802.11ac	38	5190	5.97				
10	(VHT40)	46	5230	6.13				
40	802.11n	38	5190	6.01				
	(HT40)	46	5230	6.10				
80	802.11ac (VHT80)	42	5210	5.76				

WIFI 5G U-NII-1(Right ANT1)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		36	5180	11.47				
	802.11ac (VHT20)	40	5200	11.68				
	(11120)	48	5240	12.03				
		36	5180	11.56				
20	802.11n (HT20)	40	5200	11.77				
		48	5240	11.92				
		36	5180	11.63				
	802.11a	40	5200	11.76				
		48	5240	12.07				
	802.11ac	38	5190	6.62				
40	(VHT40)	46	5230	6.87				
40	802.11n	38	5190	6.65				
	(HT40)	46	5230	6.93				
80	802.11ac (VHT80)	42	5210	6.48				

WIFI 5G U-NII-1(Right ANT2)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		36	5180	11.79				
	802.11ac (VHT20)	40	5200	11.89				
	(11120)	48	5240	12.23				
		36	5180	11.81				
20	802.11n (HT20)	40	5200	11.89				
		48	5240	12.17				
		36	5180	12.01				
	802.11a	40	5200	12.12				
		48	5240	12.30				
	802.11ac	38	5190	6.72				
10	(VHT40)	46	5230	6.93				
40	802.11n	38	5190	6.73				
	(HT40)	46	5230	6.93				
80	802.11ac (VHT80)	42	5210	6.42				

WIFI 5G U-NII-3(Left ANT1)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		149	5745	8.50				
	802.11ac (VHT20)	157	5785	8.40				
	(11120)	165	5825	8.24				
		149	5745	8.39				
20	802.11n (HT20)	157	5785	8.32				
		165	5825	8.26				
		149	5745	8.54				
	802.11a	157	5785	8.31				
		165	5825	8.29				
	802.11ac	151	5755	9.09				
40	(VHT40)	159	5795	8.80				
40	802.11n	151	5755	9.07				
	(HT40)	159	5795	8.82				
80	802.11ac (VHT80)	155	5775	8.58				

WIFI 5G U-NII-3(Left ANT2)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		149	5745	10.26				
	802.11ac (VHT20)	157	5785	10.59				
	(11120)	165	5825	10.62				
		149	5745	9.34				
20	802.11n (HT20)	157	5785	9.13				
		165	5825	9.34				
		149	5745	9.33				
	802.11a	157	5785	9.26				
		165	5825	8.29				
	802.11ac	151	5755	9.74				
10	(VHT40)	159	5795	9.75				
40	802.11n	151	5755	10.07				
	(HT40)	159	5795	9.89				
80	802.11ac (VHT80)	155	5775	9.43				

WIFI 5G U-NII-3(Right ANT1)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		149	5745	10.06				
	802.11ac (VHT20)	157	5785	10.26				
	(11120)	165	5825	10.16				
		149	5745	10.09				
20	802.11n (HT20)	157	5785	10.13				
		165	5825	10.13				
		149	5745	10.27				
	802.11a	157	5785	10.16				
		165	5825	10.17				
	802.11ac	151	5755	10.70				
40	(VHT40)	159	5795	10.70				
40	802.11n	151	5755	10.71				
	(HT40)	159	5795	10.59				
80	802.11ac (VHT80)	155	5775	10.30				

WIFI 5G U-NII-3(Right ANT2)								
Bandwidth	Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)				
		149	5745	10.03				
	802.11ac (VHT20)	157	5785	10.16				
	(11120)	165	5825	10.26				
		149	5745	9.92				
20	802.11n (HT20)	157	5785	10.17				
		165	5825	10.29				
		149	5745	9.90				
	802.11a	157	5785	10.09				
		165	5825	10.28				
	802.11ac	151	5755	10.52				
10	(VHT40)	159	5795	10.75				
40	802.11n	151	5755	10.67				
	(HT40)	159	5795	10.72				
80	802.11ac (VHT80)	155	5775	10.20				

12. Maximum Tune-up Limit

WiFi 5G U-NII-1							
		Maximum Tu	ine-up (dBm)				
Mada		Burst Aver	age Power				
Mode	Le	əft	Right				
	ANT1	ANT2	ANT1	ANT2			
802.11ac(VHT20)	10.50	12.00	12.50	12.50			
802.11n(HT20)	10.50	12.00	12.00	12.50			
802.11a	11.50	12.00	12.50	12.50			
802.11ac(VHT40)	5.00	6.50	7.00	7.00			
802.11n(HT40)	5.00	6.50	7.00	7.00			
802.11ac(VHT80)	5.00	6.00	7.00	7.00			

WiFi 5G U-NII-3									
	Maximum Tune-up (dBm)								
Mada		Burst Aver	age Power						
Mode	Le	eft	Right						
	ANT1	ANT2	ANT1	ANT2					
802.11ac(VHT20)	9.00	11.00	10.50	10.50					
802.11n(HT20)	9.00	9.50	10.50	10.50					
802.11a	9.00	9.50	10.50	10.50					
802.11ac(VHT40)	9.50	10.00	11.00	11.00					
802.11n(HT40)	9.50	10.50	11.00	11.00					
802.11ac(VHT80)	9.00	9.50	10.50	10.50					

Note:

When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

13. RF Exposure Conditions (Test Configurations)

13.1. Antenna Location



13.2. Standalone SAR test exclusion considerations

KDB 447498 with KDB 616217:

a) For 100 MHz to 6 GHz and *test separation distances* \leq 50 mm, the 1-g SAR *test exclusion thresholds* are determined by the following:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance,

mm)] · [$\sqrt{f}(GHz)$] ≤ 3.0 for 1-g SAR

When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.

b) For 100 MHz to 6 GHz and *test separation distances* > 50 mm, the 1-g and 10-g *SAR test exclusion thresholds* are determined by the following :

1) {[Power allowed at *numeric threshold* for 50 mm in step a)] + [(test separation distance - 50 mm)·(f(MHz)/150)]} mW, for 100 MHz to 1500 MHz

2) {[Power allowed at *numeric threshold* for 50 mm in step a)] + [(test separation distance - 50 mm) \cdot 10]} mW, for > 1500 MHz and ≤6 GHz

Tx	Frequency	Output Power			separ	ation distance	s (mm)		Calculated Infeshold Value				
Interface	(MHz)	dBm	mW	Rear	Left	Right	Тор	Bottom	Rear	Left	Right	Тор	Bottom
WIFI 5G U- NII-1 Left ANT1	5240	11.50	14.1	8	7	329	7	248	4.0 MEASURE	4.6 MEASURE	> 50 mm	8.1 MEASURE	> 50 mm
WIFI 5G U- NII-1 Left ANT2	5240	12.00	15.8	5	16	314	48	182	7.3 MEASURE	2.3 EXEMPT	> 50 mm	0.8 EXEMPT	> 50 mm
WIFI 5G U- NII-1 Right ANT1	5240	12.50	17.8	5	316	12	48	184	8.1 MEASURE	> 50 mm	3.4 MEASURE	0.8 EXEMPT	> 50 mm
WIFI 5G U- NII-1 Right ANT2	5240	12.50	17.8	8	332	7	7	248	5.1 MEASURE	> 50 mm	5.8 MEASURE	5.8 MEASURE	> 50 mm
WIFI 5G U- NII-3 Left ANT1	5755	9.50	8.9	8	7	329	7	248	2.7 EXEMPT	3.1 MEASURE	> 50 mm	3.1 MEASURE	> 50 mm
WIFI 5G U- NII-3 Left ANT2	5825	11.00	12.6	5	16	314	48	182	6.1 MEASURE	1.9 EXEMPT	> 50 mm	0.6 EXEMPT	> 50 mm
WIFI 5G U- NII-3 Right ANT1	5745	10.50	11.2	5	316	12	48	184	5.4 MEASURE	> 50 mm	2.2 EXEMPT	0.6 EXEMPT	> 50 mm
WIFI 5G U- NII-3 Right ANT2	5795	11.00	12.6	8	332	7	7	248	3.8 MEASURE	> 50 mm	4.3 MEASURE	4.3 MEASURE	> 50 mm

Antennas \leq 50mm to adjacent edges

Antennas > 50mm to adjacent edges

Тx	Frequency	Output Power			separation distances (mm)				Calculated Threshold Value				
Interface (MHz)	(MHz)	dBm	mW	Rear	Left	Right	Тор	Bottom	Rear	Left	Right	Тор	Bottom
WIFI 5G U- NII-1 Left ANT1	5240	11.50	14.1	8	7	329	7	248	≤ 50mm	≤ 50mm	2856 mW EXEMPT	≤ 50mm	2046 mW EXEMPT
WIFI 5G U- NII-1 Left ANT2	5240	12.00	15.8	5	16	314	48	182	≤ 50mm	≤ 50mm	2706 mW EXEMPT	≤ 50mm	1386 mW EXEMPT
WIFI 5G U- NII-1 Right ANT1	5240	12.50	17.8	5	316	12	48	184	≤ 50mm	2726 mW EXEMPT	≤ 50mm	≤ 50mm	1406 mW EXEMPT
WIFI 5G U- NII-1 Right ANT2	5240	12.50	17.8	8	332	7	7	248	≤ 50mm	2886 mW EXEMPT	≤ 50mm	≤ 50mm	2046 mW EXEMPT
WIFI 5G U- NII-3 Left ANT1	5755	9.50	8.9	8	7	329	7	248	≤ 50mm	≤ 50mm	2853 mW EXEMPT	≤ 50mm	2043 mW EXEMPT
WIFI 5G U- NII-3 Left ANT2	5825	11.00	12.6	5	16	314	48	182	≤ 50mm	≤ 50mm	2702 mW EXEMPT	≤ 50mm	1382 mW EXEMPT
WIFI 5G U- NII-3 Right ANT1	5745	10.50	11.2	5	316	12	48	184	≤ 50mm	2723 mW EXEMPT	≤ 50mm	≤ 50mm	1403 mW EXEMPT
WIFI 5G U- NII-3 Right ANT2	5795	11.00	12.6	8	332	7	7	248	≤ 50mm	2882 mW EXEMPT	≤ 50mm	≤ 50mm	2042 mW EXEMPT

13.3. Required Test Configurations

The table below identifies the standalone test configurations required for this device according to the findings in Section 13.2:

Test Configurations	Rear	Left	Right	Тор	Bottom
WIFI 5G U-NII-1 Left ANT1	Yes	Yes	No	Yes	No
WIFI 5G U-NII-1 Left ANT2	Yes	No	No	No	No
WIFI 5G U-NII-1 Roght ANT1	Yes	No	Yes	No	No
WIFI 5G U-NII-1 Roght ANT2	Yes	No	Yes	Yes	No
WIFI 5G U-NII-3 Left ANT1	No	Yes	No	Yes	No
WIFI 5G U-NII-3 Left ANT2	Yes	No	No	No	No
WIFI 5G U-NII-3 Roght ANT1	Yes	No	No	No	No
WIFI 5G U-NII-3 Roght ANT2	Yes	No	Yes	Yes	No

14. SAR Measurement Results

SAR Test Reduction criteria are as follows:

- Reported SAR(W/kg) for WWAN = Measured SAR *Tune-up Scaling Factor
- Reported SAR(W/kg) for Wi-Fi and Bluetooth = Measured SAR * Tune-up scaling factor * Duty Cycle scaling factor
- Duty Cycle scaling factor = 1 / Duty cycle (%)

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- \leq 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is \leq 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- \leq 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is \geq 200 MHz

KDB 248227 D01 SAR meas for 802.11:

When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- a) ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- b) > 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions are tested.
 - For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
 When it is unclear, all equivalent conditions must be tested.
- c) For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required test channels are considered.
 - The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- d) When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is ≤ 1.2 W/kg, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.
- e) When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is ≤ 1.2 W/kg, testing for the band with the lower specified output power is not required; otherwise test the remaining bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the Maximum Value of SAR (measured). The position that produced the highest Maximum Value of SAR is considered the worst case position; thus used as the initial test position.

	WiFi 5G U-NII-1														
Modo	Test	Frequency		Conducted	Tune-	Tune- up	Duty	Duty Cycle	Power Drift	Measured SAR(1g)	Report SAR(1g)	Plot			
	Position	СН	MHz	(dBm)	(dBm)	scaling factor	Cycle	Scaling Factor	(dB)	(W/kg)	(W/kg)	No.			
	Rear	48	5240	11.26	11.50	1.057	95.50%	1.047	-0.12	0.415	0.459	-			
802.11a	Left	48	5240	11.26	11.50	1.057	95.50%	1.047	0.06	0.121	0.134	-			
Long and the	Тор	48	5240	11.26	11.50	1.057	95.50%	1.047	0.13	0.307	0.340	-			
802.11a Left ANT2	Rear	48	5240	11.67	12.00	1.079	95.50%	1.047	-0.07	0.104	0.117	-			
802.11a	Rear	48	5240	12.07	12.50	1.104	95.50%	1.047	0.01	0.117	0.135	-			
Right ANT1	Right	48	5240	12.07	12.50	1.104	95.50%	1.047	0.12	0.073	0.084	-			
	Rear	48	5240	12.30	12.50	1.047	95.50%	1.047	-0.14	0.498	0.546	1			
802.11a Right ANT2	Right	48	5240	12.30	12.50	1.047	95.50%	1.047	0.09	0.176	0.193	-			
RIGHT ANT 2	Тор	48	5240	12.30	12.50	1.047	95.50%	1.047	0.14	0.219	0.240	-			

	WiFi 5G U-NII-3													
Mode	Test Position	Frequency		Conducted	Tune-	e- up	Duty	Duty Cycle	Power Drift	Measured	Report	Plot		
Mode		СН	MHz	(dBm)	(dBm)	scaling factor	Cycle	Scaling Factor	(dB)	(W/kg)	(W/kg)	No.		
802.11n	Left	151	5755	9.07	9.50	1.104	94.60%	1.057	0.07	0.098	0.114	-		
Left ANT1	Тор	151	5755	9.07	9.50	1.104	94.60%	1.057	0.16	0.277	0.323	-		
802.11ac (VHT20) Left ANT2	Rear	165	5825	10.62	11.00	1.091	94.60%	1.057	-0.12	0.099	0.114	-		
802.11a Right ANT1	Rear	149	5745	10.27	10.50	1.054	94.60%	1.057	0.09	0.145	0.162	-		
802.11n (HT40) Right ANT2	Rear	159	5795	10.72	11.00	1.067	94.60%	1.057	-0.07	0.446	0.503	2		
	Right	159	5795	10.72	11.00	1.067	94.60%	1.057	0.03	0.131	0.148	-		
	Тор	159	5795	10.72	11.00	1.067	94.60%	1.057	0.11	0.206	0.232	-		

SAR Test Data Plots to the Appendix A.

15. Simultaneous Transmission analysis

No.	Simultaneous Transmission Configurations	Body	Note
1	WiFi(Left ANT1+Left ANT2+Right ANT1+Right ANT2)	Yes	

General note:

The reported SAR summation is calculated based on the same configuration and test position.

	Left WIFI+Right WIFI												
Dond	Exposure	Le	eft	Ri	Summed								
Danu	Position	ANT1	ANT2	ANT1	ANT2	(W/kg)							
	Rear	0.459	0.117	0.135	0.546	1.257							
	Left	0.134	-	-	-	0.134							
WIFI 5G U-NII-1	Right	-	-	0.084	0.193	0.277							
•••••	Тор	0.340	-	-	0.240	0.580							
	Bottom	-	-	-	-	-							
	Rear	-	0.114	0.162	0.503	0.779							
	Left	0.114	-	-	-	0.114							
WIFI 5G U-NII-3	Right	-	-	-	0.148	0.148							
	Тор	0.323	-	-	0.232	0.555							
	Bottom	-	-	-	-	-							

16. TestSetup Photos



17. External Photos of the EUT



Shenzhen Huatongwei International Inspection Co., Ltd.



-----End of Report------