

## FCC Test Report

**Report No.:** RFBHLU-WTW-P22010749-1

**FCC ID:** WQJ-VP3300BT

**Test Model:** IDMR-BT93133PV2D

**Series Model:** IDMR-BT93133XXXXXX (refer to item 3.1 for more details)

**Received Date:** Jan. 21, 2022

**Test Date:** Mar. 09 ~ Mar. 10, 2022

**Issued Date:** Mar. 25, 2022

**Applicant:** ID TECH

**Address:** 10721 Walker St. Cypress, CA 90630

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location (1):** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan

**Test Location (2):** No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan

**FCC Registration /** 788550 / TW0003

**Designation Number:** 281270 / TW0032



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

|  |           |
|--|-----------|
| <b>Release Control Record .....</b>                              | <b>3</b>  |
| <b>1 Certificate of Conformity .....</b>                         | <b>4</b>  |
| <b>2 Summary of Test Results.....</b>                            | <b>5</b>  |
| 2.1 Measurement Uncertainty.....                                 | 5         |
| 2.2 Modification Record .....                                    | 5         |
| <b>3 General Information .....</b>                               | <b>6</b>  |
| 3.1 General Description of EUT .....                             | 6         |
| 3.2 Description of Test Modes.....                               | 8         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....     | 8         |
| 3.3 Description of Support Units .....                           | 10        |
| 3.3.1 Configuration of System under Test .....                   | 10        |
| 3.4 General Description of Applied Standards and references..... | 10        |
| <b>4 Test Types and Results .....</b>                            | <b>11</b> |
| 4.1 Radiated Emission Measurement.....                           | 11        |
| 4.1.1 Limits of Radiated Emission Measurement .....              | 11        |
| 4.1.2 Test Instruments .....                                     | 12        |
| 4.1.3 Test Procedures.....                                       | 13        |
| 4.1.4 Deviation from Test Standard .....                         | 13        |
| 4.1.5 Test Set Up .....  | 13        |
| 4.1.6 EUT Operating Conditions.....                              | 14        |
| 4.1.7 Test Results .....   | 15        |
| 4.2 Conducted Emission Measurement.....                          | 26        |
| 4.2.1 Limits of Conducted Emission Measurement .....             | 26        |
| 4.2.2 Test Instruments .....                                     | 26        |
| 4.2.3 Test Procedures.....                                       | 27        |
| 4.2.4 Deviation from Test Standard .....                         | 27        |
| 4.2.5 Test Setup.....  | 27        |
| 4.2.6 EUT Operating Conditions.....                              | 27        |
| 4.2.7 Test Results .....   | 28        |
| 4.3 Frequency Stability .....                                    | 30        |
| 4.3.1 Limits of Frequency Stability Measurement .....            | 30        |
| 4.3.2 Test Setup.....  | 30        |
| 4.3.3 Test Instruments .....                                     | 30        |
| 4.3.4 Test Procedure .....                                       | 30        |
| 4.3.5 Deviation from Test Standard .....                         | 30        |
| 4.3.6 EUT Operating Conditions.....                              | 30        |
| 4.3.7 Test Results .....   | 31        |
| 4.4 20 dB Bandwidth.....   | 32        |
| 4.4.1 Limits of 20 dB Bandwidth Measurement.....                 | 32        |
| 4.4.2 Test Setup.....  | 32        |
| 4.4.3 Test Instruments .....                                     | 32        |
| 4.4.4 Test Procedures.....                                       | 32        |
| 4.4.5 Deviation from Test Standard .....                         | 32        |
| 4.4.6 EUT Operating Conditions.....                              | 32        |
| 4.4.7 Test Results .....   | 33        |
| <b>5 Pictures of Test Arrangements.....</b>                      | <b>34</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b>  | <b>35</b> |

### Release Control Record

| Issue No.              | Description      | Date Issued   |
|------------------------|------------------|---------------|
| RFBHLU-WTW-P22010749-1 | Original Release | Mar. 25, 2022 |

## 1 Certificate of Conformity

**Product:** ViVOpay VP3300BT

**Brand:** ID TECH

**Test Model:** IDMR-BT93133PV2D

**Series Model:** IDMR-BT93133XXXXXXX (refer to item 3.1 for more details)

**Sample Status:** Engineering Sample

**Applicant:** ID TECH

**Test Date:** Mar. 09 ~ Mar. 10, 2022

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.225)  
47 CFR FCC Part 15, Subpart C (Section 15.215)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Lena Wang, **Date:** Mar. 25, 2022  
Lena Wang / Specialist

**Approved by :** Jeremy Lin, **Date:** Mar. 25, 2022  
Jeremy Lin / Project Engineer

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.225, 15.215) |  |        |   |
|--|--|--------|---|
| FCC Clause   | Test Item  | Result | Remarks   |
| 15.207   | Conducted emission test  | Pass   | Meet the requirement of limit. Minimum passing margin is -5.98 dB at 0.43400 MHz. |
| 15.225 (a)   | The field strength of any emissions within the band 13.553-13.567 MHz                        | Pass   | Meet the requirement of limit. Minimum passing margin is -48.33 dB at 13.560 MHz. |
| 15.225 (b)   | The field strength of any emissions within the bands 13.410-13.553 MHz and 13.567-13.710 MHz | Pass   | Meet the requirement of limit.  |
| 15.225 (c)   | The field strength of any emissions within the bands 13.110-13.410 MHz and 13.710-14.010 MHz | Pass   | Meet the requirement of limit.  |
| 15.225 (d)   | The field strength of any emissions appearing outside of the 13.110-14.010 MHz band          | Pass   | Meet the requirement of limit. Minimum passing margin is -8.67 dB at 599.39 MHz.  |
| 15.225 (e)   | The frequency tolerance  | Pass   | Meet the requirement of limit.  |
| 15.215 (c)   | 20 dB Bandwidth  | Pass   | Meet the requirement of limit.  |
| 15.203   | Antenna Requirement  | Pass   | No antenna connector is used.   |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency        | Expanded Uncertainty (k=2) (±) |
|------------------------------------|------------------|--------------------------------|
| Conducted Emissions at mains ports | 150 kHz ~ 30 MHz | 2.79 dB                        |
| Radiated Emissions up to 1 GHz     | 9kHz ~ 30MHz     | 3.00 dB                        |
|                                    | 30MHz ~ 200MHz   | 2.91 dB                        |
|                                    | 200MHz ~1000MHz  | 2.93 dB                        |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                                 |   |
|---------------------------------|---|
| <b>Product</b>                  | ViVOpay VP3300BT                              |
| <b>Brand</b>                    | ID TECH                                       |
| <b>Test Model</b>               | IDMR-BT93133PV2D                              |
| <b>Series Model</b>             | IDMR-BT93133XXXXXXX                           |
| <b>Model Difference</b>         | Refer to Note as below                        |
| <b>Status of EUT</b>            | Engineering Sample                            |
| <b>Power Supply Rating</b>      | 5.0 Vdc (host equipment)<br>3.7 Vdc (battery) |
| <b>Modulation Type</b>          | ASK   |
| <b>Data Rate</b>                | Type A: 106 kbit/s<br>Type B: 106 kbit/s      |
| <b>Operating Frequency</b>      | 13.56 MHz                                     |
| <b>Field Strength (Maximum)</b> | 35.67 dBuV/m (30m)                            |
| <b>Antenna Type</b>             | Loop Antenna                                  |
| <b>Accessory Device</b>         | Refer to note                                 |
| <b>Data Cable Supplied</b>      | Refer to note                                 |

Note:

##### 1. EUT model definition list.

| Model definition |   | Character | Description                                       |
|------------------|---|-----------|---|
| 1st X            | MSR Encryption                            | blank     | TDES  |
|                  | Method                                    | A         | AES   |
| 2nd X            | MSR Data format                           | blank     | Enhanced  |
|                  |   | O         | Original  |
| 3rd X            | Encryption                                | blank     | N/A   |
|                  |   | P         | Encrypts all transaction methods (MSR, EMV, Ctls) |
| 4th X            | Enclosure color                           | blank     | Black   |
|                  |   | W         | White   |
|                  |   | C         | Custom Color other than Black and White           |
| 5th X            | BT CHIP                                   | V         | Avnet Chip set                                    |
| 6th X            | Firmware version on the AS3911 Rev A Chip | blank     | NEO 1.01  |
|                  |   | 2         | NEO 1.10  |
| 7th X            | Demo Key                                  | blank     | N/A   |
|                  |   | D         | Demo Key injected                                 |

##### 2. The EUT contains following accessory devices.

| Product         | Brand                                   | Model           | Description                       |
|-----------------|---|-----------------|-----------------------------------|
| Micro USB cable | Dong Guan Shen Dong Electronic Co. Ltd. | UB2001021L05736 | 1.15 m shielded cable with 1 core |
| Battery         | YOREX INTERNATIONAL CO., LIMITED        | 701235          | 3.7V, 240mAh, 0.888Wh             |

3. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

One channel was provided to this EUT:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 1       | 13.56           |

#### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable To |     |    |    | Description |
|--------------------|---------------|-----|----|----|-------------|
|                    | RE            | PLC | FS | EB |             |
| -                  | √             | √   | √  | √  | -           |

Where **RE:** Radiated Emission **PLC:** Power Line Conducted Emission  
**FS:** Frequency Stability **EB:** 20 dB Bandwidth measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.

**NOTE:** The EUT had been pre-tested on Type A and Type B data rate. The worst case was Type A. In addition to the fundamental signal test items, type A is selected for the final test.

**NOTE:** "-" means no effect.

#### Radiated Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Axis |
|--------------------|-------------------|----------------|-----------------|------|
| -                  | 1                 | 1              | ASK             | Y    |

#### Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Axis |
|--------------------|-------------------|----------------|-----------------|------|
| -                  | 1                 | 1              | ASK             | Y    |

#### Frequency Stability:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Axis |
|--------------------|-------------------|----------------|-----------------|------|
| -                  | 1                 | 1              | ASK             | Y    |



**20 dB Bandwidth:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Axis |
|--------------------|-------------------|----------------|-----------------|------|
| -                  | 1                 | 1              | ASK             | Y    |

**Test Condition:**

| Applicable To | Environmental Conditions | Input Power    | Tested By |
|---------------|--------------------------|----------------|-----------|
| RE            | 23 deg. C, 68 % RH       | 120 Vac, 60 Hz | Hans Wu   |
| FS            | 25 deg. C, 65 % RH       | 120 Vac, 60 Hz | Hans Wu   |
| PLC           | 25 deg. C, 75 % RH       | 120 Vac, 60 Hz | Hans Wu   |
| EB            | 25 deg. C, 60 % RH       | 120 Vac, 60 Hz | Hans Wu   |

### 3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| No. | Product  | Brand  | Model No.      | Serial No. | FCC ID |
|-----|----------|--------|----------------|------------|--------|
| A   | Notebook | Lenovo | 20J4 MD A003TW | PF-11H9AK  | N/A    |

| No. | Signal Cable Description Of The Above Support Units |
|-----|---|
| 1.  | Micro USB Cable: 1.15m, Provided by client          |

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items A acted as communication partners to transfer data.

#### 3.3.1 Configuration of System under Test



### 3.4 General Description of Applied Standards and references

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

**FCC Part 15, Subpart C (15.225)**

**FCC Part 15, Subpart C (15.215)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance :

KDB 414788 D01 Radiated Test Site v01r01

All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results

### 4.1 Radiated Emission Measurement

#### 4.1.1 Limits of Radiated Emission Measurement

- a. The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- b. Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- c. Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- d. The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209 as below table:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F (kHz)                      | 300                           |
| 0.490 ~ 1.705     | 24000/F (kHz)                     | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

## 4.1.2 Test Instruments

| Description & Manufacturer        | Model No.                              | Serial No.                | Cal. Date     | Cal. Due      |
|-----------------------------------|--|---------------------------|---------------|---------------|
| Test Receiver<br>KEYSIGHT         | N9038B                                 | MY60180018                | Feb. 18, 2022 | Feb. 17, 2023 |
| Spectrum Analyzer<br>KEYSIGHT     | N9020B                                 | MY60110513                | Dec. 24, 2021 | Dec. 23, 2022 |
| BILOG Antenna<br>SCHWARZBECK      | VULB9168                               | 9168-1214                 | Oct. 27, 2021 | Oct. 26, 2022 |
| HORN Antenna<br>RF SPIN           | DRH18-E                                | 210101A18E                | Nov. 14, 2021 | Nov. 13, 2022 |
| HORN Antenna<br>SCHWARZBECK       | BBHA 9170                              | 9170-1049                 | Nov. 14, 2021 | Nov. 13, 2022 |
| Loop Antenna<br>EMCI              | EM-6879                                | 269                       | Sep. 16, 2021 | Sep. 15, 2022 |
| Loop Antenna<br>TESEQ             | HLA 6121                               | 45745                     | Jul. 21, 2021 | Jul. 20, 2022 |
| Preamplifier<br>EMCI              | EMC330N                                | 980798                    | Jan. 17, 2022 | Jan. 16, 2023 |
| Preamplifier<br>EMCI              | EMC118A45SE                            | 980809                    | Dec. 30, 2021 | Dec. 29, 2022 |
| Preamplifier<br>EMCI              | EMC184045SE                            | 980786                    | Jan. 17, 2022 | Jan. 16, 2023 |
| RF signal cable<br>EMCI           | EMC104-SM-SM-<br>(9000+2000+1000)      | 201244+ 201232+<br>210103 | Jan. 17, 2022 | Jan. 16, 2023 |
| RF signal cable<br>EMCI           | EMCCFD400-NM-<br>NM-<br>(9000+300+500) | 201251+ 201249+<br>201248 | Jan. 17, 2022 | Jan. 16, 2023 |
| RF signal cable<br>EMCI           | EMC101G-KM-KM-<br>(5000+3000+2000)     | 201261+201258+20124<br>9  | Jan. 17, 2022 | Jan. 16, 2023 |
| Software<br>BV ADT                | ADT_Radiated_V7.<br>6.15.9.5           | NA                        | NA            | NA            |
| Antenna Tower<br>Max-Full         | MFA-515BSN                             | NA                        | NA            | NA            |
| Turn Table<br>Max-Full            | MFT-201SS                              | NA                        | NA            | NA            |
| Turn Table Controller<br>Max-Full | MF-7802BS                              | MF780208676               | NA            | NA            |

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in WM Chamber 9.

#### 4.1.3 Test Procedures

##### **For Radiated Emission below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz-90 kHz, 110 kHz-490 kHz) set to average detect function and peak detect function.

##### **Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz in the frequency band (9 kHz~150 kHz), and 9 kHz at frequency below 30 MHz (except 9 kHz~150 kHz).
2. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

##### **For Radiated Emission above 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

##### **Note:**



1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard

No deviation.

#### 4.1.5 Test Set Up

##### **<Radiated Emission below 30 MHz>**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### KDB 414788 OFS and Chamber Correlation Justification

- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.
- Open-field site and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

#### 4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

##### Type A


|                        |                     |  |                       |
|------------------------|---------------------|--|-----------------------|
| <b>Test Mode</b>       | Tx                  |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz        | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 13.11MHz ~ 14.01MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |

| Antenna Polarity : Parallel |                 |                               |                |             |                    |                      |                  |                          |
|-----------------------------|-----------------|-------------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                          | Frequency (MHz) | Emission Level (dBuV/m) (30m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                           | *13.560         | 34.58 QP                      | 84.00          | -49.42      | 1.00               | 178                  | 52.57            | -17.99                   |

##### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)




|                        |                     |  |                       |
|------------------------|---------------------|--|-----------------------|
| <b>Test Mode</b>       | Tx                  |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz        | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 13.11MHz ~ 14.01MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |

| Antenna Polarity : Perpendicular |                 |                               |                |             |                    |                      |                  |                          |
|----------------------------------|-----------------|-------------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                               | Frequency (MHz) | Emission Level (dBuV/m) (30m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                | *13.560         | 35.67 QP                      | 84.00          | -48.33      | 1.00               | 46                   | 53.66            | -17.99                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)





|                        |                     |  |                       |
|------------------------|---------------------|--|-----------------------|
| <b>Test Mode</b>       | Tx                  |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz        | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 13.11MHz ~ 14.01MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |


| Antenna Polarity : Ground-parallel |                 |                               |                |             |                    |                      |                  |                          |
|------------------------------------|-----------------|-------------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                 | Frequency (MHz) | Emission Level (dBuV/m) (30m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                  | *13.560         | 24.59 QP                      | 84.00          | -59.41      | 1.00               | 179                  | 42.58            | -17.99                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:




|                        |              |  |                       |
|------------------------|--------------|--|-----------------------|
| <b>Test Mode</b>       | Tx           |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 9kHz ~ 30MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |

| Antenna Polarity : Parallel |                 |                         |                |             |                    |                      |                  |                          |
|-----------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                          | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                           | 3.820           | -6.00 QP                | 29.54          | -35.54      | 1.00               | 18                   | 13.92            | -19.92                   |
| 2                           | 5.470           | -7.73 QP                | 29.54          | -37.27      | 1.00               | 18                   | 11.91            | -19.64                   |
| 3                           | 10.000          | -5.87 QP                | 29.54          | -35.41      | 1.00               | 2                    | 12.23            | -18.10                   |
| 4                           | 18.270          | -2.51 QP                | 29.54          | -32.05      | 1.00               | 99                   | 15.34            | -17.85                   |
| 5                           | 20.670          | 0.82 QP                 | 29.54          | -28.72      | 1.00               | 194                  | 18.63            | -17.81                   |
| 6                           | 27.120          | -1.47 QP                | 29.54          | -31.01      | 1.00               | 110                  | 16.47            | -17.94                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.




|                        |              |  |                       |
|------------------------|--------------|--|-----------------------|
| <b>Test Mode</b>       | Tx           |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 9kHz ~ 30MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |

| Antenna Polarity : Perpendicular |                 |                         |                |              |                    |                      |                  |                          |
|----------------------------------|-----------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| No                               | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB)  | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                | 3.760           | 21.14 QP                | 29.54          | -8.40        | 1.00               | 278                  | 41.06            | -19.92                   |
| <b>2</b>                         | <b>4.240</b>    | <b>22.14 QP</b>         | <b>29.54</b>   | <b>-7.40</b> | <b>1.00</b>        | <b>2</b>             | <b>42.02</b>     | <b>-19.88</b>            |
| 3                                | 6.370           | 13.38 QP                | 29.54          | -16.16       | 1.00               | 2                    | 32.72            | -19.34                   |
| 4                                | 15.990          | 16.60 QP                | 29.54          | -12.94       | 1.00               | 239                  | 34.52            | -17.92                   |
| 5                                | 20.640          | 20.72 QP                | 29.54          | -8.82        | 1.00               | 45                   | 38.53            | -17.81                   |
| 6                                | 27.120          | 6.62 QP                 | 29.54          | -22.92       | 1.00               | 176                  | 24.56            | -17.94                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.




|                        |              |  |                       |
|------------------------|--------------|--|-----------------------|
| <b>Test Mode</b>       | Tx           |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 9kHz ~ 30MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |

| Antenna Polarity : Ground-parallel |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                  | 3.760           | 8.05 QP                 | 29.54          | -21.49      | 1.00               | 18                   | 27.97            | -19.92                   |
| 2                                  | 6.490           | -1.07 QP                | 29.54          | -30.61      | 1.00               | 202                  | 18.22            | -19.29                   |
| 3                                  | 14.850          | 7.13 QP                 | 29.54          | -22.41      | 1.00               | 319                  | 25.08            | -17.95                   |
| 4                                  | 18.270          | -1.00 QP                | 29.54          | -30.54      | 1.00               | 80                   | 16.85            | -17.85                   |
| 5                                  | 20.430          | 9.03 QP                 | 29.54          | -20.51      | 1.00               | 164                  | 26.84            | -17.81                   |
| 6                                  | 26.610          | -8.22 QP                | 29.54          | -37.76      | 1.00               | 49                   | 9.71             | -17.93                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.




|                        |                 |                          |                  |
|------------------------|-----------------|--------------------------|------------------|
| <b>RF Mode</b>         | TX NFC-13.56MHz | <b>Channel</b>           | CH 1 : 13.56 MHz |
| <b>Frequency Range</b> | 30MHz ~ 1GHz    | <b>Detector Function</b> | Quasi-Peak (QP)  |

**Antenna Polarity & Test Distance : Horizontal at 3 m**

| No       | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB)  | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----------|-----------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| 1        | 92.08           | 25.83 QP                | 43.50          | -17.67       | 2.00 H             | 221                  | 49.55            | -23.72                   |
| 2        | 228.85          | 21.57 QP                | 46.00          | -24.43       | 1.01 H             | 271                  | 42.22            | -20.65                   |
| 3        | 363.68          | 25.72 QP                | 46.00          | -20.28       | 1.01 H             | 18                   | 41.70            | -15.98                   |
| <b>4</b> | <b>599.39</b>   | <b>37.33 QP</b>         | <b>46.00</b>   | <b>-8.67</b> | <b>1.51 H</b>      | <b>282</b>           | <b>47.68</b>     | <b>-10.35</b>            |
| 5        | 827.34          | 28.99 QP                | 46.00          | -17.01       | 1.01 H             | 246                  | 36.27            | -7.28                    |
| 6        | 895.24          | 30.95 QP                | 46.00          | -15.05       | 1.01 H             | 240                  | 37.61            | -6.66                    |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




|                        |                 |                          |                  |
|------------------------|-----------------|--------------------------|------------------|
| <b>RF Mode</b>         | TX NFC-13.56MHz | <b>Channel</b>           | CH 1 : 13.56 MHz |
| <b>Frequency Range</b> | 30MHz ~ 1GHz    | <b>Detector Function</b> | Quasi-Peak (QP)  |

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1  | 148.34          | 25.90 QP                | 43.50          | -17.60      | 1.00 V             | 199                  | 44.05            | -18.15                   |
| 2  | 375.32          | 25.47 QP                | 46.00          | -20.53      | 1.00 V             | 210                  | 41.00            | -15.53                   |
| 3  | 429.64          | 22.06 QP                | 46.00          | -23.94      | 1.49 V             | 174                  | 36.29            | -14.23                   |
| 4  | 596.48          | 32.58 QP                | 46.00          | -13.42      | 1.00 V             | 2                    | 43.01            | -10.43                   |
| 5  | 777.87          | 32.69 QP                | 46.00          | -13.31      | 1.99 V             | 2                    | 40.62            | -7.93                    |
| 6  | 933.07          | 29.49 QP                | 46.00          | -16.51      | 1.49 V             | 128                  | 35.19            | -5.70                    |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



**Type B**


|                        |                     |  |                       |
|------------------------|---------------------|--|-----------------------|
| <b>Test Mode</b>       | Tx                  |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz        | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 13.11MHz ~ 14.01MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |

| Antenna Polarity : Parallel |                 |                               |                |             |                    |                      |                  |                          |
|-----------------------------|-----------------|-------------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                          | Frequency (MHz) | Emission Level (dBuV/m) (30m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                           | *13.560         | 34.21 QP                      | 84.00          | -49.79      | 1.00               | 179                  | 52.20            | -17.99                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)




|                        |                     |  |                       |
|------------------------|---------------------|--|-----------------------|
| <b>Test Mode</b>       | Tx                  |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz        | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 13.11MHz ~ 14.01MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |

| Antenna Polarity : Perpendicular |                 |                               |                |             |                    |                      |                  |                          |
|----------------------------------|-----------------|-------------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                               | Frequency (MHz) | Emission Level (dBuV/m) (30m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                | *13.560         | 32.65 QP                      | 84.00          | -51.35      | 1.00               | 93                   | 50.64            | -17.99                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)





|                        |                     |  |                       |
|------------------------|---------------------|--|-----------------------|
| <b>Test Mode</b>       | Tx                  |  |                       |
| <b>RF Mode</b>         | NFC-13.56MHz        | <b>Channel</b>                           | CH 1 : 13.56 MHz      |
| <b>Frequency Range</b> | 13.11MHz ~ 14.01MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |


| Antenna Polarity : Ground-parallel |                 |                               |                |             |                    |                      |                  |                          |
|------------------------------------|-----------------|-------------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                 | Frequency (MHz) | Emission Level (dBuV/m) (30m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                  | *13.560         | 26.56 QP                      | 84.00          | -57.44      | 1.00               | 202                  | 44.55            | -17.99                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. The test distance for 0.49 ~ 30MHz is 3m, extrapolate the measured field strength to a distance of 30 meters.

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-Peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 Test Instruments

| Description & Manufacturer                  | Model No.                | Serial No.     | Date of Calibration | Due Date of Calibration |
|---|--------------------------|----------------|---------------------|-------------------------|
| Test Receiver<br>ROHDE & SCHWARZ            | ESCI                     | 100613         | Dec. 03, 2021       | Dec. 02, 2022           |
| RF signal cable<br>Woken                    | 5D-FB                    | Cable-cond1-01 | Jan. 15, 2022       | Jan. 14, 2023           |
| LISN/AMN<br>ROHDE & SCHWARZ<br>(EUT)        | ENV216                   | 101196         | Apr. 26, 2021       | Apr. 25, 2022           |
| LISN/AMN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100311         | Sep. 07, 2021       | Sep. 06, 2022           |
| Software<br>ADT                             | BV ADT_Cond_<br>V7.3.7.4 | NA             | NA                  | NA                      |

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
  3. The VCCI Site Registration No. is C-12040.

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz - 30 MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



- Note:**
- Support units were connected to second LISN.
  - Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.2.7 Test Results


##### Type A

|                        |                |   |                                      |
|------------------------|----------------|---|--------------------------------------|
| <b>Frequency Range</b> | 150kHz ~ 30MHz | <b>Detector Function &amp; Resolution Bandwidth</b> | Quasi-Peak (QP) / Average (AV), 9kHz |
| <b>Input Power</b>     | 120Vac, 60Hz   | <b>Environmental Conditions</b>                     | 25 °C, 75% RH                        |
| <b>Tested by</b>       | Hans Wu        | <b>Test Date</b>                                    | 2022/3/10                            |

| Phase Of Power : Line (L) |                 |                        |                      |              |                       |              |              |              |               |              |
|---------------------------|-----------------|------------------------|----------------------|--------------|-----------------------|--------------|--------------|--------------|---------------|--------------|
| No                        | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |              | Emission Level (dBuV) |              | Limit (dBuV) |              | Margin (dB)   |              |
|                           |                 |                        | Q.P.                 | AV.          | Q.P.                  | AV.          | Q.P.         | AV.          | Q.P.          | AV.          |
| 1                         | 0.16579         | 9.71                   | 33.34                | 18.97        | 43.05                 | 28.68        | 65.17        | 55.17        | -22.12        | -26.49       |
| <b>2</b>                  | <b>0.43400</b>  | <b>9.76</b>            | <b>33.14</b>         | <b>31.44</b> | <b>42.90</b>          | <b>41.20</b> | <b>57.18</b> | <b>47.18</b> | <b>-14.28</b> | <b>-5.98</b> |
| 3                         | 1.48200         | 9.78                   | 16.02                | 9.60         | 25.80                 | 19.38        | 56.00        | 46.00        | -30.20        | -26.62       |
| 4                         | 4.45800         | 9.81                   | 32.87                | 21.79        | 42.68                 | 31.60        | 56.00        | 46.00        | -13.32        | -14.40       |
| 5                         | 13.56200        | 9.86                   | 27.26                | 26.64        | 37.12                 | 36.50        | 60.00        | 50.00        | -22.88        | -13.50       |
| 6                         | 24.18600        | 9.81                   | 13.85                | 9.23         | 23.66                 | 19.04        | 60.00        | 50.00        | -36.34        | -30.96       |

##### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|                        |                |   |                                      |
|------------------------|----------------|---|--------------------------------------|
| <b>Frequency Range</b> | 150kHz ~ 30MHz | <b>Detector Function &amp; Resolution Bandwidth</b> | Quasi-Peak (QP) / Average (AV), 9kHz |
| <b>Input Power</b>     | 120Vac, 60Hz   | <b>Environmental Conditions</b>                     | 25 °C, 75% RH                        |
| <b>Tested by</b>       | Hans Wu        | <b>Test Date</b>                                    | 2022/3/10                            |

| Phase Of Power : Neutral (N) |                 |                        |                      |       |                       |       |              |       |             |        |
|------------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                           | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                              |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                            | 0.18180         | 9.77                   | 33.62                | 22.88 | 43.39                 | 32.65 | 64.40        | 54.40 | -21.01      | -21.75 |
| 2                            | 0.43370         | 9.82                   | 32.20                | 30.47 | 42.02                 | 40.29 | 57.18        | 47.18 | -15.16      | -6.89  |
| 3                            | 0.72200         | 9.83                   | 12.07                | 7.10  | 21.90                 | 16.93 | 56.00        | 46.00 | -34.10      | -29.07 |
| 4                            | 3.63000         | 9.87                   | 23.21                | 10.23 | 33.08                 | 20.10 | 56.00        | 46.00 | -22.92      | -25.90 |
| 5                            | 13.56200        | 9.97                   | 25.37                | 25.02 | 35.34                 | 34.99 | 60.00        | 50.00 | -24.66      | -15.01 |
| 6                            | 23.43800        | 10.00                  | 17.50                | 12.95 | 27.50                 | 22.95 | 60.00        | 50.00 | -32.50      | -27.05 |

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 Frequency Stability

#### 4.3.1 Limits of Frequency Stability Measurement

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01 % of the operating frequency over a temperature variation of -20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of 20 degrees C.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- Turned the EUT on and coupled its output to a spectrum analyzer.
- Turned the EUT off and set the chamber to the highest temperature specified.
- Allowed sufficient time (approximately 30 min) for the temperature of the chamber to stabilize then turned the EUT on and measured the operating frequency after 2, 5, and 10 minutes.
- Repeated step c and d with the every 10 degrees reduction until the lowest temperature achieved.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85 % to 115 % and the frequency record.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.

4.3.7 Test Results

Type A

| Frequency Stability Versus Temperature |                    |                    |                 |                    |                 |                    |                 |                    |                 |
|--|--------------------|--------------------|-----------------|--------------------|-----------------|--------------------|-----------------|--------------------|-----------------|
| Temp. (°C)                             | Power Supply (Vdc) | 0 Minute           |                 | 2 Minute           |                 | 5 Minute           |                 | 10 Minute          |                 |
|  |                    | Measured Frequency | Frequency Drift | Measured Frequency | Frequency Drift | Measured Frequency | Frequency Drift | Measured Frequency | Frequency Drift |
|  |                    | (MHz)              | %               | (MHz)              | %               | (MHz)              | %               | (MHz)              | %               |
| 50                                     | 5                  | 13.56004           | 0.00029         | 13.56005           | 0.00037         | 13.56004           | 0.00029         | 13.56005           | 0.00037         |
| 40                                     | 5                  | 13.55998           | -0.00015        | 13.55998           | -0.00015        | 13.55998           | -0.00015        | 13.55999           | -0.00007        |
| 30                                     | 5                  | 13.56003           | 0.00022         | 13.56003           | 0.00022         | 13.56003           | 0.00022         | 13.56003           | 0.00022         |
| 20                                     | 5                  | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        |
| 10                                     | 5                  | 13.55998           | -0.00015        | 13.55998           | -0.00015        | 13.55998           | -0.00015        | 13.55998           | -0.00015        |
| 0                                      | 5                  | 13.56002           | 0.00015         | 13.56002           | 0.00015         | 13.56002           | 0.00015         | 13.56001           | 0.00007         |
| -10                                    | 5                  | 13.55995           | -0.00037        | 13.55995           | -0.00037        | 13.55995           | -0.00037        | 13.55994           | -0.00044        |
| -20                                    | 5                  | 13.55997           | -0.00022        | 13.55997           | -0.00022        | 13.55997           | -0.00022        | 13.55997           | -0.00022        |

| Frequency Stability Versus Voltage |                    |                    |                 |                    |                 |                    |                 |                    |                 |
|------------------------------------|--------------------|--------------------|-----------------|--------------------|-----------------|--------------------|-----------------|--------------------|-----------------|
| Temp. (°C)                         | Power Supply (Vdc) | 0 Minute           |                 | 2 Minute           |                 | 5 Minute           |                 | 10 Minute          |                 |
|                                    |                    | Measured Frequency | Frequency Drift | Measured Frequency | Frequency Drift | Measured Frequency | Frequency Drift | Measured Frequency | Frequency Drift |
|                                    |                    | (MHz)              | %               | (MHz)              | %               | (MHz)              | %               | (MHz)              | %               |
| 20                                 | 5.75               | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        |
|                                    | 5                  | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        |
|                                    | 4.25               | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        | 13.55996           | -0.00029        |

#### **4.4 20 dB Bandwidth**

##### 4.4.1 Limits of 20 dB Bandwidth Measurement

The 20 dB bandwidth shall be specified in operating frequency band.

##### 4.4.2 Test Setup

Refer to section 4.1.5.

##### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

##### 4.4.4 Test Procedures

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 Hz RBW and 300 Hz VBW. The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

##### 4.4.5 Deviation from Test Standard

No deviation.

##### 4.4.6 EUT Operating Conditions


- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.



#### 4.4.7 Test Results

#### Type A

| 20 dBc Point (Low) | 20 dBc Point (High) | Operating Frequency Band (MHz) | Pass / Fail |
|--------------------|---------------------|--------------------------------|-------------|
| 13.56038 MHz       | 13.56064 MHz        | 13.553~13.567                  | Pass        |



Note: The signal look like CW signal, so RBW can't be match 1~5 % OBW.

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---