

# CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

# RF EXPOSURE EVALUATION

Applicant : KAONMEDIA Co., Ltd.

Applicant Address : KAONMEDIA Building, 884-3 Seongnam-daero,

Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

Kind of Product : Layer3 TV

Equipment model name

: Client VM3000C

FCC ID : WQTVM3000C

Antenna type : Chip Antenna

Antenna Gain : 1.99 dBi

# CTK Co., Ltd.

# CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

# \*\* MPE Calculations \*\*

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

 $G = Log^{-1}$  (dB antenna gain / 10)

### Power density at the specific separation:

$C = DC/(4D^2\pi)$	Whore
$S = PG/(4R^2\pi)$	Where,
	S = Maximum power density (mW/cm2)
	P = Power input to the antenna (mW)
	G = Numeric power gain of the antenna
	R = Distance to the center of the radiation of the
	antenna
	(20cm = limit for MPE)

The Maximum permissible exposure (MPE) for the general population is 1  $\rm mW/cm^2$ . The power density at 20cm does not exceed the 1  $\rm mW/cm^2$  limit.

#### Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where,
	P = Power input to the antenna (mW)
	G = Numeric power gain of the antenna
	R = Distance to the center of the radiation of the
	antenna
	(20cm = limit for MPE)



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Mode	P (dBm)	P (mW)	G (dBi)	S (mW/cm²)	R (cm)
GFSK	9.50	8.92	1.99	0.0028	20
8-DPSK	9.22	8.35		0.0026	20