

447498 D01 General RF Exposure Guidance v06  
 SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm (Appendix B)

MHz	mm																	
	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190			
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567			
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527			
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554			
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644			
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943			
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998			
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522			
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509			
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496			
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479			
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466			
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465			
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462			

test separation = 76                      idx= 3  
 min separation = 8

MHz	Extrapolated Threshold from table (mW)	Calculated Threshold (mW)	Max mW measured
100	491.2	21.26801873	
150	413	30.81898576	
300	326	58.81507501	
450	302	86.34672817	
835	308.6	156.1031445	
900	314	167.8040562	
1500	382	275.238971	
1900	369	277.150896	
2450	356	279.4756991	99.54054174
3600	339	283.6081124	
5200	326	288.3734199	
5400	325	288.9139145	15.99558029
5800	322	289.9656712	21.62718524

Report	Max dBm	Calculated max mW
EMC88304-FCC247	19.98	99.54054174
EMC88304-FCC407 UNII 1	12.04	15.99558029
EMC88304-FCC407 UNII 3	13.35	21.62718524

Step A 4.3.1 calculated with min separation of 8mm and max power from RF reports	
19.47569906	@ 2450MHz
4.559441888	@ 5200MHz
6.510644913	@ 5800MHz

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f(\text{GHz})]$$

$$\{[\text{Power allowed at numeric threshold for 50 mm in step a}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\} \text{ mW, for 100 MHz to 1500 MHz}$$

$$\{[\text{Power allowed at numeric threshold for 50 mm in step a}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\} \text{ mW, for } > 1500 \text{ MHz and } \leq 6 \text{ GHz}$$