

RF Exposure Report

Report No.: SA191014C06B

FCC ID: WR3SS001XNA

Test Model: SS-001-RUG-NA

Series Model: SS-001-0-NA, SS-001-1-NA, SS-001-2-NA, SS-001-3-NA, SS-002-0-NA,

SS-002-1-NA, SS-002-2-NA, SS-003-0-NA, SS-003-1-NA, SS-003-2-NA

Received Date: Oct. 08, 2020

Test Date: Nov. 18 ~ Dec. 22, 2020

Issued Date: Dec. 23, 2020

Applicant: OMEGA Engineering, Inc.

Address: 800 Connecticut Ave., Suite 5N01, Norwalk, CT 06854, USA.

Manufacturer: Fitivision Technology Inc.

Address: 11494 No. 13-22,2F,Section 6,Minguan East Rd., Neihu District, Taipei

City, Taiwan (R.O.C)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN

FCC Registration / 788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SA191014C06B Page No. 1 / 5 Report Format Version: 6.1.1 Reference No.: 201008C05



Table of Contents

| Rele | Release Control Record | | | |
|------|---|---|--|--|
| 1 | Certificate of Conformity | 4 | | |
| 2 | RF Exposure | 5 | | |
| 2.2 | 1 Limits for Maximum Permissible Exposure (MPE) | 5 | | |
| 3 | Calculation Result Of Maximum Conducted Power | 5 | | |



Release Control Record

| Issue No. | Description | Date Issued |
|--------------|-------------------|---------------|
| SA191014C06B | Original release. | Dec. 23, 2020 |

Report No.: SA191014C06B Reference No.: 201008C05 Page No. 3 / 5 Report Format Version: 6.1.1



1 Certificate of Conformity

Product: Smart Sensor

Brand: OMEGA

Test Model: SS-001-RUG-NA

Series Model: SS-001-0-NA, SS-001-1-NA, SS-001-2-NA, SS-001-3-NA, SS-002-0-NA,

SS-002-1-NA, SS-002-2-NA, SS-003-0-NA, SS-003-1-NA, SS-003-2-NA

Sample Status: Engineering sample

Applicant: fitivision technology Inc.

Test Date: Nov. 18 ~ Dec. 22, 2020

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance: IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Polly Chien / Specialist

Approved by: Dec. 23, 2020

Bruce Chen / Senior Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) | |
|---|----------------------------------|----------------------------------|--|---------------------------|--|
| Limits For General Population / Uncontrolled Exposure | | | | | |
| 300-1500 | | | F/1500 | 30 | |
| 1500-100,000 | | | 1.0 | 30 | |

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result Of Maximum Conducted Power

| Frequency Band (MHz) | Max AV Power (dBm) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm²) |
|----------------------|-----------------------|-----------------------|------------------|-------------------------------------|-------------------|
| 902.4 ~ 927.6 | 22.28 | 2 | 20 | 0.053 | 0.602 |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

| F | N | ח | |
|-------|---|------------------|--|
| _ | | $\boldsymbol{-}$ | |