

Report No. : FR911708B



FCC RADIO TEST REPORT

FCC ID	: WR92221123114
Equipment	: thermostat
Brand Name	: ecobee
Model Name	: ECB402
Applicant	: ecobee Inc. 207 Queens Quay West, Suite 600, Toronto, ON, Canada
Manufacturer	: ecobee Inc. 207 Queens Quay West, Suite 600, Toronto, ON, Canada
Standard	: FCC Part 15 Subpart C §15.247

The product was received on Jan. 17, 2019 and testing was started from Feb. 12, 2019 and completed on Mar. 29, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Page Number: 1 of 36Issued Date: Apr. 18, 2019Report Version: 01



Table of Contents

His	tory o	f this test report	3			
Sur	nmary	of Test Result	4			
1	General Description					
	1.1	Product Feature of Equipment Under Test	5			
	1.2	Modification of EUT	5			
	1.3	Testing Location	5			
	1.4	Applicable Standards	6			
2	Test	Configuration of Equipment Under Test	7			
	2.1	Carrier Frequency Channel	7			
	2.2	Test Mode	8			
	2.3	Connection Diagram of Test System	9			
	2.4	Support Unit used in test configuration and system	9			
	2.5	EUT Operation Test Setup	10			
	2.6	Measurement Results Explanation Example	10			
3	Test	Result	11			
	3.1	6dB and 99% Bandwidth Measurement	11			
	3.2	Output Power Measurement	16			
	3.3	Power Spectral Density Measurement	17			
	3.4	Conducted Band Edges and Spurious Emission Measurement	22			
	3.5	Radiated Band Edges and Spurious Emission Measurement	27			
	3.6	AC Conducted Emission Measurement	31			
	3.7	Antenna Requirements	33			
4	List c	f Measuring Equipment	34			
5	Unce	rtainty of Evaluation	36			
Арј	pendix	A. Conducted Test Results				
Арј	pendix	B. AC Conducted Emission Test Result				
Арј	pendix	C. Radiated Spurious Emission				
Арј	oendix	D. Radiated Spurious Emission Plots				

Appendix E. Duty Cycle Plots

Appendix F. Setup Photographs



History of this test report

Report No.	Version	Description	Issued Date
FR911708B	01	Initial issue of report	Apr. 18, 2019



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	-	
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 3.47 dB at 31.620 MHz
3.6	15.207	AC Conducted Emission Pass		Under limit 22.67 dB at 0.767 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement Pass		-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Elise Chang



1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac., and Proprietary Sensor

Product Specification subjective to this standard				
Antenna Type	WLAN: Ceramic chip Antenna Bluetooth: FPC Antenna			
	Proprietary Sensor: IFA Meander Printed PCB Type Antenna			

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC.				
	No.52, Huaya 1st Rd., Guishan Dist.,				
Test Site Legation	Taoyuan City, Taiwan (R.O.C.)				
	TEL: +886-3-327-3456				
	FAX: +886-3-328-4978				
Toot Site No	Sporton	Site No.			
Test Sile No.	TH05-HY	CO05-HY			
Note: The test site complies with ANSI C63.4 2014 requirement.					
Test Site	SPORTON INTERNATIONAL INC.				
	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist.,				
Toot Site Logation	Taoyuan City, Taiwan (R.O.C.)				
Test Site Location	TEL: +886-3-327-0868				
	FAX: +886-3-327-0855				
Tast Site No	Sporton	Site No.			
Test Sile NO.	03CH13-HY				

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No. TW1190 and TW0007



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- ANSI C63.10-2013

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
2400-2483.5 MHz	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases
Tost Itom	Data Rate / Modulation
lest item	Bluetooth – LE / GFSK
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
Test Cases	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Padiated	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
Test Cases	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC	Mode 1: WI AN (2.4GHz) Link + Bluetooth Link + Sub-gigsbertz on + Infrared on +
Conducted	PEK with Adapter
Emission	



2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	DBT32 N/A N//		Unshielded, 1.8 m
2.	WLAN AP	VLAN AP ASUS RT-AC66U MSQ-RTAC66U N/A		N/A	Unshielded, 1.8 m	
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Adapter	Jameco ADU2400		FCC DoC	N/A	AC I/P: Unshielded, 6 m



2.5 EUT Operation Test Setup

The RF test items, utility "Putty" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)



3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

- 1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) \geq 3 * RBW.
- 6. Measure and record the results in the test report.

3.1.4 Test Setup



EUT

Spectrum Analyzer



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



6 dB Bandwidth Plot on Channel 00

Date: 8.MAR.2019 09:49:14





6 dB Bandwidth Plot on Channel 19

Date: 8.MAR.2019 09:56:24

6 dB Bandwidth Plot on Channel 39



Date: 8.MAR.2019 09:59:59



3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.



99% Bandwidth Plot on Channel 00

Date: 8.MAR.2019 09:52:53





99% Occupied Bandwidth Plot on Channel 19

Date: 8.MAR.2019 09:57:29





Date: 8.MAR.2019 10:02:07

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

- 1. For Average Power, the testing follows the ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

- 1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz.
 Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



Spectrum Analyzer

3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)



PSD 100kHz Plot on Channel 00

Date: 8.MAR.2019 09:50:29

PSD 100kHz Plot on Channel 19



Date: 8.MAR.2019 09:56:46



PSD 100kHz Plot on Channel 39



Date: 8.MAR.2019 10:01:17



3.3.7 Test Result of Power Spectral Density Plots (3kHz)





Date: 8.MAR.2019 09:49:41





Date: 8.MAR.2019 09:56:35



PSD 3kHz Plot on Channel 39



Date: 8.MAR.2019 10:01:06



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

- 1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 8.MAR.2019 09:51:07

High Band Edge Plot on Channel 39



Date: 8.MAR.2019 10:01:30

3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps



GFSK Channel 00

Date: 8.MAR.2019 09:51:33

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 8.MAR.2019 09:51:58



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps



Date: 8.MAR.2019 09:57:05

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 8.MAR.2019 09:57:15



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps



GFSK Channel 39

Date: 8.MAR.2019 10:01:43

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 8.MAR.2019 10:01:54

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency	Field Strength	Measurement Distance		
(MHz)	(microvolts/meter)	(meters)		
0.009 – 0.490	2400/F(kHz)	300		
0.490 – 1.705	24000/F(kHz)	30		
1.705 – 30.0	30	30		
30 – 88	100	3		
88 – 216	150	3		
216 - 960	200	3		
Above 960	500	3		

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

- 1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.



3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



Spectrum Analyzer / Receiver





For radiated emissions above 1GHz

3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of omission (MHz)	Conducted limit (dBµV)			
Frequency of emission (MHZ)	Quasi-peak	Average		
0.15-0.5	66 to 56*	56 to 46*		
0.5-5	56	46		
5-30	60	50		

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.



3.6.4 Test Setup



EUT = Equipment under test ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



List of Measuring Equipment 4

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor	DARE	RadiPower	15I00041S NO09	10MHz~6GHz	May 07, 2018	Feb. 12, 2019~ Mar. 08, 2019	May 06, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV 30	100895	9kHz~30GHz	Apr. 20, 2018	Feb. 12, 2019~ Mar. 08, 2019	Apr. 19, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Apr. 17, 2018	Feb. 12, 2019~ Mar. 08, 2019	Apr. 16, 2019	Conducted (TH05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Mar. 05, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Mar. 05, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 05, 2019	N/A	Conduction (CO05-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Sep. 14, 2018	Mar. 05, 2019	Sep. 13, 2019	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Nov. 08, 2018	Mar. 05, 2019	Nov. 07, 2019	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Feb. 15, 2019~ Mar. 29, 2019	Jan. 06, 2020	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-124 1	1GHz ~ 18GHz	Jun. 29, 2018	Feb. 15, 2019~ Mar. 29, 2019	Jun. 28, 2019	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 13, 2018	Feb. 15, 2019~ Mar. 29, 2019	Oct. 12, 2019	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 05, 2018	Feb. 15, 2019~ Mar. 29, 2019	Dec. 04, 2019	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY532700 80	1GHz~26.5GHz	Nov. 14, 2018	Feb. 15, 2019~ Mar. 29, 2019	Nov. 13, 2020	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 21, 2018	Feb. 15, 2019~ Mar. 29, 2019	May 20, 2019	Radiation (03CH13-HY)
Amplifier	Sonoma-Instru ment	310 N	187282	9KHz~1GHz	Dec. 18, 2018	Feb. 15, 2019~ Mar. 29, 2019	Dec. 17, 2019	Radiation (03CH13-HY)
Amplifier	MITEQ	TTA1840-35-H G	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Feb. 15, 2019~ Mar. 29, 2019	Jul. 15, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Feb. 13, 2019	Feb. 15, 2019~ Mar. 29, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	804793/4	30M-18G	Feb. 13, 2019	Feb. 15, 2019~ Mar. 29, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/ 4	30M-18G	Feb. 13, 2019	Feb. 15, 2019~ Mar. 29, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 17, 2018	Feb. 15, 2019~ Mar. 29, 2019	Apr. 16, 2019	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Feb. 15, 2019~ Mar. 29, 2019	N/A	Radiation (03CH13-HY)

: Apr. 18, 2019



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Feb. 15, 2019~ Mar. 29, 2019	N/A	Radiation (03CH13-HY)
Software	AUDIX	E3 6.2009-8-24c	RK-001124	N/A	N/A	Feb. 15, 2019~ Mar. 29, 2019	N/A	Radiation (03CH13-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	20Hz ~ 8.4GHz	Nov. 01, 2018	Feb. 15, 2019~ Mar. 29, 2019	Oct. 31, 2019	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000- 60SS	SN2	3G High Pass	Jul. 16, 2018	Feb. 15, 2019~ Mar. 29, 2019	Jul. 15, 2019	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-108 0-1200-15000- 60ST	SN3	1.2G Low Pass	Jul. 05, 2018	Feb. 15, 2019~ Mar. 29, 2019	Jul. 04, 2019	Radiation (03CH13-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.2
of 95% (U = 2Uc(y))	Ζ.Ζ

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	4.0
of 95% (U = 2Uc(y))	4.9

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	54
of 95% (U = 2Uc(y))	5.4

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	4.2
of 95% (U = 2Uc(y))	4.5

Report Number : FR911708B

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Howard Lin	Temperature:	21~25	°C
Test Date:	2019/2/12~2019/3/8	Relative Humidity:	51~54	%

	<u>TEST RESULTS DATA</u> 6dB and 99% Occupied Bandwidth										
ļ											
	Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail		
	BLE	1Mbps	1	0	2402	1.033	0.707	0.50	Pass		
Ī	BLE	1Mbps	1	19	2440	1.029	0.705	0.50	Pass		
	BLE	1Mbps	1	39	2480	1.029	0.707	0.50	Pass		

TEST RESULTS DATA Average Power Table										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	12.30	30.00	2.00	14.30	36.00	Pass
BLE	1Mbps	1	19	2440	12.40	30.00	2.00	14.40	36.00	Pass
BLE	1Mbps	1	39	2480	12.20	30.00	2.00	14.20	36.00	Pass

TEST RESULTS DATA
<u>Peak Power Density</u>

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	10.80	-3.88	2.00	8.00	Pass
BLE	1Mbps	1	19	2440	10.80	-3.95	2.00	8.00	Pass
BLE	1Mbps	1	39	2480	10.62	-4.06	2.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



Appendix B. AC Conducted Emission Test Results

Tost Engineer	limmy Chang	Temperature :	24~26 ℃
rest Engineer.	Jinning Chang	Relative Humic	lity : 51~53%

EUT Information

Report NO : Test Mode : Test Voltage : Phase : 911708 Mode 1 120Vac/60Hz Line



FullSpectrum

Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500		27.28	55.75	28.47	L1	OFF	19.5
0.154500	29.36		65.75	36.39	L1	OFF	19.5
0.339000		22.52	49.23	26.71	L1	OFF	19.5
0.339000	23.73		59.23	35.50	L1	OFF	19.5
0.766500		23.33	46.00	22.67	L1	OFF	19.6
0.766500	24.73		56.00	31.27	L1	OFF	19.6
1.990500		23.14	46.00	22.86	L1	OFF	19.6
1.990500	24.29		56.00	31.71	L1	OFF	19.6
8.823750		24.90	50.00	25.10	L1	OFF	19.9
8.823750	25.91		60.00	34.09	L1	OFF	19.9
22.560000		24.92	50.00	25.08	L1	OFF	20.3
22.560000	25.96		60.00	34.04	L1	OFF	20.3

EUT Information

Report NO : Test Mode : Test Voltage : Phase : 911708 Mode 1 120Vac/60Hz Neutral



FullSpectrum

Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750		26.78	55.63	28.85	Ν	OFF	19.5
0.156750	28.83		65.63	36.80	Ν	OFF	19.5
0.278250		22.91	50.87	27.96	Ν	OFF	19.5
0.278250	24.16		60.87	36.71	Ν	OFF	19.5
0.834000		22.40	46.00	23.60	Ν	OFF	19.6
0.834000	23.58		56.00	32.42	Ν	OFF	19.6
2.386500		23.17	46.00	22.83	Ν	OFF	19.5
2.386500	24.19		56.00	31.81	Ν	OFF	19.5
5.309250		24.74	50.00	25.26	Ν	OFF	19.7
5.309250	25.76		60.00	34.24	Ν	OFF	19.7
21.237000		24.66	50.00	25.34	Ν	OFF	20.4
21.237000	25.62		60.00	34.38	Ν	OFF	20.4





Appendix C. Radiated Spurious Emission

Toot Engineer	Alox Ibong FulChon and Wilson Wu	Temperature :	24.5~25.3°C
rest Engineer .	Alex Sherig, Fu Chen, and Wilson Wu	Relative Humidity :	50~55%

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2380.665	51.86	-22.14	74	40.34	27.19	13.91	29.58	250	41	Р	Н
		2386.125	43.06	-10.94	54	31.49	27.23	13.92	29.58	250	41	А	Н
	*	2402	104.85	-	-	93.27	27.23	13.93	29.58	250	41	Ρ	Н
	*	2402	104.29	-	-	92.71	27.23	13.93	29.58	250	41	А	Н
													Н
													Н
2402MH-		2384.13	52.38	-21.62	74	40.85	27.19	13.92	29.58	258	132	Ρ	V
2402101712		2385.39	43.19	-10.81	54	31.66	27.19	13.92	29.58	258	132	А	V
	*	2402	106.73	-	-	95.15	27.23	13.93	29.58	258	132	Ρ	V
	*	2402	105.92	-	-	94.34	27.23	13.93	29.58	258	132	А	V
													V
													V
		2378.88	52.44	-21.56	74	40.92	27.19	13.91	29.58	246	42	Ρ	Н
		2385.6	42.9	-11.1	54	31.33	27.23	13.92	29.58	246	42	А	Н
	*	2440	105.08	-	-	93.33	27.37	13.96	29.58	246	42	Ρ	Н
	*	2440	104.54	-	-	92.79	27.37	13.96	29.58	246	42	А	Н
ЫЕ		2495.17	52.86	-21.14	74	40.92	27.5	14.01	29.57	246	42	Р	Н
		2497.62	43.27	-10.73	54	31.33	27.5	14.01	29.57	246	42	А	н
2440MH7		2343.6	51.92	-22.08	74	40.53	27.1	13.88	29.59	301	166	Ρ	V
244011112		2358.58	42.97	-11.03	54	31.52	27.14	13.9	29.59	301	166	А	V
	*	2440	107.44	-	-	95.69	27.37	13.96	29.58	301	166	Р	V
	*	2440	106.9	-	-	95.15	27.37	13.96	29.58	301	166	А	V
		2496.99	52.35	-21.65	74	40.41	27.5	14.01	29.57	301	166	Р	V
		2497.13	43.38	-10.62	54	31.44	27.5	14.01	29.57	301	166	А	V



BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	/110/0
		(INITIZ)	(αθμν/m)	(ab)	(abh v/w)	(α Βμν)	(ab/m)	(ab)	(a B)	(cm)	(aeg)	(P/A)	(H/V)
	*	2480	105.98	-	-	94.09	27.46	14	29.57	271	43	Р	Н
	*	2480	105.34	-	-	93.45	27.46	14	29.57	271	43	А	Н
		2484	52.55	-21.45	74	40.66	27.46	14	29.57	271	43	Р	Н
		2485.12	43.93	-10.07	54	32.04	27.46	14	29.57	271	43	А	Н
													Н
BLE													Н
	*	2480	108.66	-	-	96.77	27.46	14	29.57	285	135	Р	V
240010172	*	2480	108.05	-	-	96.16	27.46	14	29.57	285	135	А	V
		2483.56	53.84	-20.16	74	41.95	27.46	14	29.57	285	135	Р	V
		2483.56	44.45	-9.55	54	32.56	27.46	14	29.57	285	135	А	V
													V
													V
Remark	1. No 2. All	o other spurious results are PA	s found. SS against F	Peak and	Average lim	it line.							



2.4GHz 2400~2483.5MHz

							,						
BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBµV/m)	(dB)	Line (dBµV/m)	Levei (dBµV)	Factor (dB/m)	Loss (dB)	(dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
		4804	42.99	-31.01	74	62.97	31.22	6.39	57.59	100	0	Р	н
													н
													Н
BLE													н
		4804	40.95	-33.05	74	60.93	31.22	6.39	57.59	100	0	Р	V
240211172													V
													V
													V
		4880	44.11	-29.89	74	63.59	31.36	6.6	57.44	100	0	Ρ	н
		7320	44.52	-29.48	74	57.34	36.22	8.24	57.28	100	0	Р	Н
51 5													Н
													Н
СП 19 2440МН 7		4880	42.33	-31.67	74	61.81	31.36	6.6	57.44	100	0	Р	V
244010112		7320	43.34	-30.66	74	56.16	36.22	8.24	57.28	100	0	Р	V
													V
													V
		4960	45.5	-28.5	74	64.42	31.53	6.83	57.28	100	0	Р	Н
		7440	43.62	-30.38	74	56.3	36.49	8.26	57.43	100	0	Р	н
DI E													н
													Н
2480MHz		4960	43.16	-30.84	74	62.08	31.53	6.83	57.28	100	0	Р	V
		7440	46.35	-27.65	74	59.03	36.49	8.26	57.43	100	0	Р	V
													V
													V
Remark	1. No 2. All	o other spurious results are PA	s found. SS against F	eak and	l Average lim	it line.							

BLE (Harmonic @ 3m)



Emission below 1GHz

BLE	Note	Frequency		Over	Limit	Read	Antenna	Path	Preamn	Ant	Table	Poak	Pol
	Note	Trequency	Level	Limit	Line	Level	Factor		Factor	Pos	Pos	Ava.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		31.35	24.76	-15.24	40	33.04	23.58	0.43	32.29	-	-	Ρ	Н
		91.02	24.47	-19.03	43.5	40.94	14.95	0.8	32.22	-	-	Р	Н
		156.36	20.13	-23.37	43.5	34.39	16.88	1.03	32.17	-	-	Р	Н
		342	32.13	-13.87	46	42.64	20.12	1.52	32.15	-	-	Р	Н
		663.3	34.21	-11.79	46	37.79	26.36	2.21	32.15	100	0	Р	Н
		798.4	33.24	-12.76	46	34.7	28.03	2.4	31.89	-	-	Р	Н
													Н
													Н
													Н
													Н
2.4GHz													Н
BLE													Н
LF		31.62	36.53	-3.47	40	44.93	23.46	0.43	32.29	100	0	Р	V
		42.96	26.48	-13.52	40	40.52	17.75	0.5	32.29	-	-	Р	V
		53.22	25.12	-14.88	40	43.95	12.9	0.55	32.28	-	-	Р	V
		395.9	26.32	-19.68	46	35.19	21.53	1.76	32.16	-	-	Р	V
		662.6	33.58	-12.42	46	37.16	26.35	2.22	32.15	-	-	Р	V
		959.4	32.35	-13.65	46	29.81	30.85	2.6	30.91	-	-	Р	V
													V
													V
													V
													V
													V
													V
Remark	1. No 2. All	o other spurious results are PA	s found. .SS against li	mit line.									



*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not
	exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

Note symbol



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	н
CH 00 2402MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	н

- 1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- 2. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- = 55.45 (dBµV/m)
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- = 43.54 (dBµV/m)
- 2. Over Limit(dB)
- = Level(dB μ V/m) Limit Line(dB μ V/m)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".



Appendix D. Radiated Spurious Emission Plots

Toot Engineer	Alox Ibong Fu Chon and Wilson Wu	Temperature :	24.5~25.3°C
Test Engineer :	Alex sheng, Fu Chen, and wilson wu	Relative Humidity :	50~55%

Note symbol

-L	Low channel location
-R	High channel location



2.4GHz 2400~2483.5MHz





















BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m							
ANT	BLE CH19 2	2440MHz - R						
2	Horizontal	Fundamental						
Peak	101 101 101 101 101 102 101 101 101 101 101 103 101 101 101 101 101 104 100 100 100 100 100 105 100 100 100 100 100 105 100 100 100 100 100 105 100 100 100 100 100 105 100 100 100 100 100 105 100 100 100 100 100 105 100 100 100 100 100 106 100 100 100 100 100 107 100 100 100 100 100 108 100 100 100 100 100 109 100 100 100 100 100 109 100 100 100 100 100 109 100 100 100 100 100 109 100 100 100 100 100 109 100 100 100 <th>Left blank</th>	Left blank						
Avg.	123 104:2019-2019 123 104:2019-2019 124 104:2019-2019 125 104:2019-2019 126 246 127 246 128 246 129 246 <	Left blank						











BLE	2.4GHz 2400~2483.5M	/Hz Band Edge @ 3m
ANT	BLE CH19 2	2440MHz - R
2	Vertical	Fundamental
Peak	Image: statistic time Different Statistics 123 124 123 124 124 124 125 124 126 124 127 124 128 124 129 124	Left blank
Avg.	1 Det 2019-02.19 1 1	Left blank











2.4GHz 2400~2483.5MHz



BLE (Harmonic @ 3m)















Emission below 1GHz



2.4GHz BLE (LF)



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth -LE	60.06	376	2.66	3kHz	2.21

Bluetooth - LE



Date: 12.FEB.2019 15:42:59

