

Report No. : FC911708-01



FCC EMI TEST REPORT

FCC ID	: WR92221123114
Equipment	: thermostat
Brand Name	: ecobee
Model Name	: ECB402
Applicant	: ecobee Inc. 207 Queens Quay West, Suite 600, Toronto, ON, Canada
Manufacturer	: ecobee Inc. 207 Queens Quay West, Suite 600, Toronto, ON, Canada
Standard	: FCC 47 CFR FCC Part 15 Subpart B

The product was received on May 10, 2019 and testing was started from May 23, 2019 and completed on May 24, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Jones Tsai

Approved by: Jones Tsai SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report	.3
Summary of Test Result	.4
1. General Description	.5
 1.1. Product Feature of Equipment Under Test 1.2. Modification of EUT 1.3. Test Location	.5 .5 .5
2. Test Configuration of Equipment Under Test	.6
 2.1. Test Mode 2.2. Connection Diagram of Test System 2.3. Support Unit used in test configuration and system 2.4. EUT Operation Test Setup 	.6 .6 .7 .7
3. Test Result	.8
3.1. Test of AC Conducted Emission Measurement	.8 10
4. List of Measuring Equipment1	2
5. Uncertainty of Evaluation1	3

Appendix B. Radiated Emission Test Result



History of this test report

Report No.	Version	Description	Issued Date
FC911708-01	01	Initial issue of report	May 31, 2019



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.107	AC Conducted Emission	Pass	Under limit 19.51 dB at 4.992 MHz
3.2	15.109	Radiated Emission	Pass	Under limit 4.11 dB at 662.440 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Louis Wu

Report Producer: Jessie Ho



1. General Description

1.1. Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, and Proprietary Sensor

Product Specification subjective to this standard			
Antenna Type	WLAN: Ceramic Chip Antenna Bluetooth: FPC Antenna		
	Proprietary Sensor: IFA Meander Printed PCB Type Antenna		

1.2. Modification of EUT

No modifications are made to the EUT during all test items.

1.3. Test Location

Test Site	SPORTON INTERNATIONAL INC.		
	No.52, Huaya 1st Rd., Guishan Dist.,		
Test Site Location	Taoyuan City, Taiwan (R.O.C.)		
	TEL: +886-3-327-3456		
	FAX: +886-3-328-4978		
Tast Site No	Sporton Site No.		
Test Site No.	CO05-HY		
Test Oits			
Test Site	SPORTON INTERNATIONAL INC.		
Test Site	SPORTON INTERNATIONAL INC. No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist.,		
Test Site Location	SPORTON INTERNATIONAL INC. No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)		
Test Site Test Site Location	SPORTON INTERNATIONAL INC. No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868		
Test Site Test Site Location	SPORTON INTERNATIONAL INC. No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855		
Test Site Test Site Location	SPORTON INTERNATIONAL INC. No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855 Sporton Site No.		

FCC Designation No. TW1093 and TW1098

1.4. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- + ANSI C63.4-2014
- **Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + Sub-gigahertz on + Infrared on + PEK with Adapter
Emission	Mode 2: WLAN (5GHz) Link + Bluetooth Link + Sub-gigahertz on + Infrared on + PEK with Adapter
Radiated	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + Sub-gigahertz on + Infrared on + PEK with Adapter
Emissions	Mode 2: WLAN (5GHz) Link + Bluetooth Link + Sub-gigahertz on + Infrared on + PEK with Adapter
Remark:	
1. The worst case	of AC is mode 1; only the test data of this mode was reported.

2. The worst case of RE is mode 2; only the test data of this mode was reported.

2.2. Connection Diagram of Test System





2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord		
1.	Bluetooth Base Station	R&S	CBT32 N/A N		CBT32 N/A N/A		N/A	Unshielded, 1.8 m
2.	Adapter	Jameco	ADU240050	DU240050 FCC DoC N/		N/A		
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m		
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m		

2.4. EUT Operation Test Setup

The EUT was attached to the Bluetooth base station and WLAN AP, and the following programs installed in the EUT were programmed during the test.

- 1. Turn on Sub-gigahertz to transmit 920.2MHz signals continuously.
- 2. Turn on Infrared function.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission	Conducted limit (dBuV)			
(MHz)	Quasi-peak	Average		
0.15-0.5	66 to 56*	56 to 46*		
0.5-5	56	46		
5-30	60	50		

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedure

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.



3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency	Field Strength	Measurement Distance	
(MHz)	(microvolts/meter)	(meters)	
30 – 88	100	3	
88 – 216	150	3	
216 - 960	200	3	
Above 960	500	3	

3.2.2. Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3. Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter above ground.
- 2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest radiation.
- 4. The antenna height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
- 5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
- 7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
- 8. Emission level $(dB\mu V/m) = 20 \log Emission level (\mu V/m)$
- 9. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level



3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz



.



3.2.5. Test Result of Radiated Emission

Please refer to Appendix B.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 24, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	May 24, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	May 24, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	May 24, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	May 24, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	May 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	May 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 23, 2018	May 23, 2019	Oct. 22, 2019	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35413&02	30MHz~1GHz	Feb. 12, 2019	May 23, 2019	Feb. 11, 2020	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Oct. 02, 2018	May 23, 2019	Oct. 01, 2019	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JAP00101800 -30-10P	160118550004	1GHz~18GHz	Apr. 16, 2019	May 23, 2019	Apr. 15, 2020	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Nov. 02, 2018	May 23, 2019	Nov. 01, 2019	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1~4m	N/A	May 23, 2019	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	May 23, 2019	N/A	Radiation (03CH10-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	May 23, 2019	N/A	Radiation (03CH10-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY54130085	20Hz ~ 8.4GHz	Nov. 01, 2018	May 23, 2019	Oct. 31, 2019	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE ,MY11693/4P E,MY2855/2	30M-1G	Nov. 08, 2018	May 23, 2019	Nov. 07, 2019	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE ,MY11693/4P E,MY2855/2	1G-18G	Nov. 08, 2018	May 23, 2019	Nov. 07, 2019	Radiation (03CH10-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.2
of 95% (U = 2Uc(y))	۷.۷

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

	Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.6
--	--	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	5.0
of 95% (U = 2Uc(y))	5.9



Appendix A. AC Conducted Emission Test Results

Test Engineer :	limmy Chong	Temperature :	24~26 ℃
	Simmy Chang	Relative Humidity :	51~53%

EUT Information

Report NO : Test Mode : Test Voltage : Phase : 911708-01 Mode 1 120Vac/60Hz Line



Full Spectrum

Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250		28.42	55.88	27.46	L1	OFF	19.5
0.152250	30.68		65.88	35.20	L1	OFF	19.5
0.233250		25.54	52.33	26.79	L1	OFF	19.5
0.233250	27.60		62.33	34.73	L1	OFF	19.5
0.930750		22.25	46.00	23.75	L1	OFF	19.6
0.930750	23.20		56.00	32.80	L1	OFF	19.6
1.857750		22.78	46.00	23.22	L1	OFF	19.6
1.857750	23.64		56.00	32.36	L1	OFF	19.6
4.992000		26.49	46.00	19.51	L1	OFF	19.7
4.992000	28.03		56.00	27.97	L1	OFF	19.7
20.933250		24.54	50.00	25.46	L1	OFF	20.3
20.933250	25.49		60.00	34.51	L1	OFF	20.3

EUT Information

Report NO : Test Mode : Test Voltage : Phase : 911708-01 Mode 1 120Vac/60Hz Neutral



Full Spectrum

Final_Result

Frequency	QuasiPeak			Margin	Line	Filter	Corr.
(11172)	(авич)	(ubuv)	(ubuv)	(UD)			(ub)
0.152250		29.79	55.88	26.09	Ν	OFF	19.5
0.152250	32.05		65.88	33.83	Ν	OFF	19.5
0.233250		26.26	52.33	26.07	Ν	OFF	19.5
0.233250	28.60		62.33	33.73	Ν	OFF	19.5
0.480750		22.42	46.33	23.91	Ν	OFF	19.5
0.480750	23.48		56.33	32.85	Ν	OFF	19.5
0.852000		22.29	46.00	23.71	Ν	OFF	19.6
0.852000	23.14		56.00	32.86	Ν	OFF	19.6
4.701750		24.58	46.00	21.42	Ν	OFF	19.7
4.701750	25.51		56.00	30.49	Ν	OFF	19.7
20.231250		24.45	50.00	25.55	Ν	OFF	20.3
20.231250	25.49		60.00	34.51	Ν	OFF	20.3



Appendix B. Radiated Emission Test Result

Test Engineer . D		Derini I	Danial Lao			Temperature :		22~2	22~24°C				
lest Engineel	r :	Daniel	Lee		Relative Humidity :		53~5	53~56%					
Test Distance	;	3m				Polari	Polarization :			Horizontal			
Remark:		#7 is fundamental signal which can be ignored.											
97	Leve	l (dBuV/m)	1								Date: 201	19-05-23	
84.9													
72.8				<u> </u>							FCC CI	LASS-B	
60.6													
										FCC	CLASS	B (AVG)	
48.5	;—							- 11	12		13		
		.1	8		9	1	10	Ϊ					
36.4	_	4											
	23	5											
24.3													
12.1	Ш												
12.1													
0													
	30	1000.	30	00.	5000). Freque	7000.	7)	9000.	110	00.	13000	
Cita			00.01.110			Teque	IICy (minz	-)					
Sile	litio		03CHIU	-HY ACC B 2		01200	UE LIO		A1				
Proje	act		911708	01	MINUKIN	91200-	ni no	RIZUNT	AL				
Powe	201 2r		120Vac	/60Hz									
Mode	e	:	2	001.2									
	-		_	0ver	Limit	Read/	Antenna	a Cable	Preamp	A/Pos	T/Pos		
		Freq	Level	Limit	Line	Level	Factor	• Loss	Factor			Remark	
		MH7	dBuV/m	dB	dBuV/m				dB		deg		
		11112	ubuvym	40	ubuv/m	ubuv	00/1		ub	Chi	uce		
1		30.00	26.10	-13.90	40.00	33.13	25.30	0.45	32.78			Peak	
2		342.34	29.34	-16.66	46.00	39.82	20.15	5 1.98	32.61			Peak	
3		454.86	28.81	-17.19	46.00	35.92	23.10) 2.42	32.63			Peak	
4		663.41	38.10	-/.90	46.00	41.25	26.50) 2.99	32.62	100	0	Peak	
2		/94.00	31.70 33.10	12 00	46.00	32.33	20.00) 5.25 7 7 /1	32.30			Peak	
7	*	920 16	16 21	-12.00	40.00	11 96	29.09	3.41	21 62			Peak	
, 8	٠,	1990.40	40.21	-30 55	74 00	73 29	25.41	5 6 60	61 70			Peak	
9	1	4734.00	40.65	-33,35	74.00	63,22	31.17	7 8.56	62.30			Peak	
10	(5470.00	43.65	-30.35	74.00	62.57	34.02	2 10.05	62.99			Peak	
11	5	3082.00	44.75	-29.25	74.00	60.12	37.06	5 11.25	63.68			Peak	
12	9	9362.00	46.94	-27.06	74.00	60.98	38.52	2 12.14	64.70	100	0	Peak	
13	11	1352.00	46.38	-27.62	74.00	57.31	39.45	5 13.49	63.87			Peak	





-THE END