



FCC RADIO TEST REPORT

FCC ID : WR974100118120
Equipment : SmartCamera with voice control
Brand Name : ecobee
Model name : EBSCV01
Applicant : ecobee Incorporated
207 Queens Quay West, Suite 600, Toronto,
Ontario, M5J 1A7 , Canada
Manufacturer : Wistron Corporation
21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist,
New Taipei City 221, Taiwan R.O.C
Standard : FCC Part 15 Subpart E §15.407

The product was received on Jul. 23, 2019 and testing was started from Jul. 30, 2019 and completed on Aug. 19, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report..... 3

Summary of Test Result..... 4

1 General Description 5

 1.1 Product Feature of Equipment Under Test..... 5

 1.2 Modification of EUT 5

 1.3 Testing Location 5

 1.4 Applicable Standards..... 6

2 Test Configuration of Equipment Under Test 7

 2.1 Carrier Frequency and Channel 7

 2.2 Test Mode 8

 2.3 Connection Diagram of Test System 9

 2.4 Support Unit used in test configuration and system 9

 2.5 EUT Operation Test Setup 10

 2.6 Measurement Results Explanation Example..... 10

3 Test Result 11

 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 11

 3.2 Maximum Conducted Output Power Measurement 14

 3.3 Power Spectral Density Measurement 15

 3.4 Unwanted Emissions Measurement 17

 3.5 AC Conducted Emission Measurement..... 22

 3.6 Automatically Discontinue Transmission 24

 3.7 Antenna Requirements 25

4 List of Measuring Equipment..... 26

5 Uncertainty of Evaluation 28

Appendix A. Conducted Test Results

Appendix B. AC Conducted Emission Test Result

Appendix C. Radiated Spurious Emission

Appendix D. Radiated Spurious Emission Plots

Appendix E. Duty Cycle Plots



History of this test report

Report No.	Version	Description	Issued Date
FR972333E	01	Initial issue of report	Oct. 24, 2019



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407 (a)	Maximum Conducted Output Power	Pass	-
3.3	15.407 (a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 7.29 dB at 384.050 MHz
3.5	15.207	AC Conducted Emission	Pass	Under limit 18.05 dB at 0.508 MHz
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass	-
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang**Report Producer: Jessie Ho**



1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, and Sub-gig

Product Specification subjective to this standard	
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna Sub-gig: PIFA Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH11-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

- 1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
- 2. The above Frequency and Channel in "#n" were 802.11ac VHT80.



2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) TX + Bluetooth TX + Adapter

Ch. #	Band IV : 5725-5850 MHz			
	802.11a	802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L Low	149	149	151	-
M Middle	157	157	-	155
H High	165	165	159	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Spectrum Analyzer	Agilent	N9030A	N/A	N/A	Unshielded,1.8m



2.5 EUT Operation Test Setup

The RF test items, utility “adb cmd” was installed in EUT which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

Method SA-3

(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 1 MHz.
 - Set VBW \geq 3 MHz
 - Number of points in sweep \geq 2 Span / RBW.
 - Sweep time \leq (number of points in sweep) \times T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
 - Detector = power averaging (rms).
 - Trace mode = max hold.
 - Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:
 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW ≥ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold




(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
 3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
 4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
 5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
 6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 30, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jul. 30, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jul. 30, 2019	Nov. 13, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 30, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jul. 30, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jul. 30, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 19, 2018	Aug. 07, 2019~ Aug. 19, 2019	Dec. 18, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	Aug. 07, 2019~ Aug. 19, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Aug. 07, 2019~ Aug. 19, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	EM	EMSW18	SW1070903	N/A	Dec. 19, 2018	Aug. 07, 2019~ Aug. 19, 2019	Dec. 18, 2019	Conducted (TH05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Aug. 11, 2019~ Aug. 16, 2019	Dec. 05, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 04, 2018	Aug. 11, 2019~ Aug. 16, 2019	Dec. 03, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-0 6	35414&AT- N0602	30MHz~1GHz	Oct. 13, 2018	Aug. 11, 2019~ Aug. 16, 2019	Oct. 12, 2019	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-132 6	1GHz ~ 18GHz	Oct. 30, 2018	Aug. 11, 2019~ Aug. 16, 2019	Oct. 29, 2019	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 22, 2018	Aug. 11, 2019~ Aug. 16, 2019	Nov. 21, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY532700 80	1GHz~26.5GHz	Nov. 14, 2018	Aug. 11, 2019~ Aug. 16, 2019	Nov. 13, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz ~ 44GHz	Oct. 19, 2018	Aug. 11, 2019~ Aug. 16, 2019	Oct. 18, 2019	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1~4m	N/A	Aug. 11, 2019~ Aug. 16, 2019	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Aug. 11, 2019~ Aug. 16, 2019	N/A	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 20, 2019	Aug. 11, 2019~ Aug. 16, 2019	May 19, 2020	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 05, 2018	Aug. 11, 2019~ Aug. 16, 2019	Dec. 04, 2019	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	N/A	Nov. 01, 2018	Aug. 11, 2019~ Aug. 16, 2019	Oct. 31, 2019	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-00104 2	N/A	N/A	Aug. 11, 2019~ Aug. 16, 2019	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz-30MHz	Mar. 13, 2019	Aug. 11, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	Aug. 11, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	30M-18G	Mar. 13, 2019	Aug. 11, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 13, 2019	Aug. 11, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN11	1G Low Pass	Sep. 16, 2018	Aug. 11, 2019~ Aug. 16, 2019	Sep. 17, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHKX8-5872. 5-6750-18000 -40ST	SN3	6.75GHz High Pass	Sep. 17, 2018	Aug. 11, 2019~ Aug. 16, 2019	Sep. 16, 2019	Radiation (03CH11-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Nick Yu	Temperature:	21~25	°C
Test Date:	2019/8/7~2019/8/19	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	17.10	-	34.50	-	16.25	-	0.5	Pass
11a	6Mbps	1	157	5785	17.10	-	35.10	-	16.24	-	0.5	Pass
11a	6Mbps	1	165	5825	17.25	-	36.50	-	16.25	-	0.5	Pass
VHT20	MCS0	1	149	5745	17.85	-	31.70	-	17.54	-	0.5	Pass
VHT20	MCS0	1	157	5785	17.85	-	34.01	-	17.50	-	0.5	Pass
VHT20	MCS0	1	165	5825	17.95	-	37.70	-	17.54	-	0.5	Pass
VHT40	MCS0	1	151	5755	36.60	-	41.58	-	36.30	-	0.5	Pass
VHT40	MCS0	1	159	5795	36.60	-	41.69	-	36.29	-	0.5	Pass
VHT80	MCS0	1	155	5775	76.80	-	81.69	-	76.56	-	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	18.20	-		30.00	-	4.40	-	Pass
11a	6Mbps	1	157	5785	17.90	-		30.00	-	4.40	-	Pass
11a	6Mbps	1	165	5825	18.20	-		30.00	-	4.40	-	Pass
HT20	MCS0	1	149	5745	17.00	-		30.00	-	4.40	-	Pass
HT20	MCS0	1	157	5785	16.70	-		30.00	-	4.40	-	Pass
HT20	MCS0	1	165	5825	17.10	-		30.00	-	4.40	-	Pass
HT40	MCS0	1	151	5755	12.50	-		30.00	-	4.40	-	Pass
HT40	MCS0	1	159	5795	12.20	-		30.00	-	4.40	-	Pass
VHT20	MCS0	1	149	5745	17.10	-		30.00	-	4.40	-	Pass
VHT20	MCS0	1	157	5785	16.80	-		30.00	-	4.40	-	Pass
VHT20	MCS0	1	165	5825	17.20	-		30.00	-	4.40	-	Pass
VHT40	MCS0	1	151	5755	12.60	-		30.00	-	4.40	-	Pass
VHT40	MCS0	1	159	5795	12.30	-		30.00	-	4.40	-	Pass
VHT80	MCS0	1	155	5775	11.30	-		30.00	-	4.40	-	Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.00	-	2.22	-	8.71	-		30.00	-	4.40	-	Pass
11a	6Mbps	1	157	5785	0.00	-	2.22	-	8.63	-		30.00	-	4.40	-	Pass
11a	6Mbps	1	165	5825	0.00	-	2.22	-	8.91	-		30.00	-	4.40	-	Pass
VHT20	MCS0	1	149	5745	0.00	-	2.22	-	7.75	-		30.00	-	4.40	-	Pass
VHT20	MCS0	1	157	5785	0.00	-	2.22	-	7.42	-		30.00	-	4.40	-	Pass
VHT20	MCS0	1	165	5825	0.00	-	2.22	-	7.98	-		30.00	-	4.40	-	Pass
VHT40	MCS0	1	151	5755	0.00	-	2.22	-	-0.17	-		30.00	-	4.40	-	Pass
VHT40	MCS0	1	159	5795	0.00	-	2.22	-	-0.45	-		30.00	-	4.40	-	Pass
VHT80	MCS0	1	155	5775	0.00	-	2.22	-	-4.30	-		30.00	-	4.40	-	Pass




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	25.5~26.3°C
		Relative Humidity :	58~61%

EUT Information

Report NO : 972333
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.168000	---	26.46	55.06	28.60	L1	OFF	19.4
0.168000	33.54	---	65.06	31.52	L1	OFF	19.4
0.219750	---	24.14	52.83	28.69	L1	OFF	19.4
0.219750	26.92	---	62.83	35.91	L1	OFF	19.4
0.507750	---	27.95	46.00	18.05	L1	OFF	19.4
0.507750	30.39	---	56.00	25.61	L1	OFF	19.4
1.110750	---	23.74	46.00	22.26	L1	OFF	19.5
1.110750	25.48	---	56.00	30.52	L1	OFF	19.5
3.306750	---	23.98	46.00	22.02	L1	OFF	19.6
3.306750	25.06	---	56.00	30.94	L1	OFF	19.6
5.894250	---	25.11	50.00	24.89	L1	OFF	19.7
5.894250	26.20	---	60.00	33.80	L1	OFF	19.7
20.217750	---	24.44	50.00	25.56	L1	OFF	20.2
20.217750	25.55	---	60.00	34.45	L1	OFF	20.2

EUT Information

Report NO : 972333
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	30.12	55.75	25.63	N	OFF	19.5
0.154500	35.16	---	65.75	30.59	N	OFF	19.5
0.213000	---	24.04	53.09	29.05	N	OFF	19.5
0.213000	27.43	---	63.09	35.66	N	OFF	19.5
0.519000	---	24.74	46.00	21.26	N	OFF	19.5
0.519000	27.93	---	56.00	28.07	N	OFF	19.5
2.103000	---	22.95	46.00	23.05	N	OFF	19.6
2.103000	23.77	---	56.00	32.23	N	OFF	19.6
4.805250	---	24.60	46.00	21.40	N	OFF	19.7
4.805250	25.49	---	56.00	30.51	N	OFF	19.7
21.054750	---	24.58	50.00	25.42	N	OFF	20.3
21.054750	25.66	---	60.00	34.34	N	OFF	20.3



Appendix C. Radiated Spurious Emission

Test Engineer :	Bill Kuo, Fu Chen and Troye Hsie	Temperature :	21.3~27.3°C
		Relative Humidity :	48.7~65.9%

Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11a CH 149 5745MHz		5646	55.11	-13.09	68.2	46.07	31.71	10.49	33.16	213	266	P	H	
		5696	56.67	-45.58	102.25	47.35	31.98	10.51	33.17	213	266	P	H	
		5717.6	66.2	-43.93	110.13	56.82	32.04	10.52	33.18	213	266	P	H	
		5724.2	73.59	-46.79	120.38	64.19	32.05	10.53	33.18	213	266	P	H	
	*	5745	113.39	-	-	103.95	32.09	10.54	33.19	213	266	P	H	
	*	5745	106.58	-	-	97.14	32.09	10.54	33.19	213	266	A	H	
														H
														H
			5641.6	54.97	-13.23	68.2	45.93	31.72	10.48	33.16	192	19	P	V
			5696.2	57.72	-44.68	102.4	48.4	31.98	10.51	33.17	192	19	P	V
			5716.6	66.97	-42.88	109.85	57.6	32.03	10.52	33.18	192	19	P	V
			5724.8	74.9	-46.84	121.74	65.5	32.05	10.53	33.18	192	19	P	V
	*	5745	113.87	-	-	104.43	32.09	10.54	33.19	192	19	P	V	
	*	5745	106.46	-	-	97.02	32.09	10.54	33.19	192	19	A	V	
														V
														V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5650	54.05	-14.15	68.2	45.02	31.7	10.49	33.16	211	268	P	H
		5677.25	55.02	-33.39	88.41	45.83	31.86	10.5	33.17	211	268	P	H
		5718.75	55.1	-55.35	110.45	45.71	32.04	10.53	33.18	211	268	P	H
		5724	54.77	-65.15	119.92	45.37	32.05	10.53	33.18	211	268	P	H
	*	5785	112.99	-	-	103.46	32.17	10.56	33.2	211	268	P	H
	*	5785	104.98	-	-	95.45	32.17	10.56	33.2	211	268	A	H
		5853.5	53.23	-60.99	114.22	43.55	32.31	10.59	33.22	211	268	P	H
		5856	52.6	-57.92	110.52	42.91	32.32	10.59	33.22	211	268	P	H
		5879	53.62	-48.61	102.23	43.83	32.42	10.6	33.23	211	268	P	H
		5935.5	51.4	-16.8	68.2	41.46	32.57	10.62	33.25	211	268	P	H
													H
													H
802.11a													
CH 157													
5785MHz		5605.5	53.63	-14.57	68.2	44.52	31.79	10.46	33.14	198	21	P	V
		5682	55.08	-36.84	91.92	45.85	31.89	10.51	33.17	198	21	P	V
		5701.25	54.68	-50.87	105.55	45.33	32	10.52	33.17	198	21	P	V
		5724.5	55.34	-65.72	121.06	45.94	32.05	10.53	33.18	198	21	P	V
	*	5785	113.43	-	-	103.9	32.17	10.56	33.2	198	21	P	V
	*	5785	105.93	-	-	96.4	32.17	10.56	33.2	198	21	A	V
		5850	54.61	-67.59	122.2	44.94	32.3	10.59	33.22	198	21	P	V
		5874.25	56	-49.41	105.41	46.23	32.4	10.6	33.23	198	21	P	V
		5880.5	54.53	-46.58	101.11	44.74	32.42	10.6	33.23	198	21	P	V
		5933.25	53.86	-14.34	68.2	43.92	32.57	10.62	33.25	198	21	P	V
													V
													V



WiFi Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11a CH 165 5825MHz	*	5825	112.1	-	-	102.48	32.25	10.58	33.21	219	268	P	H	
	*	5825	104.89	-	-	95.27	32.25	10.58	33.21	219	268	A	H	
		5852.2	61.14	-56.04	117.18	51.46	32.31	10.59	33.22	219	268	P	H	
		5855	60.12	-50.68	110.8	50.43	32.32	10.59	33.22	219	268	P	H	
		5884.8	54.35	-43.57	97.92	44.54	32.44	10.6	33.23	219	268	P	H	
		5929.6	52.1	-16.1	68.2	42.17	32.56	10.62	33.25	219	268	P	H	
														H
														H
	*	5825	113.54	-	-	103.92	32.25	10.58	33.21	221	22	22	P	V
	*	5825	106.38	-	-	96.76	32.25	10.58	33.21	221	22	22	A	V
		5851.2	64.16	-55.3	119.46	54.49	32.3	10.59	33.22	221	22	22	P	V
		5855.6	61.79	-48.84	110.63	52.1	32.32	10.59	33.22	221	22	22	P	V
		5879.4	54.96	-46.97	101.93	45.17	32.42	10.6	33.23	221	22	22	P	V
		5926.4	53.52	-14.68	68.2	43.6	32.55	10.62	33.25	221	22	22	P	V
														V
														V
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	54.39	-19.61	74	53.77	39.7	17.23	56.31	208	48	P	H
		11490	43.83	-10.17	54	43.21	39.7	17.23	56.31	208	48	A	H
		17235	48.63	-19.57	68.2	42.63	40.51	22.06	56.57	100	0	P	H
													H
		11490	54.62	-19.38	74	54	39.7	17.23	56.31	283	4	P	V
		11490	43.73	-10.27	54	43.11	39.7	17.23	56.31	283	4	A	V
		17235	48.73	-19.47	68.2	42.73	40.51	22.06	56.57	100	0	P	V
802.11a CH 157 5785MHz		11570	53.64	-20.36	74	53.11	39.49	17.34	56.3	205	46	P	H
		11570	43	-11	54	42.47	39.49	17.34	56.3	205	46	A	H
		17355	48.53	-19.67	68.2	42.17	40.98	22.18	56.8	100	0	P	H
													H
		11570	54.81	-19.19	74	54.28	39.49	17.34	56.3	255	9	P	V
		11570	43.89	-10.11	54	43.36	39.49	17.34	56.3	255	9	A	V
		17355	48.88	-19.32	68.2	42.52	40.98	22.18	56.8	100	0	P	V
802.11a CH 165 5825MHz		11650	49.79	-24.21	74	49.43	39.2	17.46	56.3	100	0	P	H
		17475	49.9	-18.3	68.2	43.06	41.58	22.29	57.03	100	0	P	H
													H
													H
		11650	53.14	-20.86	74	52.78	39.2	17.46	56.3	248	9	P	V
		11650	42.31	-11.69	54	41.95	39.2	17.46	56.3	248	9	A	V
		17475	49.07	-19.13	68.2	42.23	41.58	22.29	57.03	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ac VHT20 CH 149 5745MHz		5633.8	54.13	-14.07	68.2	45.07	31.73	10.48	33.15	225	269	P	H	
		5669.8	56.56	-26.33	82.89	47.4	31.82	10.5	33.16	225	269	P	H	
		5716.4	64.48	-45.31	109.79	55.11	32.03	10.52	33.18	225	269	P	H	
		5725	72.87	-49.33	122.2	63.47	32.05	10.53	33.18	225	269	P	H	
	*	5745	112.46	-	-	103.02	32.09	10.54	33.19	225	269	P	H	
	*	5745	104.39	-	-	94.95	32.09	10.54	33.19	225	269	A	H	
														H
														H
			5648	54.87	-13.33	68.2	45.84	31.7	10.49	33.16	191	19	P	V
			5699.6	56.06	-48.85	104.91	46.72	32	10.51	33.17	191	19	P	V
			5719.6	64.88	-45.81	110.69	55.49	32.04	10.53	33.18	191	19	P	V
			5725	74.72	-47.48	122.2	65.32	32.05	10.53	33.18	191	19	P	V
	*		5745	113.11	-	-	103.67	32.09	10.54	33.19	191	19	P	V
	*		5745	105.68	-	-	96.24	32.09	10.54	33.19	191	19	A	V
													V	
													V	



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5610.25	54.26	-13.94	68.2	45.16	31.78	10.47	33.15	228	266	P	H
		5697	55.49	-47.5	102.99	46.17	31.98	10.51	33.17	228	266	P	H
		5718.5	55.77	-54.61	110.38	46.38	32.04	10.53	33.18	228	266	P	H
		5721.5	55.71	-58.51	114.22	46.32	32.04	10.53	33.18	228	266	P	H
	*	5785	112.01	-	-	102.48	32.17	10.56	33.2	228	266	P	H
	*	5785	103.75	-	-	94.22	32.17	10.56	33.2	228	266	A	H
		5852.25	52.1	-64.97	117.07	42.42	32.31	10.59	33.22	228	266	P	H
		5865	52.27	-55.73	108	42.54	32.36	10.6	33.23	228	266	P	H
		5914	53.76	-22.55	76.31	43.85	32.53	10.62	33.24	228	266	P	H
		5935	51.38	-16.82	68.2	41.44	32.57	10.62	33.25	228	266	P	H
802.11ac													H
VHT20													H
CH 157		5650	55.15	-13.05	68.2	46.12	31.7	10.49	33.16	221	22	P	V
5785MHz		5695.5	55.26	-46.62	101.88	45.95	31.97	10.51	33.17	221	22	P	V
		5715.75	56.12	-53.49	109.61	46.75	32.03	10.52	33.18	221	22	P	V
		5720.25	56.26	-55.11	111.37	46.87	32.04	10.53	33.18	221	22	P	V
	*	5785	113.01	-	-	103.48	32.17	10.56	33.2	221	22	P	V
	*	5785	105.09	-	-	95.56	32.17	10.56	33.2	221	22	A	V
		5850.5	55.21	-65.85	121.06	45.54	32.3	10.59	33.22	221	22	P	V
		5856.25	55.63	-54.82	110.45	45.93	32.33	10.59	33.22	221	22	P	V
		5875.75	55.71	-48.93	104.64	45.94	32.4	10.6	33.23	221	22	P	V
		5937.25	53.58	-14.62	68.2	43.64	32.57	10.62	33.25	221	22	P	V
													V
													V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ac VHT20 CH 165 5825MHz	*	5825	111.57	-	-	101.95	32.25	10.58	33.21	219	266	P	H	
	*	5825	103.64	-	-	94.02	32.25	10.58	33.21	219	266	A	H	
		5850.4	63.36	-57.93	121.29	53.69	32.3	10.59	33.22	219	266	P	H	
		5856.4	59.39	-51.02	110.41	49.69	32.33	10.59	33.22	219	266	P	H	
		5906.8	54.51	-27.12	81.63	44.63	32.51	10.61	33.24	219	266	P	H	
		5925.2	53.54	-14.66	68.2	43.62	32.55	10.62	33.25	219	266	P	H	
														H
														H
	*	5825	113.58	-	-	103.96	32.25	10.58	33.21	222	23	P	V	
	*	5825	105.7	-	-	96.08	32.25	10.58	33.21	222	23	A	V	
		5850.6	65.2	-55.63	120.83	55.53	32.3	10.59	33.22	222	23	P	V	
		5855.6	60.42	-50.21	110.63	50.73	32.32	10.59	33.22	222	23	P	V	
		5891.6	56.56	-36.32	92.88	46.72	32.47	10.61	33.24	222	23	P	V	
		5930	55.53	-12.67	68.2	45.6	32.56	10.62	33.25	222	23	P	V	
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ac VHT20 CH 149 5745MHz		11490	49.7	-24.3	74	49.08	39.7	17.23	56.31	100	0	P	H	
		17235	49.17	-19.03	68.2	43.17	40.51	22.06	56.57	100	0	P	H	
													H	
													H	
			11490	53.77	-20.23	74	53.15	39.7	17.23	56.31	256	0	P	V
			11490	42.84	-11.16	54	42.22	39.7	17.23	56.31	256	0	A	V
			17235	48.65	-19.55	68.2	42.65	40.51	22.06	56.57	100	0	P	V
802.11ac VHT20 CH 157 5785MHz													V	
			11570	49.05	-24.95	74	48.52	39.49	17.34	56.3	100	0	P	H
			17355	47.29	-20.91	68.2	40.93	40.98	22.18	56.8	100	0	P	H
													H	
													H	
			11570	53.63	-20.37	74	53.1	39.49	17.34	56.3	253	8	P	V
			11570	42.4	-11.6	54	41.87	39.49	17.34	56.3	253	8	A	V
802.11ac VHT20 CH 165 5825MHz													V	
			11650	49.03	-24.97	74	48.67	39.2	17.46	56.3	100	0	P	H
			17475	50.68	-17.52	68.2	43.84	41.58	22.29	57.03	100	0	P	V
													H	
													H	
			11650	52.92	-21.08	74	52.56	39.2	17.46	56.3	248	7	P	V
			11650	42.14	-11.86	54	41.78	39.2	17.46	56.3	248	7	A	V
Remark		17475	48.65	-19.55	68.2	41.81	41.58	22.29	57.03	100	0	P	V	
													V	
1. No other spurious found. 2. All results are PASS against Peak and Average limit line.														



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5644.75	51.62	-16.58	68.2	42.59	31.71	10.48	33.16	287	43	P	H
		5699.25	52.44	-52.21	104.65	43.1	32	10.51	33.17	287	43	P	H
		5713	62.56	-46.28	108.84	53.19	32.03	10.52	33.18	287	43	P	H
		5724	65.12	-54.8	119.92	55.72	32.05	10.53	33.18	287	43	P	H
	*	5755	104.8	-	-	95.33	32.11	10.55	33.19	287	43	P	H
	*	5755	97.02	-	-	87.55	32.11	10.55	33.19	287	43	A	H
		5852	52.73	-64.91	117.64	43.05	32.31	10.59	33.22	287	43	P	H
		5875	51.1	-54.1	105.2	41.33	32.4	10.6	33.23	287	43	P	H
		5880.75	51.88	-49.05	100.93	42.09	32.42	10.6	33.23	287	43	P	H
		5928	50.75	-17.45	68.2	40.82	32.56	10.62	33.25	287	43	P	H
													H
													H
802.11ac													
VHT40													
CH 151		5625	51.42	-16.78	68.2	42.35	31.75	10.47	33.15	203	19	P	V
5755MHz		5696.25	53.04	-49.4	102.44	43.72	31.98	10.51	33.17	203	19	P	V
		5719.25	65.37	-45.22	110.59	55.98	32.04	10.53	33.18	203	19	P	V
		5724.75	66.76	-54.87	121.63	57.36	32.05	10.53	33.18	203	19	P	V
	*	5755	105.89	-	-	96.42	32.11	10.55	33.19	203	19	P	V
	*	5755	97.56	-	-	88.09	32.11	10.55	33.19	203	19	A	V
		5850	50.23	-71.97	122.2	40.56	32.3	10.59	33.22	203	19	P	V
		5872.5	52.4	-53.5	105.9	42.64	32.39	10.6	33.23	203	19	P	V
		5893.5	51.22	-40.25	91.47	41.38	32.47	10.61	33.24	203	19	P	V
		5942.75	51.5	-16.7	68.2	41.53	32.59	10.63	33.25	203	19	P	V
													V
													V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5637.75	51.57	-16.63	68.2	42.52	31.72	10.48	33.15	279	44	P	H
		5692.5	52.35	-47.32	99.67	43.06	31.95	10.51	33.17	279	44	P	H
		5715	52.35	-57.05	109.4	42.98	32.03	10.52	33.18	279	44	P	H
		5720.75	52.12	-60.39	112.51	42.73	32.04	10.53	33.18	279	44	P	H
	*	5795	104.53	-	-	94.97	32.19	10.57	33.2	279	44	P	H
	*	5795	96.79	-	-	87.23	32.19	10.57	33.2	279	44	A	H
		5851.5	52.14	-66.64	118.78	42.46	32.31	10.59	33.22	279	44	P	H
		5868.5	52.15	-54.87	107.02	42.41	32.37	10.6	33.23	279	44	P	H
		5889.75	52.65	-41.6	94.25	42.81	32.46	10.61	33.23	279	44	P	H
		5927.75	52.3	-15.9	68.2	42.37	32.56	10.62	33.25	279	44	P	H
802.11ac													H
VHT40													H
CH 159		5639.5	50.96	-17.24	68.2	41.91	31.72	10.48	33.15	202	20	P	V
5795MHz		5655.75	52.73	-19.74	72.47	43.67	31.73	10.49	33.16	202	20	P	V
		5700.5	52.47	-52.87	105.34	43.12	32	10.52	33.17	202	20	P	V
		5723.25	51.54	-66.67	118.21	42.14	32.05	10.53	33.18	202	20	P	V
	*	5795	105.61	-	-	96.05	32.19	10.57	33.2	202	20	P	V
	*	5795	97.58	-	-	88.02	32.19	10.57	33.2	202	20	A	V
		5854.75	51.98	-59.39	111.37	42.29	32.32	10.59	33.22	202	20	P	V
		5865.25	51.83	-56.1	107.93	42.1	32.36	10.6	33.23	202	20	P	V
		5897.75	52.48	-35.85	88.33	42.62	32.49	10.61	33.24	202	20	P	V
		5940.75	51.83	-16.37	68.2	41.87	32.58	10.63	33.25	202	20	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ac VHT40 CH 151 5755MHz		11510	47.57	-26.43	74	46.95	39.67	17.25	56.3	100	0	P	H	
		17265	48.21	-19.99	68.2	42.15	40.6	22.09	56.63	100	0	P	H	
													H	
													H	
			11510	47.45	-26.55	74	46.83	39.67	17.25	56.3	100	0	P	V
			17265	49.1	-19.1	68.2	43.04	40.6	22.09	56.63	100	0	P	V
														V
802.11ac VHT40 CH 159 5795MHz		11590	48.2	-25.8	74	47.7	39.43	17.37	56.3	100	0	P	H	
		17385	48.14	-20.06	68.2	41.69	41.12	22.2	56.87	100	0	P	H	
													H	
													H	
			11590	47.29	-26.71	74	46.79	39.43	17.37	56.3	100	0	P	V
			17385	48.83	-19.37	68.2	42.38	41.12	22.2	56.87	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5620	51.04	-17.16	68.2	41.96	31.76	10.47	33.15	267	45	P	H
		5694	55.64	-45.14	100.78	46.34	31.96	10.51	33.17	267	45	P	H
		5713.5	60.29	-48.69	108.98	50.92	32.03	10.52	33.18	267	45	P	H
		5723	60.04	-57.6	117.64	50.64	32.05	10.53	33.18	267	45	P	H
	*	5775	100.75	-	-	91.24	32.15	10.56	33.2	267	45	P	H
	*	5775	92.92	-	-	83.41	32.15	10.56	33.2	267	45	A	H
		5853.25	52.9	-61.89	114.79	43.22	32.31	10.59	33.22	267	45	P	H
		5858	52.03	-57.93	109.96	42.33	32.33	10.59	33.22	267	45	P	H
		5911.5	50.15	-28.01	78.16	40.26	32.52	10.61	33.24	267	45	P	H
		5930.25	50.89	-17.31	68.2	40.96	32.56	10.62	33.25	267	45	P	H
													H
													H
802.11ac VHT80 CH 155 5775MHz		5647.75	52.25	-15.95	68.2	43.22	31.7	10.49	33.16	200	20	P	V
		5700	56.5	-48.7	105.2	47.16	32	10.51	33.17	200	20	P	V
		5714.5	60.82	-48.44	109.26	51.45	32.03	10.52	33.18	200	20	P	V
		5720.5	60.12	-51.82	111.94	50.73	32.04	10.53	33.18	200	20	P	V
	*	5775	100.81	-	-	91.3	32.15	10.56	33.2	200	20	P	V
	*	5775	92.58	-	-	83.07	32.15	10.56	33.2	200	20	A	V
		5850.75	55.48	-65.01	120.49	45.81	32.3	10.59	33.22	200	20	P	V
		5866	55.33	-52.39	107.72	45.6	32.36	10.6	33.23	200	20	P	V
		5903	52.35	-32.09	84.44	42.47	32.51	10.61	33.24	200	20	P	V
		5928.75	51.01	-17.19	68.2	41.08	32.56	10.62	33.25	200	20	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ac VHT80 CH 155 5775MHz		11550	47.38	-26.62	74	46.82	39.55	17.31	56.3	100	0	P	H	
		17325	48.92	-19.28	68.2	42.67	40.83	22.15	56.73	100	0	P	H	
													H	
													H	
			11550	47.49	-26.51	74	46.93	39.55	17.31	56.3	100	0	P	V
			17325	47.92	-20.28	68.2	41.67	40.83	22.15	56.73	100	0	P	V
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission below 1GHz
5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
5GHz 802.11a LF		137.67	32.19	-11.31	43.5	45.74	17.18	1.56	32.29	-	-	P	H	
		140.58	32.3	-11.2	43.5	45.89	17.13	1.57	32.29	-	-	P	H	
		384.05	38.71	-7.29	46	47.16	21.05	2.66	32.16	100	0	P	H	
		937.92	32.66	-13.34	46	29.52	29.85	4.29	31	-	-	P	H	
		951.5	33.13	-12.87	46	29.06	30.64	4.31	30.88	-	-	P	H	
		956.35	33.35	-12.65	46	29	30.85	4.33	30.83	-	-	P	H	
														H
														H
														H
														H
														H
														H
			72.68	26.34	-13.66	40	45.22	12.3	1.17	32.35	-	-	P	V
			130.88	30.18	-13.32	43.5	43.7	17.26	1.52	32.3	-	-	P	V
			140.58	28.88	-14.62	43.5	42.47	17.13	1.57	32.29	-	-	P	V
			890.39	32.22	-13.78	46	30.41	29.04	4.17	31.4	-	-	P	V
			951.5	33.07	-12.93	46	29	30.64	4.31	30.88	-	-	P	V
			955.38	33.47	-12.53	46	29.18	30.81	4.32	30.84	100	0	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Bill Kuo, Fu Chen and Troye Hsie	Temperature :	21.3~27.3°C
		Relative Humidity :	48.7~65.9%

Note symbol



-L	Low channel location
-R	High channel location



Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Fundamental
Peak	<p> Date: 2019-08-11 PEAK_BE(84)_TC(3) </p> <p> Site : 03CH11-HY Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333 </p>	<p> Date: 2019-08-11 PEAK(UN)B </p> <p> Site : 03CH11-HY Condition : PEAK(UN)I 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333 </p>
	<p> Date: 2019-08-11 PEAK(UN)B </p> <p> Site : 03CH11-HY Condition : PEAK(UN)I 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333 </p>	<p> Date: 2019-08-11 PEAK(UN)B </p> <p> Site : 03CH11-HY Condition : PEAK(UN)I 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333 </p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Vertical	Fundamental
<p>Peak</p>	 <p>Date: 2019-08-11 PEAK_BE(49)_15.20</p> <p>Site : 03CH11-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	 <p>Date: 2019-08-11 PEAK(UN)I</p> <p>Site : 03CH11-HY Condition : PEAK(UN)I] 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Fundamental
Peak		
Peak		Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Fundamental
<p>Peak</p>	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNI) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>



Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VSW:3000.000KHz SWT:Auto Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNI) 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VSW:3000.000KHz SWT:Auto Project : 972333</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1	Vertical	Fundamental
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK_UNI(I) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 972333</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	 <p>Site : 03CH11-HY Condition : PEAK(U)B 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1	Vertical	Fundamental
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	 <p>Site : 03CH11-HY Condition : PEAK(U)B 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNIT) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 972333</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(FUNB)_802.11 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(FUNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	Left blank



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNB) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(FUNB) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 972333</p>	Left blank





Band 4 - 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-4FY Condition : PEAK(UNII) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	<p>Site : 03CH11-4FY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	 <p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>





Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK(LINE) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(LINE) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Date: 2019-08-14</p> <p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>	 <p>Date: 2019-08-14</p> <p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>



**Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH151 5755MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK(LINE) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(LINE) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Date: 2019-08-14</p> <p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	 <p>Date: 2019-08-14</p> <p>Site : 03CH11-HY Condition : PEAK(UNED) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>





**Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : PEAK(LINE) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 972333</p>	<p>Site : 03CH11-HY Condition : PEAK(LINE) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 972333</p>



Emission below 1GHz
5GHz WIFI 802.11a (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11a LF	
1	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH11-4FY Condition : QP_3m BT-LOG 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 972333</p>	 <p>Site : 03CH11-4FY Condition : QP_3m BT-LOG 6111D-LF_ETC VERTICAL Detector : Peak Project : 972333</p>




Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1	802.11a	100.00	-	-	10Hz	0.00
1	5GHz 802.11n HT20	100.00	-	-	10Hz	0.00
1	5GHz 802.11n HT40	100.00	-	-	10Hz	0.00
1	5GHz 802.11ac VHT20	100.00	-	-	10Hz	0.00
1	5GHz 802.11ac VHT40	100.00	-	-	10Hz	0.00
1	5GHz 802.11ac VHT80	100.00	-	-	10Hz	0.00




802.11a



Date: 7.AUG.2019 05:21:32


802.11n HT20



Date: 7.AUG.2019 05:22:48




802.11n HT40



Date: 7.AUG.2019 05:25:15


802.11ac VHT20



Date: 7.AUG.2019 05:23:54




802.11ac VHT40



Date: 7.AUG.2019 05:37:30

802.11ac VHT80



Date: 7.AUG.2019 05:27:02

————THE END————