

Global EMC Inc. Labs EMC & RF Test Report

As per

RSS 247 Issue 1:2015

&

FCC Part 15 Subpart C: 2014

Unlicensed Intentional Radiators

on the

Si



Min Xie
Project Engineer
11 Gordon Collins Dr,
Gormley, ON, L0H 1G0 Canada
Ph: (905) 883-8189

Testing produced for



See Appendix A for full customer & EUT details.





Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Table of Contents

Table of Contents	2
Report Scope	3
Summary	4
Test Results Summary	5
Justifications, Descriptions, or Deviations.....	6
Applicable Standards, Specifications and Methods.....	7
Sample calculation(s).....	8
Document Revision Status.....	8
Definitions and Acronyms	9
Testing Facility	10
Calibrations and Accreditations.....	10
Testing Environmental Conditions and Dates	11
Detailed Test Results Section	12
6dB Bandwidth of Digitally Modulated Systems – 15.247	13
Maximum Peak Envelope Conducted Power - DM.....	24
Antenna Spurious Conducted Emissions (-20 dBc Requirement) – 15.247.....	29
Radiated Emissions – 15.247.....	36
Power Spectral Density – 15.247 DM	81
Maximum Permissible Exposure – 15.247	86
Power Line Conducted Emissions	87
Appendix A – EUT Summary.....	93
Appendix B – EUT and Test Setup Photographs.....	96

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Report Scope

This report addresses the EMC verification testing and test results of Ecobee Inc's **Si**, herein referred to as EUT (Equipment Under Test) performed at Global EMC Labs.

The EUT was tested for compliance against the following standards:


RSS 247 Issue 1:2014
FCC Part 15 Subpart C 15:2015

Test procedures, results, justifications, and engineering considerations, if any, follow later in this report.

The results contained in this report relate only to the item(s) tested.

This report does not imply product endorsement by A2LA or any other accreditation agency, any government, or Global EMC Inc.


Opinions/interpretations expressed in this report, if any, are outside the scope of Global EMC Inc accreditation. Any opinions expressed do not necessarily reflect the opinions of Global EMC Inc, unless otherwise stated.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Summary

The results contained in this report relate only to the item(s) tested.

EUT FCC Certification #, FCC ID:	WR9EBSTATSI01
EUT Industry Canada Certification #, IC:	7981A-EBSTATSI01
EUT Passed all tests performed.	Yes (see test results summary)
Tests conducted by	Min Xie


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Test Results Summary

Standard/Method	Description	Class/Limit	Result
FCC 15.203	Antenna Requirement	Unique	Pass See Justification
FCC 15.205 RSS-GEN (Table 3)	Restricted Bands for intentional operation	QuasiPeak Average	Pass
FCC 15.207 RSS-GEN (Table 3)	Power line conducted emissions	QuasiPeak Average	Pass
FCC 15.209 RSS-GEN (Table 4)	Spurious Radiated emissions	QuasiPeak Average	Pass
FCC 15.247(a)2 RSS-247 (5.2)	6 dB Bandwidth	> 500 kHz	Pass
FCC 15.247(b)2 RSS-247 (5.4)	Max output power	< 1 Watt	Pass
FCC 15.247(b)4 RSS-247 (5.4)	Antenna Gain	< 6 dBi	Pass See Justifications
FCC 15.247(d) RSS-247 (5.5)	Antenna conducted spurious	< 20 dBc	Pass
FCC 15.247(e) RSS-247 (5.2)	Spectral Density	< 8 dBm (3 kHz BW)	Pass
FCC 15.247(i) RSS-102	Maximum Permissible Exposure	> 20 cm separation.	Pass See justification and calculations
Overall Result			PASS

All tests were performed by Min Xie.

If the product as tested or otherwise complies with the specification, the EUT is deemed to comply with the requirement and is deemed a 'PASS' grade. If not 'FAIL' grade will be issued. Note that 'PASS' / 'FAIL' grade is independent of any measurement uncertainties. A 'PASS' / 'FAIL' grade within measurement uncertainty is marked with a '*'.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Justifications, Descriptions, or Deviations

The following justifications for tests not performed or deviations from the above listed specifications apply:

For the Antenna requirement specified in FCC 15.203 (RSS 210 section A8.4(5)), the unit uses a permanently connected SMD antenna (2.1 dBi gain – Antenova Rufa 2.4 GHz SMD Antenna) which is less than 6 dBi gain.

For the Restricted Bands of operation, the EUT is designed to only operate between 2400 – 2483.5 MHz band.

For maximum permissible exposure, this device operates at less than 1 Watt at 2400 – 2483.5 MHz and is designed to operate greater than 20 cm from any personnel during normal operation. No testing is required, however worst case calculated exposure compliance follows later in this report.

The EUT is not a hybrid system and FCC 15.247 (f) does not apply to it. However the 15.247 (d) requirement of power density were met and are detailed later in this test report.

For the scope of this test report the EUT was mounted in three orthogonal axes to maximize emissions. Worst case results are presented.


The device contains two transmitters; the current 15.247 device operating 802.11B, G, and N protocols, and a modularly certified 15.247 2.4 GHz DTS transmitter with FCC ID: DI2CT-EM2606. Each transmitter have its' own antenna. Antenna co-location testing was performed on the device to verify compliance with 15.247(d) radiated emission requirements.

During the time of testing, RSS-247 was not publish. Therefore the EUT was test performed to the requirements of RSS-210. There are no differences between the two standards for a DTS system operating in the 2400 – 2483.5 MHz band. The EUT meets all the requirements of RSS-247. See test summary for further details.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Applicable Standards, Specifications and Methods

ANSI C63.4:2014	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10:2013	American national standard for testing unlicensed wireless devices
CFR 47 FCC 15	Code of Federal Regulations – Radio Frequency Devices
CISPR 22:2008	Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement
FCC KDB 558074	FCC KDB 558074 Digital Transmission Systems, measurements and procedures
ICES-003:2012	Digital Apparatus - Spectrum Management and Telecommunications Policy Interference-Causing Equipment Standard
ISO 17025:2005	General Requirements for the competence of testing and calibration laboratories
RSS-GEN Issue 4	General Requirements and Information for the Certification of Radio Apparatus
RSS 210 Issue 8	Spectrum Management and Telecommunications Policy. Radio Standards Specification Low Power License-Exempt Radiocommunication Devices
RSS 210 Issue 8	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSS) and Licence-Exempt Local Area Network (LE-LAN) Devices
RSS 102 Issue 5	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Sample calculation(s)

Margin = limit – (received signal + antenna factor + cable loss – pre-amp gain)


Margin = 50.5dBuV/m – (50dBuV + 10dB + 2.5dB – 20dB)

Margin = 8.5 dB

Document Revision Status

Revision 1 - July 23, 2015
Initial release

Revision 2 March 3, 2016
Revised according TCB reviewers comments.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Definitions and Acronyms

The following definitions and acronyms are applicable in this report.
See also ANSI C63.14.

AE – Auxillary Equipment.

BW – Bandwidth. Unless otherwise stated, this is refers to the 6 dB bandwidth.

EMC – Electro-Magnetic Compatibility

EMI – Electro-Magnetic Immunity

EUT – Equipment Under Test

ITE – Information Technology Equipment with a primary function(s) of entry, storage, display, retrieval, transmission, processing, switching, or control, of data.

LISN – Line impedance stabilization network

NCR – No Calibration Required

RF – Radio Frequency


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Testing Facility

Testing for EMC on the EUT was carried out at Global EMC labs in Toronto, Ontario, Canada. The testing lab consists of a 3m semi-anechoic chamber calibrated to be able to allow measurements on an EUT with a maximum width or length of up to 2m and height up to 3m. The chamber is equipped with a turn table that is capable of testing devices up to 3300lb in weight. This facility is capable of testing products that are rated for 120 Vac and 240Vac single phase, or 208 Vac 3 phase input. DC capability is also available. The chamber is equipped with an antenna mast that controls polarization and height from the control room adjoining the shielded chamber. Radiated emissions measurements are performed using a Bilog and Horn antenna where applicable. Conducted emissions, unless otherwise stated, are performed using a LISN.

Calibrations and Accreditations


The 3m semi-anechoic chamber is registered with Federal Communications Commission (FCC, 377448), Industry Canada (IC, 6844A-3) and VCCI (R-4023, G-506, T-1246, and C-4498). This semi-anechoic chamber complies with the requirements of EN55016-2-3:2006, section 7.5 and the site attenuation requirements of EN55016-1-4. This chamber was additionally calibrated for Normalized Site Attenuation (NSA) using test procedures outlined in ANSI C63.4 “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz”. The chamber is lined with ferrite tiles and absorption cones to minimize any undesired reflections. The NSA data is kept on file at Global EMC. For radiated susceptibility testing, a 16 point field calibration has been performed on the chamber. The field uniformity data is kept on file at Global EMC. Global EMC Inc is accredited to ISO 17025 by A2LA with Testing Certificate #2555.01. The laboratories current scope of accreditation listing can be found as listed on the A2LA website. All measuring equipment is calibrated on an annual or bi-annual basis as listed for each respective test.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Testing Environmental Conditions and Dates

Following were the environmental conditions in the facility during time of testing –

Date	Test	Init.	Temperature (°C)	Humidity (%)	Pressure (kPa)
2015/4/29 to 2015/5/1	Radiated emission	MX	20-24°C	39 - 50%	96 -102kPa
2015/5/7	Antenna conducted	MX	20-24°C	39 - 50%	96 -102kPa
2015/5/7	Power line conducted	MX	20-24°C	39 - 50%	96 -102kPa

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Detailed Test Results Section

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

6dB Bandwidth of Digitally Modulated Systems – 15.247

Purpose

The purpose of this test is to ensure that the bandwidth occupied exceeds a stated minimum. This helps ensure the utilization of the frequency allocation is sufficiently wide. This also helps prevent corruption of data by ensuring adequate data separation to distinguish the reception of the intended information.

Limits and Methods

The Limit is as specified in FCC Part 15 and RSS 210.

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz. This should be measured with a 100 kHz RBW and a 300 kHz VBW.

The method is given in Section 8.1 of FCC KDB 558074.

Results

The EUT passed. The minimum measured 6 dB BW was:


B-Mode	10.3 MHz
G-Mode	16.6 MHz
N-Mode	16.7 MHz

And the minimum measured 20 dB BW was:

B-Mode	16.0 MHz
G-Mode	19.9 MHz
N-Mode	22.5 MHz

99% Bandwidth


B-Mode	13.97 MHz
G-Mode	16.92 MHz
N-Mode	18.44 MHz

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Graph(s)

The graphs showed below shows the OBW during the operation of the device. This is measured by a max hold on the spectrum analyzer and the highest resolution bandwidth that is sufficiently low to exhibit the 6 dB bandwidth of a channel during operation of the EUT. This measurement is a peak measurement. Max hold is performed for a duration of not less than 1 minute.

B-Protocol, Hi Channel




Date: 7.MAY.2015 14:04:28

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

B-Protocol, Mid Channel




Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz M1[1] -9.40 dBm
 Ref 12.5 dBm SWT 2.5ms 2.431810000 GHz



CF 2.437 GHz

Span 25.0 MHz


Date: 7.MAY.2015 13:45:53

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B-Protocol, Low Channel



Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz **M1[1]** -9.31 dBm
 Ref 12.5 dBm SWT 2.5ms **2.417090000 GHz**




Date: 7.MAY.2015 13:59:42

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G-Protocol, Hi Channel



Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz M1[1] -8.04 dBm
 Ref 12.5 dBm SWT 2.5ms 2.470296000 GHz




Date: 7.MAY.2015 13:12:06

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

G-Protocol, Mid Channel




Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz M1[1] -5.41 dBm
 Ref 12.5 dBm SWT 2.5ms 2.428671000 GHz



CF 2.436967 GHz Span 25.5 MHz


Date: 7.MAY.2015 12:58:20

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G-Protocol, Low Channel



Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz M1[1] -9.42 dBm
 Ref 10.5 dBm SWT 2.5ms 2.420296000 GHz




Date: 7.MAY.2015 12:41:52

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

N-Protocol, Hi Channel




Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz M1[1] -5.02 dBm
 Ref 10.5 dBm SWT 5ms 2.470280000 GHz



CF 2.462 GHz

Span 50.0 MHz


Date: 7.MAY.2015 10:17:19

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

N-Protocol, Mid Channel




Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz M1[1] -8.96 dBm
 Ref 10.5 dBm SWT 5ms 2.445320000 GHz



CF 2.436937 GHz

Span 40.0 MHz


Date: 7.MAY.2015 10:40:43

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

N-Protocol, Low Channel




Offs 12.5 dB * RBW 100 kHz
 Att 20 dB VBW 300 kHz M1[1] -9.65 dBm
 Ref 10.5 dBm SWT 5ms 2.403622000 GHz



Date: 7.MAY.2015 11:07:23


Note: See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration /Verification date	Next calibration/Verification due date	Asset #
Spectrum Analyzer	ESL6	Rohde & Schwarz	Nov-15, 2013	Nov-15, 2015	GEMC 160
Attenuator 10 dB	8493B	Agilent	Feb-11, 2015	Feb-11, 2016	GEMC133
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	Feb-10, 2015	Feb-10, 2016	GEMC 29

This report module is based on GEMC template "FCC – Power Line Conducted Emissions Class B_Rev1"

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Maximum Peak Envelope Conducted Power - DM

Purpose

The purpose of this test is to ensure that the maximum power conducted to the radiating element does not exceed the limits specified. This ensures that if the end-user replaces the antenna, that the maximum power does not exceed an amount which may create an excessive power level.

Limits and Methods

The limits are defined in FCC Part 15.247(b) and RSS 210.


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands, the peak limit is 1 watt.

The method is given in Section 9.1.2 of FCC KDB 558074: June 5, 2014.

Results


The EUT passed. The power of the EUT was set to transmit at maximum power. Three Channels 1, 6, and 11 were measured for each Protocol. The following tables show the peak power:

B Protocol						
Channel	Frequency (MHz)	Power (dBm) (raw)	Attenuator (dB)	Cable loss (dB)	Peak Power (dBm)	Peak Power (mW)
Lo Channel (1)	2412	-2.15	10	1.5	9.4	8.6
Mid Channel (6)	2437	-1.33	10	1.5	10.2	10.4
Hi Channel (11)	2462	-1.55	10	1.5	10.0	9.9

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

G Protocol						
Channel	Frequency (MHz)	Power (dBm) (raw)	Attenuator (dB)	Cable loss (dB)	Peak Power (dBm)	Peak Power (mW)
Lo Channel (1)	2412	4.13	10	1.5	15.6	36.6
Mid Channel (6)	2437	5.60	10	1.5	17.1	51.3
Hi Channel (11)	2462	5.53	10	1.5	17.0	50.5

N Protocol						
Channel	Frequency (MHz)	Power (dBm) (raw)	Attenuator (dB)	Cable loss (dB)	Peak Power (dBm)	Peak Power (mW)
Lo Channel (1)	2412	4.30	10	1.5	15.8	38.0
Mid Channel (6)	2437	5.75	10	1.5	17.3	53.1
Hi Channel (11)	2462	5.68	10	1.5	17.2	52.2

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Readings

The photos shown below shows the peak power output of the device during the antenna conducted measurement during transmit operation of the EUT.

Tests were conducted using a power meter.



Figure 1: Power reading of B Protocol, Mid channel - photo


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	



Figure 2: Power reading of G Protocol, Mid channel – photo


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	




Figure 3: Power reading of N Protocol, Mid channel – photo

Note: See ‘Appendix B – EUT & Test Setup Photographs’ for photos showing the test set-up.

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration/ Verification date	Next calibration/ Verification due date	Asset #
Power Head	PH 2000	AR	Jan-22, 2015	Jan-22, 2017	GEMC 15
Power meter	PM 2002	AR	Jan-21, 2015	Jan-21, 2017	GEMC 16
Attenuator 10 dB	8493B	Agilent	Feb-11, 2015	Feb-11, 2016	GEMC133
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	Feb-10, 2015	Feb-10, 2016	GEMC 29

This report module is based on GEMC template “FCC – Power Line Conducted Emissions Class B_Rev1”

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Antenna Spurious Conducted Emissions (-20 dBc Requirement) – 15.247

Purpose

The purpose of this test is to ensure that the maximum power conducted to the radiating element at frequencies outside of the authorized spectrum does not exceed the limits specified. This ensures that the only the intended signal is delivered to the radiating element.


Limits and Methods

The limits are defined in 15.247(d). In any 100 kHz band, the peak spurious harmonics emissions must be at least 20 dB below the fundamental. Spurious Conducted emissions are to be evaluated up to the 10th harmonic. This -20 dBc requirement also applies at the ‘band edge’ or 2.4 GHz and 2.4835 GHz.

The method is given in Section 11 of FCC KDB 558074: June 5, 2014.


Results


The EUT passed the limits. B, G and N protocols are measured; low, middle and high channels were measured for each Protocol. The worst case was presented as a graph for the spectrum. The -20 dBc requirement is shown for the lower band edge at 2.4 GHz in the low band. The -20 dBc requirement is also shown for the higher band edge at 2.4835 GHz in the high band.


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Graph(s)

The graphs shown below shows the peak power output of the device during the antenna conducted measurement during transmit operation of the EUT.




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	



Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G- Protocol: -20 dBc

Reference level: 0.68 dBm




Date: 7.MAY.2015 13:01:08

2400 MHz Bandedge





Date: 7.MAY.2015 13:17:59

2483.5 MHz Bandedge





Date: 7.MAY.2015 13:16:00


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	



Client	Ecobee Inc
Product	Si
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015



Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	




Note: See ‘Appendix B – EUT & Test Setup Photographs’ for photos showing the test set-up.

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Spectrum Analyzer	8566B	HP	Oct-9, 2014	Oct-9, 2016	GEMC 193
Quasi Peak Adapter	85650A	HP	May-22, 2014	May-22, 2016	GEMC 194
Spectrum Analyzer	ESL6	Rohde & Schwarz	Nov-15, 2013	Nov-15, 2015	GEMC 160
Attenuator 10 dB	8493B	Agilent	Feb-11, 2015	Feb-11, 2016	GEMC133
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	Feb-10, 2015	Feb-10, 2016	GEMC 29

This report module is based on GEMC template “FCC – Power Line Conducted Emissions Class B_Rev1”

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Radiated Emissions – 15.247

Purpose

The purpose of this test is to ensure that the RF energy unintentionally emitted from the EUT does not exceed the limits listed below as defined in the applicable test standard, as measured from a receiving antenna. This helps protect broadcast radio services such as television, FM radio, pagers, cellular telephones, emergency services, and so on, from unwanted interference.

Limit and Method

The method is given in Section 12.1 of FCC KDB 558074: June 5, 2014

The limits are as defined in FCC Part 15, Section 15.209:

The limits, as defined in 15.247(d) for unintentional radiated emissions apply for those emissions that fall in the restricted bands, as defined in Section 15.205(a). These emissions must comply with the radiated emission limits specified in Section 15.209(a).

All unintentional emissions must also meet the ‘Spurious Conducted Emissions’ requirements of -20 dBc or greater. See also ‘Spurious Conducted Emissions’ for further details.

0.009 MHz – 0.490 MHz, 2400/F (kHz) uV/m at 300 m¹

0.490 MHz – 1.705 MHz, 24000/F (kHz) uV/m at 30 m¹

1.705 MHz – 30 MHz, 30 uV/m at 30 m¹

30 MHz – 88 MHz, 100 uV/m (40.0 dBuV/m¹) at 3 m

88 MHz – 216 MHz, 150 uV/m (43.5 dBuV/m¹) at 3 m

216 MHz – 960 MHz, 200 uV/m (46.0 dBuV/m¹) at 3 m

Above 960 MHz, 500 uV/m (54.0 dBuV/m¹) at 3 m


Above 1000 MHz, 500 uV/m (54 dBuV/m²) at 3m

Above 1000 MHz, 500 uV/m (74 dBuV/m³) at 3m


¹Limit is with Quasi Peak detector with bandwidths as defined in CISPR-16-1-1

²Limit is with 1 MHz measurement bandwidth and using an Average detector

³Limit is with 1 MHz measurement bandwidth and using a Peak detector

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Typical Radiated Emissions Setup



Measurement Uncertainty


The expanded measurement uncertainty is calculated in accordance with CISPR 16-4-2 and is +/-4.4 dB with a 'k=2' coverage factor and a 95% confidence level.

Preliminary Graphs

Note the graphs shown below are for graphical illustration only. For final measurements with the appropriate detector, please refer to the final measurement table where applicable. The graph shown below is a maximized peak measurement graph, measured with a resolution bandwidth greater than the final required detector and over a full 0-360 rotation. This peaking process is done as a worst case measurement. This process enables the detection of frequencies of concern for final measurement, and provides considerable time savings.

In accordance with FCC Part 15, Subpart A, Section 15.33, the device was scanned to the 10th harmonic (a minimum of a 24.835 GHz).


Devices scanned may be scanned at alternate test distances, and in accordance with FCC Part 15, Subpart A, Section 15.31, an extrapolation factor of 20 dB/decade was used above


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

30 MHz and 40 dB/decade below 30 MHz. For example for 1 meter measurements, an extrapolation factor 9.5 dB from 20 Log (1m / 3m) is applied.


B, G and N protocols were measured. For each protocol, low, middle and high channels were measured, each in three orthogonal axes were checked; however the worst case graphs are presented.


Band edge measure graphs were shown for illustrations purpose. See final measurement section for all measurements.




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

150 kHz – 30 MHz




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


**Mid Channel - 30 MHz – 1 GHz
Vertical – Peak Emission Graph**




Note: See Final Measurements and Results section on page 76 for measurements and explanations.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


**Mid Channel – 30 MHz – 1 GHz
Horizontal - Peak Emission Graph**




Note: See Final Measurements and Results section on page 76 for measurements and explanations.


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 1 GHz – 2 GHz
Vertical - Peak Emission Graph




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Mid Channel – 1 GHz – 2 GHz
Horizontal - Peak Emission Graph




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 2 GHz – 4 GHz
Vertical - Peak Emission Graph




Note: See Final Measurements and Results section starting on page 76 for measurements.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 2 GHz – 4 GHz
Horizontal - Peak Emission Graph




Note: See Final Measurements and Results section starting on page 76 for measurements.


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 4 GHz – 10GHz
Vertical - Peak Emission Graph




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 6 GHz – 10 GHz
Vertical - Peak Emission Graph




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 10 GHz – 18 GHz
Vertical - Peak Emission Graph




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Mid Channel – 10 GHz – 18 GHz
Horizontal - Peak Emission Graph




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 18 GHz – 26 GHz
Horizontal - Peak Emission Graph




Plot was taken at 1 meter distances. All emissions shown were instrument noise floor of measurement instrument. No emissions were found in this frequency range.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Mid Channel – 18 GHz – 26 GHz
Vertical - Peak Emission Graph




Plot was taken at 1 meter distances. All emissions shown were instrument noise floor of measurement instrument. No emissions were found in this frequency range.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Low Channel
Vertical - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Low Channel
Horizontal - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Low Channel
Vertical – Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Low Channel
Horizontal - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Hi Channel
Vertical - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Hi Channel
Horizontal - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Hi Channel
Vertical - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B Protocol, Band Edge – Hi Channel
Horizontal - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Low Channel
Vertical - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Low Channel
Horizontal - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Low Channel
Vertical – Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Low Channel
Horizontal - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Hi Channel
Vertical - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Hi Channel
Horizontal - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Hi Channel
Vertical - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G Protocol, Band Edge – Hi Channel
Horizontal - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


N Protocol, Band Edge – Low Channel
Vertical - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


N Protocol, Band Edge – Low Channel
Horizontal - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


N Protocol, Band Edge – Low Channel
Vertical – Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


N Protocol, Band Edge – Low Channel
Horizontal - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


N Protocol, Band Edge – Hi Channel
Vertical - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


N Protocol, Band Edge – Hi Channel
Horizontal - Peak Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


N Protocol, Band Edge – Hi Channel
Vertical - Average Emission




Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

N Protocol, Band Edge – Hi Channel
Horizontal - Average Emission



Note: Bandedge plots were taken with 3 m measurements distance. The marker shows the raw value; see Final Measurements and Results section for corrected values.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Final Measurements and Results


The EUT passed the limits. B, G and N Protocols are measured; and for each Protocol, Low, middle and high bands were measured.

In accordance with 15.247(d), only frequencies exceeding the 15.209 limit that occur within the bands listed in 15.205, need to be verified with a final detector.


For frequency shown on the peak graphs and not listed in 15.205, measurements were taken for reference.

The measurements were maximized by rotating the turn table over a full 0-360 rotation and the antenna height was varied from 1 m to 4 m.


Vertical Emission Table							
Frequency (MHz)	Detector	Raw (dBuV)	Correcti on Factors (dB)	Level (dBuV/ m)	Limit (dBuV/ m)	Margin (dB)	Pass/Fail
150.765	QP	54.6	-18.8	35.8	43.5	7.7	Pass
153.287	QP	53.3	-18.4	34.9	43.5	8.6	Pass
Horizontal Emission Table							
150.183	QP	55.8	-19.0	36.8	43.5	6.7	Pass
151.998	QP	53.3	-19.0	34.3	43.5	9.2	Pass
153.481	QP	53.8	-18.7	35.1	43.5	8.4	Pass
142.617	QP	50.7	-19.8	30.9	43.5	12.6	Pass

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Project Name		S-I B Protocol									
Test Frequency (MHz)	Detection mode	Antenna polarity (Horz/Vert)	Raw signal dB(µV)	Antenna factor dB	Cable loss dB +	Attenuator dB	Pre-Amp Gain dB	Received signal dB(µV/m)	Emission limit dB(µV/m)	Margin dB(µV)	Result
Low Channel (1) - X axis (Horizontal)											
2412	Peak	Horz	92.8	26.1	5.4	10.0	35.8	98.5			PASS
2412	Avg	Horz	87.1	26.1	5.4	10.0	35.8	92.8			PASS
2412	Peak	Vert	89.0	26.1	5.4	10.0	35.8	94.7			PASS
2412	Avg	Vert	83.0	26.1	5.4	10.0	35.8	88.7			PASS
2390	Peak	Horz	44.6	26.1	5.4	10.0	35.8	50.3	74.0	23.7	PASS
2390	Avg	Horz	31.7	26.1	5.4	10.0	35.8	37.4	54.0	16.6	PASS
2390	Peak	Vert	42.9	26.1	5.4	10.0	35.8	48.6	74.0	25.4	PASS
2390	Avg	Vert	31.3	26.1	5.4	10.0	35.8	37.0	54.0	17.0	PASS
4824	Peak	Horz	43.9	27.6	7.7	0.0	35.2	44.0	74.0	30.0	PASS
4824	Avg	Horz	32.0	27.6	7.7	0.0	35.2	32.1	54.0	21.9	PASS
4824	Peak	Vert	44.4	27.6	7.7	0.0	35.2	44.5	74.0	29.5	PASS
4824	Avg	Vert	32.0	27.6	7.7	0.0	35.2	32.1	54.0	21.9	PASS
7236	Peak	Horz	47.3	28.9	9.6	0.0	35.6	50.2	74.0	23.8	PASS
7236	Avg	Horz	33.7	28.9	9.6	0.0	35.6	36.6	54.0	17.4	PASS
7236	Peak	Vert	45.8	28.9	9.6	0.0	35.6	48.7	74.0	25.3	PASS
7236	Avg	Vert	33.8	28.9	9.6	0.0	35.6	36.7	54.0	17.3	PASS
Mid Channel (6) - Z axis (Flat)											
2437	Peak	Horz	91.9	26.1	5.4	10.0	35.8	97.6			PASS
2437	Avg	Horz	86.4	26.1	5.4	10.0	35.8	92.1			PASS
2437	Peak	Vert	90.4	26.1	5.4	10.0	35.8	96.1			PASS
2437	Avg	Vert	84.5	26.1	5.4	10.0	35.8	90.2			PASS
Mid Channel (6) - X axis (Horizontal)											
2437	Peak	Horz	91.9	26.1	5.4	10.0	35.8	97.6			PASS
2437	Avg	Horz	86.2	26.1	5.4	10.0	35.8	91.9			PASS
2437	Peak	Vert	93.1	26.1	5.4	10.0	35.8	98.8			PASS
2437	Avg	Vert	87.3	26.1	5.4	10.0	35.8	93.0			PASS
4874	Peak	Horz	43.2	27.6	7.7	0.0	35.8	42.7	74.0	31.3	PASS
4874	Avg	Horz	31.5	27.6	7.7	0.0	35.8	31.0	54.0	23.0	PASS
4874	Peak	Vert	45.9	27.6	7.7	0.0	35.8	45.4	74.0	28.6	PASS
4874	Avg	Vert	31.4	27.6	7.7	0.0	35.8	30.9	54.0	23.1	PASS
7311	Peak	Vert	46.3	28.9	9.6	0.0	35.9	48.9	74.0	25.1	PASS
7311	Avg	Vert	32.7	28.9	9.6	0.0	35.9	35.3	54.0	18.7	PASS
7311	Peak	Horz	46.2	28.9	9.6	0.0	35.9	48.8	74.0	25.2	PASS
7311	Avg	Horz	32.5	28.9	9.6	0.0	35.8	35.2	54.0	18.8	PASS
Mid Channel (6) - Y axis (Vertical)											
2437	Peak	Horz	86.8	26.1	5.4	10.0	35.8	92.5			PASS
2437	Avg	Horz	81.5	26.1	5.4	10.0	35.8	87.2			PASS
2437	Peak	Vert	87.1	26.1	5.4	10.0	35.8	92.8			PASS
2437	Avg	Vert	81.6	26.1	5.4	10.0	35.8	87.3			PASS
High Channel (11) - X axis (Horizontal)											
2462	Peak	Horz	93.9	26.1	5.4	10.0	35.8	99.6			PASS
2462	Avg	Horz	88.2	26.1	5.4	10.0	35.8	93.9			PASS
2462	Peak	Vert	89.4	26.1	5.4	10.0	35.8	95.1			PASS
2462	Avg	Vert	83.6	26.1	5.4	10.0	35.8	89.3			PASS
2483.5	Peak	Horz	44.4	26.1	5.4	10.0	35.8	50.1	74.0	23.9	PASS
2483.5	Avg	Horz	32.8	26.1	5.4	10.0	35.8	38.5	54.0	15.5	PASS
2483.5	Peak	Vert	45.5	26.1	5.4	10.0	35.8	51.2	74.0	22.8	PASS
2483.5	Avg	Vert	31.9	26.1	5.4	10.0	35.8	37.6	54.0	16.4	PASS
4924	Peak	Horz	43.5	27.6	7.7	0.0	35.2	43.6	74.0	30.4	PASS
4924	Avg	Horz	31.7	27.6	7.7	0.0	35.2	31.8	54.0	22.2	PASS
4924	Peak	Vert	43.3	27.6	7.7	0.0	35.2	43.4	74.0	30.6	PASS
4924	Avg	Vert	31.6	27.6	7.7	0.0	35.2	31.7	54.0	22.3	PASS
7386	Peak	Vert	46.4	28.9	9.6	0.0	35.6	49.3	74.0	24.7	PASS
7386	Avg	Vert	32.6	28.9	9.6	0.0	35.6	35.5	54.0	18.5	PASS
7386	Peak	Horz	46.3	28.9	9.6	0.0	35.6	49.2	74.0	24.8	PASS
7386	Avg	Horz	32.5	28.9	9.6	0.0	35.6	35.4	54.0	18.6	PASS

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Project Name		S-I-G Protocol										Result
Test Frequency (MHz)	Detection mode	Antenna polarity (Horz/Vert)	Raw signal dB(µV)	Antenna factor dB	Cable loss dB +	Atten uator dB	Pre-Amp Gain dB	Received signal dB(µV/m)	Emission limit dB(µV/m)	Margin dB(µV)		
Low Channel (1) - X axis (Horizontal)												
2412	Peak	Horz	95.4	26.1	5.4	10.0	35.8	101.1			PASS	
2412	Avg	Horz	83.8	26.1	5.4	10.0	35.8	89.5			PASS	
2412	Peak	Vert	97.8	26.1	5.4	10.0	35.8	103.5			PASS	
2412	Avg	Vert	85.9	26.1	5.4	10.0	35.8	91.6			PASS	
2390	Peak	Horz	54.8	26.1	5.4	10.0	35.8	60.5	74.0	13.5	PASS	
2390	Avg	Horz	36.1	26.1	5.4	10.0	35.8	41.8	54.0	12.2	PASS	
2390	Peak	Vert	55.6	26.1	5.4	10.0	35.8	61.3	74.0	12.7	PASS	
2390	Avg	Vert	36.5	26.1	5.4	10.0	35.8	42.2	54.0	11.8	PASS	
4824	Peak	Horz	44.1	27.6	7.7	0.0	35.3	44.1	74.0	29.9	PASS	
4824	Avg	Horz	30.9	27.6	7.7	0.0	35.3	30.9	54.0	23.1	PASS	
4824	Peak	Vert	43.9	27.6	7.7	0.0	35.3	43.9	74.0	30.1	PASS	
4824	Avg	Vert	30.7	27.6	7.7	0.0	35.3	30.7	54.0	23.3	PASS	
7236	Peak	Horz	46.5	28.9	9.6	0.0	35.6	49.4	74.0	24.6	PASS	
7236	Avg	Horz	33.9	28.9	9.6	0.0	35.6	36.8	54.0	17.2	PASS	
7236	Peak	Vert	46.3	28.9	9.6	0.0	35.6	49.2	74.0	24.8	PASS	
7236	Avg	Vert	33.5	28.9	9.6	0.0	35.6	36.4	54.0	17.6	PASS	
Mid Channel (6) - Z axis (Flat)												
2437	Peak	Horz	94.4	26.1	5.4	10.0	35.8	100.1			PASS	
2437	Avg	Horz	82.9	26.1	5.4	10.0	35.8	88.6			PASS	
2437	Peak	Vert	92.0	26.1	5.4	10.0	35.8	97.7			PASS	
2437	Avg	Vert	80.6	26.1	5.4	10.0	35.8	86.3			PASS	
Mid Channel (6) - X axis (Horizontal)												
2437	Peak	Horz	95.1	26.1	5.4	10.0	35.8	100.8			PASS	
2437	Avg	Horz	83.2	26.1	5.4	10.0	35.8	88.9			PASS	
2437	Peak	Vert	97.6	26.1	5.4	10.0	35.8	103.3			PASS	
2437	Avg	Vert	85.7	26.1	5.4	10.0	35.8	91.4			PASS	
4874	Peak	Horz	43.1	27.6	7.7	0.0	35.3	43.1	74.0	30.9	PASS	
4874	Avg	Horz	30.4	27.6	7.7	0.0	35.3	30.4	54.0	23.6	PASS	
4874	Peak	Vert	42.8	27.6	7.7	0.0	35.3	42.8	74.0	31.2	PASS	
4874	Avg	Vert	30.5	27.6	7.7	0.0	35.3	30.5	54.0	23.5	PASS	
7311	Peak	Vert	46.2	28.9	9.6	0.0	35.6	49.1	74.0	24.9	PASS	
7311	Avg	Vert	33.8	28.9	9.6	0.0	35.6	36.7	54.0	17.3	PASS	
7311	Peak	Horz	46.1	28.9	9.6	0.0	35.6	49.0	74.0	25.0	PASS	
7311	Avg	Horz	33.6	28.9	9.6	0.0	35.6	36.5	54.0	17.5	PASS	
Mid Channel (6) - Y axis (Vertical)												
2437	Peak	Horz	89.6	26.1	5.4	10.0	35.8	95.3			PASS	
2437	Avg	Horz	78.7	26.1	5.4	10.0	35.8	84.4			PASS	
2437	Peak	Vert	87.8	26.1	5.4	10.0	35.8	93.5			PASS	
2437	Avg	Vert	76.5	26.1	5.4	10.0	35.8	82.2			PASS	
High Channel (11) - X axis (Horizontal)												
2462	Peak	Horz	95.9	26.1	5.4	10.0	35.8	101.6			PASS	
2462	Avg	Horz	83.7	26.1	5.4	10.0	35.8	89.4			PASS	
2462	Peak	Vert	97.5	26.1	5.4	10.0	35.8	103.2			PASS	
2462	Avg	Vert	86.0	26.1	5.4	10.0	35.8	91.7			PASS	
2483.5	Peak	Horz	55.6	26.1	5.4	10.0	35.8	61.3	74.0	12.7	PASS	
2483.5	Avg	Horz	39.1	26.1	5.4	10.0	35.8	44.8	54.0	9.2	PASS	
2483.5	Peak	Vert	57.0	26.1	5.4	10.0	35.8	62.7	74.0	11.3	PASS	
2483.5	Avg	Vert	40.7	26.1	5.4	10.0	35.8	46.4	54.0	7.6	PASS	
4924	Peak	Horz	42.3	27.6	7.7	0.0	35.3	42.3	74.0	31.7	PASS	
4924	Avg	Horz	30.3	27.6	7.7	0.0	35.3	30.3	54.0	23.7	PASS	
4924	Peak	Vert	43.1	27.6	7.7	0.0	35.3	43.1	74.0	30.9	PASS	
4924	Avg	Vert	30.4	27.6	7.7	0.0	35.3	30.4	54.0	23.6	PASS	
7386	Peak	Vert	46.0	28.9	9.6	0.0	35.6	48.9	74.0	25.1	PASS	
7386	Avg	Vert	33.6	28.9	9.6	0.0	35.6	36.5	54.0	17.5	PASS	
7386	Peak	Horz	46.1	28.9	9.6	0.0	35.6	49.0	74.0	25.0	PASS	
7386	Avg	Horz	33.6	28.9	9.6	0.0	35.6	36.5	54.0	17.5	PASS	

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Project Name		S-I-N Protocol										Result
Test Frequency (MHz)	Detection mode	Antenna polarity (Horz/Vert)	Raw signal dB(µV)	Antenna factor dB	Cable loss	Attenuator dB	Pre-Amp Gain dB	Received signal dB(µV/m)	Emission limit dB(µV/m)	Margin dB(µV)		
Low Channel (1) - X axis (Horizontal)												
2412	Peak	Horz	95.7	26.1	5.4	10.0	35.8	101.4			PASS	
2412	Avg	Horz	84.3	26.1	5.4	10.0	35.8	90.0			PASS	
2412	Peak	Vert	97.5	26.1	5.4	10.0	35.8	103.2			PASS	
2412	Avg	Vert	85.9	26.1	5.4	10.0	35.8	91.6			PASS	
2390	Peak	Horz	58.5	26.1	5.4	10.0	35.8	64.2	74.0	9.8	PASS	
2390	Avg	Horz	41.9	26.1	5.4	10.0	35.8	47.6	54.0	6.4	PASS	
2390	Peak	Vert	59.7	26.1	5.4	10.0	35.8	65.4	74.0	8.6	PASS	
2390	Avg	Vert	42.9	26.1	5.4	10.0	35.8	48.6	54.0	5.4	PASS	
4824	Peak	Horz	44.5	27.6	7.7	0.0	35.3	44.5	74.0	29.5	PASS	
4824	Avg	Horz	31.8	27.6	7.7	0.0	35.3	31.8	54.0	22.2	PASS	
4824	Peak	Vert	44.1	27.6	7.7	0.0	35.3	44.1	74.0	29.9	PASS	
4824	Avg	Vert	32.1	27.6	7.7	0.0	35.3	32.1	54.0	21.9	PASS	
7236	Peak	Horz	45.9	28.9	9.6	0.0	35.6	48.8	74.0	25.2	PASS	
7236	Avg	Horz	33.8	28.9	9.6	0.0	35.6	36.7	54.0	17.3	PASS	
7236	Peak	Vert	45.3	28.9	9.6	0.0	35.6	48.2	74.0	25.8	PASS	
7236	Avg	Vert	33.4	28.9	9.6	0.0	35.6	36.3	54.0	17.7	PASS	
Mid Channel (6) - Z axis (Flat)												
2437	Peak	Horz	97.6	26.1	5.4	10.0	35.8	103.3			PASS	
2437	Avg	Horz	86.4	26.1	5.4	10.0	35.8	92.1			PASS	
2437	Peak	Vert	95.7	26.1	5.4	10.0	35.8	101.4			PASS	
2437	Avg	Vert	84.0	26.1	5.4	10.0	35.8	89.7			PASS	
Mid Channel (6) - X axis (Horizontal)												
2437	Peak	Horz	97.1	26.1	5.4	10.0	35.8	102.8			PASS	
2437	Avg	Horz	86.4	26.1	5.4	10.0	35.8	92.1			PASS	
2437	Peak	Vert	99.2	26.1	5.4	10.0	35.8	104.9			PASS	
2437	Avg	Vert	87.9	26.1	5.4	10.0	35.8	93.6			PASS	
4874	Peak	Horz	45.0	27.6	7.7	0.0	35.8	44.5	74.0	29.5	PASS	
4874	Avg	Horz	31.8	27.6	7.7	0.0	35.8	31.3	54.0	22.7	PASS	
4874	Peak	Vert	44.1	27.6	7.7	0.0	35.8	43.6	74.0	30.4	PASS	
4874	Avg	Vert	31.9	27.6	7.7	0.0	35.8	31.4	54.0	22.6	PASS	
7311	Peak	Vert	45.7	28.9	9.6	0.0	35.6	48.6	74.0	25.4	PASS	
7311	Avg	Vert	33.6	28.9	9.6	0.0	35.6	36.5	54.0	17.5	PASS	
7311	Peak	Horz	45.9	28.9	9.6	0.0	35.6	48.8	74.0	25.2	PASS	
7311	Avg	Horz	33.9	28.9	9.6	0.0	35.6	36.8	54.0	17.2	PASS	
Mid Channel (6) - Y axis (Vertical)												
2437	Peak	Horz	92.7	26.1	5.4	10.0	35.8	98.4			PASS	
2437	Avg	Horz	81.0	26.1	5.4	10.0	35.8	86.7			PASS	
2437	Peak	Vert	93.7	26.1	5.4	10.0	35.8	99.4			PASS	
2437	Avg	Vert	82.7	26.1	5.4	10.0	35.8	88.4			PASS	
High Channel (11) -X axis (Horizontal)												
2462	Peak	Horz	98.9	26.1	5.4	10.0	35.8	104.6			PASS	
2462	Avg	Horz	87.8	26.1	5.4	10.0	35.8	93.5			PASS	
2462	Peak	Vert	99.9	26.1	5.4	10.0	35.8	105.6			PASS	
2462	Avg	Vert	88.5	26.1	5.4	10.0	35.8	94.2			PASS	
2483.5	Peak	Horz	63.6	26.1	5.4	10.0	35.8	69.3	74.0	4.7	PASS	
2483.5	Avg	Horz	47.3	26.1	5.4	10.0	35.8	53.0	54.0	1.0	PASS	
2483.5	Peak	Vert	63.6	26.1	5.4	10.0	35.8	69.3	74.0	4.7	PASS	
2483.5	Avg	Vert	47.5	26.1	5.4	10.0	35.8	53.2	54.0	0.8	PASS	
4924	Peak	Horz	44.2	27.6	7.7	0.0	35.3	44.2	74.0	29.8	PASS	
4924	Avg	Horz	30.5	27.6	7.7	0.0	35.3	30.5	54.0	23.5	PASS	
4924	Peak	Vert	44.5	27.6	7.7	0.0	35.3	44.5	74.0	29.5	PASS	
4924	Avg	Vert	31.1	27.6	7.7	0.0	35.3	31.1	54.0	22.9	PASS	
7386	Peak	Vert	45.8	28.9	9.6	0.0	35.6	48.7	74.0	25.3	PASS	
7386	Avg	Vert	33.7	28.9	9.6	0.0	35.6	36.6	54.0	17.4	PASS	
7386	Peak	Horz	45.9	28.9	9.6	0.0	35.6	48.8	74.0	25.2	PASS	
7386	Avg	Horz	33.6	28.9	9.6	0.0	35.6	36.5	54.0	17.5	PASS	

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration /Verification date	Next calibration /Verification due date	Asset #
Spectrum Analyzer	8566B	HP	Oct 2, 2013	Oct 2, 2015	GEMC 190
Quasi Peak Adapter	85650A	HP	Oct 1, 2013	Oct 1, 2015	GEMC 191
Loop Antenna	EM 6871	Electro-Metrics	Feb 3, 2015	Feb 5, 2017	GEMC 70
Loop Antenna	EM 6872	Electro-Metrics	Feb 3, 2015	Feb 5, 2017	GEMC 71
BiLog Antenna	3142-C	ETS	Feb 4, 2013	Feb 4, 2015	GEMC 137
Attenuator 10 dB	8493B	Agilent	Feb-11, 2015	Feb-11, 2016	GEMC 133
4GHZ-12GHZ High Pass filter	11SH10-4000/T12000-0/0	K & L Microwave	Apr 9, 2015	Apr 9, 2015	GEMC 119
Chase Preamp 9kHz - 2 GHz	CPA9231A	Chase	Sept 9, 2014	Sept 9, 2016	GEMC 6403
Q-Par Horn Antenna (2 to 18 GHz)	WBH218HN	Q-par	Jan-23, 2014	Jan-23,2016	GEMC 6375
Horn Antenna 18 GHz - 26.5 GHz	SAS-572	A.H. Systems	Sept 9, 2014	Sept 9, 2016	GEMC 6371
18.0-26.5 GHz Harmonic Mixer	11970K	HP	Jan 28, 2014	Jan 28, 2016	GEMC 158
1-26G pre-amp	HP 8449B	HP	Sept 9, 2014	Sept 9, 2016	GEMC 6351
2.0-8.0 GHz Amplifier	11975A	HP	Jan 28, 2014	Jan 28, 2016	GEMC157
RF Cable 7m	LMR-400-7M-50OHM-MN-MN	LexTec	Feb 10, 2015	Feb 15, 2016	GEMC 28
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	Feb 10, 2015	Feb 15, 2016	GEMC 29
RF Cable 0.5M	LMR-400-0.5M-50OHM-MN-MN	LexTec	Feb 10, 2015	Feb 15, 2016	GEMC 31

This report module is based on GEMC template "FCC - 15.209 - Radiated Emissions_Rev1.doc"

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Power Spectral Density – 15.247 DM

Purpose

The purpose of this test is to ensure that the maximum power spectral density to the radiating element does not exceed the limits specified. This ensures that the modulation is significantly wide enough, or low enough in power that it will allow for co-operation of other wireless devices operating within this frequency allocation.

Limits and Methods

The limits are defined in 15.247(e).

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

The method is given in Section 10.2 of FCC KDB 558074: June 5, 2014.


Results

The EUT passed. Low, medium, and high band was tested. The worst case values for each protocol were measured with a 3 kHz resolution bandwidth.


B-Mode	-12.9 dBm/3 kHz
G-Mode	-12.6 dBm/3 kHz
N-Mode	-12.4 dBm/3 kHz


Graph(s)

The graphs shown below show the power spectral density of the device during the conducted measurement operation of the EUT. Low, middle, and high channel was investigated in each mode, with the worst case being presented.


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


B - Protocol: PSD




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


G - Protocol: PSD



Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	




Note: See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration /Verification date	Next calibration /Verification due date	Asset #
Spectrum Analyzer	ESL6	Rohde & Schwarz	Nov-15, 2013	Nov-15, 2015	GEMC 160
Attenuator 10 dB	8493B	Agilent	Feb-11, 2015	Feb-11, 2016	GEMC133
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	Feb-10, 2015	Feb-10, 2016	GEMC 29

This report module is based on GEMC template "FCC -- Power Line Conducted Emissions Class B_Rev1"

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Maximum Permissible Exposure – 15.247

Purpose

The purpose of this test is to ensure that the RF energy intentionally transmitted, in terms of power density emitted from the EUT at a stated operating distance does not exceed the limits listed below as defined in the applicable test standard, as calculated based upon readings obtained during testing. This helps protect human exposure to excessive RF fields.

Limit(s) and Method

The limits, as defined in FCC 15.247(i) and FCC 1.1310 Table 1 (B) limits for general public exposure was applied. The limit for the frequency range of 1.5 GHz to 100 GHz was applied to the 15.247 device. This is a limit of 1.0 mW/cm². The distance used for calculations was 20 cm, as this is the minimum distance an operator will be from the EUT during normal operation, as stated by the manufacturer.

Results

The EUT passed the requirements. The worst case calculated power density was 0.017 mW/cm², this is significantly under the 1.0 mW/cm² requirement.

Calculations

Method 1 (conducted power)

Internal antenna

$$P_d = (P_t * G) / (4 * \pi * R^2)$$

Where $P_t = 17.3$ dBm or 53.1 mW as per Peak power conducted output


Where $G = 2.1$ dBi, or numerically 1.62

Where $R = 20$ cm

$$P_d = (53.1 \text{ mW} * 1.62) / (4 * \pi * 20\text{cm}^2)$$

$$P_d = 86.02 \text{ mW} / 5026 \text{ cm}^2$$

$$P_d = 0.017 \text{ mW/cm}^2$$

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Power Line Conducted Emissions

Purpose

The purpose of this test is to ensure that the RF energy unintentionally emitted from the EUT's power line does not exceed the limits listed below as defined in the applicable test standard, as measured from a LISN. This helps protect lower frequency radio services such as AM radio, shortwave radio, amateur radio operators, maritime radio, CB radio, and so on, from unwanted interference.

Limits & Method

The limits are as defined in 47 CFR FCC Part 15 Section 15.207


Method is as defined in ANSI C64.10:2009

Average Limits		QuasiPeak Limits	
150 kHz – 500 kHz	56 to 46 dBuV	150 kHz – 500 kHz	66 to 56 dBuV
500 kHz – 5 MHz	46 dBuV	500 kHz – 5 MHz	56 dBuV
5 MHz – 30 MHz	50 dBuV	500 kHz – 30 MHz	60 dBuV


The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

Note: If the Peak or Quasi Peak detector measurements do not exceed the Average limits, then the EUT is deemed to have passed the requirements.

Both limits are applicable, and each is specified as being measured with a 9 kHz measurement bandwidth.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Typical Setup Diagram




Measurement Uncertainty

The expanded measurement uncertainty is calculated in accordance with CISPR 16-4-2 and is +/-3.6 dB with a 'k=2' coverage factor and a 95% confidence level.


Preliminary Graphs


Note the graphs shown below are for graphical illustration only. For final measurements with the appropriate detector where applicable, please refer to the table. The graph shown below is a peak measurement graph, measured with a resolution bandwidth greater than or equal to the final required detector. These graphs are performed as a worst case measurement to enable the detection of frequencies of concern and for considerable time savings.

Power line conducted emissions were performed with the transmitter transmitting at 100% duty cycle.


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


L1 (Line) – 120Vac 60Hz



Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

L2 (Neutral) – 120Vac 60Hz




Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Final Measurements

Product Category	Class B						
Product	WEM01						
Supply	120 VAC 60 Hz						
Line Emission Table							
Frequency (MHz)	Detector	Raw (dBuV)	Factors	Level (dBuV)	Limit (dB)	Margin (dB)	Pass/Fail
27.9819	Peak	31.6	10.3	41.9	50	8.1	Pass
27.9949	Peak	25.9	10.3	36.2	50	13.8	Pass
0.1987	Peak	29.4	10	39.4	53.7	14.3	Pass
28.235	Peak	25.5	10.3	35.8	50	14.2	Pass
0.1889	Peak	29.8	10	39.8	54.1	14.3	Pass
28.0078	Peak	25.4	10.3	35.7	50	14.3	Pass
Neutral Emission Table							
0.2019	Peak	29.2	10	39.2	53.5	14.3	Pass
0.1857	Peak	29.1	10	39.1	54.2	15.1	Pass
0.2084	Peak	27.3	10	37.3	53.3	16	Pass
10.0816	Peak	21.7	10.1	31.8	50	18.2	Pass
0.1533	Peak	27.6	10	37.6	55.8	18.2	Pass
13.0147	Peak	21.2	10.2	31.4	50	18.6	Pass

Notes:


1. No peak emissions exceeded power line conducted emission average limits; therefore, the unit was deemed to meet power line conducted emission requirements base on peak emissions.
2. Power line conducted emissions was performed on the 120 Vac to 24 Vac step-down transformer.
3. See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up for the highest line conducted emission

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	


Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Spectrum Analyzer	ESL 6	Rohde & Schwarz	Nov 15, 2013	Nov 15, 2015	GEMC 160
LISN	FCC-LISN-50/250-16-2-01	FCC	Jan-15, 2015	Jan-15, 2017	GEMC 65
RF Cable 7m	LMR-400-7M-50OHM-MN-MN	LexTec	Feb-10, 2015	Feb-10, 2016	GEMC 28

This report module is based on GEMC template "FCC -- Power Line Conducted Emissions Class B_Rev1"

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Appendix A – EUT Summary


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

For further details for filing purposes, refer to filing package.

General EUT Description

Client	
Organization	Ecobee Inc 250 University Ave., Ste 400 Toronto, ON., Canada M5H 3E5
Contact	Kashif Ahmed
Phone	416 987 1048
Email	kashif@ecobee.com
EUT Details	
EUT Name (for report title)	Si
EUT Model / SN (if known)	Si
FCC ID	WR9
Industry Canada #	7981A-
Equipment category	Wireless thermostat
EUT is powered using	AC
Input voltage range(s) (V)	24 Vac
Frequency range(s) (Hz)	60 Hz
Rated input current (A)	2 A
Number of power supplies in EUT	1
Transmits RF energy? (describe)	Yes
Basic EUT functionality description	Smart thermostat

Note the EUT is considered to have been received the date of the commencement of the first test, unless otherwise stated. For a close-up picture of the EUT, see ‘Appendix B – EUT & Test Setup Photographs’.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

EUT Configuration


Please see Appendix B for a picture of the unit running in normal conditions.

- Wireless were configured to transmit at 100% duty cycle

Operational Setup

These devices are required to be attached to the EUT for its normal operation.

- A debug board was connected to the EUT.

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	

Appendix B – EUT and Test Setup Photographs



Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	



Figure 4: Radiated emission setup – photo 1

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	




Figure 5: Radiated emission setup – photo 2

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	



Figure 6: Radiated emission setup – photo 3



Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	



Figure 7: Antenna port conducted emission setup – photo

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	





Figure 8: Antenna port conducted emission, power meter setup - photo

Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	




Figure 9: Power line conducted emission setup – photo 1


Client	Ecobee Inc	
Product	Si	
Standard(s)	RSS 247 Issue 1:2014 / FCC Part 15 Subpart C 15:2015	



Figure 10: Power line conducted emission setup – photo 2