


Client	Ecobee Inc	
Product	WEM01	
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	

Maximum Permissible Exposure

Purpose

The purpose of this test is to ensure that the RF energy intentionally transmitted, in terms of power density emitted from the EUT at a stated operating distance does not exceed the limits listed below as defined in the applicable test standard, as calculated based upon readings obtained during testing. This helps protect human exposure to excessive RF fields.

Limit(s) and Method

The limits, as defined FCC 1.1310 Table 1 (B) limits for general public exposure was applied. The limits for the frequency ranges 300 MHz to 1.5 GHz and 1.5 GHz to 100 GHz was applied. The limits are $f/1500 \text{ mW/cm}^2$ and 1.0 mW/cm^2 respectively. The distance used for calculations was 20 cm, as this is the minimum distance an operator will be from the EUT during normal operation, as stated by the manufacturer.

Results

The EUT passed the requirements. The worst case calculated power density was 0.017 mW/cm^2 , this is significantly under the 1.0 mW/cm^2 requirement.

Calculations

Method 1 (conducted power)

Internal antenna

$$P_d = (P_t * G) / (4 * \pi * R^2)$$

Where $P_t = 17.3 \text{ dBm}$ or 53.1 mW as per Peak power conducted output


Where $G = 2.1 \text{ dBi}$, or numerically 1.62

Where $R = 20 \text{ cm}$

$$P_d = (53.1 \text{ mW} * 1.62) / (4 * \pi * 20\text{cm}^2)$$

$$P_d = 86.02 \text{ mW} / 5026 \text{ cm}^2$$

$$P_d = 0.017 \text{ mW/cm}^2$$

Client	Ecobee Inc	
Product	WEM01	
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	

Antenna Co-location

The MPE requirement for collocated antennas are that the sum of ratios should be less than 1.

The power density for Zigbee module (FCC ID: DI2CT-EM2606) is 0.010 mW/cm²

The sum of ratios (P_d / Limit) for each transmitter is
 $(P_d(\text{WIFI})/\text{Limit}(\text{WIFI})) + (P_d(\text{Zigbee})/\text{Limit})$

$$(0.017/1.0) + (0.010/1.0) = 0.027 < 1$$

The EUT meets the antenna collocation MPE requirements.