

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C

CLASS II PERMISSIVE CHANGE

Test Standard	FCC Part 15.247
Product name	WLAN Module
Brand Name	JORJIN
Model No.	WG6031-00
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Approved by:



Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	March 22, 2021	Initial Issue	ALL	Mita Wu
01	April 22, 2021	See the following Note Rev.(01)	P.1, 4, 7	Allison Chen

Note:**Rev.(01)**

1. Added designation number.
2. Modify product name.

Table of contents

1. GENERAL INFORMATION	4
1.1 EUT INFORMATION.....	4
1.2 EUT CHANNEL INFORMATION	5
1.3 ANTENNA INFORMATION	5
1.4 MEASUREMENT UNCERTAINTY	6
1.5 FACILITIES AND TEST LOCATION	7
1.6 INSTRUMENT CALIBRATION.....	7
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT.....	8
1.8 TEST METHODOLOGY AND APPLIED STANDARDS.....	8
2. TEST SUMMARY	9
3. DESCRIPTION OF TEST MODES	10
3.1 THE WORST MODE OF OPERATING CONDITION.....	10
3.2 THE WORST MODE OF MEASUREMENT	11
3.3 EUT DUTY CYCLE	12
4. TEST RESULT.....	13
4.1 AC POWER LINE CONDUCTED EMISSION.....	13
4.3 OUTPUT POWER MEASUREMENT.....	14
4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION.....	17
APPENDIX 1 - PHOTOGRAPHS OF EUT	A-1

Report No.: T210115W02-RP

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Jorjin Technologies Inc. 17F.-1, NO.239, SEC. 1, DATONG RD., XIZHI DIST. New Taipei City, 22161 Taiwan
Manufacturer	Jorjin Technologies Inc. 17F.-1, NO.239, SEC. 1, DATONG RD., XIZHI DIST. New Taipei City, 22161 Taiwan
Equipment	WLAN Module
Model Name	WG6031-00
Model Discrepancy	N/A
Trade Name	JORJIN
Received Date	January 15, 2021
Date of Test	January 28, 2021 ~ February 01, 2021
Power Supply	Power from Host System.
HW Version	WG6031-00-PCB-D01
SW Version	02_Jorjin RTL8189ES_default_map_R05c_MP_20201125.MAP
EUT Serial #	WG6031P00 + WG6031E00

Remark:

1. For more details, refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

Report No.: T210115W02-RP

1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT 20: 2412MHz ~ 2462MHz 802.11n HT40: 2422MHz ~ 2452MHz
Modulation Type	1. IEEE 802.11b mode: CCK 2. IEEE 802.11g mode: OFDM 3. IEEE 802.11n HT 20 MHz mode : OFDM 4. IEEE 802.11n HT40 Mode: OFDM
Number of channel	1. IEEE 802.11b mode: 11 Channels 2. IEEE 802.11g mode: 11 Channels 3. IEEE 802.11n HT 20 MHz mode : 11 Channels 4. IEEE 802.11n HT40 Mode : 7 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
<input type="checkbox"/> 1 MHz or less	1	Middle
<input type="checkbox"/> 1 MHz to 10 MHz	2	1 near top and 1 near bottom
<input checked="" type="checkbox"/> More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Specification	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input checked="" type="checkbox"/> Dipole <input type="checkbox"/> Coils
Antenna Gain	Gain: 2 dBi
Antenna connector	SMA

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

Report No.: T210115W02-RP

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	N/A	Not applicable, because EUT doesn't connect to AC Main Source direct.
Radiation	Ray Li, Jerry Chang	-
RF Conducted	Ryan Du	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Coaxial Cable	Woken	WC12	CC001	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/17/2020	09/16/2021
Power Meter	Anritsu	ML2495A	1149001	5/21/2020	5/20/2021
Power Sensor	Anritsu	MA2491A	030982	5/21/2020	5/20/2021
Software	N/A				

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/25/2020	02/24/2021
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2020	02/24/2021
Coaxial Cable	EMCI	EMC105	190914+327109/4	09/19/2020	09/18/2021
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/06/2021	01/05/2022
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	09/30/2020	09/29/2021
Loop Ant	COM-POWER	AL-130	121051	03/27/2020	03/26/2021
Pre-Amplifier	EMEC	EM330	060609	02/25/2020	02/24/2021
Pre-Amplifier	HP	8449B	3008A00965	02/25/2020	02/24/2021
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

Remark: Each piece of equipment is scheduled for calibration once a year.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247.

2. TEST SUMMARY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	N/A
15.247(a)(2)	4.2	6 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)	4.3	Output Power Measurement	Pass
15.247(e)	4.4	Power Spectral Density	Pass
15.247(d)	4.5	Conducted Band Edge	Pass
15.247(d)	4.5	Conducted Spurious Emission	Pass
15.247(d)	4.6	Radiation Band Edge	Pass
15.247(d)	4.6	Radiation Spurious Emission	Pass

Report No.: T210115W02-RP

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	IEEE 802.11b mode :1Mbps IEEE 802.11g mode :6Mbps IEEE 802.11n HT20 mode :MCS0 IEEE 802.11n HT40 mode :MCS0
Test Channel Frequencies	IEEE 802.11b mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11g mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11n HT20 mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11n HT40 Mode : 1. Lowest Channel : 2422MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2452MHz
Operation Transmitter	IEEE 802.11b mode : 1T1R IEEE 802.11g mode : 1T1R IEEE 802.11n HT20 mode : 1T1R IEEE 802.11n HT40 mode : 1T1R

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Host System
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4
Worst Position	<input type="checkbox"/> Placed in fixed position. <input checked="" type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane) <input type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Host System
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in two axis ,X,Y and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report

Report No.: T210115W02-RP

3.3 EUT DUTY CYCLE


Temperature: 23.8°C

Humidity: 55.7% RH

Tested by: Ryan Du

Test date: February 01, 2021

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11b	98.80%	0.05	0.12	0.01
802.11g	97.22%	0.12	0.71	1.00
802.11n HT20	94.20%	0.26	0.77	1.00
802.11n HT40	94.44%	0.25	1.47	2.00



Report No.: T210115W02-RP

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a)(2),

Frequency Range (MHz)	Limits(dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

Not applicable, because EUT doesn't connect to AC Main Source direct.

Report No.: T210115W02-RP

4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b),

Peak output power :

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm) and the e.i.r.p. shall not exceed 4Watt(36 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	<input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 30dBm <input type="checkbox"/> Antenna with DG greater than 6 dBi : [Limit = 30 – (DG – 6)] <input type="checkbox"/> Point-to-point operation :
-------	---


Average output power : For reporting purposes only.

4.3.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup



Report No.: T210115W02-RP

4.3.4 Test Result

Temperature: 23.8°C **Test date:** February 01, 2021
Humidity: 55.7% RH **Tested by:** Ryan Du

Peak output power :

Wifi 2.4G								
Config	CH	Freq. (MHz)	Power Setting	PK Power (dBm)	PK Total Power (dBm)	PK Total Power (W)	DG (dBi)	Limit (dBm)
IEEE 802.11b Data rate: 1Mbps	Low	2412	38	18.47	18.47	0.0703	2	30
	Mid	2437	37	18.45	18.45	0.0700		
	High	2462	37	18.82	18.82	0.0762		
IEEE 802.11g Data rate: 6Mbps	Low	2412	45	23.68	23.68	0.2333		
	Mid	2437	44	23.59	23.59	0.2286		
	High	2462	44	23.71	23.71	0.2350		
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	42	21.54	21.54	0.1426		
	Mid	2437	41	21.59	21.59	0.1442		
	High	2462	41	21.88	21.88	0.1542		
IEEE 802.11n HT40 Data rate: MCS0	Low	2422	43	21.91	21.91	0.1552		
	Mid	2437	43	22.15	22.15	0.1641		
	High	2452	42	21.82	21.82	0.1521		

Report No.: T210115W02-RP

Average output power :

Wifi 2.4G				
Config	CH	Freq. (MHz)	Power Setting	AV Power (dBm)
IEEE 802.11b Data rate: 1Mbps	Low	2412	38	16.11
	Mid	2437	37	16.06
	High	2462	37	16.38
IEEE 802.11g Data rate: 6Mbps	Low	2412	45	13.94
	Mid	2437	44	13.92
	High	2462	44	14.22
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	42	12.41
	Mid	2437	41	12.59
	High	2462	41	12.78
IEEE 802.11n HT40 Data rate: MCS0	Low	2422	43	12.51
	Mid	2437	43	12.77
	High	2452	42	12.50

4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency	Field Strength (microvolts/m)	Measurement Distance (metres)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Report No.: T210115W02-RP

4.6.2 Test Procedure

Test method Refer as KDB 662911 D01, ANSI C63.10:2013.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4. The SA setting following :

(1) Below 1G : RBW = 100kHz, VBW \geq 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G :

(2.1) For Peak measurement : RBW = 1MHz, VBW \geq 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2.2) For Average measurement : RBW = 1MHz, VBW


·If Duty Cycle \geq 98%, VBW=10Hz.

·If Duty Cycle < 98%, VBW=1/T.


Report No.: T210115W02-RP

4.6.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz



Above 1 GHz




Report No.: T210115W02-RP

4.6.4 Test Result

Band Edge Test Data


Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	21.3(°C)/ 58%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2388.24	Peak	55.20	-1.15	54.05	74.00	-19.95
2388.24	Average	42.95	-1.15	41.80	54.00	-12.20
2390.00	Peak	53.15	-1.14	52.01	74.00	-21.99
2390.00	Average	42.30	-1.14	41.16	54.00	-12.84

Report No.: T210115W02-RP


Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	21.3(°C)/ 58%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	49.26	-1.14	48.12	74.00	-25.88
2390.00	Average	36.58	-1.14	35.44	54.00	-18.56

Report No.: T210115W02-RP


Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	21.3(°C)/ 58%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
2483.50	Peak	52.49	-0.80	51.69	74.00	-22.31
2483.50	Average	41.22	-0.80	40.42	54.00	-13.58
2486.50	Peak	55.07	-0.78	54.29	74.00	-19.71
2486.50	Average	41.80	-0.78	41.02	54.00	-12.98

Report No.: T210115W02-RP


Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	21.3(°C)/ 58%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	48.98	-0.80	48.18	74.00	-25.82
2483.50	Average	36.98	-0.80	36.18	54.00	-17.82

Report No.: T210115W02-RP


Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	61.39	-1.14	60.25	74.00	-13.75
2390.00	Average	42.69	-1.14	41.55	54.00	-12.45

Report No.: T210115W02-RP


Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
2390.00	Peak	46.63	-1.14	45.49	74.00	-28.51
2390.00	Average	36.33	-1.14	35.19	54.00	-18.81

Report No.: T210115W02-RP


Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	61.21	-0.80	60.41	74.00	-13.59
2483.50	Average	44.72	-0.80	43.92	54.00	-10.08

Report No.: T210115W02-RP


Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2483.50	Peak	49.18	-0.80	48.38	74.00	-25.62
2483.50	Average	36.01	-0.80	35.21	54.00	-18.79

Report No.: T210115W02-RP


Test Mode	IEEE 802.11n HT20 Low CH 2412MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
2390.00	Peak	56.88	-1.14	55.74	74.00	-18.26
2390.00	Average	41.60	-1.14	40.46	54.00	-13.54

Report No.: T210115W02-RP


Test Mode	IEEE 802.11 n20 Low CH 2412MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	48.82	-1.14	47.68	74.00	-26.32
2390.00	Average	36.58	-1.14	35.44	54.00	-18.56

Report No.: T210115W02-RP


Test Mode	IEEE 802.11n HT20 High CH 2462MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2483.50	Peak	53.75	-0.80	52.95	74.00	-21.05
2483.50	Average	43.61	-0.80	42.81	54.00	-11.19

Report No.: T210115W02-RP


Test Mode	IEEE 802.11n20 High CH 2462MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
2483.50	Peak	47.67	-0.80	46.87	74.00	-27.13
2483.50	Average	35.40	-0.80	34.60	54.00	-19.40

Report No.: T210115W02-RP


Test Mode	IEEE 802.11n HT40 Low CH 2422MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2390.00	Peak	53.55	-1.14	52.41	74.00	-21.59
2390.00	Average	41.92	-1.14	40.78	54.00	-13.22

Report No.: T210115W02-RP


Test Mode	IEEE 802.11 n40 Low CH 2422MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	48.12	-1.14	46.98	74.00	-27.02
2390.00	Average	36.25	-1.14	35.11	54.00	-18.89

Report No.: T210115W02-RP


Test Mode	IEEE 802.11n HT40 High CH 2452MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2483.50	Peak	54.26	-0.80	53.46	74.00	-20.54
2483.50	Average	43.22	-0.80	42.42	54.00	-11.58

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n40 High CH 2452MHz	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Band Edge	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	46.53	-0.80	45.73	74.00	-28.27
2483.50	Average	36.26	-0.80	35.46	54.00	-18.54

Report No.: T210115W02-RP

Below 1G Test Data

Test Mode	Mode 1	Temp/Hum	20.9(°C)/ 55%RH
Test Item	30MHz-1GHz	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
42.61	Peak	49.70	-11.59	38.11	40.00	-1.89
183.26	Peak	50.78	-11.44	39.34	43.50	-4.16
416.06	Peak	46.06	-5.16	40.90	46.00	-5.10
516.94	Peak	47.92	-3.14	44.78	46.00	-1.22
613.94	Peak	42.97	-1.49	41.48	46.00	-4.52
796.30	Peak	39.59	1.52	41.11	46.00	-4.89

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Report No.: T210115W02-RP

Test Mode	Mode 1	Temp/Hum	20.9(°C)/ 55%RH
Test Item	30MHz-1GHz	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
46.49	Peak	46.52	-13.90	32.62	40.00	-7.38
102.75	Peak	48.92	-12.09	36.83	43.50	-6.67
216.24	Peak	51.83	-11.87	39.96	46.00	-6.04
416.06	Peak	45.96	-5.16	40.80	46.00	-5.20
647.89	Peak	44.65	-0.53	44.12	46.00	-1.88
949.56	Peak	29.78	4.44	34.22	46.00	-11.78

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Report No.: T210115W02-RP

Above 1G Test Data

Test Mode	IEEE 802.11b Low CH Main	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2411.64	Peak	107.74	-1.10	106.64	74.00	32.64
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b Low CH Main	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2411.64	Peak	94.40	-1.10	93.30	74.00	19.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b Low CH Main	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2412.00	Peak	100.16	-1.10	99.06	74.00	25.06
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b Low CH Main	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2412.36	Peak	102.63	-1.10	101.53	74.00	27.53
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4824.00	Peak	34.26	5.65	39.91	74.00	-34.09
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4824.00	Peak	36.86	5.65	42.51	74.00	-31.49
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4874.00	Peak	34.36	5.90	40.26	74.00	-33.74
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4874.00	Peak	35.18	5.90	41.08	74.00	-32.92
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	36.29	6.34	42.63	74.00	-31.37
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11b High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4924.00	Peak	39.15	6.34	45.49	74.00	-28.51
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11g Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4824.00	Peak	35.05	5.65	40.70	74.00	-33.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11g Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4824.00	Peak	35.16	5.65	40.81	74.00	-33.19
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	34.26	5.90	40.16	74.00	-33.84
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4874.00	Peak	35.41	5.90	41.31	74.00	-32.69
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11g High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4924.00	Peak	35.79	6.34	42.13	74.00	-31.87
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11g High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4924.00	Peak	37.02	6.34	43.36	74.00	-30.64
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4824.00	Peak	34.13	5.65	39.78	74.00	-34.22
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4824.00	Peak	35.15	5.65	40.80	74.00	-33.20
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4874.00	Peak	34.00	5.90	39.90	74.00	-34.10
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4874.00	Peak	35.63	5.90	41.53	74.00	-32.47
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	35.74	6.34	42.08	74.00	-31.92
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4924.00	Peak	36.64	6.34	42.98	74.00	-31.02
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4844.00	Peak	34.44	5.71	40.15	74.00	-33.85
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4844.00	Peak	34.89	5.71	40.60	74.00	-33.40
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4874.00	Peak	34.67	5.90	40.57	74.00	-33.43
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4874.00	Peak	35.65	5.90	41.55	74.00	-32.45
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4904.00	Peak	35.52	6.14	41.66	74.00	-32.34
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210115W02-RP

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	20.9(°C)/ 55%RH
Test Item	Harmonic	Test Date	January 28, 2021
Polarize	Horizontal	Test Engineer	
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
4904.00	Peak	37.73	6.14	43.87	74.00	-30.13
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

- End of Test Report -