

FCC RF EXPOSURE REPORT

FCC ID:WS2-WG6611

Project No. : 1707167
Equipment : WLAN module
Model : WG6611-00, WG6611P00
Applicant : Jorjin Technologies INC.
Address : 17F, No 239, Datong Road, Sec 1, Xizhi
District, New Taipei City, Taiwan 22161

According: : FCC Guidelines for Human Exposure IEEE
C95.1 & FCC Part 2.1091

B T L I N C .

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan
TEL: +886-2-2657-3299 FAX: +886-2-2657-3331

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Unictron	AA273	PIFA	IPEX	3.58

TEST RESULTS

EUT :	WLAN module	Model Name :	WG6611-00, WG6611P00
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		

2.4G WIFI

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.58	2.2803	23.23	210.3778	0.09549	1	Complies

Note: the calculated distance is 20 cm.