

# FCC Test Report

Report No.: AGC00213221202FE03

FCC ID	:	WSG-M109
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Bluetooth headset
BRAND NAME	:	N/A
MODEL NAME	:	M109, M110, LE-HS013 Superior, KH120M, KH122M, FX-HS012, DY102, BM202, OS301, HP101, EH-HS01, CT001, CT002
APPLICANT	:	SKY WING Communication Electronics Co., Ltd
DATE OF ISSUE	:	Jan. 05, 2023
STANDARD(S)	:	FCC Part 15.247
REPORT VERSION	:	V1.0
<u>Attestation of <b>G</b></u>	0	Compliance (Shenzhen) Co., Ltd





#### **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan. 05, 2023	Valid	Initial Release



#### **TABLE OF CONTENTS**

. VERIFICATION OF CONFORMITY	5
. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RECEIVER INPUT BANDWIDTH	7
2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE	7
2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR	7
2.6. RELATED SUBMITTAL(S) / GRANT (S)	8
2.7. TEST METHODOLOGY	8
2.8. SPECIAL ACCESSORIES	8
2.9. EQUIPMENT MODIFICATIONS	8
2.10. ANTENNA REQUIREMENT	8
. MEASUREMENT UNCERTAINTY	9
. DESCRIPTION OF TEST MODES	10
SYSTEM TEST CONFIGURATION	11
5.1. CONFIGURATION OF EUT SYSTEM	11
5.2. EQUIPMENT USED IN TESTED SYSTEM	11
5.3. SUMMARY OF TEST RESULTS	11
. TEST FACILITY	12
. PEAK OUTPUT POWER	13
7.1. MEASUREMENT PROCEDURE	13
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
7.3. LIMITS AND MEASUREMENT RESULT	
. 20DB BANDWIDTH	18
8.1. MEASUREMENT PROCEDURE	18
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	18
8.3. LIMITS AND MEASUREMENT RESULTS	19
. CONDUCTED SPURIOUS EMISSION	23

Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



APPENDIX A: PHOTOGRAPHS OF TEST SETUP	60
14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	
14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	
14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	57
14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	56
14.1. LIMITS OF LINE CONDUCTED EMISSION TEST	56
14. LINE CONDUCTED EMISSION TEST	56
13.4. LIMITS AND MEASUREMENT RESULT	55
13.3. MEASUREMENT EQUIPMENT USED	
13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
13.1. MEASUREMENT PROCEDURE	55
13. FREQUENCY SEPARATION	55
12.4. LIMITS AND MEASUREMENT RESULT	
12.3. MEASUREMENT EQUIPMENT USED	
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
12.1. MEASUREMENT PROCEDURE	
12. TIME OF OCCUPANCY (DWELL TIME)	51
11.4. LIMITS AND MEASUREMENT RESULT	50
11.3. MEASUREMENT EQUIPMENT USED	
11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
11.1. MEASUREMENT PROCEDURE	
11. NUMBER OF HOPPING FREQUENCY	50
10.4. TEST RESULT	
10.3. LIMITS AND MEASUREMENT RESULT	
10.2. TEST SETUP	
10.1. MEASUREMENT PROCEDURE	37
10. RADIATED EMISSION	37
9.4. LIMITS AND MEASUREMENT RESULT	23
9.3. MEASUREMENT EQUIPMENT USED	
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	



#### **1. VERIFICATION OF CONFORMITY**

Applicant	SKY WING Communication Electronics Co., Ltd	
Address	No.10 Road 63#, Long yan, Humen Town, Dongguan City, Guangdong, China	
Manufacturer	SKY WING Communication Electronics Co., Ltd	
Address	No.10 Road 63#, Long yan, Humen Town, Dongguan City, Guangdong, China	
Factory	SKY WING Communication Electronics Co., Ltd	
Address	No.10 Road 63#, Long yan, Humen Town, Dongguan City, Guangdong, China	
Product Designation	Bluetooth headset	
Brand Name	N/A	
Test Model	M109	
Series Model	M110, LE-HS013 Superior, KH120M, KH122M, FX-HS012, DY102, BM202, OS301, HP101, EH-HS01, CT001, CT002	
Declaration Difference	All the same except for the model name	
Date of receipt of test item	Dec. 09, 2022	
Date of test	Dec. 09, 2022 to Jan. 05, 2023	
Deviation	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result	Pass	
Report Template	AGCRT-US-BR/RF	

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC PART 15.247.

Prepared By

an Duan

Alan Duan (Project Engineer)

Jan. 05, 2023

Reviewed By

Calvin Liu (Reviewer)

Jan. 05, 2023

Approved By

Max 200

Max Zhang (Authorized Officer)

Jan. 05, 2023



# 2. GENERAL INFORMATION

#### 2.1. PRODUCT DESCRIPTION

The EUT is designed as "Bluetooth headset". It is designed by way of utilizing the GFSK, Pi/4 DQPSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402GHz to 2.480GHz
RF Output Power	0.387dBm (Max)
Bluetooth Version	V5.2
Modulation	BR⊠GFSK, EDR⊠π /4-DQPSK, ⊡8DPSK BLE⊡GFSK 1Mbps □GFSK 2Mbps
Number of channels	79 Channels
Hardware Version	V001
Software Version	V01
Antenna Designation	Ceramic Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	2.67dBi
Power Supply	DC 3.7V by battery or DC 5V by adapter

#### 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402 MHz
	1	2403 MHz
	:	:
	38	2440 MHz
2402~2480MHz	39	2441 MHz
	40	2442 MHz
		:
	77	2479 MHz
	78	2480 MHz



#### 2.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

#### 2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a hopping sequence in data mode: 40, 21, 44, 23, 04, 15, 66, 56, 19, 78, 07, 28, 69, 55, 36, 45, 05, 13, 43, 74, 57, 35, 67, 76, 02, 34, 54, 63, 42, 11, 30, 06, 64, 25, 75, 48, 17, 33, 58, 01, 29, 14, 51, 72, 03, 31, 50, 61, 77, 18, 10, 47, 12, 68, 08, 49, 20, 00, 73, 09, 16, 60, 71, 41, 24, 53, 38, 26, 46, 37, 65, 32, 70, 52, 27, 59, 22, 62, 39

# 2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD\_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For

Transmitting the wanted data the complete hopping sequence was not used. The connection ended.



The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.

#### 2.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: WSG-M109** filing to comply with the FCC PART 15.247 requirements.

#### 2.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### 2.8. SPECIAL ACCESSORIES

Refer to section 5.2.

#### 2.9. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.10. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



# **3. MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	U <sub>c</sub> = ±2.7 %
Uncertainty of Occupied Channel Bandwidth	U <sub>c</sub> = ±2 %



#### **4. DESCRIPTION OF TEST MODES**

NO.	TEST MODE DESCRIPTION	
1	Low channel GFSK	
2	Middle channel GFSK	
3	High channel GFSK	
4	Low channel π/4-DQPSK	
5	Middle channel π/4-DQPSK	
6	High channel π/4-DQPSK	
7	Hopping mode GFSK	
8	Hopping mode π/4-DQPSK	

Note: 1. Only the result of the worst case was recorded in the report, if no other cases.

2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

#### Software Setting

BT_Tool		_ □	×
COMx Baudrate			
Classic BLE			
Test Mode			
FCC Test  BT addre		Stop	
DUT Test O 5555555			
RF Control			
RF Mode TX TEST $\sim$	Packet Type	DH5	$\sim$
Hopping ON $\checkmark$	TX Frequency	2480	$\sim$
TX Power 3 ~	RX Frequency	2402	$\sim$
Scenario PRBS Pattern			$\sim$
LOG: BR/EDR Test			^
LOG: Test end			
LOG: BR/EDR Test LOG: Test end			
LOG: BR/EDR Test			
LOG: Test end			
LOG: BR/EDR Test			
			~
COM9 is open	1500000bps		



# 5. SYSTEM TEST CONFIGURATION

#### 5.1. CONFIGURATION OF EUT SYSTEM

Radiated Emission Configure:

EUT

Conducted Emission Configure:

EUT	AE

#### 5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Bluetooth headset	M109	WSG-M109	EUT
2	Control Box	USB TO TTL	N/A	AE
3	Charger line	N/A	0.6m unshielded	Accessory
4	Adapter	HW-050200C01	DC 5V	AE

#### **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT	
15.247 (b)(1)	Peak Output Power	Compliant	
15.247 (a)(1)	20 dB Bandwidth	Compliant	
15.247 (d)	Conducted Spurious Emission	Compliant	
15.209	Radiated Emission	Compliant	
15.247 (a)(1)(iii)	Number of Hopping Frequency	Compliant	
15.247 (a)(1)(iii)	Time of Occupancy	Compliant	
15.247 (a)(1)	Frequency Separation	Compliant	
15.207	Conducted Emission	Compliant	



### 6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	ation 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China		
Designation Number	CN1259		
FCC Test Firm Registration Number	975832		
A2LA Cert. No.	5054.02		
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA		

#### TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test Software	FARA	EZ-EMC	Ver. AGC-CON03A1	N/A	N/A

#### TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Agilent	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Signal Analyzer	Aglient	N9020A	MY52090123	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA9170	768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Double-Ridged Waveguide Horn	ETS	3117	00154520	Sep. 06, 2021	Sep. 05, 2023
Preamplifier Assembly	ETS	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-49 4	Jan. 08, 2021	Jan. 07, 2023
Test Software	FARA	EZ-EMC	Ver.RA-03A	N/A	N/A



# 7. PEAK OUTPUT POWER

#### 7.1. MEASUREMENT PROCEDURE


For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW  $\geq$ RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

# 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

#### PEAK POWER TEST SETUP







#### 7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power					
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail	
	2402	-2.839	≪21	Pass	
GFSK	2441	-2.007	≤21	Pass	
	2480	-1.646	≤21	Pass	
	2402	-0.734	≪21	Pass	
π /4-DQPSK	2441	0.085	≤21	Pass	
	2480	0.387	≤21	Pass	


#### **Test Graphs of Conducted Output Power**



















### 8. 20DB BANDWIDTH

#### **8.1. MEASUREMENT PROCEDURE**

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

#### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)







Test Data of Occupied Bandwidth and -20dB Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail
	2402	0.838	0.951	N/A	Pass
GFSK	2441	0.839	0.952	N/A	Pass
	2480	0.837	0.953	N/A	Pass
	2402	1.159	1.284	N/A	Pass
π /4-DQPSK	2441	1.158	1.282	N/A	Pass
	2480	1.157	1.283	N/A	Pass

#### 8.3. LIMITS AND MEASUREMENT RESULTS














Test\_Graph\_EDR\_ANT1\_2441\_2Mbps\_OBW


 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/







# 9. CONDUCTED SPURIOUS EMISSION

#### 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
- Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
   RBW = 100 kHz; VBW= 300 kHz; Sweep = auto; Detector function = peak.
- 4. Set SPA Trace 1 Max hold, then View.

#### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 8.2

#### 9.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6

#### 9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT				
Applieghte Limite	Measurement Result			
Applicable Limits	Test Data	Criteria		
In any 100 kHz Bandwidth Outside the	At least -20dBc than the limit			
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS		
intentional radiator is operating, the radio frequency	Channel			
power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the TOP Channel	PASS		









#### Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands













































#### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands
















# **10. RADIATED EMISSION**

## **10.1. MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




## **10.2. TEST SETUP**


Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



## RADIATED EMISSION TEST SETUP ABOVE 1000MHz





## **10.3. LIMITS AND MEASUREMENT RESULT**

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

## 10.4. TEST RESULT


## Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



EUT	Bluetooth headset	Model Name	M109
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Horizontal

#### Radiated emission from 30MHz to 1000MHz




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		121.1231	6.79	21.64	28.43	43.50	-15.07	peak
2	*	315.4808	15.35	26.05	41.40	46.00	-4.60	peak
3		383.9318	10.03	24.04	34.07	46.00	-11.93	peak
4		423.5403	8.17	26.68	34.85	46.00	-11.15	peak
5		609.9217	6.62	26.65	33.27	46.00	-12.73	peak
6		872.1832	7.41	31.05	38.46	46.00	-7.54	peak

# **RESULT: PASS**



EUT	Bluetooth headset	Model Name	M109
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Vertical



## **RESULT: PASS**

6

938.8325

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

5.66

2. All test modes had been pre-tested. The mode 6 is the worst case and recorded in the report.

30.78

36.44

46.00

-9.56

peak



## **Radiated emission above 1GHz**

EUT	Bluetooth headset	Model Name	M109
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4804.000	50.34	0.08	50.42	74	-23.58	peak	
4804.000	38.67	0.08	38.75	54	-15.25	AVG	
7206.000	45.16	2.21	47.37	74	-26.63	peak	
7206.000	34.93	2.21	37.14	54	-16.86	AVG	
Remark:							
actor = Anter	nna Factor + Cab	le Loss – Pre-	amplifier.				

EUT	Bluetooth headset	Model Name M109	
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	- Value Type	
4804.000	48.53	0.08	48.61	74	-25.39	peak	
4804.000	36.89	0.08	36.97	54	-17.03	AVG	
7206.000	43.15	2.21	45.36	74	-28.64	peak	
7206.000	32.07	2.21	34.28	54	-19.72	AVG	
Remark:							
actor = Anter	na Factor + Cabl	e Loss – Pre-a	mplifier.				



EUT	Bluetooth headset	Model Name M109	
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 5	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4882.000	51.39	0.14	51.53	74	-22.47	peak
4882.000	39.87	0.14	40.01	54	-13.99	AVG
7323.000	44.57	2.36	46.93	74	-27.07	peak
7323.000	35.02	2.36	37.38	54	-16.62	AVG
Remark:						
actor = Anter	na Factor + Cab	e Loss – Pre-a	amplifier.			

EUT	Bluetooth headset	Model Name	M109
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 5	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4882.000	48.97	0.14	49.11	74	-24.89	peak
4882.000	37.34	0.14	37.48	54	-16.52	AVG
7323.000	44.27	2.36	46.63	74	-27.37	peak
7323.000	32.67	2.36	35.03	54	-18.97	AVG
Remark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			



EUT	Bluetooth headset	Model Name	M109
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4960.000	50.62	0.22	50.84	74	-23.16	peak
4960.000	38.52	0.22	38.74	54	-15.26	AVG
7440.000	43.62	2.64	46.26	74	-27.74	peak
7440.000	33.78	2.64	36.42	54	-17.58	AVG
Remark:						
actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Bluetooth headset	Model Name	M109
Temperature	21°C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4960.000	47.82	0.22	48.04	74	-25.96	peak
4960.000	36.86	0.22	37.08	54	-16.92	AVG
7440.000	42.78	2.64	45.42	74	-28.58	peak
7440.000	31.44	2.64	34.08	54	-19.92	AVG
emark:						

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

#### **RESULT: PASS**

## Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Emission Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been tested. The  $\pi$  /4-DQPSK modulation is the worst case and recorded in the report.




EUT	Bluetooth headset	Model Name	M109	
Temperature	25°C	Relative Humidity	60%	
Pressure	985hPa	Test Voltage	Normal Voltage	
Test Mode	Mode 4	Antenna	Horizontal	

## Test result for band edge emission at restricted bands

# Test Graph for Peak Measurement



Test Graph for Average Measurement



#### **RESULT: PASS**




#### Report No.: AGC00213221202FE03 Page 47 of 60

EUT	Bluetooth headset	Model Name	M109
Temperature	25°C	Relative Humidity	60%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



## **RESULT: PASS**




#### Report No.: AGC00213221202FE03 Page 48 of 60

EUT	Bluetooth headset	Model Name	M109
Temperature	25°C	Relative Humidity	60%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



## **RESULT: PASS**



#### Report No.: AGC00213221202FE03 Page 49 of 60

EUT	Bluetooth headset	Model Name	M109
Temperature	25°C	Relative Humidity	60%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



## **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer. The  $\pi$  /4-DQPSK modulation is the worst case and recorded in the report.



# **11. NUMBER OF HOPPING FREQUENCY**

## **11.1. MEASUREMENT PROCEDURE**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may

be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.

2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

3. VBW  $\geq$  RBW. Sweep: Auto. Detector function: Peak. Trace: Max hold.

4. Allow the trace to stabilize.

## 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

## **11.3. MEASUREMENT EQUIPMENT USED**

The same as described in section 6

## **11.4. LIMITS AND MEASUREMENT RESULT**

Test Data of Number of Hopping Frequency					
Test Mode Number of Hopping Frequency Limits Pass or Fail					
GFSK Hopping 79 >=15 Pass					

# Test Graphs of Number of Hopping Frequency



#### Note: The GFSK modulation is the worst case and recorded in the report.



# 12. TIME OF OCCUPANCY (DWELL TIME)

# 12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Zero span, centered on a hopping channel.

2. RBW shall be  $\leq$  channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.

3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

4. Detector function: Peak. Trace: Max hold.

5. Use the marker-delta function to determine the transmit time per hop.

6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer)  $\times$  (period specified in the requirements / analyzer sweep time).

7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

# 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2


## **12.3. MEASUREMENT EQUIPMENT USED**

The same as described in section 6


## **12.4. LIMITS AND MEASUREMENT RESULT**

Test Data of Dwell Time					
Channel	Time of Pulse for DH5 (ms)	Number of hops in the period specified in the requirements	Sweep Time (ms)	Limit (ms)	Pass or Fail
2402	2.902	31.0*4	359.848	400	Pass
2441	2.902	30.0*4	348.240	400	Pass
2480	2.902	30.0*4	348.240	400	Pass

Note: The GFSK modulation is the worst case and recorded in the report.









## Test Graphs of Dwell Time











# **13. FREQUENCY SEPARATION**

## **13.1. MEASUREMENT PROCEDURE**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Wide enough to capture the peaks of two adjacent channels.

2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

3. Video (or average) bandwidth (VBW)  $\geq$  RBW.

4. Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

## **13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)**


Same as described in section 6.2

## **13.3. MEASUREMENT EQUIPMENT USED**

The same as described in section 6.3

## **13.4. LIMITS AND MEASUREMENT RESULT**

Test Data of Frequency Separation						
Test Mode	Channel Separation (MHz)	Limits	Pass or Fail			
GFSK Hopping	0.973	>= 2/3 -20dB BW	Pass			



## **Test Graphs of Number of Hopping Frequency**

Note: The GFSK modulation is the worst case and recorded in the report.



# **14. LINE CONDUCTED EMISSION TEST**


## 14.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage				
Frequency	Q.P. (dBµV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





# 14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST


- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

## 14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.





## 14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



#### MEASUREMENT RESULT: "agc\_fin"

2022/12/12 17:	:49						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
0.162000	41.70	6.8	65	23.7	QP	L1	GND
0.410000	31.10	5.7	58	26.5	ÕP	L1	GND
0.418000	33.40	5.6	58	24.1	ÕP	L1	GND
0.518000	42.90	5.4	56	13.1	ÕP	L1	GND
0.738000	27.90	5.4	56	28.1	ÕP	L1	GND
1.738000	27.50	6.3	56	28.5	0P	L1	GND
1.,50000	27.00	0.0	00	20.0	×-		0110


#### MEASUREMENT RESULT: "agc\_fin2"

2022/12/12	17:49						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
0.194000	28.10	6.6	54	25.8	AV	L1	GND
0.322000	20.60	5.9	50	29.1	AV	L1	GND
0.454000	20.20	5.5	47	26.6	AV	L1	GND
0.486000	28.10	5.4	46	18.1	AV	L1	GND
0.518000	37.70	5.4	46	8.3	AV	L1	GND
0.758000	20.90	5.4	46	25.1	AV	L1	GND

#### **RESULT: PASS**



## LINE CONDUCTED EMISSION TEST-N



## MEASUREMENT RESULT: "agc\_fin"

2022/12/12 1	7:45						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
0.150000	48.80	6.9	66	17.2	QP	N	GND
0.186000	46.60	6.6	64	17.6	QP	N	GND
0.222000	43.80	6.4	63	18.9	QP	N	GND
0.258000	40.60	6.2	62	20.9	QP	N	GND
0.298000	36.90	6.0	60	23.4	QP	N	GND
0.518000	41.30	5.4	56	14.7	QP	N	GND

#### MEASUREMENT RESULT: "agc\_fin2"

2022/12/12	17:45						
Frequen	cy Level	. Transd	Limit	Margin	Detector	Line	PE
M	Hz dBµV	dB	dBµV	dB			
0.3340	00 26.00	5.9	49	23.4	AV	N	GND
0.4820	00 30.00	5.4	46	16.3	AV	N	GND
0.5180	00 38.60	5.4	46	7.4	AV	N	GND
0.5540	26.10	5.4	46	19.9	AV	N	GND
0.7420	00 26.90	5.4	46	19.1	AV	N	GND
0.7780	00 25.00	5.4	46	21.0	AV	N	GND

#### **RESULT: PASS**

Note: All the test modes had been tested, the Mode 6 was the worst case. Only the data of the worst case would be record in this test report.



# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC00213221202AP01

# **APPENDIX B: PHOTOGRAPHS OF EUT**

Refer to the Report No.: AGC00213221202AP02

----END OF REPORT----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.