

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Report No.: SZEM160500405901

Email: ee.shenzhen@sgs.com Page: 1 of 89

### **FCC REPORT**

Application No: SZEM1605004059CR

Applicant:SKY WING COMMUNICATION ELECTRONICS CO.,LTDManufacturer:SKY WING COMMUNICATION ELECTRONICS CO.,LTDFactory:SKY WING COMMUNICATION ELECTRONICS CO.,LTD

Product Name: Bluetooth Adapter

Model No.(EUT): SK-BTI-020V

SK-BTI-015, SK-BTI-016, SK-BTI-017, SK-BTI-018, SK-BTI-020,

Add Model No.: SK-BTI-021, SK-BTI-021V, SK-BTI-025, SK-BTI-026, SK-BTI-028,

DA88, TROND BT-DUO, TROND BT-DUO S, TROND BT-DUO X,

MG-BTTR100, JACK AIR

Trade Mark: Levn

FCC ID: WSGSK-BTI-020V

Standards: 47 CFR Part 15, Subpart C (2015)

**Date of Receipt:** 2016-06-13

**Date of Test:** 2016-06-14 to 2016-06-21

**Date of Issue:** 2016-06-27

Test Result: PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM160500405901

Page: 2 of 89

### 2 Version

Revision Record						
Version Chapter Date Modifier Remark						
01		2016-06-27		Original		

Authorized for issue by:		
Tested By	Brir Chen	2016-06-21
	(Bill Chen) /Project Engineer	Date
Prepared By	Wendy Jiang	2016-06-27
	(Wendy Jiang) /Clerk	Date
Checked By	Eric Fu	2016-06-27
	(Eric Fu) /Reviewer	Date



Report No.: SZEM160500405901

Page: 3 of 89

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	I frequency ANSI C63.10 (201		PASS

#### **Declaration of EUT Family Grouping:**

Model No.: SK-BTI-020V, SK-BTI-015, SK-BTI-016, SK-BTI-017, SK-BTI-018, SK-BTI-020, SK-BTI-021, SK-BTI-021V, SK-BTI-025, SK-BTI-026, SK-BTI-028, DA88, TROND BT-DUO, TROND BT-DUO S, TROND BT-DUO X, MG-BTTR100, JACK AIR

Only the model SK-BTI-020V was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above models, with only difference on outward appearance.



Report No.: SZEM160500405901

Page: 4 of 89

### 4 Contents

			Page
1	CC	OVER PAGE	1
2	VE	ERSION	2
3		ST SUMMARY	
J			
4	CC	ONTENTS	4
5	GE	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT	5
	5.3	TEST ENVIRONMENT	7
	5.4	DESCRIPTION OF SUPPORT UNITS	7
	5.5	TEST LOCATION	7
	5.6	TEST FACILITY	8
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	9
6	TE	EST RESULTS AND MEASUREMENT DATA	12
	6.1	ANTENNA REQUIREMENT	12
	6.2	CONDUCTED EMISSIONS	13
	6.3	CONDUCTED PEAK OUTPUT POWER	17
	6.4	20DB OCCUPY BANDWIDTH	24
	6.5	CARRIER FREQUENCIES SEPARATION	
	6.6	HOPPING CHANNEL NUMBER	
	6.7	DWELL TIME	
	6.8	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.9	Spurious RF Conducted Emissions	
	6.10	OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	
	6.11	RADIATED SPURIOUS EMISSION	
	• • • • • • • • • • • • • • • • • • • •	11.1 Radiated Emission below 1GHz	
		11.2 Transmitter Emission above 1GHz	
	6 17	RECTURATED DANIDE ADOLIND ELINDAMENTAL EDECLIENCY	20 20



Report No.: SZEM160500405901

Page: 5 of 89

#### 5 General Information

#### 5.1 Client Information

Applicant:	SKY WING COMMUNICATION ELECTRONICS CO.,LTD						
Address of Applicant:	NO.63, Road 10, Longyan, Humen Town, Dongguan City, Guangdong, China (523920)						
Manufacturer:	SKY WING COMMUNICATION ELECTRONICS CO.,LTD						
Address of Manufacturer:	NO.63, Road 10, Longyan, Humen Town, Dongguan City, Guangdong, China (523920)						
Factory:	SKY WING COMMUNICATION ELECTRONICS CO.,LTD						
Address of Factory:	NO.63, Road 10, Longyan, Humen Town, Dongguan City, Guangdong, China (523920)						

#### 5.2 General Description of EUT

Product Name:	Bluetooth Adapter
Model No.:	SK-BTI-020V
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.1 with EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Antenna Type:	Integral
Antenna Gain:	1dBi
Power Supply:	Rechargeable battery: DC 3.7V 250mAh 9.25Wh (charge by USB)



Report No.: SZEM160500405901

Page: 6 of 89

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

#### Note

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency		
The Lowest channel	2402MHz		
The Middle channel	2441MHz		
The Highest channel	2480MHz		



Report No.: SZEM160500405901

Page: 7 of 89

#### 5.3 Test Environment

Operating Environment:			
Temperature:	25.0 °C		
Humidity:	53 % RH		
Atmospheric Pressure:	1005mbar		

#### 5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.					
Adapter	Apple A1357 W010A						
Laptop	Lenovo	T430u					
Test board	Supply by SGS	N/A					

#### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM160500405901

Page: 8 of 89

#### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### • FCC - Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### 5.7 Deviation from Standards

None.

#### 5.8 Abnormalities from Standard Conditions

None.

#### 5.9 Other Information Requested by the Customer

None.



Report No.: SZEM160500405901

Page: 9 of 89

### 5.10 Equipment List

	Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)	
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13	
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2015-10-09	2016-10-09	
3	LISN	ETS- LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25	
4	8 Line ISN	Fischer Custom Communication s Inc.	FCC- TLISN-T8- 02	EMC0120	2015-08-30	2016-08-30	
5	4 Line ISN	Fischer Custom Communication s Inc.	FCC- TLISN-T4- 02	EMC0121	2015-08-30	2016-08-30	
6	2 Line ISN	Fischer Custom Communication s Inc.	FCC- TLISN-T2- 02	EMC0122	2015-08-30	2016-08-30	
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25	
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2015-10-09	2016-10-09	



Report No.: SZEM160500405901

Page: 10 of 89

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2015-08-01	2016-08-01
2	EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEM004-01	2016-04-25	2017-04-25
3	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-17	2016-01-26	2017-01-26
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-04-25	2017-04-25
5	Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015-08-14	2016-08-14

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEM004-04	2016-04-25	2017-04-25
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2015-10-09	2016-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2014-11-24	2017-11-24
7	Low Noise Amplifier	Black Diamond Series	BDLNA- 0118- 352810	SEM005-05	2015-10-09	2016-10-09
8	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A



Report No.: SZEM160500405901

Page: 11 of 89

	RF connected test						
Item	Test Equipment	Manufacturer	Model No.	Model No. Inventory No.		Cal.Due date	
					(yyyy-mm-dd)	(yyyy-mm-dd)	
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2015-10-09	2016-10-09	
2	Spectrum Analyzer	Rohde &	FSP	SEM004-06	2015-10-17	2016-10-17	
_	opcolitaini 7 inaiy20i	Schwarz	1 01	OLIVIOOT OO	2010 10 17	2010 10 17	
3	Cianal Congretor	Rohde &	SML03	SEM006-02	2016-04-25	2017 04 25	
3	Signal Generator	Schwarz	SIVILUS	3EIVIUU6-U2	2016-04-25	2017-04-25	
	Power Meter	Rohde &	NRVS	SEM014-02	2015-10-09	2016 10 00	
4	rower Meter	Schwarz	INHA2	S⊑IVIU14-U2	2015-10-09	2016-10-09	



Report No.: SZEM160500405901

Page: 12 of 89

#### 6 Test results and Measurement Data

### 6.1 Antenna Requirement

Standard 47 CFR Part 15C Section 15.203 /247(c) requirement:


#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna:**



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1dBi.



Report No.: SZEM160500405901

Page: 13 of 89


#### 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207					
Test Method:	ANSI C63.10: 2013					
Test Frequency Range:	150kHz to 30MHz					
Limit:	Limit (dBuV)					
	Frequency range (MHz)	Quasi-peak	Average			
	0.15-0.5	66 to 56*	56 to 46*			
	0.5-5	56	46			
	5-30	60	50			
	* Decreases with the logarithm	n of the frequency.		_		
Test Procedure:	<ol> <li>The mains terminal disturb room.</li> </ol>	bance voltage test was	s conducted in a shi	elded		
	<ol> <li>The EUT was connected to Impedance Stabilization Not impedance. The power call connected to a second LIS reference plane in the same measured. A multiple sock power cables to a single Lifexceeded.</li> <li>The tabletop EUT was place ground reference plane. At placed on the horizontal ground reference plane. At placed on the horizontal ground reference plane. The LISN unit under test and bonded mounted on top of the ground between the closest points the EUT and associated ed.</li> <li>In order to find the maximule equipment and all of the in ANSI C63.10: 2013 on contract.</li> </ol>	etwork) which provides oles of all other units of SN 2, which was bonder the way as the LISN 1 for et outlet strip was used ISN provided the rating old the rating of the upon a non-metallic and for floor-standing are cound reference plane, the a vertical ground referom the vertical ground referom the vertical ground reference old to a ground reference plane. The first of the LISN 1 and the quipment was at least 0 am emission, the relative terface cables must be	is a 50Ω/50μH + 5Ω lift the EUT were do to the ground or the unit being do to connect multiple of the LISN was not contained to the LI	he was ear ne he of 2.		



Report No.: SZEM160500405901

Page: 14 of 89





Report No.: SZEM160500405901


Page: 15 of 89

#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room Condition : CE LINE Job No. : 4059CR Test Mode : Charge+TX


	Freq		LISN Factor				Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15733	0.02	9.59	36.03	45.64	55.60	-9.96	Peak
2	0.19969	0.02	9.60	34.86	44.48	53.62	-9.14	Peak
3	0.23533	0.02	9.60	32.98	42.60	52.26	-9.66	Peak
4	0.61400	0.02	9.61	31.30	40.92	46.00	-5.08	Peak
5	1.636	0.02	9.60	23.71	33.32	46.00	-12.68	Peak
6	7.810	0.01	9.69	25.30	35.00	50.00	-15.00	Peak



Report No.: SZEM160500405901

Page: 16 of 89

#### Neutral line:



Site : Shielding Room Condition : CE NEUTRAL Job No. : 4059CR Test Mode : Charge+TX

		Cable	LISN	Read		Limit	Over	
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15403	0.02	9.62	36.13	45.77	55.78	-10.01	Peak
2	0.20181	0.02	9.62	33.51	43.14	53.54	-10.39	Peak
3	0.24422	0.02	9.61	32.67	42.29	51.95	-9.66	Peak
4	0.36338	0.01	9.62	31.65	41.28	48.65	-7.37	Peak
5 @	0.62715	0.02	9.63	32.39	42.04	46.00	-3.96	Peak
6	7.137	0.01	9.74	25.25	35.01	50.00	-14.99	Peak

#### Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM160500405901

Page: 17 of 89

### 6.3 Conducted Peak Output Power





Report No.: SZEM160500405901

Page: 18 of 89

#### **Measurement Data**

	weasurement bata						
	GFSK mode						
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	-2.91	30.00	Pass				
Middle	1.42	30.00	Pass				
Highest	2.01	30.00	Pass				
	π/4DQPSK mode						
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	-7.68	30.00	Pass				
Middle	-3.18	30.00	Pass				
Highest	-2.77	30.00	Pass				
	8DPSK mo	de					
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	-6.55	30.00	Pass				
Middle	-2.16	30.00	Pass				
Highest	-1.71	30.00	Pass				




Report No.: SZEM160500405901


Page: 19 of 89

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest












Report No.: SZEM160500405901

Page: 20 of 89














Report No.: SZEM160500405901

Page: 21 of 89

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM160500405901

Page: 22 of 89

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM160500405901

Page: 23 of 89








Report No.: SZEM160500405901

Page: 24 of 89

#### 6.4 20dB Occupy Bandwidth



#### **Measurement Data**

Toot channel	20dB Occupy Bandwidth (kHz)				
Test channel	GFSK	π/4DQPSK	8DPSK		
Lowest	931.385	1264.423	1254.808		
Middle	898.308	1259.615	1249.000		
Highest	894.231	1259.192	1249.000		





Report No.: SZEM160500405901


Page: 25 of 89

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM160500405901

Page: 26 of 89

Test mode: GFSK Test channel: Highest











Report No.: SZEM160500405901

Page: 27 of 89













Report No.: SZEM160500405901

Page: 28 of 89

Test mode: 8DPSK Test channel: Lowest











Report No.: SZEM160500405901

Page: 29 of 89








Report No.: SZEM160500405901

Page: 30 of 89

#### 6.5 Carrier Frequencies Separation





Report No.: SZEM160500405901

Page: 31 of 89

#### **Measurement Data**

Measurement Data						
	GFSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	1005	≥598.872	Pass			
	π/4DQPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	Middle 1005		Pass			
	8DPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	1023	≥832.667	Pass			

Note: According to section 6.4,

Mode	20dB bandwidth (kHz)	Limit (kHz)
····ous	(worse case)	(Carrier Frequencies Separation)
GFSK	898.308	598.872
π/4DQPSK	1264.423	842.949
8DPSK	1249.000	832.667





Report No.: SZEM160500405901


Page: 32 of 89

#### Test plot as follows:

Test mode: GFSK Test channel: Middle











Report No.: SZEM160500405901

Page: 33 of 89








Report No.: SZEM160500405901

Page: 34 of 89

#### 6.6 Hopping Channel Number



#### **Measurement Data**

Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15




Report No.: SZEM160500405901


Page: 35 of 89

Test plot as follows:

Test mode: GFSK




Test mode: π/4DQPSK






Report No.: SZEM160500405901

Page: 36 of 89








Report No.: SZEM160500405901

Page: 37 of 89

#### 6.7 Dwell Time



#### **Measurement Data**

Mode	Packet	Dwell time (second)	Limit (second)		
GFSK	DH1	0.123	0.4		
	DH3	0.282	0.4		
	DH5	0.320	0.4		
π/4DQPSK	2-DH1	0.132	0.4		
	2-DH3	0.350	0.4		
	2-DH5	0.350	0.4		
8DPSK	3-DH1	0.135	0.4		
	3-DH3	0.366	0.4		
	3-DH5	0.379	0.4		



Report No.: SZEM160500405901

Page: 38 of 89

#### Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

On (ms)\*total number=dwell time (ms)

The middle channel (2441MHz), as below:

DH1 time slot=0.390(ms)\*total number= 123.07(ms)

DH3 time slot=1.656(ms)\* total number = 281.50(ms)

DH5 time  $slot=2.912(ms)^*$  total number = 320.32(ms)

2-DH1 time slot=0.411(ms)\*total number= 131.52(ms)

2-DH3 time slot=1.668(ms)\* total number = 350.28(ms)

2-DH5 time slot=2.920(ms)\* total number = 450.40(ms)

3-DH1 time slot=0.410(ms)\*total number= 135.3 0(ms)

3-DH3 time slot=1.665(ms)\* total number =366.30(ms)

3-DH5 time slot=2.916(ms)\* total number = 379.08(ms)





Report No.: SZEM160500405901

Page: 39 of 89

Test plot as follows:

Test Packet: DH1









Report No.: SZEM160500405901

Page: 40 of 89











Report No.: SZEM160500405901

Page: 41 of 89











Report No.: SZEM160500405901

Page: 42 of 89












Report No.: SZEM160500405901

Page: 43 of 89











Report No.: SZEM160500405901

Page: 44 of 89











Report No.: SZEM160500405901

Page: 45 of 89












Report No.: SZEM160500405901

Page: 46 of 89











Report No.: SZEM160500405901

Page: 47 of 89










Report No.: SZEM160500405901

Page: 48 of 89

#### 6.8 Band-edge for RF Conducted Emissions







Report No.: SZEM160500405901

Page: 49 of 89

Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM160500405901

Page: 50 of 89











Report No.: SZEM160500405901

Page: 51 of 89












Report No.: SZEM160500405901

Page: 52 of 89











Report No.: SZEM160500405901

Page: 53 of 89












Report No.: SZEM160500405901

Page: 54 of 89









Report No.: SZEM160500405901

Page: 55 of 89

#### 6.9 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)				
Test Method:	ANSI C63.10:2013 Section 7.8.8				
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane				
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.				
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type				
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.				
Instruments Used:	Refer to section 5.10 for details				
Test Results:	Pass				




Report No.: SZEM160500405901

Page: 56 of 89











Report No.: SZEM160500405901

Page: 57 of 89











Report No.: SZEM160500405901

Page: 58 of 89









Report No.: SZEM160500405901

Page: 59 of 89












Report No.: SZEM160500405901

Page: 60 of 89











Report No.: SZEM160500405901

Page: 61 of 89









Report No.: SZEM160500405901

Page: 62 of 89











Report No.: SZEM160500405901

Page: 63 of 89











Report No.: SZEM160500405901

Page: 64 of 89








Report No.: SZEM160500405901


Page: 65 of 89






Report No.: SZEM160500405901

Page: 66 of 89








Report No.: SZEM160500405901

Page: 67 of 89





Start 10 GHz




Report No.: SZEM160500405901

Page: 68 of 89










Report No.: SZEM160500405901

Page: 69 of 89



#### Remark:

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.



Report No.: SZEM160500405901

Page: 70 of 89

#### 6.10 Other requirements Frequency Hopping Spread Spectrum System

#### **Test Requirement:**

#### 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

#### Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage


outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.



Report No.: SZEM160500405901

Page: 71 of 89

#### Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

#### Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: SZEM160500405901

Page: 72 of 89

#### 6.11 Radiated Spurious Emission


Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10: 2013								
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark				
	0.009MHz-0.090MHz		Peak	10kHz	z 30kHz	Peak			
	0.009MHz-0.090MHz		Average	10kHz	z 30kHz	Average			
	0.090MHz-0.110MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak			
	0.110MHz-0.490MHz		Peak	10kHz	z 30kHz	Peak			
	0.110MHz-0.490MHz		Average	10kHz	z 30kHz	Average			
	0.490MHz -30MHz		Quasi-peak	10kHz	30kHz	Quasi-peak			
	30MHz-1GHz	30MHz-1GHz Quasi-peak 100 kHz		lz 300kHz	Quasi-peak				
	Above 1GHz		Peak	1MHz	3MHz	Peak			
			Peak	1MHz	10Hz	Average			
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m	11		
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300			
	0.490MHz-1.705MHz	24000/F(kHz)		-	-	30			
	1.705MHz-30MHz		30	-	-	30			
	30MHz-88MHz	100		40.0	Quasi-peak 3				
	88MHz-216MHz	150		43.5	Quasi-peak	3			
	216MHz-960MHz		200	46.0	Quasi-peak 3				
	960MHz-1GHz		500	54.0	Quasi-peak 3				
	Above 1GHz		500	54.0	Average	3			
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.								



Report No.: SZEM160500405901

Page: 73 of 89

### Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

#### Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified



Report No.: SZEM160500405901

Page: 74 of 89

	<ul> <li>Bandwidth with Maximum Hold Mode.</li> <li>g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>h. Test the EUT in the lowest channel (2402MHz), the middle channel</li> </ul>
	<ul> <li>(2441MHz),the Highest channel (2480MHz)</li> <li>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>j. Repeat above procedures until all frequencies measured was complete.</li> </ul>
Fundamenta mu Talat Manda	
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of
	data type
	Transmitting mode, Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case.
	Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case
	For below 1GHz part, through pre-scan, the worst case is the lowest channel.
	Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Report No.: SZEM160500405901

Page: 75 of 89

### 6.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Charge+ Transmitting	Vertical



Condition: 10m VERTICAL

Job No. : 4059CR Test Mode: Charge+TX


		. 6						
		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	47.66	6.85	12.48	33.00	26.66	12.99	29.50	-16.51
2	63.98	7.00	11.94	32.93	27.47	13.48	29.50	-16.02
3	104.54	7.22	10.05	32.79	28.70	13.18	33.10	-19.92
4	163.18	7.50	12.74	32.73	26.20	13.71	33.10	-19.39
5	526.40	8.72	18.76	32.60	27.54	22.42	35.60	-13.18
6 pp	922.52	9.51	23.23	32.50	26.30	26.54	35.60	-9.06



Report No.: SZEM160500405901

Page: 76 of 89





Condition: 10m HORIZONTAL

Job No. : 4059CR Test Mode: Charge+TX

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	42.60	6.80	12.23	32.99	25.75	11.79	29.50	-17.71
2	60.49	7.00	12.43	32.95	25.28	11.76	29.50	-17.74
3	157.56	7.49	13.00	32.73	26.87	14.63	33.10	-18.47
4	327.89	8.14	13.64	32.60	26.54	15.72	35.60	-19.88
5 pp	533.83	8.74	18.71	32.60	25.52	20.37	35.60	-15.23
6	982.62	9.60	23.65	32.50	26.11	26.86	43.50	-16.64



Report No.: SZEM160500405901

Page: 77 of 89

### 6.11.2 Transmitter Emission above 1GHz

Worse case	mode:	GF	SK(DH1)		Test	channel:	Lowest		Rema	ırk:	Peak
Frequency (MHz)	Anten Facto (dB/r	or	Cable Loss (dB)	Fac	amp ctor IB)	Read Level (dBuV)	Level (dBuV/m)		Line V/m)	Over Limit (dB)	Polarization
3995.234	33.1	0	7.81	38	.56	47.47	49.82	7	4	-24.18	Vertical
4804.000	34.1	0	8.87	38	.75	49.57	53.79	7	4	-20.21	Vertical
6051.874	34.7	3	10.49	38	.89	45.24	51.57	7	4	-22.43	Vertical
7206.000	35.6	0	10.68	37	.64	40.53	49.17	7	4	-24.83	Vertical
9608.000	37.1	0	12.50	36	.35	35.09	48.34	7	4	-25.66	Vertical
12713.160	37.9	6	14.75	37	.86	36.28	51.13	7	4	-22.87	Vertical
3348.720	31.8	0	7.60	38	.30	45.82	46.92	7	4	-27.08	Horizontal
4804.000	34.1	0	8.87	38	.75	49.00	53.22	7	4	-20.78	Horizontal
6069.413	34.7	4	10.47	38	.87	45.91	52.25	7	4	-21.75	Horizontal
7206.000	35.6	0	10.68	37	.64	40.27	48.91	7	4	-25.09	Horizontal
9608.000	37.1	0	12.50	36	.35	35.59	48.84	7	4	-25.16	Horizontal
12639.790	37.9	2	14.55	37	.79	38.23	52.91	7	4	-21.09	Horizontal



Report No.: SZEM160500405901

Page: 78 of 89

Worse case	mode:	GFSK(DH1)	Tes	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3599.965	32.10	7.67	38.41	45.27	46.63	74	-27.37	Vertical
4882.000	34.18	8.98	38.77	49.15	53.54	74	-20.46	Vertical
6087.002	34.74	10.45	38.85	45.13	51.47	74	-22.53	Vertical
7323.000	35.54	10.72	37.59	42.49	51.16	74	-22.84	Vertical
9764.000	37.10	12.58	36.14	38.04	51.58	74	-22.42	Vertical
12530.530	37.83	14.24	37.68	37.67	52.06	74	-21.94	Vertical
3477.098	31.92	7.62	38.36	45.67	46.85	74	-27.15	Horizontal
4882.000	34.18	8.98	38.77	49.02	53.41	74	-20.59	Horizontal
6338.673	34.80	10.13	38.52	45.99	52.40	74	-21.60	Horizontal
7323.000	35.54	10.72	37.59	42.46	51.13	74	-22.87	Horizontal
9764.000	37.10	12.58	36.14	37.66	51.20	74	-22.80	Horizontal
12603.270	37.90	14.44	37.75	37.63	52.22	74	-21.78	Horizontal



Report No.: SZEM160500405901

Page: 79 of 89

Worse case	mode: 0	GFSK(DH1)	Tes	t channel:	Highest	ı	Remark:	Peak
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Li (dBuV/	I I imit	Polarization
3995.234	33.10	7.81	38.56	49.06	51.41	74	-22.59	Vertical
4960.000	34.26	9.09	38.78	48.51	53.08	74	-20.92	Vertical
6051.874	34.73	10.49	38.89	46.23	52.56	74	-21.44	Vertical
7440.000	35.60	10.77	37.54	36.44	45.27	74	-28.73	Vertical
9920.000	37.22	12.67	35.93	38.98	52.94	74	-21.06	Vertical
12676.420	37.94	14.65	37.82	37.74	52.51	74	-21.49	Vertical
3368.157	31.80	7.60	38.31	44.72	45.81	74	-28.19	Horizontal
4960.000	34.26	9.09	38.78	48.37	52.94	74	-21.06	Horizontal
6069.413	34.74	10.47	38.87	45.68	52.02	74	-21.98	Horizontal
7440.000	35.60	10.77	37.54	36.36	45.19	74	-28.81	Horizontal
9920.000	37.22	12.67	35.93	38.57	52.53	74	-21.47	Horizontal
12530.530	37.83	14.24	37.68	37.28	51.67	74	-22.33	Horizontal

### Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
  - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the above measurement data were shown in the report.




Report No.: SZEM160500405901

Page: 80 of 89

### 6.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205					
Test Method:	ANSI C63.10: 2013					
Test Site:	Measurement Distance: 3n	n (Semi-Anechoic Chambe	r)			
Limit:	Frequency	Limit (dBuV/m @3m)	Remark			
	30MHz-88MHz	40.0	Quasi-peak Value			
	88MHz-216MHz	43.5	Quasi-peak Value			
	216MHz-960MHz	46.0	Quasi-peak Value			
	960MHz-1GHz	54.0	Quasi-peak Value			
	Above 1GHz	54.0	Average Value			
	Above IGHZ	74.0	Peak Value			
			_			
Test Setup:						








Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: SZEM160500405901

Page: 81 of 89

Test Procedure:	<ul> <li>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> <li>h. Test the EUT in the lowest channel, the Highest channel</li> <li>i. The radiation measurements are performed in X, Y, Z axis positioning or Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>j. Repeat above procedures until all frequencies measured was complete.</li> </ul>
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of
Exploratory Foot Wood.	data type
	Transmitting mode, Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is
	the worst case.
	Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case
	Only the worst case is recorded in the report.
Instruments Used:	Only the worst case is recorded in the report.  Refer to section 5.10 for details




Report No.: SZEM160500405901

Page: 82 of 89

Test plot as follows:





Condition: 3m VERTICAL

Job No: : 4059CR

Mode: : 2402 Band edge Cahla


				Preamp Factor			Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	
							2390.000 2402.288	



Report No.: SZEM160500405901

Page: 83 of 89

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL

Job No: : 4059CR

Mode: : 2402 Band edge


			Cable	Ant	Preamp	Read		Limit	0ver
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	-								
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1		2200 000	E 24	20 57	20 11	44.20	10 10	74.00	22.00
		2390.000							
2	pp	2402.288	5.35	28.61	38.11	97.44	93.29	74.00	19.29



Report No.: SZEM160500405901

Page: 84 of 89

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Average Vertical



Condition: 3m VERTICAL

Job No: : 4059CR

Mode: : 2402 Band edge


				Preamp Factor			Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	
							2390.000	



Report No.: SZEM160500405901

Page: 85 of 89

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Average Horizontal



Condition: 3m HORIZONTAL

Job No: : 4059CR

Mode: : 2402 Band edge


				Preamp Factor			Freq		
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-	
							2390.000		



Report No.: SZEM160500405901

Page: 86 of 89

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Vertical
			9			



Condition: 3m VERTICAL Job No: : 4059CR

Mode: : 2480 Band edge


				Preamp Factor			Freq		
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	-	
							2479.863 2483.500		



Report No.: SZEM160500405901

Page: 87 of 89

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Peak Horizontal



Condition: 3m HORIZONTAL

Job No: : 4059CR

Mode: : 2480 Band edge


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Level Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m 1 pp 2479.863 5.41 28.97 38.12 101.99 98.25 74.00 24.25 2483.500 5.41 28.98 38.12 63.00 59.27 74.00 -14.73



Report No.: SZEM160500405901

Page: 88 of 89

		Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Average	Vertical
--	--	------------------	------------	---------------	---------	---------	---------	----------



Condition: 3m VERTICAL Job No: : 4059CR

Mode: : 2480 Band edge


Cable Ant Preamp Read Limit 0ver Loss Factor Factor Level Level dBuV dBuV/m dBuV/m MHz dB dB/m dB 1 pp 2480.082 5.41 28.97 38.12 77.90 74.16 54.00 2483.500 28.98 38.12 41.83 38.10 54.00 -15.90 5.41



Report No.: SZEM160500405901

Page: 89 of 89

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Average	Horizontal
	J. J. ( )					



Condition: 3m HORIZONTAL

Job No: : 4059CR

Mode: : 2480 Band edge

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
р	2480.082	5.41	28.97	38.12	86.57	82.83	54.00	28.83
	2483.500	5.41	28.98	38.12	50.49	46.76	54.00	-7.24

#### Note:

1 p

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor