



849 NW STATE ROAD 45
 NEWBERRY, FL 32669 USA
 PH: 888.472.2424 OR 352.472.5500
 FAX: 352.472.2030
 EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

FCC PART 90 AND IC RSS-119, RSS-GEN TEST REPORT

APPLICANT	TELTRONIC, S.A.U.
	POLIGONO MALPICA CALLE F PARCELA 12 ZARAGOZA 50057 SPAIN
FCC ID	FCC ID: WT7PTRUNK25RF410
IC CERTIFICATION	IC: 8624A-PT25410
MODEL NUMBER	RF Unit 409-430MHz
PRODUCT DESCRIPTION	409-430 MHz UHF Radio
DATE SAMPLE RECEIVED	3/11/2010
DATE TESTED	4/7/2010
TESTED BY	Joe Scoglio
APPROVED BY	Mario de Aranzeta
TIMCO REPORT NO.	550AUT10TestReport.PDF
TEST RESULTS	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



TABLE OF CONTENTS

GENERAL REMARKS 3

DUT SPECIFICATION 4

TEST EQUIPMENT AND ENVIRONMENT 5

TEST PROCEDURES 6

RF POWER OUTPUT 7

MODULATION CHARACTERISTICS 8

AUDIO FREQUENCY RESPONSE 9

AUDIO LOW PASS FILTER 10

AUDIO INPUT VERSUS MODULATION 11

OCCUPIED BANDWIDTH 12

SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED) 17

FIELD STRENGTH OF SPURIOUS EMISSIONS 20

RECEIVER RADIATED SPURIOUS EMISSIONS (For IC Filing) 24

FREQUENCY STABILITY 25

TRANSIENT FREQUENCY BEHAVIOR 26

EMC EQUIPMENT LIST 29

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: 4/7/2010

DUT SPECIFICATION

DUT Description	409-430 MHz UHF Radio
FCC ID	FCC ID: WT7PTRUNK25RJ410
IC Certification	IC: 8624A-PT25410
Model Number	RF Unit 409-430MHz
Serial Number	N/A
Operating Frequency	409 ~ 430 MHz
Type of Emission	F3E, F1W
Modulation	FM
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz
	<input checked="" type="checkbox"/> DC Power 24V
	<input type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
Type of Equipment	<input checked="" type="checkbox"/> Fixed
	<input type="checkbox"/> Mobile
	<input type="checkbox"/> Portable

TEST EQUIPMENT AND ENVIRONMENT

Test Conditions	The temperature was 26°C with a relative humidity of 50%.
Modification to the DUT	None
Test Exercise	The DUT was placed in continuous transmit mode.
Applicable Standards	ANSI/TIA 603-C:2004, FCC CFR 47 Part 90, IC RSS-119, RSS-GEN
Test Facility	Timco Engineering Inc. at 849 NW State Road 45 Newberry, FL 32669 USA.

TEST PROCEDURES

Power Line Conducted Interference: The procedure used was ANSI/TIA 603-C:2004 using a 50uH LISN. Both lines were observed with the DUT transmitting. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

Bandwidth 20 dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 1 MHz and the video bandwidth (VBW) = 3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Radiation Interference: The test procedure used was ANSI/TIA 603-C:2004 using an Agilent spectrum receiver with pre-selector. The bandwidth (RBW) of the spectrum receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a micro volt at the output of the antenna.


RF POWER OUTPUT

Rule Part No.: FCC Part 2.1046(a), IC RSS-119 4.1 and 5.4, RSS-GEN 4.8

Test Requirements: FCC Part 2.1046(a), IC RSS-119 4.1 and 5.4, RSS-GEN 4.8

Method of Measurement: RF power is measured by connecting a 50-ohm, resistive wattmeter to the RF output connector. With a nominal battery voltage, and the transmitter properly adjusted the RF output measures:

Test Setup Diagram:



Test Data:

OUTPUT POWER: HIGH 100 Watts
 LOW 0.6 Watts

Part 2.1033 (C)(8) DC Input into the final amplifier

FOR LOW POWER SETTING INPUT POWER: $(24.0V)(4.0A) = 96$ Watts
 FOR HIGH POWER SETTING INPUT POWER: $(24.0V)(16.5A) = 396$ Watts

MODULATION CHARACTERISTICS

Rule Part No.: Part 2.1033(c) (4), FCC Part 90.209, IC RSS-119 5.5, FCC Part 90.207

Requirements: Part 2.1033(c) (4)

Type of Emission:

Type of Emission: 11K2F3E

$$B_n = 2M + 2DK$$

$$M = 3000$$

$$D = 2100$$

$$K=1$$

$$B_n = 2(3000)+2(2100) = 10.2k$$

Type of Emission: 16K0F3E

$$B_n = 2M + 2DK$$

$$M = 3000$$

$$D = 4700$$

$$K=1$$

$$B_n = 2(3000)+2(4700) = 15.4k$$

APCO 25 Phase 1

8k1F1W

4800 baud and 2 bit symbol. This yields 9600 bps.

Applicant: TELTRONIC, S.A.U

FCC ID: WT7PTRUNK25RF410

IC CERT #: 8624A-PT25410

Report: T\TELTRONIC S.A.U\550AUT10\550AUT10TestReport.doc Page 8 of 29

AUDIO FREQUENCY RESPONSE



Rule Part No.: FCC Part 2.1047(a)(b), IC RSS-119 5.2

Test Requirements:

Method of Measurement:

The audio frequency response was measured in accordance with ANSI/TIA 603-C:2004. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 – 5000Hz shall be submitted. The audio frequency response curve is shown below.

AUDIO FREQUENCY RESPONSE PLOT



AUDIO LOW PASS FILTER

VOICE MODULATED COMMUNICATION EQUIPMENT

Part 2.1047(a) Voice modulated communication equipment: For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all the circuitry installed between the modulation limiter and the modulated stage shall be submitted.

AUDIO LOW PASS FILTER

N/A

AUDIO INPUT VERSUS MODULATION


Rule Part No.: FCC Part 2.1047(b) & 90, IC RSS-119 5.2

Test Requirements:

Method of Measurement: The audio input level needed for a particular deviation was measured in accordance with FCC procedure or ANSI/TIA 603-C: 2004. The audio input curves versus modulation are shown below. Curves are provided for audio input frequencies of 300, 1000, and 3000 Hz.

Test data:

Modulation Limiting Plot



OCCUPIED BANDWIDTH

Rule Part No.: FCC Part 2.1049(c), RSS-GEN 4.6, FCC Part 90.210(b) RSS-119 4.2

Requirements:

FCC Part 90.210(b) RSS-119 4.2 Channel Spacing

Data in the plots show that on any frequency removed from the assigned frequency by more than 50%, but not more than 100%: At least 25dB. On any frequency removed from the assigned frequency by more than 100%, but not more than 250%: At least 35 dB. On any frequency removed from the assigned frequency by more than 250%, of the authorized bandwidth: At least $43 + 10\log(P)$ dB.

Part 90.210(c) 12.5kHz Channel Spacing Not Equipped with a Low Pass Filter

For transmitters that are not equipped with an audio low pass filter pursuant to S90.211 (b), the power of any emission must be attenuated below the un-modulated carrier output power as follows; (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5 kHz but not more than 10 kHz: At least $83 \log(f_d/5)$ dB; (2) ON any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 10 kHz, but not more than 250% of the authorized bandwidth: At least $29 \log(f_d^2/11)$ dB or 50 dB, whichever is the lesser attenuation; (3) On any frequency removed from the center of the authorized bandwidth by more than 250% of the authorized bandwidth: At least $43 + 10 \log(P_o)$ dB.

Part 90.210(d) Emission Mask D - 12.5 kHz channel BW equipment

For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10\log(P)$ dB or 70 dB, whichever is the lesser attenuation.

Part 90.210(e) Emission Mask E – 6.25 kHz channel BW equipment

For transmitters designed to operate with a 6.25 kHz bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 3.0 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least $30 + 16.67(f_d - 3.0 \text{ kHz})$ or $55 + 10 \log(P)$ or 65, whichever us the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6kHz: At least $55 + 10\log(P)$ dB or 65 dB, whichever is the lesser attenuation.

Applicant: TELTRONIC, S.A.U

FCC ID: WT7PTRUNK25RF410


IC CERT #: 8624A-PT25410

Report: T\TELTRONIC S.A.U\550AUT10\550AUT10TestReport.doc Page 12 of 29

Test procedure: ANSI/TIA-603-C:2004 para 2.2.11.

Test Setup Diagram:

OCCUPIED BANDWIDTH MEASUREMENT




Test Data: See the plots below

12.5 kHz

NOTES:


FCC 90.210 Mask D



25 kHz

NOTES:

FCC 90.210 Mask C




Digital

12.5 kHz

NOTES:

FCC 90.210 Mask D



Applicant: TELTRONIC, S.A.U
 FCC ID: WT7PTRUNK25RF410
 IC CERT #: 8624A-PT25410
 Report: T\TELTRONIC S.A.U\550AUT10\550AUT10TestReport.doc

SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)

Rule Part No.: FCC Part 2.1051(a), RSS-GEN 7.1.4

Method of Measurement: The carrier was modulated 100% using a 2500 Hz tone. The spectrum was scanned from 0.4 to at least the 10th harmonic of the fundamental. The measurements were made in accordance with standard ANSI/TIA 603-C:2004.

FCC Limit for:
 25kHz Channel Spacing = 63
 12.5kHz Spacing = 70
 6.25kHz Channel Spacing = N/A


Test Data:

TF HIGH POWER	EF	dB below carrier		TF LOW POWER	EF	dB below carrier
409	409	0		409	409	0
	818	90.9			818	90.9
	1227	81.5			1227	94.2
	1636	102.8			1636	95.9
	2045	96.8			2045	109.6
	2454	113.7			2454	110.4
	2863	106.9			2863	112.3
	3272	106				
	3681	121.5				
	4090	117.4				

TF HIGH POWER	EF	dB below carrier		TF LOW POWER	EF	dB below carrier
423	423	0		423	423	0
	846	98.5			846	88.6
	1269	85.5			1269	94.5
	1692	101.4			1692	98.8
	2115	96.7			2115	111.9
	2538	111.5			2538	112.7
	2961	111.4			2961	112.8
	3384	113.9				
	3807	120				
	4230	117.4				

TF HIGH POWER	EF	dB below carrier		TF LOW POWER	EF	dB below carrier
430	430	0		430	430	0
	860	103.4			860	88.1
	1290	87			1290	92.3
	1720	104.7			1720	93.6
	2150	100.9			2150	106.1
	2580	114.3			2580	109.1
	3010	115.9			3010	108.7
	3440	119.8			3440	
	3870	125.9			3870	
	4300	115.9			4300	

Method of Measuring Conducted Spurious Emissions



METHOD OF MEASUREMENT: The procedure used was ANSI/TIA 603-C:2004. The measurements were made at TIMCO ENGINEERING INC. 849 N.W. State Road 45, Newberry, Florida 32669.


FIELD STRENGTH OF SPURIOUS EMISSIONS

Rule Parts. No.: FCC Part 2.1053, RSS-GEN 4.9

Requirements: The FCC limits for radiated emissions are the same as previously stated for the conducted emissions.

Method of Measurement: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 MHz to at least the tenth harmonic of the fundamental. This test was conducted per ANSI/TIA 603-C:2004 using the substitution method. Measurements were made at the test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

Test Setup Diagram:



Test Data:

HI

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
409.00	V	0
818.00	V	95.80
1227.00	H	92.04
1636.00	V	102.32
2045.00	V	96.66
2454.00	V	101.68
2863.00	V	101.74
3272.00	H	100.79
3681.00	H	102.14
4090.00	H	103.73

LO

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
409.00	V	0
818.00	V	91.20
1227.00	V	82.14
1636.00	V	79.72
2045.00	V	81.36

[Continued]

HI

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
423.00	V	0
846.00	V	98.90
1269.00	V	92.31
1692.00	H	103.72
2115.00	V	99.00
2538.00	V	103.19
2961.00	V	104.92
3384.00	V	101.55
3807.00	H	101.48
4230.00	H	104.06

LO

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
423.00	V	0
846.00	V	88.20
1269.00	V	82.01
1692.00	H	80.62
2115.00	V	83.20

[Continued]

HI

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
430.00	V	0
860.00	V	97.52
1290.00	V	93.59
1720.00	H	101.58
2150.00	V	97.34
2580.00	V	97.58
3010.00	V	96.58
3440.00	V	102.00
3870.00	H	104.01
4300.00	H	100.52

LO

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
437.00	V	0
860.00	H	85.02
1290.00	H	78.99
1720.00	H	76.58
2150.00	H	80.44

RECEIVER RADIATED SPURIOUS EMISSIONS (For IC Filing)

Rule Parts. No.: FCC Part 15.109, RSS-GEN 4.10, 6

Requirements:

30-88 MHz	40.0 dB μ V/m measured at 3 meters
88-216 MHz	43.5 dB μ V/m
216-960 MHz	46.0 dB μ V/m
ABOVE 960 MHz	54.0 dB μ V/m

Receiver data as shown below is not part of the FCC certification process. Per FCC Rules Part 15.101(b), the receiver is subject to verification.

The data shown below is part of the IC Certification process only.

Test Data:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μ V	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dB μ V/m	Margin dB
410.0	500.00	9.9	H	1.30	17.90	29.10	16.90
410.0	500.00	10.2	V	1.30	17.90	29.40	16.60
425.0	525.00	5.6	H	1.39	18.50	25.49	20.51
425.0	525.00	6.3	V	1.39	17.70	25.39	20.61
430.0	530.00	5.3	H	1.48	18.80	25.58	20.42
430.0	530.00	7.6	V	1.48	18.10	27.18	18.82

FREQUENCY STABILITY

Rule Parts. No.: FCC Part 2.1055, Part 90.213, RSS-119 5.3, RSS-GEN 7.2.4

Requirements: Temperature range requirements: -30 to +50° C.
Voltage Variation +, -15%
±1.5 PPM

Method of Measurements: ANSI/TIA 603-C:2004

Test Data:

Assigned Frequency (Ref. Frequency) (MHz)		
Temperature (°C)	Frequency (MHz)	Frequency Stability (PPM)
-30	425.00004	-0.01
-20	425.000039	-0.01
-10	425.000039	-0.01
0	425.000040	-0.01
+10	425.000039	-0.01
+20	425.00004	-0.01
+30	425.000039	-0.01
+40	425.000039	-0.01
+50	425.00004	-0.01

Assigned Frequency (Ref. Frequency) (MHz)		
% Battery (%)	Frequency (MHz)	Frequency Stability (PPM)
-15%	425.000041	0.00
+15%	425.000042	0.00

TRANSIENT FREQUENCY BEHAVIOR

Rule Part No.: FCC Part 2.1055(a)(1), FCC Part 90.214, IC RSS-119 5.8

Requirements: Transmitters designed to operate in the 150-174 MHz and 421-512 MHz frequency bands must maintain transient frequencies within the maximum transient frequencies within the maximum frequency difference limits during the time intervals indicated:

Time Intervals	Maximum frequency difference	All Equipment	
		150-174 MHz	421-512 MHz

Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels



t_1^4	± 25.0 kHz	5.0 ms	10.0 ms
t_2	± 12.5 kHz	20.0 ms	25.0 ms
t_3^4	± 25.0 kHz	5.0 ms	10.0 ms

Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels

t_1^4	± 12.5 kHz	5.0 ms	10.0 ms
t_2	± 6.25 kHz	20.0 ms	25.0 ms
t_3^4	± 12.5 kHz	5.0 ms	10.0 ms


Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels

t_1^4	± 6.25 kHz	5.0 ms	10.0 ms
t_2	± 3.125 kHz	20.0 ms	25.0 ms
t_3^4	± 6.25 kHz	5.0 ms	10.0 ms



Test Procedure: ANSI/TIA 603-C:2004 PARA 2.2.19

1. Using the variable attenuator the transmitter level was set to 40 dB below the test receivers maximum input level, then the transmitter was turned off.
2. With the transmitter off the signal generator was set 20dB below the level of the transmitter in the above step, this level will be maintained with the signal generator through-out the test.
3. Reduce the attenuation between the transmitter and the RF detector by 30 dB. With the levels set as above the transient frequency behavior was observed & recorded.



EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/20/10	3/19/13
3-Meter OATS	TEI	N/A	N/A	Listed 1/11/09	1/10/12
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 5/11/07	5/11/10
AC Voltmeter	HP	400FL	2213A14499	CAL 12/29/08	12/29/10
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 11/30/09	11/30/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/30/09	11/30/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/30/09	11/30/11
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/30/09	11/30/11
Coaxial Cable #64	Semflex Inc.	60637	Timco #64	CHAR 3/30/09	3/30/11
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	152	CAL 3/3/09	3/3/12
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 4/5/09	4/5/12
Frequency Counter	HP	5385A	2730A03025	CAL 7/6/09	7/6/11
Hygro-Thermometer	Extech	445703	0602	CAL 11/15/09	11/15/11
Antenna: Log-Periodic	Electro-Metrics	LPA-25	1122	CAL 12/1/08	12/1/10
Measuring Tape-7.5M	Kraftixx	7.5M PROFI		CHAR 11/13/09	11/13/11
Modulation Analyzer	HP	8901A	3435A06868	CAL 5/9/09	5/9/11
Digital Multimeter	Fluke	FLUKE-77-3	79510405	CAL 5/14/09	5/14/11
System One	Audio Precision	System One	SYS1-45868	CHAR 2/27/10	2/27/12
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/08	4/25/10