



## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	CAMWIFI
<b>Model Number</b>	BT532767
<b>FCC ID</b>	WUI-BT532767
<b>Antenna gain (Max)</b>	0 dBi
<b>Operation Frequency</b>	2.412GHz ~ 2.462GHz
<b>Input Rating</b>	DC 12V, DC 24V for host
<b>Max. output power</b>	802.11b: 10.46dBm 802.11g: 10.27dBm 802.11n(HT20): 9.71dBm 802.11n(HT40): 12.83dBm

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF)

Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

### 11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1416

R = 20cm distance between observation point and center of the radiator in cm


At the limit of MPE,  $1\text{mW}/\text{cm}^2$ . If we know the maximum gain of the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### 11.2 Measurement Result

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
			Ant1		
802.11b	1	2412	9.05	30	PASS
	6	2437	9.68	30	PASS
	11	2462	10.46	30	PASS
802.11g	1	2412	8.87	30	PASS
	6	2437	9.79	30	PASS
	11	2462	10.27	30	PASS
802.11n (HT20)	1	2412	8.89	30	PASS
	6	2437	9.71	30	PASS
	11	2462	8.25	30	PASS
802.11n (HT20)	3	2422	11.19	30	PASS
	6	2437	11.99	30	PASS
	9	2452	12.83	30	PASS

802.11b	1	9±1	10	10.000	0	1	0.001989	1
	6	10±1	11	12.589	0	1	0.002505	1
	11	11±1	12	15.849	0	1	0.003153	1
802.11g	1	9±1	10	10.000	0	1	0.001989	1
	6	10±1	11	12.589	0	1	0.002505	1
	11	10±1	11	12.589	0	1	0.002505	1
802.11n (HT20)	1	9±1	10	10.000	0	1	0.001989	1
	6	10±1	11	12.589	0	1	0.002505	1
	11	8±1	9	7.943	0	1	0.001580	1
802.11n (HT40)	3	11±1	12	15.849	0	1	0.003153	1
	6	12±1	13	19.953	0	1	0.003969	1
	9	13±1	14	25.119	0	1	0.004997	1

Signature:



Tomas Yang

Date: 2022-06-10