

FCC ID : WUI-LM56176

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

$$11.1 \text{ Friis transmission formula: } P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm^2 , If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

WIFI

Antenna gain: 2.8dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
11b	2412	17.10	16 to 18	18	1.91	0.024	1
	2437	16.16	15 to 17	17	1.91	0.019	1
	2462	15.65	14 to 16	16	1.91	0.015	1
11g	2412	14.30	13 to 15	15	1.91	0.012	1
	2437	14.32	13 to 15	15	1.91	0.012	1
	2462	14.15	13 to 15	15	1.91	0.012	1
11n HT20	2412	15.46	14 to 16	16	1.91	0.015	1
	2437	14.52	13 to 15	15	1.91	0.012	1
	2462	14.28	13 to 15	15	1.91	0.012	1

5.8G

Antenna gain: -0.3dBi

modulation	Channel Freq. (MHz)	Field strength (dBuV/m)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	5830.6	98.03	2.80	1 to 3	3	0.9	0.00037	1