

CFR 47 FCC PART 15 SUBPART C(DTS) TEST REPORT

For

ROADCAM DUAL

MODEL NUMBER: BT532968

REPORT NUMBER: E04A23110087F00101

ISSUE DATE: Nov. 24, 2023

FCC ID: WUI-M08PRO

Prepared for

Winplus Co., Ltd.

Suites 6-11, 7th Floor, Corporation Park, 11 On La Shatin, Hong Kong

Prepared by

Guangdong Global Testing Technology Co., Ltd.

Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

This report shall not be reproduced, except in full, without the written approval of Guangdong Global Testing Technology Co., Ltd.

TRF No.: 04-E001-1A TRF Originator: GTG TRF Date: 2023-08-25 Web: www.gtggroup.com E-mail: info@gtggroup.com Tel.: 86-400 755 8988

REPORT NO.: E04A23110087F00101 Page 2 of 51

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	Nov. 24, 2023	Initial Issue	Win

REPORT NO.: E04A23110087F00101 Page 3 of 51

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	N/A
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.11 & Clause 11.12	FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

Note:

^{1.} N/A: In this whole report not applicable.

^{*}This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

^{*}The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C(DTS)> when <Accuracy Method> decision rule is applied.

CONTENTS

1.	ATTES	STATION OF TEST RESULTS	5
2.	TEST I	METHODOLOGY	6
3.	FACIL	ITIES AND ACCREDITATION	6
4.	CALIB	RATION AND UNCERTAINTY	7
	4.1.	MEASURING INSTRUMENT CALIBRATION	7
	4.2.	MEASUREMENT UNCERTAINTY	7
5.	EQUIP	MENT UNDER TEST	8
	5.1.	DESCRIPTION OF EUT	8
	5.2.	CHANNEL LIST	8
	5.3.	CONDUCTED OUTPUT AVERAGE POWER	9
	5.4.	TEST CHANNEL CONFIGURATION	9
	5.5.	THE WORSE CASE POWER SETTING PARAMETER	9
	5.6.	DESCRIPTION OF AVAILABLE ANTENNAS	10
	5.7.	EUT ACCESSORY	10
	5.8.	SUPPORT UNITS FOR SYSTEM TEST	10
	5.9.	SETUP DIAGRAM	11
6.	MEAS	URING EQUIPMENT AND SOFTWARE USED	12
7.	ANTEN	NNA PORT TEST RESULTS	14
	7.1.	Conducted Output Power	14
	7.2.	6dB Bandwidth	15
	7.3.	Power Spectral Density	17
	7.4.	Conducted Band edge and spurious emission	18
	7.5.	Duty Cycle	20
8.	RADIA	TED TEST RESULTS	21
9.	ANTEN	NNA REQUIREMENT	38
10).	AC POWER LINE CONDUCTED EMISSION	39
11	l .	TEST DATA	41
ΑI	PPENDIX	: PHOTOGRAPHS OF TEST CONFIGURATION	42
ΑF	PPENDIX	: PHOTOGRAPHS OF THE EUT	43

REPORT NO.: E04A23110087F00101 Page 5 of 51

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Winplus Co., Ltd.

Address: Suites 6-11, 7th Floor, Corporation Park, 11 On La Shatin, Hong

Kong

Manufacturer Information

Company Name: ADC Solutions Auto, LLC

Address: 2975 Red Hill Ave., Ste. 100, Costa Mesa, CA 92626

EUT Information

Product Description: ROADCAM DUAL

Model: BT532968 Brand: YADA

Sample Received Date: Nov. 03, 2023

Sample Status: Normal

Sample ID: A23110087 002

Date of Tested: Nov. 03, 2023 to Nov. 24, 2023

APPLICABLE STANDARDS					
STANDARD TEST RESULTS					
CFR 47 FCC PART 15 SUBPART C(DTS)	Pass				

Prepared By:

Win Huang

Project Engineer

Laboratory Manager

Checked By:

Alan He

Laboratory Leader

REPORT NO.: E04A23110087F00101 Page 6 of 51

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C(DTS)

3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 6947.01)		
	Guangdong Global Testing Technology Co., Ltd.		
	has been assessed and proved to be in compliance with A2LA.		
	FCC (FCC Designation No.: CN1343)		
	Guangdong Global Testing Technology Co., Ltd.		
	has been recognized to perform compliance testing on equipment		
Accreditation Certificate	subject to Supplier's Declaration of Conformity (SDoC) and		
	Certification rules		
	ISED (Company No.: 30714)		
	Guangdong Global Testing Technology Co., Ltd.		
	has been registered and fully described in a report filed with ISED.		
	The Company Number is 30714 and the test lab Conformity		
	Assessment Body Identifier (CABID) is CN0148.		

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

REPORT NO.: E04A23110087F00101 Page 7 of 51

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty	
DTS Bandwidth	1.96	±9.2 PPM	
20dB Emission Bandwidth	1.96	±9.2 PPM	
Carrier Frequency Separation	1.96	±9.2 PPM	
Time of Occupancy	1.96	±0.57%	
Conducted Output Power	1.96	±1.5 dB	
Power Spectral Density Level	1.96	±1.9 dB	
		9 kHz-30 MHz: ± 0.95 dB	
Conducted Spurious Emission	1.96	30 MHz-1 GHz: ± 1.5 dB	
'		1GHz-12.75GHz: ± 1.8 dB	
		12.75 GHz-26.5 GHz: ± 2.1dB	

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

REPORT NO.: E04A23110087F00101 Page 8 of 51

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name		ROADCAM DUAL	
Model		BT532968	
Hardware Version		M08pro-MAIN-V01	
Software Version		20231116	
Ratings		DC 12V/24V	
Dower Cumply	DC	12V/24V	
Power Supply	Battery	1	

Frequency Band:	2400 MHz to 2483.5 MHz		
Frequency Range:	2412 MHz to 2462 MHz		
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40		
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)		
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n: Up to MCS7		
Number of Channels:	IEEE 802.11b/g/n-HT20: 11 IEEE 802.11n-HT40: 7		
Maximum Output Power:	IEEE 802.11b: 15.30 dBm IEEE 802.11g: 14.70 dBm IEEE 802.11n-HT20: 14.72 dBm IEEE 802.11n-HT40: 13.31 dBm		
Antenna Type:	FPC Antenna		
Antenna Gain:	1.22dBi		
Normal Test Voltage:	5 Vdc		
EUT Test software:	SecureCRT		

5.2. CHANNEL LIST

	Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
1	2412	4	2427	7	2442	10	2457	
2	2417	5	2432	8	2447	11	2462	
3	2422	6	2437	9	2452	1	1	

	Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
3	2422	5	2432	7	2442	9	2452	
4	2427	6	2437	8	2447	1	1	

REPORT NO.: E04A23110087F00101 Page 9 of 51

5.3. CONDUCTED OUTPUT AVERAGE POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted Output Power (dBm)	Maximum EIRP (dBm)
b	2412 ~ 2462	1-11[11]	15.30	/
g	2412 ~ 2462	1-11[11]	14.70	/
n HT20	2412 ~ 2462	1-11[11]	14.72	/
n HT40	2422 ~ 2452	3-9[7]	13.31	/

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The V	The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Softv	vare			Secu	ıreCRT			
NA 1 1 C	Transmit			Test C	Channel			
Modulation Mode	Antenna	1	NCB: 20MHz			NCB: 40MHz		
Wiode	Number	CH 1	CH 6	CH 11	CH 3	CH 6	CH 9	
802.11b	1	40	40	40				
802.11g	1	48 48 48 /						
802.11n HT20	1	48 48 48						
802.11n HT40	1		/		45	45	45	

WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

REPORT NO.: E04A23110087F00101 Page 10 of 51

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps 802.11g mode: 6 Mbps 802.11n HT20 mode: MCS0 802.11n HT40 mode: MCS0

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	FPC Antenna	1.22

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	⊠1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	⊠1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	⊠1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	⊠1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
Note:		

Note: The value of the antenna gain was declared by customer.

5.7. EUT ACCESSORY

	Cable					
Accessory: USB cable						
Model No.:	N/A					
Description:	Car Charger Type-C Plug Cable					
Cable Type:	Unshielded without ferrite; Unshielded with two ferrite					
Length:	2.74 Meter					

5.8. SUPPORT UNITS FOR SYSTEM TEST

The EUT has been tested as an independent unit

Equipment	Manufacturer	Model No.
ROADCAM DUAL	Winplus Co., Ltd.	BT532968
PC	Lenovo	T14

REPORT NO.: E04A23110087F00101 Page 11 of 51

5.9. SETUP DIAGRAM

Radiated emissions:



REPORT NO.: E04A23110087F00101 Page 12 of 51

6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF						
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date	
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2023/09/18	2024/09/17	
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2023/09/18	2024/09/17	
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2023/09/18	2024/09/17	
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2023/09/18	2024/09/17	
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2023/09/18	2024/09/17	
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2023/09/18	2024/09/17	
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2023/09/18	2024/09/17	
temperature humidity chamber	Espec	SH-241	SH-241-2014	2023/09/18	2024/09/17	
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A	

	Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date	
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2022/08/30	2025/08/29	
EMI Test Receiver	Rohde & Schwarz	ESCI3	101409	2023/09/18	2024/09/17	
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17	
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2023/09/18	2024/09/17	
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2022/10/10	2025/10/09	
Biconilog Antenna	ETS	3142E	00243646	2022/03/23	2025/03/22	
Loop Antenna	ETS	6502	243668	2022/03/30	2025/03/29	
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A	

Test Equipment of Radiated emissions above 1GHz						
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date	
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2022/08/30	2025/08/29	
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2023/09/18	2024/09/17	
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17	
Pre-Amplifier	A-INFO	HPA-1G1850	HYPA21003	2023/09/18	2024/09/17	
Horn antenna	A-INFO	3117	246069	2022/03/11	2025/03/10	
Pre-Amplifier	ZKJC	HPA-184057	HYPA21004	2023/09/18	2024/09/17	

REPORT NO.: E04A23110087F00101 Page 13 of 51

Horn antenna	ZKJC	3116C	246265	2022/03/29	2025/03/28
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2022/10/29	2025/10/28
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2023/09/18	2024/09/17
LISN/AMN	Rohde & Schwarz	ENV216	102843	2023/09/18	2024/09/17
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2023/09/18	2024/09/17
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

REPORT NO.: E04A23110087F00101 Page 14 of 51

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS


CFR 47 FCC Part15 (15.247) Subpart C					
Section Test Item Limit Frequency Range (MHz)					
CFR 47 FCC 15.247(b)(3)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5		

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

REPORT NO.: E04A23110087F00101 Page 15 of 51

7.2. 6DB BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C				
Section Test Item Limit Frequency Range (MHz)				
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5	

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz
VBW	For 6 dB Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

REPORT NO.: E04A23110087F00101 Page 16 of 51

TEST RESULTS

Please refer to section "Test Data" - Appendix A

REPORT NO.: E04A23110087F00101 Page 17 of 51

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C				
Section Test Item Limit Frequency Ran (MHz)				
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5	

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	3 kHz ≤ RBW ≤ 100 kHz
VBW	≥3 × RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

REPORT NO.: E04A23110087F00101 Page 18 of 51

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section Test Item Limit			
Conducted at least 20 dB below that in the 100 kHz Bandedge and Spurious Emissions the highest level of the desired power			

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.


Change the settings for emission level measurement:

1.2020	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
measurement points	≥span/RBW
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

REPORT NO.: E04A23110087F00101 Page 19 of 51

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

REPORT NO.: E04A23110087F00101 Page 20 of 51

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

REPORT NO.: E04A23110087F00101 Page 21 of 51

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz							
Frequency Range	Field Strength Limit	Field Strength Limit					
(MHz)	(uV/m) at 3 m	(dBuV/m) at 3 m					
		Quasi-l	Реак				
30 - 88	100	40					
88 - 216	150	43.5					
216 - 960	200	46					
Above 960	500	54					
Above 1000	500	Peak	Average				
Above 1000	500	74	54				

FCC Emissions radiated outside of the specified frequency bands below 30 MHz							
Frequency (MHz) Field strength (microvolts/meter) Measurement distance (meters)							
0.009-0.490	2400/F(kHz)	300					
0.490-1.705	24000/F(kHz)	30					
1.705-30.0	30	30					

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

REPORT NO.: E04A23110087F00101 Page 22 of 51

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

- 1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
- 2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
- 3. The EUT was placed on a turntable with 80 cm above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
- 5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
- 6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode remeasured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
- 7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
- 8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to Y-51.5 = Z dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP

REPORT NO.: E04A23110087F00101 Page 23 of 51

Trace	Max hold

- 1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 3. The EUT was placed on a turntable with 80 cm above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G


The setting of the spectrum analyser

RBW	1 MHz
IVRW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

- 1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 3. The EUT was placed on a turntable with 1.5 m above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
- 6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.


REPORT NO.: E04A23110087F00101 Page 24 of 51


X axis, Y axis, Z axis positions:




Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST SETUP





REPORT NO.: E04A23110087F00101 Page 25 of 51



TEST ENVIRONMENT

¯emperature 24.3°C		Relative Humidity	54%
Atmosphere Pressure	101kPa		


REPORT NO.: E04A23110087F00101 Page 26 of 51

TEST RESULTS

Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)


We tested all modes, The worst case scenario is as follows:

Mode:	2.4G-B-2412
Power:	DC 5V
TE:	Berny
Date	2023/11/9
T/A/P	24.3°C/54%/101Kpa



No.	Freq.	Reading	Meas.	Limit	Margin	Det.	Height	Pol.	Azimuth	Corr.
	(MHz)	(dBµV)	$(dB\mu V/m)$	$(dB\mu V/m)$	$(dB\mu V/m)$		(cm)		(deg)	(dB)
1	68.800	52.65	27.68	40.00	12.32	PK+	100.1	Н	360.1	-24.97
2	143.490	58.67	35.15	43.50	8.35	PK+	100.1	Н	360.1	-23.52
3	191.990	64.00	41.43	43.50	2.07	PK+	100.1	Н	360.1	-22.57
4	239.520	60.88	41.22	46.00	4.78	PK+	100.1	Н	360.1	-19.66
5	314.210	57.80	39.56	46.00	6.44	PK+	100.1	Н	360.1	-18.24
6	384.050	50.78	36.10	46.00	9.90	PK+	100.1	Н	360.1	-14.68

Mode:	2.4G-B-2412
Power:	DC 5V
TE:	Berny
Date	2023/11/9
T/A/P	24.3□/54%/101Kpa



No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	45.520	51.11	28.55	40.00	11.45	PK+	100.1	V	-0.1	-22.56
2	68.800	55.45	30.48	40.00	9.52	PK+	100.1	V	-0.1	-24.97
3	137.670	58.62	34.77	43.50	8.73	PK+	100.1	V	-0.1	-23.85
4	143.490	64.54	41.02	43.50	2.48	PK+	100.1	٧	-0.1	-23.52
5	191.990	60.07	37.50	43.50	6.00	PK+	100.1	٧	-0.1	-22.57
6	314.210	58.32	40.08	46.00	5.92	PK+	100.1	V	-0.1	-18.24

Note:


- 1. Measurement = Reading Level + Correct Factor.
- 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- 3. Peak: Peak detector.
- 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

REPORT NO.: E04A23110087F00101 Page 28 of 51

Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)


We tested all modes, The worst case scenario is as follows:

Mode:	2.4G WIFI b 2412
Power:	DC 5V
TE:	Vier
Date	2023/11/20
T/A/P	24.1°C/53%/101Kpa




No.	Freq.	Reading	Meas.	Limit	Margin	Det.	Height	Pol.	Azimuth	Corr.
10.	(MHz)	(dBµV)	$(dB\mu V/m)$	$(dB\mu V/m)$	$(dB\mu V/m)$	Det.	(cm)	roi.	(deg)	(dB)
1	3189.000	59.00	43.88	74.00	30.12	PK+	150	Н	184.7	-15.12
2	4083.000	58.15	45.06	74.00	28.94	PK+	150	Н	321.8	-13.09
3	4824.000	57.83	46.41	74.00	27.59	PK+	150	Н	124.7	-11.42
4	7236.000	52.00	44.37	74.00	29.63	PK+	150	Н	274.4	-7.63
5	12451.500	49.26	44.86	74.00	29.14	PK+	150	Н	213.5	-4.4
6	17809.500	48.41	47.92	74.00	26.08	PK+	150	Ι	172.3	-0.49

Mode:	2.4G WIFI b 2412
Power:	DC 5V
TE:	Vier
Date	2023/11/20
T/A/P	24.1□/53%/101Kpa




No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	2666.000	65.85	49.01	74.00	24.99	PK+	150	>	292.5	-16.84
2	3981.000	59.87	46.61	74.00	27.39	PK+	150	٧	160.7	-13.26
3	4822.500	56.84	45.43	74.00	28.57	PK+	150	V	280.7	-11.41
4	7233.000	51.71	44.07	74.00	29.93	PK+	150	٧	3.5	-7.64
5	10960.500	49.31	44.48	74.00	29.52	PK+	150	>	360.1	-4.83
6	14004.000	49.64	46.36	74.00	27.64	PK+	150	>	322.8	-3.28

Mode:	2.4G WIFI b 2437
Power:	DC 5V
TE:	Vier
Date	2023/11/20
T/A/P	24.1□/53%/101Kpa




No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	1876.000	68.79	49.31	74.00	24.69	PK+	150	Н	117.6	-19.48
2	4873.500	55.20	44.22	74.00	29.78	PK+	150	Н	36.9	-10.98
3	6675.000	51.10	42.91	74.00	31.09	PK+	150	Н	90.8	-8.19
4	11215.500	47.95	44.61	74.00	29.39	PK+	150	Н	227.9	-3.34
5	16168.500	47.43	47.51	74.00	26.49	PK+	150	Н	321.8	80.0
6	17724.000	47.36	47.86	74.00	26.14	PK+	150	Н	138.2	0.5

Mode:	2.4G WIFI b 2437
Power:	DC 5V
TE:	Vier
Date	2023/11/20
T/A/P	24.1□/53%/101Kpa




No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	1876.000	68.82	49.34	74.00	24.66	PK+	150	V	360.1	-19.48
2	2668.000	65.83	48.97	74.00	25.03	PK+	150	V	303.2	-16.86
3	3955.500	62.53	49.25	74.00	24.75	PK+	150	V	156.2	-13.28
4	4873.500	57.01	46.03	74.00	27.97	PK+	150	٧	311.2	-10.98
5	12063.000	49.64	45.16	74.00	28.84	PK+	150	>	79.2	-4.48
6	17718.000	47.55	47.93	74.00	26.07	PK+	150	>	262.7	0.38

Mode:	2.4G WIFI b 2462
Power:	DC 5V
TE:	Vier
Date	2023/11/20
T/A/P	24.1□/53%/101Kpa



No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	2664.000	64.73	47.91	74.00	26.09	PK+	150	V	292.5	-16.82
2	4047.000	61.97	48.84	74.00	25.16	PK+	150	V	157.2	-13.13
3	4924.500	56.54	45.35	74.00	28.65	PK+	150	V	360.1	-11.19
4	7387.500	54.31	46.08	74.00	27.92	PK+	150	V	25.4	-8.23
5	12477.000	49.46	45.28	74.00	28.72	PK+	150	V	292.5	-4.18
6	17727.000	48.12	48.63	74.00	25.37	PK+	150	V	162.5	0.51

Mode:	2.4G WIFI b 2462
Power:	DC 5V
TE:	Vier
Date	2023/11/20
T/A/P	24.1□/53%/101Kpa



No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	1876.000	65.64	46.16	74.00	27.84	PK+	150	Н	214.5	-19.48
2	2664.000	61.02	44.20	74.00	29.80	PK+	150	Н	293.4	-16.82
3	4923.000	57.63	46.43	74.00	27.57	PK+	150	Н	123.0	-11.2
4	7389.000	52.42	44.21	74.00	29.79	PK+	150	Н	260.0	-8.21
5	12874.500	49.41	45.09	74.00	28.91	PK+	150	Н	17.7	-4.32
6	17362.500	48.98	48.42	74.00	25.58	PK+	150	Н	46.8	-0.56

Other harmonics emissions are lower than 20dB below the allowable limit.


Note:

- 1. Measurement = Reading Level + Correct Factor.
- 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- 3. Peak: Peak detector.
- 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

REPORT NO.: E04A23110087F00101 Page 34 of 51


Band Edge

Mode:	2.4G-B-2412
Power:	DC 5V
TE:	Berny
Date	2023/11/9
T/A/P	24.3°C/54%/101Kpa




No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	2386.272	61.90	43.90	74.00	30.10	PK+	V	-18
2	2390.000	60.46	42.47	74.00	31.53	PK+	V	-17.99

Mode:	2.4G-B-2412
Power:	DC 5V
TE:	Berny
Date	2023/11/9
T/A/P	24.3□/54%/101Kpa




No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dΒμV/m)	Det.	Pol.	Corr. (dB)
1	2388.176	61.71	43.72	74.00	30.28	PK+	Н	-17.99
2	2390.000	60.91	42.92	74.00	31.08	PK+	Н	-17.99

Mode:	2.4G-B-2462
Power:	DC 5V
TE:	Berny
Date	2023/11/9
T/A/P	24.3□/54%/101Kpa



No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	2483.500	64.14	46.43	74.00	27.57	PK+	149	V	170.5	-17.71
2	2488.112	63.98	46.28	74.00	27.72	PK+	149	V	188.3	-17.7

Mode:	2.4G-B-2462
Power:	DC 5V
TE:	Berny
Date	2023/11/9
T/A/P	24.3□/54%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
1	2483.500	62.82	45.11	74.00	28.89	PK+	149.9	Н	0.0	-17.71
2	2487.964	63.66	45.96	74.00	28.04	PK+	149.9	Τ	0.0	-17.7

Note:

- 1. Measurement = Reading Level + Correct Factor.
- 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- 3. Peak: Peak detector.
- 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

REPORT NO.: E04A23110087F00101 Page 38 of 51

9. ANTENNA REQUIREMENT

REQUIREMENT

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2412-2462MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

DESCRIPTION

Pass

TRF No.: 04-E001-1A

REPORT NO.: E04A23110087F00101 Page 39 of 51

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT

Temperature	\mathbb{C}	Relative Humidity	%
Atmosphere Pressure	kPa		

REPORT NO.: E04A23110087F00101 Page 40 of 51

TEST RESULTS

N/A.

TRF No.: 04-E001-1A

REPORT NO.: E04A23110087F00101 Page 41 of 51

11. TEST DATA


Please refer to section "Test Data" - Appendix A


TRF No.: 04-E001-1A

REPORT NO.: E04A23110087F00101 Page 42 of 51

APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION







REPORT NO.: E04A23110087F00101 Page 43 of 51

APPENDIX: PHOTOGRAPHS OF THE EUT














































END OF REPORT