



FCC LISTED, REGISTRATION
 NUMBER: 720267

Informe de ensayo nº:
 Test report No:

IC LISTED REGISTRATION
 NUMBER IC 4621A-2

NIE: 51555RRF.003

Test report

USA FCC Part 15.247, 15.209
 CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and
 5725 - 5850 MHz.

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt
 Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

| | |
|--|--|
| Identificación del objeto ensayado.....: Identification of item tested | Radio car with Bluetooth handsfree |
| Marca Trademark | Panasonic |
| Modelo y/o referencia tipo Model and /or type reference | NTG5*2 US, NTG5*2 BASE, NTG5*2 CD |
| Other identification of the product | FCC ID: WUQ-NTG5STAR2 IC: 216R- NTG5STAR2 |
| Final HW version | C3 samples |
| Final SW version | E528.0 |
| Características Features | NTG5*2 US: Bluetooth EDR, GPS, AM/FM receiver NTG5*2 BASE: Bluetooth EDR, AM/FM receiver NTG5*2 CD: Bluetooth EDR, GPS, AM/FM receiver |
| Solicitante Applicant | Panasonic Automotive & Industrial Systems Europe GmbH Robert Bosch Str. 27-29 – 63225 Langen. Germany |
| Método de ensayo solicitado, norma.....: Test method requested, standard | USA FCC Part 15.247 10-1-15 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 10-1-15 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 1 (May 2015). CANADA RSS-Gen Issue 4 (November 2014). Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r05 dated 04/08/2016. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices. |
| Resultado.....: Summary | IN COMPLIANCE |

| | |
|---|------------------------------|
| Aprobado por (nombre / cargo y firma) Approved by (name / position & signature) | A. Llamas RF Lab. Manager |
| Fecha de realización Date of issue | 2017-02-22 |
| Formato de informe No. Report template No | FDT08_18 |

Index

| | |
|--|----|
| Competences and guarantees..... | 4 |
| General conditions..... | 4 |
| Uncertainty | 4 |
| Usage of samples..... | 5 |
| Test sample description | 6 |
| Identification of the client | 6 |
| Testing period..... | 6 |
| Environmental conditions..... | 6 |
| Remarks and comments..... | 7 |
| Testing verdicts | 8 |
| Appendix A – Test result (Bluetooth EDR) | 10 |

Competences and guarantees

AT4 wireless is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

AT4 wireless is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

AT4 wireless is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621A-2.

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the AT4 wireless internal document PODT000.

Usage of samples

Samples undergoing test have been selected by: **the client**

Sample S/01 is composed of the following elements:

| Control N° | Description | Model | Serial N° | Date of reception |
|------------|--------------------|-----------|----------------------|-------------------|
| 51555C/003 | Radio car | NTG5*2 US | 522 PA1701G0000296 4 | 2017-01-09 |
| 51555C/034 | BT antenna | --- | --- | 2017-01-10 |
| 48818/026 | GPS antenna | --- | --- | 2016-07-19 |
| 51555C/024 | HU CAN power cable | --- | --- | 2017-01-10 |
| 51555C/033 | Power cable | --- | --- | 2017-01-10 |

1. Sample S/01 has undergone following test(s).
All radiated tests indicated in appendix A.

Sample S/02 is composed of the following elements:

| Control N° | Description | Model | Serial N° | Date of reception |
|------------|--------------------|-----------|----------------------|-------------------|
| 51555C/003 | Radio car | NTG5*2 US | 522 PA1701G0000296 4 | 2017-01-09 |
| 51555C/024 | HU CAN power cable | --- | --- | 2017-01-10 |
| 51555C/033 | Power cable | --- | --- | 2017-01-10 |

1. Sample S/02 has undergone following test(s).
All conducted tests indicated in appendix A.

Auxiliary elements used with samples S/01 and S/02:

| Control N° | Description | Model | Serial N° | Date of reception |
|------------|------------------|--------|-----------|-------------------|
| 51555C/012 | CAN BOX | --- | N#2 | 2017-01-10 |
| 51555C/017 | AC/DC Adapter | BS-910 | --- | 2017-01-10 |
| 51555C/062 | Interface Board | --- | --- | 2017-01-10 |
| 45810B/042 | Connection cable | --- | --- | 2016-12-21 |
| 51555C/026 | VGA cable | --- | --- | 2017-01-10 |

Test sample description

The test sample consists of a radio car with Bluetooth handsfree.

Identification of the client

Panasonic Automotive & Industrial Systems Europe GmbH
Robert Bosch Str. 27-29 – 63225 Langen. Germany

Testing period

The performed test started on 2017-01-12 and finished on 2017-01-30.

The tests have been performed at AT4 wireless.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

| | |
|--------------------------------------|------------------------------|
| Temperature | Min. = 15 °C Max. = 35 °C |
| Relative humidity | Min. = 20 % Max. = 75 % |
| Shielding effectiveness | > 100 dB |
| Electric insulation | > 10 kΩ |
| Reference resistance to earth | < 1 Ω |

In the semianechoic chamber, the following limits were not exceeded during the test.

| | |
|--------------------------------------|---|
| Temperature | Min. = 15 °C Max. = 35 °C |
| Relative humidity | Min. = 20 % Max. = 75 % |
| Air pressure | Min. = 860 mbar Max. = 1060 mbar |
| Shielding effectiveness | > 100 dB |
| Electric insulation | > 10 kΩ |
| Reference resistance to earth | < 1 Ω |
| Normal site attenuation (NSA) | < ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz) |
| Field homogeneity | More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz). |

In the chamber for conducted measurements, the following limits were not exceeded during the test:

| | |
|--------------------------------------|-------------------------------------|
| Temperature | Min. = 15 °C Max. = 35 °C |
| Relative humidity | Min. = 20 % Max. = 75 % |
| Air pressure | Min. = 860 mbar Max. = 1060 mbar |
| Shielding effectiveness | > 100 dB |
| Electric insulation | > 10 kΩ |
| Reference resistance to earth | < 1 Ω |

Remarks and comments

1: According to the applicant's stamen below, the model NTG5*2 US is identical in hardware and software to the equipment family models NTG5*2 CD. Model NTG5*2 BASE is a depopulated version of NTG5*2 CD.

The test was performed with model NTG5*2 US which was the worst case for radiated spurious emissions.

2: Used instrumentation:

Conducted Measurements

| | Last Cal. date | Cal. due date |
|-------------------------------------|----------------|---------------|
| 1. Spectrum analyser Agilent E4440A | 2015/10 | 2017/10 |
| 2. DC power supply R&S NGPE 40/40 | 2014/11 | 2017/11 |

Radiated Measurements

| | Last Cal. date | Cal. due date |
|---|----------------|---------------|
| 1. Semianechoic Absorber Lined Chamber ETS FACT3 200STP | N.A. | N.A. |
| 2. BiconicalLog antenna ETS LINDGREN 3142E | 2014/03 | 2017/03 |
| 3. Multi Device Controller EMCO 2090 | N.A. | N.A. |
| 4. Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D | 2013/11 | 2016/11 |
| 5. Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170 | 2014/03 | 2017/03 |
| 6. EMI Test Receiver R&S ESU 40 | 2016/03 | 2018/03 |
| 7. Spectrum analyser Rohde & Schwarz FSW50 | 2015/12 | 2017/12 |
| 8. RF pre-amplifier 10 MHz-6 GHz SCHWARZBECK BBV9743 | 2016/04 | 2017/04 |
| 9. RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-1M | 2016/02 | 2018/02 |
| 10. RF pre-amplifier 18-40 GHz BONN ELEKTRONIK BLMA 1840-1M | 2015/12 | 2017/12 |

Testing verdicts

| | |
|-----------------------------|-----|
| Not applicable | N/A |
| Pass | P |
| Fail | F |
| Not measured | N/M |

BT EDR

| FCC PART 15 PARAGRAPH / RSS-247 | | VERDICT | | | |
|---|--|---------|---|---|----|
| | | NA | P | F | NM |
| FCC 15.247 Subclause (a) (1) / RSS-247 Clause 5.1 (2) | 20 dB Bandwidth and Carrier frequency separation | | P | | |
| FCC 15.247 Subclause (a)(1)(iii) / RSS-247 Clause 5.1 (4) | Number of hopping channels | | P | | |
| FCC 15.247 Subclause (a)(1)(iii) / RSS-247 Clause 5.1 (4) | Time of occupancy (Dwell Time) | | P | | |
| FCC 15.247 Subclause (b) / RSS-247 Clause 5.4 (2) | Maximum peak output power and antenna gain | | P | | |
| FCC 15.247 Subclause (d) / RSS-247 Clause 5.5 | Emission limitations conducted (Transmitter) | | P | | |
| FCC 15.247 Subclause (d) / RSS-247 Clause 5.5 | Emission limitations radiated (Transmitter) | | P | | |

Appendix A – Test result (Bluetooth EDR)

INDEX

| | |
|--|----|
| TEST CONDITIONS | 12 |
| FCC Section 15.247 Subclause (a) (1) / RSS-247 Clause 5.1 (2). 20 dB Bandwidth and Carrier frequency separation..... | 14 |
| FCC Section 15.247 Subclause (a) (1) (iii) / RSS-247 Clause 5.1 (4). Number of hopping channels..... | 21 |
| FCC Section 15.247 Subclause (a) (1) (iii) / RSS-247 Clause 5.1 (4). Time of occupancy (Dwell Time) | 27 |
| FCC Section 15.247 Subclause (b) / RSS-247 Clause 5.4 (2). Maximum peak output power and antenna gain | 37 |
| FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Band-edge compliance of conducted emissions (Transmitter) | 43 |
| FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations conducted (Transmitter)..... | 50 |
| FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5 Emission limitations radiated (Transmitter) | 56 |

TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 12.8 \text{ Vdc}$$

Type of power supply = DC voltage from external power supply

Type of antenna = External antenna

Declared Gain for antenna (maximum) = +2.4 dBi

TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyzer using a low loss RF cable. The reading of the spectrum analyzer is corrected with the cable loss.



The DC supply voltage is applied using an external calibrated power supply.

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).


For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission.


It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz



Radiated measurements setup $f > 1$ GHz



FCC Section 15.247 Subclause (a) (1) / RSS-247 Clause 5.1 (2). 20 dB Bandwidth and Carrier frequency separation

SPECIFICATION

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

RESULTS

(See next plots)

Modulation: GFSK

| | Lowest frequency | Middle frequency | Highest frequency |
|--------------------------------|------------------|------------------|-------------------|
| | 2402 MHz | 2441 MHz | 2480 MHz |
| 20 dB Spectrum bandwidth (kHz) | 717.062 | 716.884 | 719.195 |
| Measurement uncertainty (kHz) | <±5.00 | | |

Modulation: Π/4-DQPSK (2Mbps)

| | Lowest frequency | Middle frequency | Highest frequency |
|--------------------------------|------------------|------------------|-------------------|
| | 2402 MHz | 2441 MHz | 2480 MHz |
| 20 dB Spectrum bandwidth (kHz) | 1127 | 1126 | 1188 |
| Measurement uncertainty (kHz) | <±5.00 | | |


Modulation: 8-DPSK (3Mbps)

| | Lowest frequency | Middle frequency | Highest frequency |
|--------------------------------|------------------|------------------|-------------------|
| | 2402 MHz | 2441 MHz | 2480 MHz |
| 20 dB Spectrum bandwidth (kHz) | 1129 | 1136 | 1145 |
| Measurement uncertainty (kHz) | <±5.00 | | |

Modulation: GFSK


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation




The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

Modulation: $\Pi/4$ -DQPSK


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation




The hopping channel carrier frequencies are separated by a minimum of the two-thirds of the 20 dB bandwidth of the hopping channel

Verdict: PASS

Modulation: 8-DPSK


20 dB BANDWIDTH

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation



The hopping channel carrier frequencies are separated by a minimum of the two-thirds of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

FCC Section 15.247 Subclause (a) (1) (iii) / RSS-247 Clause 5.1 (4). Number of hopping channels


SPECIFICATION

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 channels.


RESULTS

The number of hopping channels is 79 for all three modes (see next plots).

Modulation: GFSK



Number of hopping frequencies: 39




Number of hopping frequencies: 40


Total number of hopping frequencies: 79

Verdict: PASS

Modulation: Π/4-DQPSK



Number of hopping frequencies: 39




Number of hopping frequencies: 40


Total number of hopping frequencies: 79

Verdict: PASS

Modulation: 8-DPSK



Number of hopping frequencies: 39



Number of hopping frequencies: 40

Total number of hopping frequencies: 79

Verdict: PASS

FCC Section 15.247 Subclause (a) (1) (iii) / RSS-247 Clause 5.1 (4). Time of occupancy (Dwell Time)

SPECIFICATION


The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed = $0.4 \times 79 = 31.6$ seconds.

RESULTS


Modulation: GFSK

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

- Tx- time per hop = 384.3 μ s (see next plot).



- Number of hops over a period of 1 seconds = 9 (see next plot).



Number of hops in the period specified in the requirements = (9 hops) x (31.6 s / 1 s) = 284.4 hops.


Averaging time of occupancy = 384.3 μs x 284.4 hops = 109.29 ms per 31.6 seconds.

| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|


Verdict: PASS

2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

- Tx- time per hop = 1.644 ms (see next plot).



- Number of hops over a period of 3 seconds = 12 (see next plot).




Number of hops in the period specified in the requirements = (12 hops) x (31.6 s / 3 s) = 126.4 hops.
 Averaging time of occupancy = 1.644 ms x 126.4 hops = 268.92 ms per 31.6 seconds.

| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|


Verdict: PASS

3. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH5.

- Tx- time per hop = 2.887 ms (see next plot).



- Number of hops over a period of 3 seconds = 11 (see next plot).



Number of hops in the period specified in the requirements = (11 hops) x (31.6 s / 3 s) = 115.87 hops.
 Averaging time of occupancy = 2.887 ms x 115.87 hops = 334.51 ms per 31.6 seconds.


| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|

Verdict: PASS


Modulation: Π/4-DQPSK

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE 2-DH1.

- Tx- time per hop = 398.9 μs (see next plot).



- Number of hops over a period of 1 second = 10 (see next plot).




Number of hops in the period specified in the requirements = (10 hops) x (31.6 s / 1 s) = 316 hops.
 Averaging time of occupancy = 398.9 μs x 316 hops = 126.05 ms per 31.6 seconds.

| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|


Verdict: PASS

2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE 2-DH3.

- Tx- time per hop = 1.661 ms (see next plot).



- Number of hops over a period of 3 seconds = 14 (see next plot).




Number of hops in the period specified in the requirements = (14 hops) x (31.6 s / 3 s) = 147.47 hops.
 Averaging time of occupancy = 1.661 ms x 147.47 hops = 244.94 ms per 31.6 seconds.

| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|


Verdict: PASS

3. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE 2-DH5.

- Tx- time per hop = 2.903 ms (see next plot).



- Number of hops over a period of 3 seconds = 11 (see next plot).



Number of hops in the period specified in the requirements = (11 hops) x (31.6 s / 3 s) = 115.87 hops.
 Averaging time of occupancy = 2.903 ms x 115.87 hops = 336.36 ms per 31.6 seconds.


| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|

Verdict: PASS


Modulation: 8-DPSK

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE 3-DH1.

- Tx- time per hop = 398.9 μs (see next plot).



- Number of hops over a period of 1 second = 10 (see next plot).




Number of hops in the period specified in the requirements = (10 hops) x (31.6 s / 1 s) = 316 hops.
 Averaging time of occupancy = 398.9 μs x 316 hops = 126.05 ms per 31.6 seconds.

| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|


Verdict: PASS

2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE 3-DH3.

- Tx- time per hop = 1.657 ms (see next plot).



- Number of hops over a period of 3 seconds = 18 (see next plot).




Number of hops in the period specified in the requirements = (18 hops) x (31.6 s / 3 s) = 189.6 hops.
 Averaging time of occupancy = 1.657 ms x 189.6 hops = 314.17 ms per 31.6 seconds.

| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|


Verdict: PASS

3. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE 3-DH5.

- Tx- time per hop = 2.904 ms (see next plot).



- Number of hops over a period of 3 seconds = 13 (see next plot).



Number of hops in the period specified in the requirements = (13 hops) x (31.6 s / 3 s) = 136.93 hops.
 Averaging time of occupancy = 2.904 ms x 136.93 hops = 397.65 ms per 31.6 seconds.

| | |
|-----------------------------|--------|
| Measurement uncertainty (%) | <±0.01 |
|-----------------------------|--------|

Verdict: PASS

FCC Section 15.247 Subclause (b) / RSS-247 Clause 5.4 (2). Maximum peak output power and antenna gain

SPECIFICATION

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels: 1 watt (30 dBm). The e.i.r.p. shall not exceed 4 W (RSS-247).

MAXIMUM OUTPUT POWER. See next plots.

Declared maximum antenna gain: 2.4 dBi.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

Modulation: GFSK

| | Lowest frequency 2402 MHz | Middle frequency 2441 MHz | Highest frequency 2480 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum peak power (dBm) | -0.1 | -0.37 | -0.92 |
| Maximum EIRP power (dBm) | 2.3 | 2.03 | 1.48 |
| Measurement uncertainty (dB) | <±0.78 | | |

Modulation: Π/4-DQPSK (2Mbps)

| | Lowest frequency 2402 MHz | Middle frequency 2441 MHz | Highest frequency 2480 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum peak power (dBm) | 1.49 | 1.58 | 1.27 |
| Maximum EIRP power (dBm) | 3.89 | 3.98 | 3.67 |
| Measurement uncertainty (dB) | <±0.78 | | |

Modulation: 8-DPSK (3Mbps)

| | Lowest frequency 2402 MHz | Middle frequency 2441 MHz | Highest frequency 2480 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum peak power (dBm) | 1.45 | 1.50 | 1.22 |
| Maximum EIRP power (dBm) | 3.85 | 3.90 | 3.62 |
| Measurement uncertainty (dB) | <±0.78 | | |


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

PEAK OUTPUT POWER (CONDUCTED).


Modulation: GFSK

Lowest Channel: 2402 MHz.



Modulation: GFSK


Middle Channel: 2441 MHz.



PEAK OUTPUT POWER (CONDUCTED).


Modulation: GFSK

Highest Channel: 2480 MHz.



Modulation: $\Pi/4$ -DQPSK


Lowest Channel: 2402 MHz



PEAK OUTPUT POWER (CONDUCTED)


Modulation: $\Pi/4$ -DQPSK

Middle Channel: 2441 MHz.



Modulation: $\Pi/4$ -DQPSK


Highest Channel: 2480 MHz.



PEAK OUTPUT POWER (CONDUCTED).


Modulation: 8-DPSK

Lowest Channel: 2402 MHz



Modulation: 8-DPSK


Middle Channel: 2441 MHz



PEAK OUTPUT POWER (CONDUCTED).

Modulation: 8-DPSK

Highest Channel: 2480 MHz.



FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Band-edge compliance of conducted emissions (Transmitter)


SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power.

RESULTS:


Modulation: GFSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.




Verdict: PASS

| | |
|------------------------------|--------|
| Measurement uncertainty (dB) | <±2.03 |
|------------------------------|--------|


Modulation: $\Pi/4$ -DQPSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.




Verdict: PASS

| | |
|------------------------------|--------|
| Measurement uncertainty (dB) | <±2.03 |
|------------------------------|--------|


Modulation: 8-DPSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

| | |
|------------------------------|--------|
| Measurement uncertainty (dB) | <±2.03 |
|------------------------------|--------|

FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations conducted (Transmitter)

SPECIFICATION


In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

RESULTS:

All peaks are more than 20 dB below the limit.

Modulation: GFSK


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS


2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limits is the carrier frequency.

Verdict: PASS

| | |
|------------------------------|--------|
| Measurement uncertainty (dB) | <±2.03 |
|------------------------------|--------|

Modulation: $\Pi/4$ -DQPSK


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS


2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peaks above the limits are the carrier frequencies.

Verdict: PASS

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

| | |
|------------------------------|--------|
| Measurement uncertainty (dB) | <±2.03 |
|------------------------------|--------|

Modulation: 8-DPSK


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS


2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peaks above the limit are the carrier frequencies.

Verdict: PASS

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS

| | |
|------------------------------|--------|
| Measurement uncertainty (dB) | <±2.03 |
|------------------------------|--------|

FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5 Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

| Frequency Range (MHz) | Field strength ($\mu\text{V/m}$) | Field strength ($\text{dB}\mu\text{V/m}$) | Measurement distance (m) |
|-----------------------|------------------------------------|---|--------------------------|
| 0.009-0.490 | 2400/F(kHz) | - | 300 |
| 0.490-1.705 | 24000/F(kHz) | - | 30 |
| 1.705 - 30.0 | 30 | - | 30 |
| 30 - 88 | 100 | 40 | 3 |
| 88 - 216 | 150 | 43.5 | 3 |
| 216 - 960 | 200 | 46 | 3 |
| 960 - 25000 | 500 | 54 | 3 |

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

A preliminary test was performed with models NTG5*2 US and NTG5*2 BASE.

The test was performed with model NTG5*2 US which was the worst case for radiated spurious emissions.

Frequency range 30 MHz-1000 MHz.

Note: The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

Spurious signals closest to the limit

| Spurious frequency (MHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|-----------|-------------------------------|------------------------------|
| 399.958 | PV | QuasiPeak | 28.45 | ± 3.88 |
| 471.350 | PH | QuasiPeak | 29.87 | ± 3.88 |
| 574.073 | PV | QuasiPeak | 30.64 | ± 3.88 |
| 604.725 | PH | QuasiPeak | 33.62 | ± 3.88 |
| 614.425 | PH | QuasiPeak | 36.17 | ± 3.88 |
| 725.684 | PV | QuasiPeak | 30.58 | ± 3.88 |
| 747.703 | PV | QuasiPeak | 31.96 | ± 3.88 |
| 1000.000 | PH | QuasiPeak | 30.21 | ± 3.88 |

Frequency range 1 GHz-25 GHz

The results in the next tables show the maximum measured levels in the 1-25 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Modulation: GFSK

1. CHANNEL: LOWEST (2402 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 1.331167 | PV | Peak | 45.99 | ± 4.87 |
| 2.376215 | PV | Peak | 49.54 | ± 4.87 |
| 2.494661 | PV | Peak | 48.81 | ± 4.87 |
| 3.247250 | PV | Peak | 42.65 | ± 4.87 |
| 4.803750 | PH | Peak | 49.61 | ± 4.87 |
| 6.180250 | PV | Peak | 38.69 | ± 4.87 |
| 7.205750 | PV | Peak | 54.99 | ± 4.87 |
| | | Average | 53.67 | |
| 9.607250 | PV | Peak | 45.32 | ± 4.87 |

2. CHANNEL: MIDDLE (2441 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.361471 | H | Peak | 48.04 | ± 4.87 |
| 2.494704 | H | Peak | 49.29 | ± 4.87 |
| 3.419250 | H | Peak | 41.71 | ± 4.87 |
| 4.882250 | H | Peak | 55.61 | ± 4.87 |
| | | Average | 53.59 | |
| 7.322250 | V | Peak | 54.92 | ± 4.87 |
| | | Average | 52.69 | |
| 9.763250 | V | Peak | 44.66 | ± 4.87 |
| 12.204250 | V | Peak | 50.84 | ± 4.87 |

3. CHANNEL: HIGHEST (2480 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 1.322233 | V | Peak | 46.06 | ± 4.87 |
| 2.328372 | V | Peak | 48.56 | ± 4.87 |
| 2.489476 | V | Peak | 49.08 | ± 4.87 |
| 3.455750 | V | Peak | 41.31 | ± 4.87 |
| 4.959750 | H | Peak | 53.68 | ± 4.87 |
| 7.439750 | V | Peak | 52.18 | ± 4.87 |
| 12.399250 | V | Peak | 51.02 | ± 4.87 |

Verdict: PASS

Modulation: Π/4-DQPSK

1. CHANNEL: LOWEST (2402 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 1.335300 | V | Peak | 45.39 | ± 4.87 |
| 2.362145 | V | Peak | 52.16 | ± 4.87 |
| 2.386436 | V | Peak | 52.91 | ± 4.87 |
| 2.441633 | V | Peak | 53.94 | ± 4.87 |
| 2.492149 | V | Peak | 48.88 | ± 4.87 |
| 3.251250 | H | Peak | 40.43 | ± 4.87 |
| 4.804250 | V | Peak | 53.94 | ± 4.87 |
| 5.604750 | H | Peak | 45.11 | ± 4.87 |
| 7.206250 | H | Peak | 54.06 | ± 4.87 |
| | | Average | 52.76 | |
| 8.807750 | H | Peak | 43.86 | ± 4.87 |
| 9.608750 | H | Peak | 47.72 | ± 4.87 |

2. CHANNEL: MIDDLE (2441 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 1.332167 | V | Peak | 45.86 | ± 4.87 |
| 2.101033 | V | Peak | 53.61 | ± 4.87 |
| 2.387175 | V | Peak | 53.21 | ± 4.87 |
| 2.401367 | H | Peak | 47.33 | ± 4.87 |
| 2.480767 | H | Peak | 47.09 | ± 4.87 |
| 2.492798 | H | Peak | 59.94 | ± 4.87 |
| | | Average | 42.10 | |
| 3.38075 | H | Peak | 40.18 | ± 4.87 |
| 4.88225 | H | Peak | 52.16 | ± 4.87 |
| 5.69625 | H | Peak | 43.50 | ± 4.87 |
| 7.32375 | H | Peak | 52.91 | ± 4.87 |
| 8.13725 | H | Peak | 43.27 | ± 4.87 |
| 8.95075 | H | Peak | 44.11 | ± 4.87 |
| 9.76425 | H | Peak | 45.93 | ± 4.87 |

3. CHANNEL: HIGHEST (2480 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 1.130033 | V | Peak | 45.83 | ± 4.87 |
| 2.314076 | H | Peak | 48.08 | ± 4.87 |
| 2.334777 | V | Peak | 48.16 | ± 4.87 |
| 2.387500 | V | Peak | 51.95 | ± 4.87 |
| 2.439967 | V | Peak | 54.92 | ± 4.87 |
| | | Average | 50.96 | |
| 2.494292 | V | Peak | 64.90 | ± 4.87 |
| | | Average | 45.12 | |
| 2.520167 | V | Peak | 53.43 | ± 4.87 |
| 3.201250 | V | Peak | 42.31 | ± 4.87 |
| 3.412750 | H | Peak | 40.35 | ± 4.87 |
| 4.960250 | H | Peak | 55.12 | ± 4.87 |
| | | Average | 51.26 | |
| 5.786750 | H | Peak | 44.60 | ± 4.87 |
| 7.440250 | H | Peak | 50.31 | ± 4.87 |
| 8.267250 | H | Peak | 43.67 | ± 4.87 |
| 9.093750 | V | Peak | 44.81 | ± 4.87 |
| 9.920250 | V | Peak | 45.97 | ± 4.87 |

Verdict: PASS

Modulation: 8-DPSK

1. CHANNEL: LOWEST (2402 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 1.129767 | V | Peak | 45.49 | ± 4.87 |
| 2.361833 | H | Peak | 46.51 | ± 4.87 |
| 2.376988 | V | Peak | 62.65 | ± 4.87 |
| | | Average | 43.31 | |
| 2.441967 | V | Peak | 55.13 | ± 4.87 |
| | | Average | 50.35 | |
| 2.486566 | H | Peak | 48.88 | ± 4.87 |
| | | Average | 37.64 | |
| 3.212750 | V | Peak | 41.54 | ± 4.87 |
| 3.316750 | H | Peak | 39.48 | ± 4.87 |
| 4.803750 | V | Peak | 51.68 | ± 4.87 |
| 5.604750 | V | Peak | 45.17 | ± 4.87 |
| 7.205750 | V | Peak | 53.70 | ± 4.87 |
| 9.608250 | V | Peak | 45.82 | ± 4.87 |

2. CHANNEL: MIDDLE (2441 MHz).


| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 1.129900 | V | Peak | 44.21 | ± 4.87 |
| 2.362420 | V | Peak | 48.21 | ± 4.87 |
| 2.387700 | V | Peak | 52.01 | ± 4.87 |
| 2.400833 | H | Peak | 49.33 | ± 4.87 |
| 2.401167 | V | Peak | 53.54 | ± 4.87 |
| 2.480767 | V | Peak | 52.62 | ± 4.87 |
| 2.494002 | V | Peak | 64.99 | ± 4.87 |
| | | Average | 45.45 | |
| 3.419250 | H | Peak | 41.04 | ± 4.87 |
| 4.881750 | H | Peak | 53.16 | ± 4.87 |
| 7.322750 | V | Peak | 53.44 | ± 4.87 |
| 9.764250 | V | Peak | 48.15 | ± 4.87 |
| 12.205250 | V | Peak | 47.55 | ± 4.87 |

3. CHANNEL: HIGHEST (2480 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB μ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.355433 | H | Peak | 48.90 | ± 4.87 |
| 2.386633 | V | Peak | 51.64 | ± 4.87 |
| 2.440167 | V | Peak | 54.39 | ± 4.87 |
| | | Average | 49.41 | |
| 2.488728 | V | Peak | 71.17 | ± 4.87 |
| | | Average | 50.38 | |
| 2.519967 | V | Peak | 52.68 | ± 4.87 |
| 3.201750 | V | Peak | 42.99 | ± 4.87 |
| 4.959250 | H | Peak | 55.86 | ± 4.87 |
| | | Average | 49.83 | |
| 5.786750 | H | Peak | 42.12 | ± 4.87 |
| 7.440250 | H | Peak | 50.09 | ± 4.87 |

Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels and all modulation modes).

FREQUENCY RANGE 1 GHz to 3 GHz.


Modulation: GFSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot above the limits is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot above the limits is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot above the limits is the carrier frequency.


Modulation: $\Pi/4$ -DQPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot above the limits is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot above the limits is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot above the limits is the carrier frequency.


Modulation: 8-DPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot above the limits is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot above the limits is the carrier frequency.

CHANNEL: Highest (2480 MHz).




Note: The peak shown in the plot above the limits is the carrier frequency.


FREQUENCY RANGE 3 GHz to 18 GHz.

Modulation: GFSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).




Modulation: $\Pi/4$ -DQPSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).




Modulation: 8-DPSK


CHANNEL: Lowest (2402 MHz).




CHANNEL: Middle (2441 MHz).



CHANNEL: Highest (2480 MHz).



FREQUENCY RANGE 18 GHz to 26 GHz.




(This plot is valid for all three channels and all modulation modes).


FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)

CHANNEL: Lowest


Modulation: GFSK



Modulation: $\Pi/4$ -DQPSK




Modulation: 8-DPSK




CHANNEL: Middle


Modulation: GFSK



Modulation: $\Pi/4$ -DQPSK




Modulation: 8-DPSK




CHANNEL: Highest


Modulation: GFSK



Modulation: $\Pi/4$ -DQPSK




Modulation: 8-DPSK




FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)

CHANNEL: Lowest


Modulation: GFSK



Modulation: Π/4-DQPSK




Modulation: 8-DPSK




CHANNEL: Middle


Modulation: GFSK



Modulation: $\Pi/4$ -DQPSK




Modulation: 8-DPSK




CHANNEL: Highest

Modulation: GFSK



Modulation: Π/4-DQPSK



Modulation: 8-DPSK

