



FCC LISTED, REGISTRATION
NUMBER: 2764.01

ISED LISTED REGISTRATION
NUMBER: 23595-1

Test report No:
3818ERM.015

Test report

FCC Rules and Regulations CFR 47, Part 15, Subpart B (10-1-20 Edition)
&
ICES-003 ISSUE 7 – October (2020)

(*) Identification of item tested	Headunit with radio and bluetooth
(*) Trademark	Panasonic
(*) Model and /or type reference tested	MIB3E_MQB_BT
Other identification of the product	FCC ID: WUQ-MIB3HBT IC: 216R-MIB3HBT
(*) Features	Bluetooth, FM, AM, DAB USB.
Manufacturer	PANASONIC AUTOMOTIVE SYSTEMS EUROPE GMBH Robert Bosch Str. 27-29 – 63225 Langen Germany
Test method requested, standard	FCC Rules and Regulations CFR 47, Part 15, Subpart B (10-1-20 Edition) ICES-003 ISSUE 7 – October (2020)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Domingo Galvez EMC&RF Lab Manager
Date of issue	10-03-2022
Report template No	FDT08_23

(*) "Data provided by the client"

Index

Competences and guarantees	3
General conditions	3
Uncertainty	3
Data provided by the client	4
Usage of samples	5
Test sample description	6
Identification of the client	7
Testing period and place	7
Document history	8
Environmental conditions	8
Remarks and comments	8
Testing verdicts	9
Summary	9
List of equipment used during the test	10
Appendix A: Test results	11

Competences and guarantees

DEKRA Certification Inc. is a testing laboratory accredited by A2LA (The American Association for Laboratory Accreditation), to perform the tests indicated in the Certificate 2764.01

DEKRA Certification Inc. is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor k=2) was calculated according to the DEKRA Certification internal document PODT000.

	Frequency (MHz)	U (k=2)	Units
Radiated emission	30 - 1000	5.94	dB
	1000-18000	5.89	dB

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample consists of an Automotive head unit to be installed in cars with the following features:
Automotive head unit to be installed in cars with the following features: Bluetooth, FM, AM, DAB, USB.
3. Additional information: PN: 654.035.869.J

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples used for test have been selected by **The Client**.

Sample S/01 is composed of the following elements, accessories and auxiliary equipment:

Id	Control Number	Description	Manufacturer / Model	Serial N°	Date of Reception	Application
S/01	3818/15	Car radio Scala 6.5 - VE CV-RV4BXEAEB	Panasonic / MIB3E_MQB_BT	PM6-00105 08 22413G0396	2022-08-28	Element Under Test
S/01	3818/40	AM/FM TL Dummy	MIB-LSW-TLD-022	-	2022-08-28	Accessory
S/01	3818/41	BNC to Fakra(Dual) RF cable	-	-	2022-08-28	Accessory
S/01	3818/66	USB CAN Adapter	-	-	2022-08-28	Accessory
S/01	2271/16	Fakra antenna cable	-	-	2018-12-21	Accessory
S/01	2271/23	Harness (with Speaker, & load box)	-	-	2018-12-21	Accessory
S/01	2271/24	USB Hub power cables	-	-	2018-12-21	Accessory
S/01	2271/29	USB Hub	-	-	2018-12-21	Accessory
S/01	2271/30	BT Antenna	-	-	2018-12-21	Accessory
S/01	2271/39	Fakra to Fakra cable	-	-	2018-12-21	Accessory
S/01	Dekra 47	FM/AM antenna	-	-	-	Auxiliary Element

1. Sample S/01 was used for the following test(s): All Radiated tests indicated in appendix A


Test sample description

Test Sample description (compulsory information for EMC and RF testing services)

Ports.....	Port name and description	Cable				
		Specified length [m]	Attached during test	Shielded	Coupled to patient	
	No Data Provided		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Supplementary information to the ports.....	No Data Provided					
Rated power supply	Voltage and Frequency	Reference poles				
		L1	L2	L3	N	
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
		<input checked="" type="checkbox"/>	DC: 12 Vdc			
		<input type="checkbox"/>	DC:			
Rated Power	4.5 A					
Clock frequencies.....	No Data Provided					
Other parameters	External fuse of 20 A					
Software version	Y780					
Hardware version	Y10					
Dimensions in cm (W x H x D)	No Data Provided					
Mounting position	<input type="checkbox"/>	Table top equipment				
	<input type="checkbox"/>	Wall/Ceiling mounted equipment				
	<input type="checkbox"/>	Floor standing equipment				
	<input type="checkbox"/>	Hand-held equipment				
	<input checked="" type="checkbox"/>	Other: Installed in a vehicle				
Modules/parts.....	Module/parts of test item		Type		Manufacturer	
	No Data Provided					

Accessories (not part of the test item)	Description	Type	Manufacturer
	No Data Provided		
Documents as provided by the applicant	Description	File name	Issue date
	Declaration Equipment Data	FDT30_18 Declaration Equipment Data_Scala_BT_DAB_6.5_VE_Signed	08/23/2022

Copy of marking plate:



Identification of the client

PANASONIC AUTOMOTIVE SYSTEMS EUROPE GMBH
Robert Bosch Str. 27-29 – 63225 Langen
Germany

Testing period and place

Test Location	DEKRA Certification Inc.
Date (start)	09-14-2022
Date (finish)	09-26-2022

Document history

Report number	Date	Description
3818ERM.015	10-03-2022	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semi-anechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 60 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

1. The tests have been performed by the technical personnel: Nasir Khan, Qi Zhang, and Koji Nishimoto .

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

Emission Test				
Report Section	Requirement – Test case	Verdict	Remark	
A.1	Radiated emission test (30 MHz – 1000 MHz)	P	N/A	
A.1	Radiated emission test (1 GHz – 18 GHz)	P	N/A	
-	Radiated emission test (18 GHz – 26 GHz)	N/A	Refer 1	
-	Conducted emission test (150 kHz to 30 MHz)	N/A	Refer 2	

Supplementary information and remarks:

- 1) According with the requirements of FCC Rules and Regulations, title 47, Chapter I, Subchapter A, Part 15, Subpart A, §15.33 Frequency range of radiated measurements, (b) for unintentional radiators, (1) due to The Highest frequency generated or used in the device above 1000MHz, The Upper frequency of measurement range is up to 5th harmonic of the highest frequency or 40GHz, whichever is lower.
- 2) According with the requirements of FCC Rules and Regulations, title 47, Chapter I, Subchapter A, Part 15, Subpart B, §15.107 Conducted limits, (d) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation, and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

List of equipment used during the test

Radiated Emission Equipment

Control Number	Description	Manufacturer	Model	Last Calibration	Next Calibration
981	RF pre-amplifier 1-18 GHz	Bonn Elektronik	BLMA 0118-2A	2020/11	2022/11
1012	ESR26 EMI Test Receiver	Rohde & Schwarz	ESR26	2022/04	2024/04
1014	FSV40 Signal Analyzer 40GHz	Rohde & Schwarz	FSV40	2021/05	2023/05
1057	Double-ridge Waveguide Horn antenna	ETS Lindgren	3115	2020/06	2023/06
1065	Biconical log Antenna	ETS Lindgren	3142E	2020/08	2023/08
1108	Ethernet SNMP Thermometer- CR Room	HW Group	HWg-STE Plain	2020/09	2022/09
1111	Ethernet SNMP Thermometer- SAC	HW Group	HWg-STE Plain	2020/09	2022/09
1179	Semi-Anechoic Chamber	Frankonia	SAC 3plus 'L'	N/A	N/A
1217	Frankonia Transparent Test Table 1	Frankonia	FFT-Square	N/A	N/A
1314	Wireless measurement software EMC 32	Rohde & Schwarz	-	N/A	N/A

Appendix A: Test results

Appendix A Content

DESCRIPTION OF THE OPERATION MODES.....	13
A.1. RADIATED EMISSION ELECTROMAGNETIC FIELD	14

DESCRIPTION OF THE OPERATION MODES

The operation modes described in this paragraph represent functionalities of the sample under test.

The following operation modes of the samples were used during the test executions:

OPERATION MODE	DESCRIPTION
OM#01*	EUT ON. Power supply 12 Vdc. <ul style="list-style-type: none">• 2.4 GHz BTBR/EDR in IDLE mode

* Worst case observed

A.1. RADIATED EMISSION ELECTROMAGNETIC FIELD

LIMITS:

Product standard:	FCC CFR 47, Part 15, Subpart B (10-1-20 Edition), Secs. 15.109 & ICES-003 Issue 7 – October (2020)	
Test standard:	FCC CFR 47, Part 15, Subpart B (10-1-20 Edition), Secs. 15.109 & ICES-003 Issue 7 – October (2020); ANSI C63.4 (2014)	

Limits of interference Class B

The applied limit for radiated emissions, 3 m distance, in the frequency range 30 MHz to 40 GHz for class B equipment, according with the requirements of:

FCC Rules and Regulations 47 CFR Part 15, Subpart B, Secs. 15.109 (a) (10-01-20 Edition).

Frequency range (MHz)	QP Limit for 3 m	
	(μ V/m)	(dB μ V/m)
30 to 88	100	40
88 to 216	150	43.5
216 to 960	200	46
Above 960	500	54

Frequency range (MHz)	AVG Limit for 3 m		PK Limit for 3 m (1)
	(μ V/m)	(dB μ V/m)	(dB μ V/m)
Above 1000	500	54	74

(1) Frequencies above 1 GHz, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test, as per §15.35(b)

ICES-003 Issue 7, Secs 3.2.2, table 2 & 4 (October 2020).

Frequency range (MHz)	QP Limit for 3 m	
	(μ V/m)	(dB μ V/m)
30 to 88	100	40
88 to 216	150	43.5
216 to 230	200	46
230 to 960	224	47
Above 960	500	54

Frequency range (MHz)	AVG Limit for 3 m		PK Limit for 3 m (1)
	(μ V/m)	(dB μ V/m)	(dB μ V/m)
Above 1000	500	54	74

TEST SETUP

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30-1000 MHz (Bilog antenna) and 1-18 GHz (Double ridge horn antenna).

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

TEST SETUP (CONT.)




Fig A1: Generic setup for measurements from 30 to 1000 MHz





Fig A2: Generic setup for measurements from 1 to 18 GHz

TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	OM#01
TEST RESULTS:	CRmmnnxx: CR: Radiation Condition, mm: Sample number, nn: Operation mode, xx: Frequency Range

CRmmnnxx	Description	Result
CR0101LR	Range: 30 - 1000 MHz Horizontal and Vertical Polarization	P
CR0101HR	Range: 1 - 18 GHz Horizontal and Vertical Polarization	P

TEST RESULTS (Cont.):


CR0101LR



Frequency (MHz)	QuasiPeak (dB μ V/m)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
30.582690	26.06	37.40	40.00	13.94	254.0	V	80.0
85.483510	16.52	28.48	40.00	23.48	129.0	H	112.0
176.761580	16.55	28.36	43.50	26.95	118.0	H	-162.0
264.934679	20.86	33.42	46.00	25.14	115.0	H	44.0
342.049387	19.18	32.07	46.00	26.82	300.0	H	-30.0
845.333517	26.91	39.63	46.00	19.09	137.0	V	-86.0

TEST RESULTS (Cont.):

CR0101HR



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
2380.500000	59.9	52.2	53.9	1.7	150.0	H	12.0
3970.000000	53.1	43.2	53.9	10.7	150.0	V	22.0
17890.500000	54.9	47.2	53.9	6.7	150.0	V	-150.0