

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1529	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5180MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT20---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26052.838	35.20	16.50	51.70	74.00	-22.30	peak			
2	26052.838	22.53	16.50	39.03	54.00	-14.97	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1530	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT20---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26163.916	35.09	16.50	51.59	74.00	-22.41	peak			
2	26163.916	23.61	16.50	40.11	54.00	-13.89	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1531	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT20---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26002.504	34.79	17.23	52.02	74.00	-21.98	peak			
2	26002.504	22.88	17.23	40.11	54.00	-13.89	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1532	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5220MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT20---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26133.575	34.32	17.14	51.46	74.00	-22.54	peak			
2	26133.575	22.63	17.14	39.77	54.00	-14.23	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1533	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5220MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT20---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26042.764	35.09	16.50	51.59	74.00	-22.41	peak			
2	26042.764	22.46	16.50	38.96	54.00	-15.04	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1534	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5240MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT20---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25992.449	34.70	16.50	51.20	74.00	-2.80	peak			
2	25992.449	23.12	16.50	39.62	54.00	-14.38	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1535	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5240MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT20---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26103.270	32.91	17.16	50.07	74.00	-23.93	peak			
2	26103.270	22.40	17.16	39.56	54.00	-14.44	AVG			

## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5180MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Horizontal  
Operator Name:  
Comment: 802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz





## Radiated Emission


### EUT Information

EUT Model Name:	WiFi Advisor M/N:WFED-300AC
Operation mode:	TX 5180MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

### Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5200MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Horizontal  
Operator Name:  
Comment: 802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



## Radiated Emission


### EUT Information

EUT Model Name:	WiFi Advisor M/N:WFED-300AC
Operation mode:	TX 5200MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

### Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



## Radiated Emission


### EUT Information

EUT Model Name:	WiFi Advisor M/N:WFED-300AC
Operation mode:	TX 5220MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

### Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5220MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Vertical  
Operator Name:  
Comment: 802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



## Radiated Emission


### EUT Information

EUT Model Name:	WiFi Advisor M/N:WFED-300AC
Operation mode:	TX 5240MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

### Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5240MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Vertical  
Operator Name:  
Comment: 802.11an HT20---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



**Produkte**  
 Products

802.11n HT40\_1TX- Non Beamforming




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1804	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	85.1770	38.06	-15.38	22.68	40.00	-17.32	QP			
2	331.7857	41.10	-8.31	32.79	46.00	-13.21	QP			



**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1805	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	86.9917	42.76	-15.26	27.50	40.00	-12.50	QP			
2	331.7857	34.57	-8.31	26.26	46.00	-19.74	QP			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1806	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.6052	42.88	-15.23	27.65	40.00	-12.35	QP			
2	332.9536	34.52	-8.29	26.23	46.00	-19.77	QP			

Produkte  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1807	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	84.8782	38.43	-15.42	23.01	40.00	-16.99	QP			
2	332.9534	41.18	-8.29	32.89	46.00	-13.11	QP			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1962	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16446.926	9.16	40.27	49.43	74.00	-24.57	peak			
2	16446.926	-0.45	40.27	39.82	54.00	-14.18	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1963	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15744.284	9.41	40.05	49.46	74.00	-24.54	peak			
2	15744.284	-0.38	40.05	39.67	54.00	-14.33	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1964	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15882.369	9.54	40.02	49.56	74.00	-24.44	peak			
2	15882.369	-0.60	40.02	39.42	54.00	-14.58	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1965	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15471.706	9.29	40.16	49.45	74.00	-24.55	peak			
2	15471.706	-0.47	40.16	39.69	54.00	-14.31	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1536	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25962.307	34.46	17.26	51.72	74.00	-22.28	peak			
2	25962.307	22.43	17.26	39.69	54.00	-14.31	AVG			



**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1537	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26113.368	35.72	16.50	52.22	74.00	-21.78	peak			
2	26113.368	23.28	16.50	39.78	54.00	-14.22	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1538	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26052.838	35.84	16.50	52.34	74.00	-21.66	peak			
2	26052.838	23.73	16.50	40.23	54.00	-13.77	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1539	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26032.693	34.70	17.21	51.91	74.00	-22.09	peak			
2	26032.693	22.36	17.21	39.57	54.00	-14.43	AVG			

Test

1 / 1

## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5190MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Horizontal  
Operator Name:  
Comment: 802.11an HT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5190MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Vertical  
Operator Name:  
Comment: 802.11an HT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5230MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Horizontal  
Operator Name:  
Comment: 802.11an HT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



## Radiated Emission


### EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC  
Operation mode: TX 5230MHz  
Test Voltage: AC 120V/60Hz  
Comment: JDSU

### Common Information

Test Site: SMQ EMC Lab.  
Environment Conditions:  
Antenna Polarization: Vertical  
Operator Name:  
Comment: 802.11an HT40---1TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



**Produkte**  
 Products

802.11n HT40\_2TX - Non Beamforming




**ACCURATE TECHNOLOGY CO., LTD.**  
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1808	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	84.8782	38.93	-15.42	23.51	40.00	-16.49	QP			
2	335.3016	41.41	-8.25	33.16	46.00	-12.84	QP			



**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1809	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.6051	42.45	-15.23	27.22	40.00	-12.78	QP			
2	335.3016	35.19	-8.25	26.94	46.00	-19.06	QP			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1810	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.6051	42.34	-15.23	27.11	40.00	-12.89	QP			
2	332.9534	33.93	-8.29	25.64	46.00	-20.36	QP			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1811	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	84.5806	39.69	-15.49	24.20	40.00	-15.80	QP			
2	331.7858	41.08	-8.31	32.77	46.00	-13.23	QP			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1966	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16542.951	9.05	40.42	49.47	74.00	-24.53	peak			
2	16542.951	-0.41	40.42	40.01	54.00	-13.99	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1967	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16591.174	9.13	40.56	49.69	74.00	-24.31	peak			
2	16591.174	-0.53	40.56	40.03	54.00	-13.97	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1968	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16639.536	9.17	40.69	49.86	74.00	-24.14	peak			
2	16639.536	-0.52	40.69	40.17	54.00	-13.83	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1969	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16542.951	8.70	40.42	49.12	74.00	-24.88	peak			
2	16542.951	-0.64	40.42	39.78	54.00	-14.22	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1540	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26012.563	33.82	17.22	51.04	74.00	-22.96	peak			
2	26012.563	21.71	17.22	38.93	54.00	-15.07	AVG			



**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1541	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25962.307	35.35	16.50	51.85	74.00	-22.15	peak			
2	25962.307	22.05	16.50	38.55	54.00	-15.45	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1542	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26002.504	34.46	16.50	50.96	74.00	-23.04	peak			
2	26002.504	22.36	16.50	38.86	54.00	-15.14	AVG			

**Produkte**  
 Products




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: pz #1543	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---2TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26072.999	34.43	17.18	51.61	74.00	-22.39	peak			
2	26072.999	22.77	17.18	39.95	54.00	-14.05	AVG			