

Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC
Operation mode: TX 5190MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Horizontal
Operator Name:
Comment: 802.11an HT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC
Operation mode: TX 5190MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Vertical
Operator Name:
Comment: 802.11an HT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC
Operation mode: TX 5230MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Horizontal
Operator Name:
Comment: 802.11an HT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N:WFED-300AC
Operation mode:	TX 5230MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT40---2TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Produkte
 Products

802.11n HT40_3TX - Non Beamforming




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1812	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	84.5806	38.93	-15.49	23.44	40.00	-16.56	QP			
2	334.1254	40.37	-8.28	32.09	46.00	-13.91	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1813	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.2980	42.81	-15.24	27.57	40.00	-12.43	QP			
2	333.9534	34.05	-8.28	25.77	46.00	-20.23	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1917	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	84.5811	38.99	-15.49	23.50	40.00	-16.50	QP			
2	331.7934	40.76	-8.31	32.45	46.00	-13.55	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1918	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	86.9920	42.87	-15.26	27.61	40.00	-12.39	QP			
2	332.9544	34.50	-8.29	26.21	46.00	-19.79	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1970	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16115.207	9.91	40.07	49.98	74.00	-24.02	peak			
2	16115.207	-0.56	40.07	39.51	54.00	-14.49	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1971	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16883.475	8.43	41.37	49.80	74.00	-24.20	peak			
2	16883.475	-1.51	41.37	39.86	54.00	-14.14	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1972	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15471.706	9.79	40.16	49.95	74.00	-24.05	peak			
2	15471.706	-0.48	40.16	39.68	54.00	-14.32	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1973	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15882.369	9.07	40.02	49.09	74.00	-24.91	peak			
2	15882.369	-0.42	40.02	39.60	54.00	-14.40	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1544	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26042.764	34.59	17.20	51.79	74.00	-22.21	peak			
2	26042.764	21.35	17.20	38.55	54.00	-15.45	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1545	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5190MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25962.307	34.61	16.50	51.11	74.00	-22.89	peak			
2	25962.307	23.35	16.50	39.85	54.00	-14.15	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1546	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26062.917	35.96	16.50	52.46	74.00	-21.54	peak			
2	26062.917	23.67	16.50	40.17	54.00	-13.83	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1547	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5230MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11an HT40---3TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26012.563	33.56	17.22	50.78	74.00	-23.22	peak			
2	26012.563	19.46	17.22	36.68	54.00	-17.32	AVG			

Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC
Operation mode: TX 5190MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Horizontal
Operator Name:
Comment: 802.11an HT40---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N:WFED-300AC
Operation mode:	TX 5190MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT40---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name: WiFi Advisor M/N:WFED-300AC
Operation mode: TX 5230MHz
Test Voltage: AC 120V/60Hz
Comment: JDSU

Common Information

Test Site: SMQ EMC Lab.
Environment Conditions:
Antenna Polarization: Horizontal
Operator Name:
Comment: 802.11an HT40---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Radiated Emission


EUT Information

EUT Model Name:	WiFi Advisor M/N:WFED-300AC
Operation mode:	TX 5230MHz
Test Voltage:	AC 120V/60Hz
Comment:	JDSU

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	802.11an HT40---3TX (Non-Beamforming)

Copy of FCC Electric Field Strength 26.5-40GHz



Produkte
 Products

802.11ac VHT20_1TX - Non Beamforming




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1814	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5180MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.6052	42.91	-15.23	27.68	40.00	-12.32	QP			
2	334.1255	33.99	-8.28	25.71	46.00	-20.29	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1815	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5180MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	85.1771	38.94	-15.38	23.56	40.00	-16.44	QP			
2	331.7858	41.49	-8.31	33.18	46.00	-12.82	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1816	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	85.1771	39.14	-15.38	23.76	40.00	-16.24	QP			
2	331.7858	41.17	-8.31	32.86	46.00	-13.14	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1817	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.2980	42.65	-15.24	27.41	40.00	-12.59	QP			
2	334.1255	33.94	-8.28	25.66	46.00	-20.34	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1818	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5220MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.6052	43.09	-15.23	27.86	40.00	-12.14	QP			
2	335.3016	33.65	-8.25	25.40	46.00	-20.60	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1819	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5220MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	85.1770	38.93	-15.38	23.55	40.00	-16.45	QP			
2	331.7857	41.40	-8.31	33.09	46.00	-12.91	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1820	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5240MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	331.7857	41.78	-8.31	33.47	46.00	-12.53	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1821	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/11/15/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5240MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	87.6050	42.69	-15.23	27.46	40.00	-12.54	QP			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1974	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5180MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16494.869	8.89	40.30	49.19	74.00	-24.81	peak			
2	16494.869	-0.70	40.30	39.60	54.00	-14.40	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1975	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5180MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16162.183	9.20	40.10	49.30	74.00	-24.70	peak			
2	16162.183	-0.72	40.10	39.38	54.00	-14.62	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1976	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16446.926	9.31	40.27	49.58	74.00	-24.42	peak			
2	16446.926	-0.63	40.27	39.64	54.00	-14.36	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1977	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16162.183	9.55	40.10	49.65	74.00	-24.35	peak			
2	16162.183	-0.58	40.10	39.52	54.00	-14.48	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1978	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5220MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20--1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16209.295	9.46	40.13	49.59	74.00	-24.41	peak			
2	16209.295	-0.66	40.13	39.47	54.00	-14.53	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1979	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5220MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15516.806	10.09	40.10	50.19	74.00	-23.81	peak			
2	15516.806	-0.42	40.10	39.68	54.00	-14.32	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1980	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5240MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	16162.183	10.13	40.10	50.23	74.00	-23.77	peak			
2	16162.183	-0.38	40.10	39.72	54.00	-14.28	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1981	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/16
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5240MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	15790.179	9.43	40.04	49.47	74.00	-24.53	peak			
2	15790.179	-0.50	40.04	39.54	54.00	-14.46	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1548	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5180MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26042.764	34.10	17.20	51.30	74.00	-22.70	peak			
2	26042.764	21.74	17.20	38.94	54.00	-15.06	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1549	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5180MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26012.563	34.85	16.50	51.35	74.00	-22.65	peak			
2	26012.563	22.53	16.50	39.03	54.00	-14.97	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1550	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.1ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26062.917	34.90	16.50	51.40	74.00	-22.60	peak			
2	26062.917	22.94	16.50	39.44	54.00	-14.56	AVG			

Produkte
 Products




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: pz #1551	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2014/11/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: WiFi Advisor	Engineer Signature: PEI
Mode: TX 5200MHz	Distance: 3m
Model: WFED-300AC	
Manufacturer: JDSU	

Note: 802.11ac VHT20---1TX (Non-Beamforming)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26032.693	34.35	17.21	51.56	74.00	-22.44	peak			
2	26032.693	22.71	17.21	39.92	54.00	-14.08	AVG			